

Package ‘mtk’

July 22, 2014

Type Package

Title Mexico ToolKit library (MTK)

Encoding UTF-8

Version 1.0

Date 2014-07-15

Author Juhui WANG Hervé Richard Hervé Monod Robert Faivre

Maintainer Juhui WANG <Juhui.Wang@jouy.inra.fr>

Description Mexico ToolKit library

License GPL-3

LazyLoad yes

Depends R (>= 2.15.0), base, stringr, graphics, methods, XML,sensitivity, lhs, rgl

Suggests MASS

Collate 'mtkAllGenerics.R' 'globalsMtkFuncts.R' 'mtkValue.R'
'mtkFeature.R' 'mtkLevels.R' 'mtkParameter.R' 'mtkDomain.R'
'mtkFactor.R' 'mtkExpFactors.R' 'mtkProcess.R'
'mtkExpWorkflow.R' 'mtkExperiment.R' 'mtkParsor.R'
'mtkResult.R' 'mtkDesignerResult.R' 'mtkDesigner.R'
'mtkMorrisDesigner.R' 'mtkBasicMonteCarloDesigner.R'
'mtkRandLHSDesigner.R' 'mtkNativeDesigner.R'
'mtkSobolDesigner.R' 'mtkFastDesigner.R' 'mtkEvaluatorResult.R'
'mtkEvaluator.R' 'mtkNativeEvaluator.R' 'mtkIshigamiEvaluator.R' 'mtkWWDMEvaluator.R'
'mtkSystemEvaluatorResult.R' 'mtkSystemEvaluator.R'
'mtkAnalyserResult.R' 'mtkAnalyser.R' 'mtkNativeAnalyser.R'
'mtkDefaultAnalyser.R' 'mtkRegressionAnalyser.R'
'mtkMorrisAnalyser.R' 'mtkSobolAnalyser.R' 'mtkPLMMAAnalyser.R'
'mtkFastAnalyser.R' 'mtk.addons.R' 'mtkPackage.R'

R topics documented:

mtk-package	5
addProcess-methods	7
ANY	8
BasicMonteCarlo	9
deleteProcess-methods	10
extractData-methods	12
Fast	13
getData-methods	15
getDiscreteDistributionLevels-methods	17
getDiscreteDistributionType-methods	17
getDiscreteDistributionWeights-methods	18
getDistributionName-methods	19
getDistributionNames-methods	20
getDistributionNominalValue-methods	21
getDistributionNominalValues-methods	21
getDistributionNominalValueType-methods	22
getDistributionNominalValueTypes-methods	23
getDistributionParameters-methods	24
getDomain-methods	24
getFactorFeatures-methods	25
getFactorNames-methods	26
getFactors-methods	27
getFeatures-methods	28
getLevels-methods	28
getMTKFeatures-methods	29
getName-methods	30
getNames-methods	30
getNominalValue-methods	31
getNominalValueType-methods	32
getParameters-methods	33
getProcess-methods	34
getResult-methods	35
getType-methods	36
getValue-methods	37
getWeights-methods	38
is.finished-methods	38
is.ready-methods	39
Ishigami	40
Ishigami.factors	42
make.mtkFactor	43
make.mtkFeatureList	44
make.mtkParameterList	45
Morris	45
mtk.analyserAddons	48
mtk.designerAddons	50
mtk.evaluatorAddons	52
mtkAnalyser	54
mtkAnalyser-class	55
mtkAnalyserResult	57
mtkAnalyserResult-class	58

mtkBasicMonteCarloDesigner	59
mtkBasicMonteCarloDesigner-class	60
mtkBasicMonteCarloDesignerResult	62
mtkBasicMonteCarloDesignerResult-class	63
mtkDefaultAnalyser	64
mtkDefaultAnalyser-class	65
mtkDesigner	67
mtkDesigner-class	68
mtkDesignerResult	70
mtkDesignerResult-class	70
mtkDomain	71
mtkDomain-class	72
mtkEvaluator	74
mtkEvaluator-class	75
mtkEvaluatorResult	77
mtkEvaluatorResult-class	77
mtkExperiment	78
mtkExperiment-class	80
mtkExpFactors	82
mtkExpFactors-class	82
mtkExpWorkflow	84
mtkExpWorkflow-class	85
mtkFactor	88
mtkFactor-class	89
mtkFastAnalyser	90
mtkFastAnalyser-class	91
mtkFastAnalyserResult	93
mtkFastAnalyserResult-class	94
mtkFastDesigner	95
mtkFastDesigner-class	96
mtkFastDesignerResult	98
mtkFastDesignerResult-class	99
mtkFeature	100
mtkFeature-class	101
mtkIshigamiEvaluator	102
mtkIshigamiEvaluator-class	103
mtkLevels	105
mtkLevels-class	106
mtkMorrisAnalyser	107
mtkMorrisAnalyser-class	108
mtkMorrisAnalyserResult	110
mtkMorrisAnalyserResult-class	111
mtkMorrisDesigner	112
mtkMorrisDesigner-class	113
mtkMorrisDesignerResult	115
mtkMorrisDesignerResult-class	116
mtkNativeAnalyser	117
mtkNativeAnalyser-class	118
mtkNativeDesigner	120
mtkNativeDesigner-class	121
mtkNativeEvaluator	123
mtkNativeEvaluator-class	125

mtkParameter	128
mtkParameter-class	129
mtkParsor	130
mtkParsor-class	131
mtkPLMMAlyser	132
mtkPLMMAlyser-class	133
mtkPLMMAlyserResult	134
mtkPLMMAlyserResult-class	135
mtkProcess	136
mtkProcess-class	138
mtkRandLHSDesigner	139
mtkRandLHSDesigner-class	140
mtkRandLHSDesignerResult	141
mtkRandLHSDesignerResult-class	142
mtkReadFactors-methods	143
mtkRegressionAnalyser	143
mtkRegressionAnalyser-class	144
mtkRegressionAnalyserResult	146
mtkRegressionAnalyserResult-class	147
mtkResult	148
mtkResult-class	149
mtkSobolAnalyser	150
mtkSobolAnalyser-class	151
mtkSobolAnalyserResult	152
mtkSobolAnalyserResult-class	153
mtkSobolDesigner	154
mtkSobolDesigner-class	155
mtkSobolDesignerResult	156
mtkSobolDesignerResult-class	157
mtkSystemEvaluator	158
mtkSystemEvaluator-class	159
mtkSystemEvaluatorResult	160
mtkSystemEvaluatorResult-class	161
mtkValue	162
mtkValue-class	162
mtkWWDMEvaluator	163
mtkWWDMEvaluator-class	165
mtkWWDMEvaluatorResult	167
mtkWWDMEvaluatorResult-class	168
PLMM	169
plot,mtkProcess-method	172
print,mtkProcess-method	173
Quantiles	175
RandLHS	175
reevaluate-methods	177
Regression	178
report-methods	179
run-methods	180
serializeOn-methods	181
setDistributionParameters-methods	182
setDomain-methods	183
setFactors-methods	184

setFeatures-methods	185
setLevels-methods	185
setName-methods	186
setParameters-methods	187
setProcess-methods	188
setReady-methods	189
setState-methods	190
setType-methods	191
setValue-methods	192
setWeights-methods	193
setXMLFilePath-methods	194
Sobol	195
summary,mtkProcess-method	198
WWDM	199
wwdm.climates	201
WWDM.factors	202

Index**204**

mtk-package	<i>MTK (Mexico ToolKit) for Sensitivity Analysis and Numerical Experiments</i>
-------------	--

Description

MTK is an R package for sensitivity analysis and numerical experiments . Three examples are provided:

- "Ishigami" model analysis with the "BasicMonteCarlo" and "Regression" methods.
- Using the "mtk" package from a XML file.
- "WWDM (Winter Wheat Dry Matter)" model analysis with the "Morris" methods.

To run the examples, just load the package and type respectively:

- `demo(demo1, package="mtk", ask=FALSE)`
- `demo(demo2, package="mtk", ask=FALSE)`
- `demo(demo3, package="mtk", ask=FALSE)`

The following methods and models are available for the current release:

- The "Fast" methods for experiments design and sensitivity index calculation. see `help(Fast)`.
- The "Morris" methods for experiments design and sensitivity index calculation. see `help(Morris)`.
- The "Sobol" methods for experiments design and sensitivity index calculation. see `help(Sobol)`.
- The "Monte-Carlo" methods for experiments design. see `help(BasiMonteCarlo)`.
- The "LHS" methods for experiments design. see `help(RandLHS)`.
- The "PLMM (Polynomial Linear Meta-Model)" methods for sensitivity analysis. see `help(PLMM)`.
- The "Regression" methods for sensitivity index calculation. see `help(Regression)`.
- The "Ishigami" model for model simulation. see `help(Ishigami)`.
- The "WWDM (Winter Wheat Dry Matter)" model for model simulation. see `help(WWDM)`.

Author(s)

The Mexico Group. Contact: Juhui WANG, MIA-Jouy, Juhui.Wang@jouy.inra.fr,

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
### Example 1: Sensitivity analysis of the "Ishigami" model ###

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1",
  distribName="unif", distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))
# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.Designer <- mtkMorrisDesigner(listParameters
= list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.Evaluator <- mtkIshigamiEvaluator()

# 3) the analysis process with the method "Morris".
expl.Analyser <- mtkMorrisAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(
    design=expl.Designer,
    evaluate=expl.Evaluator,
    analyze=expl.Analyser)
)

# Run the workflow and reports the results.
run(expl)
print(expl)

# Create a new process with the analysis method «Regression».
expl.AnalyserReg <- mtkRegressionAnalyser(listParameters
=list(nboot=20)
)

# Re-analyze the model "Ishigami" with the method "Regression":
## replace the process, run the workflow and report the results

setProcess(expl, expl.AnalyserReg, "analyze")
run(expl)
```

```

print(expl)

### Example 2 : Sensitivity analysis from a XML file ###

# # XML file is held in the directory of the library: "inst/extdata/"

# Specify the XML file's name
xmlFile <- "WWDM_morris.xml"

## Find where the examples are held.
xmlFilePath <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", xmlFile, sep = "")

# Create the workflow
## Nota: If your XML file is local file for example "/var/tmp/X.xml",
## you should create the workflow as follows:
## workflow <- mtkExpWorkflow(xmlFilePath="/var/tmp/X.xml")

workflow <- mtkExpWorkflow(xmlFilePath=xmlFilePath)

# Run the workflow and report the results
run(workflow)
summary(workflow)

```

addProcess-methods *The addProcess method*

Description

Adds a process to the workflow.

Usage

```
addProcess(this, p, name)
```

Arguments

<code>this</code>	an object of the class <code>mtkExpWorkflow</code> .
<code>p</code>	an object of the class <code>mtkProcess</code> .
<code>name</code>	a string from "design", "evaluate", or "analyze" to specify the type of process to add.

Value

`invisible()`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Define the factors

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Create a workflow to manager the processes used for the analysis task

ishiReg <- mtkExpWorkflow(expFactors=ishi.factors)

# Create a designer to generate the experiments design and
# put the designer under control of the workflow

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))

addProcess(ishiReg, designer, name="design")

# Creates an evaluator and add it to the workflow

model <- mtkNativeEvaluator("Ishigami" )

addProcess(ishiReg, model, name="evaluate")

# Create a analyser and add it to the workflow

analyser <- mtkNativeAnalyser("Regression" )

addProcess(ishiReg, analyser, name="analyze")

# Run the workflow and reports the results

run(ishiReg)
summary(ishiReg)
```

ANY

The ANY class

Description

ANY is a data type to represent any S4 class.

Details

S4 implements the ANY class, but does not document it.

Examples

```
# creates a new class with "ANY"
setClass(Class="mtkProcess",

representation=representation(
  name="character",
  protocol="character",
  site="character",
  service="character",
  parameters="ANY",
  ready="logical",
  state="logical",
  result="ANY"
),

prototype=prototype(parameters=NULL, ready=FALSE,
                      state=FALSE, result=NULL)

)
```

BasicMonteCarlo	<i>The BasicMonteCarlo design method</i>
-----------------	--

Description

A native mtk design method to generate Monte Carlo samples.

Usage

- `mtkBasicMonteCarloDesigner(listParameters=NULL)`
- `mtkNativeDesigner(design="BasicMonteCarlo", information=NULL)`

Parameters

size : the sample size.

Details

1. The mtk implementation of the Basic Monte-Carlo method includes the following classes:
 - `mtkBasicMonteCarloDesigner` for Basic Monte-Carlo design processes.
 - `mtkBasicMonteCarloDesignerResult` to store and manage the design.
2. Many ways to create a Basic Monte-Carlo designer are available in mtk, but we recommend the following class constructors: `mtkBasicMonteCarloDesigner` or `mtkNativeDesigner`.

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
## Experiments design with the "Basic Monte-Carlo" method for the "Ishigami" model

# Example I: by using the class constructors: mtkBasicMonteCarloDesigner()

# 1) Create a designer process based on the Basic Monte-Carlo method
MCdesign <- mtkBasicMonteCarloDesigner(listParameters = list(size=20))

# 2) Import the input factors of the "Ishigami" model
data(Ishigami.factors)

# 3) Build and run the workflow
expl <- mtkExpWorkflow(expFactors = Ishigami.factors,
                      processesVector = c(design=MCdesign))
run(expl)

# 4) Report and plot the design
show(expl)
plot(expl)

# Example II: by using the class constructors: mtkNativeDesigner()

# 1) Create a designer process based on the Basic Monte-Carlo method
MCdesign <- mtkNativeDesigner("BasicMonteCarlo", information = list(size=20))

# 2) Import the input factors of the "Ishigami" model
data(Ishigami.factors)

# 3) Build and run the workflow
expl <- mtkExpWorkflow(expFactors = Ishigami.factors,
                      processesVector = c(design=MCdesign))
run(expl)

# 4) Print and plot the design
print(expl)
plot(expl)
```

deleteProcess-methods

The deleteProcess method

Description

Deletes a process from the workflow.

Usage

```
deleteProcess(this, name)
```

Arguments

<code>this</code>	an object of the class <code>mtkExpWorkflow</code> .
<code>name</code>	a string from "design", "evaluate", or "analyze" to specify the process to delete.

Value

```
invisible()
```

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create an analysis for the Ishigami model:

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

ishiReg <- mtkExpWorkflow( expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
)
run(ishiReg)
summary(ishiReg)

# Delete the analysis process from the workflow and
# run only the model simulation:

deleteProcess(ishiReg, "analyze")
run(ishiReg)
```

```
summary(ishiReg)
```

```
extractData-methods
```

The extractData method

Description

Gets the results produced by the workflow as a data.frame.

Usage

```
extractData(this, name)
```

Arguments

<code>this</code>	an object of the class <code>mtkExpWorkflow</code> .
<code>name</code>	a vector of strings from "design", "evaluate", or "analyze" to specify the results to return. i.e. <code>name=c("design")</code> returns the experimental design produced by the designer, <code>name=c("design", "evaluate")</code> returns both the experimental design produced by the designer and the model simulation produced by the evaluator.

Value

a data.frame

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Build a workflow for sensitivity analysis with the model "Ishigami"

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
```

```

        information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

ishiReg <- mtkExpWorkflow(expFactors=ishi.factors,
  processesVector=c(design = designer,
    evaluate = model,
    analyze = analyser)
)
run(ishiReg)

# extracts the results produced by the workflow as a data.frame:

design <- extractData(ishiReg, "design")
simulation <- extractData(ishiReg, c("design", "evaluate"))

```

Fast

The extended Fourier Amplitude Sensitivity Test for sensitivity analysis

Description

A mtk compliant implementation of the so-called extended-FAST or e-Fast method for experiments design and sensitivity analysis.

Usage

- `mtkFastDesigner(listParameters = NULL)`
- `mtkNativeDesigner(design="Fast", information=NULL)`
- `mtkFastAnalyser()`
- `mtkNativeAnalyser(analyze="Fast", information=NULL)`

Parameters used to manage the sampling method

`n`: (numeric) the number of iteration.

Parameters used to manage the analysis method

No parameter is necessary.

Details

1. The mtk implementation uses the `fast99` function of the `sensitivity` package. For further details on the arguments and the behaviour, see `help(fast99, sensitivity)`.
2. The mtk implementation of the Fast method includes the following classes:
 - `mtkFastDesigner`: for Fast design processes.
 - `mtkFastAnalyser`: for Fast analysis processes.
 - `mtkFastDesignerResult`: to store and manage the design.
 - `mtkFastAnalyserResult`: to store and manage the analysis results.
3. Many ways to create a Fast designer are available in mtk, but we recommend the following class constructors: `mtkFastDesigner` or `mtkNativeDesigner`.

4. Many ways to create a `Fast` analyser are available in `mtk`, but we recommend the following class constructors: `mtkFastAnalyser` or `mtkNativeAnalyser`.
5. The method `Fast` is usually used both to build the experiment design and to carry out the sensitivity analysis. In such case, we can use the `mtkDefaultAnalyser` instead of naming explicitly the method for sensitivity analysis (see example III in the examples section)

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

```
help(fast99, sensitivity)
```

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Fast" method

# Example I: by using the class constructors: mtkFastDesigner() and mtkFastAnalyser()

# Input the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner(listParameters
  = list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)
plot(expl)

## Example II: by using the class constructors: mtkNativeDesigner() and mtkFastAnalyser

# Generate the factors
data(Ishigami.factors)
```

```

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkNativeDesigner(design = "Fast", information=list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
plot(expl)

## Example III: by using the class constructors: mtkFastDesigner() and mtkDefaultAnalyser()

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner( listParameters = list(n=2000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkDefaultAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
plot(expl)

```

getData-methods *The getData method*

Description

Returns the results produced by the process as a data.frame.

Usage

```
getData(this)
```

Arguments

`this` an object of the class `mtkProcess` or its sub-classes

Value

a data.frame.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
## Example: Sensitivity analysis for the Ishigami model

# Define the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes
designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

# Build the workflow and run it
ishiReg <- mtkExpWorkflow(expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
)
run(ishiReg)

# Extract as a data.frame the experiment design:
designer <- getProcess(ishiReg, "design")
expDesign <- getData(designer)
```

`getDiscreteDistributionLevels-methods`*The getDiscreteDistributionLevels method*

Description

Returns the levels of the discrete distribution associated with the factor's domain.

Usage

```
getDiscreteDistributionLevels(this)
```

Arguments

`this` the underlying object of the class to proceed (`mtkFactor`).

Value

a list.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a discrete domain
x1 <- make.mtkFactor(name="x1", distribName="discrete",
  distribPara= list(type='categorical',
    levels = c(1,2,3,4,5), weights=rep(0.2, 5)))

# Returns the levels of the associated discrete distribution
getDiscreteDistributionLevels(x1)
```

`getDiscreteDistributionType-methods`*The getDiscreteDistributionType method*

Description

Returns the type of the discrete distribution associated with the factor's domain.

Usage

```
getDiscreteDistributionType(this)
```

Arguments

`this` the underlying object of the class to proceed (`mtkFactor`).

Value

a string.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a discrete domain
x1 <- make.mtkFactor(name="x1", distribName="discrete",
  distribPara= list(type='categorical',
    levels = c(1,2,3,4,5), weights=rep(0.2, 5)))
# Returns the type of the associated discrete distribution
getDiscreteDistributionType(x1)
```

getDiscreteDistributionWeights-methods

The getDiscreteDistributionWeights method

Description

Returns the weights of the discrete distribution associated with the factor's domain.

Usage

```
getDiscreteDistributionWeights(this)
```

Arguments

`this` the underlying object of the class to proceed (`mtkFactor`).

Value

a list of numeric values.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a discrete domain
x1 <- make.mtkFactor(name="x1", distribName="discrete",
  distribPara= list(type='categorical',
    levels = c(1,2,3,4,5), weights=rep(0.2, 5)))
# Returns the weights of the associated discrete distribution
getDiscreteDistributionWeights(x1)
```

getDistributionName-methods

The getDistributionName method

Description

Returns the name of the distribution associated with a domain or a factor.

Usage

```
getDistributionName(this)
```

Arguments

this the underlying object of the class to proceed ([mtkDomain](#) or [mtkFactor](#)).

Value

a string.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a domain and get the name of its distribution
d <- mtkDomain(distributionName="unif", domainNominalValue=0)
distribution <- getDistributionName(d)

# For more information, see examples for the mtkDomain or
# mtkFactor classes.
```

`getDistributionNames-methods`*The getDistributionNames method*

Description

Returns the names of the distributions associated with an object of the class `mtkExpFactors`.

Usage

```
getDistributionNames(this)
```

Arguments

`this` an object of the `mtkExpFactors` class.

Value

a list.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Get the names of the distributions managed by all the factors
names <- getDistributionNames(ishi.factors)
```

`getDistributionNominalValue-methods`*The getDistributionNominalValue method*

Description

Returns the nominal value associated with the uncertainty domain of a factor.

Usage

```
getDistributionNominalValue(this)
```

Arguments

`this` an object of the class `mtkFactor`.

Value

ANY

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a a factor with a nominal value

x1 <- make.mtkFactor(name="x1", type='numeric', nominal=0.0, distribName="unif",
  distribPara=list(min=-pi, max=pi))

getDistributionNominalValue(x1)
```

`getDistributionNominalValues-methods`*The getDistributionNominalValues method*

Description

Gets the nominal values associated with the managed factors.

Usage

```
getDistributionNominalValues(this)
```

Arguments

`this` an object of the class `mtkExpFactors`)

Value

a named list

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Return the nominal values
nValues <- getDistributionNominalValues(ishi.factors)
```

getDistributionNominalValueType-methods

The getDistributionNominalValueType method

Description

Returns the nominal value associated with the uncertainty domain of a factor.

Usage

```
getDistributionNominalValueType(this)
```

Arguments

this an object of the class `mtkFactor`.

Value

string

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a a factor with a nominal value

x1 <- make.mtkFactor(name="x1", type='numeric', nominal=0.0, distribName="unif",
                     distribPara=list(min=-pi, max=pi))

getDistributionNominalValueType(x1)
```

getDistributionNominalValueTypes-methods

The getDistributionNominalValueTypes method

Description

Gets the nominal values associated with the managed factors.

Usage

```
getDistributionNominalValueTypes(this)
```

Arguments

this an object of the class `mtkExpFactors`)

Value

a named list

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
                     distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
                     distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
                     distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Return the nominal values
nTypes <- getDistributionNominalValueTypes(ishi.factors)
```

getDistributionParameters-methods

The getDistributionParameters method

Description

Gets the parameters of the distribution(s) associated with an object (`mtkDomain`, `mtkFactor` or `mtkExpFactors`).

Usage

```
getDistributionParameters(this)
```

Arguments

`this` an object of the underlying class (`mtkDomain`, `mtkFactor` or `mtkExpFactors`)

Value

a named list or a nested list

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Return the parameters of the distributions managed by all the factors as a nested list
names <- getDistributionParameters(ishi.factors)
```

getDomain-methods *The getDomain method*

Description

Returns the domain associated with the factor.

Usage

```
getDomain(this)
```


Arguments

`this` an object of the class `mtkFactor`.

Value

an object of the class `mtkDomain`

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Return the uncertainty domain associated with the factor
dom <- getDomain(x1)
```

`getFactorFeatures-methods`

The getFactorFeatures method

Description

Returns the features associated with the managed factors.

Usage

```
getFactorFeatures(this)
```

Arguments

`this` an object of the `mtkExpFactors` class

Value

a named list.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Define a list of features and associate it with the factor x1
features <- make.mtkFeatureList(list(pre=5, post=60))
setFeatures(x1, features)

x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Get the features of the managed factors as a list
factors <- getFactorFeatures(ishi.factors)
```

getFactorNames-methods

The getFactorNames method

Description

Returns the name of the managed factors.

Usage

```
getFactorNames(this)
```

Arguments

this an object of the class mtkExpFactors.

Value

a list of strings

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
```

```
distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Get the names of the factors managed by all the factors
factors <- getFactorNames(ishi.factors)
```

getFactors-methods *The getFactors method*

Description

Returns the managed factors.

Usage

```
getFactors(this)
```

Arguments

`this` the underlying object of the class `mtkExpFactors`.

Value

a list of objects from the class `mtkFactor`.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors()

# Define the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
# Assign and return the factors to the mtkExpFactors' object

setFactors(ishi.factors, list(x1,x2,x3))
getFactors(ishi.factors)
```

getFeatures-methods

The getFeatures method

Description

Returns the features associated with the underlying factor.

Usage

```
getFeatures(this)
```

Arguments

`this` an object of the `mtkFactor` class

Value

a named list.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Define a list of features and associate it with the factor
features <- make.mtkFeatureList(list(pre=5, post=60))
setFeatures(x1, features)

# Return the features associated with the factor
fl <- getFeatures(x1)
```

getLevels-methods *The getLevels method*

Description

Returns the levels associated with a discrete domain.

Usage

```
getLevels(this)
```

Arguments

`this` an object of the class `mtkDomain` or `mtkLevels`.

Value

a list

Examples

```
l <- mtkLevels(type='categorical', levels=seq(1:10), weight=rep(0.1, 10))
getLevels(l)
```

getMTKFeatures-methods

The getMTKFeatures method

Description

Returns the features associated with the underlying factor as a list of `mtkFeature` objects.

Usage

```
getMTKFeatures(this)
```

Arguments

`this` an object of the `mtkFactor` class

Value

a list of objects of the class `mtkFeature`

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Define a list of features and associate it with the factor
features <- make.mtkFeatureList(list(pre=5, post=60))
setFeatures(x1, features)

# Return the features associated with the factor
fl <- getMTKFeatures(x1)
```

getName-methods	<i>The getName method</i>
-----------------	---------------------------

Description

Returns the name of the object or a process.

Usage

```
getName(this)
```

Arguments

this the underlying object to proceed.

Value

a string

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

Examples

```
# just a method to access to the name of the underlying object or process
# Create an object of the 'mtkFeature' class.

f <- mtkFeature(name="x", type="double", val=0.0)

getName(f) # gives 'x'
```

getNames-methods	<i>The getNames method</i>
------------------	----------------------------

Description

Returns the name of the factors managed by an object of class `mtkExpFactors`.

Usage

```
getNames(this)
```

Arguments

this an object of the class `mtkExpFactors`.

Value

a list of strings

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define three factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Get the names of the factors managed by all the factors
factors <- getNames(ishi.factors)
```

getNominalValue-methods

The getNominalValue method

Description

Returns the nominal value associated with the uncertainty domain of a factor.

Usage

```
getNominalValue(this)
```

Arguments

this an object of the class `mtkDomain`.

Value

ANY

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a domain and get the type of its nominal value
d <- mtkDomain(distributionName="unif", domainNominalValue=0.0)
mv <- getNominalValue(d)

# For more information, see examples for the mtkDomain or
# mtkFactor classes.
```

getNominalValueType-methods

The getNominalValueType method

Description

Returns the data type of the nominal value associated with the uncertainty domain of a factor.

Usage

```
getNominalValueType(this)
```

Arguments

`this` an object of the class `mtkDomain`.

Value

a string

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a domain and get the type of its nominal value
d <- mtkDomain(distributionName="unif", domainNominalValue=0.0)
valueType <- getNominalValueType(d)

# For more information, see examples for the mtkDomain or
# mtkFactor classes.
```

`getParameters-methods`*The getParameters method*

Description

Returns the vector of parameters and converts it to a named list.

Usage

```
getParameters(this)
```

Arguments

`this` the underlying object of class `mtkProcess` or its sub-classes.

Value

a named list in which each element corresponds to a parameter. The vector of parameters is converted into a named list such as (name of parameter 1 = value of parameter 1, name of parameter 2 = value of parameter 2, ...).

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a native designer avec the method "Morris"
# implemented in the package "mtk"

designer <- mtkNativeDesigner(design="Morris", information=list(size=20))

# Return the parameters as named list
getParameters(designer)
```

getProcess-methods *The getProcess method*

Description

Gets a process from the workflow.

Usage

```
getProcess(this, name)
```

Arguments

this	the underlying object of class <code>mtkExpWorkflow</code> .
name	a string from "design", "evaluate", or "analyze" to specify the process to fetch.

Value

an object of the class `mtkProcess`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Build a workflow to do the sensitivity analysis for the model "Ishigami"
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

ishiReg <- mtkExpWorkflow(expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
```

```

    )
  run(ishiReg)

  # Extract the process "design" or "evaluate" from the workflow for other uses

  designer <- getProcess(ishiReg, "design")
  evaluator <- getProcess(ishiReg, "evaluate")

```

getResult-methods *The getResult method*

Description

Returns the results produced by the process as an object of the class `mtkResult` or its sub-classes.

Usage

```
getResult(this)
```

Arguments

`this` the underlying object of class `mtkProcess` or its sub-classes

Details

1. Sub-class of the class `mtkProcess` returns objects of different sub-class of the class `mtkResult`. For instance, an object of the class `mtkDesigner` returns an object of the class `mtkDesignerResult`.
2. To fetch the results as a data.frame, please use the method `getData()`.

Value

an object of the class `mtkResult`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```

# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",

```

```

      distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
      distribPara=list(min=-pi, max=pi))

factors <- mtkExpFactors(list(x1,x2,x3))

# Builds the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
      information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the Morris method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
      processesVector = c(design=expl.designer,
      evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)

# Extracts the results produced by the analysis process as an objet of the class mtkAnaly
      getResult(getProcess(expl, "analyze"))

```

getType-methods	<i>The getType method</i>
-----------------	---------------------------

Description

Returns a string indicating the data type associated with the underlying object.

Usage

```
getType(this)
```

Arguments

this	an object of the underlying class.
------	------------------------------------

Value

a string

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Return the data-type associated with the factor
t <- getType(x1)

# Create an object of the 'mtkFeature' class.

f <- mtkFeature(name="x", type="double", val=0.0)

# Return the data-type associated with the feature

getType(f) # gives 'double'
```

getValue-methods	<i>The getValue method</i>
------------------	----------------------------

Description

Returns the name and the value managed by an object of the underlying class.

Usage

```
getValue(this)
```

Arguments

this an object of the class `mtkValue` or its sub-classes.

Value

a named variable

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of the 'mtkValue'
v <- mtkValue(name="x", type="string", val="2.2")

# Fetch the value of the object as a named variable: x = "2.2"

getValue(v)
```

getWeights-methods *The getWeights method*

Description

Returns the weights of the discrete distribution associated with the factor's domain.

Usage

```
getWeights(this)
```

Arguments

`this` the underlying object of the class to proceed (`mtkLevels` and `mtkDomain`).

Value

a list of numeric values.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a discrete domain
x1 <- mtkDomain(distributionName="discrete", domainNominalValue=0,
  distributionParameters=list(type='categorical',
    levels = c(1,2,3,4,5), weights=rep(0.2, 5)))
# Returns the weights of the associated discrete distribution
getWeights(x1)
```

is.finished-methods

The is.finished method

Description

Tests if the process has run and the results produced by the process are available.

Usage

```
is.finished(this)
```

Arguments

`this` the underlying object of the class `mtkProcess`

Value

TRUE or FALSE.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Build a workflow to do the sensitivity analysis for the model "Ishigami"
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))

ishiReg <- mtkExpWorkflow(expFactors=ishi.factors,
  processesVector=c(design=designer)
)
run(ishiReg)

# Extract the process "design" and test if it is correctly executed.

designer <- getProcess(ishiReg, "design")
is.finished(designer)
```

is.ready-methods *The is.ready method*

Description

Tests if the process is ready to run.

Usage

```
is.ready(this)
```

Arguments

`this` the underlying object of the class `mtkProcess`

Value

TRUE or FALSE.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
## This method is usually used only for the package's core programming!!!

# creates an experimental design with the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

factors <- mtkExpFactors(list(x1,x2,x3))

# Build the designer:

expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# Test if the process is ready to run

is.ready(expl.designer)
```

Ishigami

The Ishigami model

Description

The `Ishigami` model is an example evaluator implemented in the native `mtk`. It corresponds to the `Ishigami` function described in Saltelli et al., 2000. The behavior of the model is influenced by three factors `x1`, `x2`, `x3`.

Usage

- `mtkIshigamiEvaluator()`
- `mtkNativeEvaluator(model="Ishigami")`
- `mtkEvaluator(protocol = "R", site = "mtk", service = "Ishigami")`

Details

1. The implementation of the `Ishigami` model includes the object `Ishigami.factors` on the input factors and the class `mtkIshigamiEvaluator` to run the simulations.
2. In `mtk`, there are a few ways to build an evaluator of the `Ishigami` model, but we usually recommend the following class constructors: `mtkIshigamiEvaluator`, `mtkNativeEvaluator`.

References

1. T. Ishigami and T. Homma (1990). An importance quantification technique in uncertainty analysis for computer models, *In: International Symposium on Uncertainty Modelling and Analysis (ISUMA'90)* (1990).
2. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
3. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(Ishigami.factors)`, `help(ishigami.fun, sensitivity)`

Examples

```
### Run simulations of the "Ishigami" model
### for a random sample of input combinations

## Example I: by using the class constructor: mtkIshigamiEvaluator()

#
# Input the factors used in the "Ishigami" model
data(Ishigami.factors)

# Build the workflow:
# 1) specify the design process
expl.designer <- mtkNativeDesigner(design = "BasicMonteCarlo",
  information = list(size=20) )

# 2) specify the evaluation process;
expl.evaluator <- mtkIshigamiEvaluator()

# 3) specify the workflow
expl <- mtkExpWorkflow(expFactors = Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator) )
# Run the workflow and report the results.
run(expl)
```

```

print(expl)

## Example II: by using the class constructor: mtkNativeEvaluator()

# Generate the Ishigami input factors
data(Ishigami.factors)

# Build the workflow:
# 1) specify the design process
expl.designer <- mtkNativeDesigner(design = "BasicMonteCarlo",
information = list(size=20) )

# 2) specify the evaluation process;
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) specify the workflow
expl <- mtkExpWorkflow(expFactors = Ishigami.factors,
                      processesVector = c(design=expl.designer, evaluate=expl.evaluator) )

# Run the workflow and report the results.
run(expl)
print(expl)

## Example III: by using the generic class constructor: mtkEvaluator()

# Generate the Ishigami input factors
data(Ishigami.factors)

# Build the workflow:
# 1) specify the design process
expl.designer <- mtkNativeDesigner(
design = "BasicMonteCarlo", information = list(size=20) )

# 2) specify the evaluation process;
expl.evaluator <- mtkEvaluator(protocol = "R", site = "mtk", service = "Ishigami")

# 3) specify the workflow
expl <- mtkExpWorkflow(expFactors = Ishigami.factors,
                      processesVector = c(design=expl.designer, evaluate=expl.evaluator) )
# Run the workflow and report the results.
run(expl)
print(expl)

```

Ishigami.factors	<i>Input factors of the Ishigami model</i>
------------------	--

Description

The names and uncertainty distributions of the 3 input factors x_1 , x_2 , x_3 involved in the [Ishigami](#) function which is usually used as a model example for uncertainty and sensitivity analysis methods.

Usage

```
data(Ishigami.factors)
```

Format

an object of class `mtkExpFactors`.

References

Saltelli, A., Chan, K., & Scott, E. M. (Eds.). (2000). Sensitivity analysis (Vol. 134). New York: Wiley.

See Also

`help(Ishigami)`, `help(ishigami.fun,sensitivity)`

Examples

```
# The code used to generate the Ishigami.factors is as follows:

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

Ishigami.factors <- mtkExpFactors(list(x1,x2,x3))

# To import the Ishigami.factors, just use the following line
data(Ishigami.factors)
```

make.mtkFactor	<i>The make.mtkFactor function</i>
----------------	------------------------------------

Description

Creates a new input factor and specifies its uncertainty distribution.

Usage

```
make.mtkFactor(name="unkown", id="unkown", unit="", type="",
  nominal=NA, distribName='unknown', distribPara=list(), features=list())
```

Arguments

name	the name of the input factor.
id	the name of the factor in the simulation code, if different from <code>name</code> (optional).
unit	the measurement unit of the factor values (optional). This can be used in graphics or reports, for example.
type	the data-type of the factor's values (optional).
nominal	the nominal value of the factor.
distribName	the name of the probability distribution describing the factor's uncertainty.
distribPara	the list of distribution parameters.
features	the list of factor's features.

Details

The `distribName` argument must use the R terminology, for example `norm` for the normal distribution or `unif` for the uniform one; see `help(distributions)`.

Value

an object of class `mtkFactor`.

Author(s)

Juhui WANG, MIA-jouy, INRA, Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod

Examples

```
# Define a new continuous factor
make.mtkFactor("A", distribName="unif", distribPara=list(min=0,max=1))
# Define a new discrete factor
make.mtkFactor("D", distribName="discrete", distribPara =
list(type='categorical', levels=c('a','b','c'),
weights=rep(0.33,3))
)
```

```
make.mtkFeatureList
```

The make.mtkFeatureList function

Description

Creates a list of `mtkFeature` elements from a simple named list.

Usage

```
make.mtkFeatureList(x=list())
```

Arguments

`x` a named list.

Value

a list of objects from the class `mtkFeature`.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a list of mtkFeature for the Features: min, max, shape.
make.mtkFeatureList(list(min=-1,max=+1,shape="square"))
```

```
make.mtkParameterList
```

The make.mtkParameterList function

Description

Creates a list of `mtkParameter` elements from a simple named list.

Usage

```
make.mtkParameterList(x=list())
```

Arguments

`x` a named list.

Value

a list of objects from the class `mtkParameter`.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a list of mtkParameter from a named list for the parameters: min, max, shape.
make.mtkParameterList(list(min=-1,max=+1,shape="hello"))
```

```
Morris
```

The Morris method

Description

A mtk compliant implementation of the `morris` method for experiments design and sensitivity analysis.

Usage

- `mtkMorrisDesigner(listParameters = NULL)`
- `mtkNativeDesigner(design="Morris", information=NULL)`
- `mtkMorrisAnalyser(listParameters = NULL)`
- `mtkNativeAnalyser(analyze="Morris", information=NULL)`

Parameters

- `r`: the number of trajectories or a pair (`r1`, `r2`) if the version due to Campolongo et al. (2007) is used.
- `type`: the type of design (either `oat` or `simplex`).
- `levels`: the number of levels per factor (if `type = "oat"`).
- `grid.jump`: the length of the steps within the trajectories (if `type = "oat"`).
- `scale.factor`: a numeric value, the homothety factor of the (isometric) simplexes (if `type = "simplex"`).
- `scale`: logical. If TRUE, the input design of experiments is scaled before computing the elementary effects so that all factors vary within the range [0,1].
- `shrink`: a scalar or a vector of scalars between 0 and 1, specifying shrinkage to be used on the probabilities before calculating the quantiles.

Details

1. The `mtk` implementation uses the `morris` function of the `sensitivity` package. For further details on the arguments and the behavior, see `help(morris, sensitivity)`.
2. The `mtk` implementation of the Morris method includes the following classes:
 - `mtkMorrisDesigner`: for the Morris design processes.
 - `mtkMorrisAnalyser`: for Morris analysis processes.
 - `mtkMorrisDesignerResult`: to store and manage the design.
 - `mtkMorrisAnalyserResult`: to store and manage the analysis results.
3. Many ways to create a Morris designer are available in `mtk`, but we recommend the following class constructors: `mtkMorrisDesigner` or `mtkNativeDesigner`.
4. Many ways to create a Morris analyser are available in `mtk`, but we recommend the following class constructors: `mtkMorrisAnalyser` or `mtkNativeAnalyser`.
5. The method `Morris` is usually used both to build the experiment design and to carry out the sensitivity analysis. In such case, we can use the `mtkDefaultAnalyser` instead of naming explicitly the method for sensitivity analysis (see example III in the examples section)

References

1. Campolongo, F., J. Cariboni, and A. Saltelli, 2007. An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. Saltelli A., Chan K. and Scott E. M., 2000. *Sensitivity Analysis*. Wiley, New York
3. Pujol G., 2009, Simplex-based screening designs for estimating metamodels, *Reliability Engineering and System Safety* 94, 1156–1160.

See Also

`help(morris, sensitivity)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Morris" method

# Example I: by using the class constructors: mtkMorrisDesigner() and mtkMorrisAnalyser()

# Generate the factors
```

```

data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner(
  listParameters = list(r=20, type="oat",
    levels=4, grid.jump=2)
)

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
    analyze=expl.analyser)
)

# Run the workflow and reports the results.
run(expl)
print(expl)
plot(expl)
# plot3d.morris(extractData(expl, name="analyze"))

## Example II: by using the class constructors: mtkNativeDesigner() and mtkMorrisAnalyser()

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkNativeDesigner(design = "Morris",
  information = list(r=20, type="oat",
    levels=4, grid.jump=2)
)

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
    analyze=expl.analyser)
)

```

```

# Run the workflow and reports the results.
run(expl)
print(expl)

## Example III: by using the class constructors: mtkMorrisDesigner() and mtkDefaultAnal

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner( listParameters =
list(r=20, type="oat",
levels=4, grid.jump=2))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkDefaultAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
processesVector = c(design=expl.designer,
evaluate=expl.evaluator,
analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)

```

mtk.analyserAddons *The mtk.analyserAddons function*

Description

A function used to extend the "mtk" package with new analysis methods programmed as R functions. The `mtk.analyserAddons` function takes a R file as input and converts it into a `mtk` compliant class which can be seamlessly integrated into the `mtk` package.

Usage

```

mtk.analyserAddons(where = NULL, library = NULL,
  authors = NULL, name = NULL,
                        main = NULL,
                        summary = NULL,
                        plot = NULL,
                        print = NULL)

```


Arguments

<code>where</code>	NULL or a file holding the R function to convert.
<code>library</code>	NULL or the name of the library if the R function to convert is held in a library.
<code>authors</code>	NULL or information about the authors of the R function.
<code>name</code>	a string to name the method when used with the "mtk" package.
<code>main</code>	the R function which implements the method.
<code>summary</code>	NULL or a subversion of the <code>summary</code> function provided with the method.
<code>plot</code>	NULL or a reprogrammed version of the <code>plot</code> function provided with the method.
<code>print</code>	NULL or a reprogrammed version of the <code>print</code> function provided with the method.

Details

The new method must be programmed according to the following syntax:

```
main <- function(X, Y, ...) where X is a data.frame holding the experiment design,
and Y is a data.frame holding the results produced by the model simulation.
```

The function `main` returns a named list with two elements: `main` and `information`. The element `main` holds the result of the sensitivity analysis and the element `information` is optional, may be used to give supplementary information about the analysis process and the produced results.

Furthermore, in order to report the analysis results more precisely, users can redefine the generic functions: `summary (object, ...)`, `plot(x,y, ...)`, `print(x, ...)`.

Value

`invisible()`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# an example implementation of the method "Regression"
# called here "RegressionTest" is held in the file
# "inst/extdata/regressionSI.R"

rFile <- "regressionSI.R"
rFile <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", rFile, sep = "")

# to convert the method "RegressionTest" to S4 classes
# compliant with the "mtk" package. The generated "mtk" compliant class
```

```
# is called "mtkXXXAnalyser.R" where XXX corresponds to the name of the method.

mtk.analyserAddons(where=rFile, authors="H. Monod, INRA",
  name="RegressionTest",
  main="regressionSI", print="print.regressionSI",
  plot="plot.regressionSI")

# To use the method "RegressionTest" with the package "mtk",
# just source the generated new files

source("mtkRegressionTestAnalyser.R")

## Use the method "RegressionTest" to do sensitivity analysis

# 1) Define the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# 2) Create a workflow with the "Ishigami" model and analyze it with the new method
ishiReg <- mtkExperiment(expFactors=ishi.factors,
  design="BasicMonteCarlo", designInfo=list(size=20),
  model="Ishigami",
  analyze="RegressionTest",
)
# 3) Run the workflow and report the results
run(ishiReg)
summary(ishiReg)
```

mtk.designerAddons *The mtk.designerAddons function*

Description

A function used to extend the `mtk` package with new design methods programmed as R functions. The `mtk.designerAddons` function takes a R file as input and converts it into a `mtk` compliant class which can be seamlessly integrated into the `mtk` package.

Usage

```
mtk.designerAddons(where = NULL, library = NULL,
  authors = NULL, name = NULL,
  main = NULL, summary = NULL,
  plot = NULL, print = NULL)
```

Arguments

<code>where</code>	NULL or the file containing the R functions to convert into native <code>mtk</code> methods.
<code>library</code>	NULL or the name of the package if the R function to convert is included in a package.

authors	NULL or information about the authors of the R function.
name	a string to name the method when used with the mtk package.
main	the name of the R function implementing the designer.
summary	NULL or a special version of the summary function provided in the file where.
plot	NULL or a special version of the plot function provided in the file where.
print	NULL or a special version of the print function provided in the file where.

Details

The main function must have the following syntax:

```
main <- function(factors, distribNames, distribParameters, ...)
```

where `factors` is either a number or a list of strings giving the names of the n input factors, `distribNames` is a list of string giving the names of the n probability distributions that describe the factors' uncertainty, and `distribParameters` is a list of n lists specifying the distribution parameters associated with the uncertainty domains.

The R function `main` returns a named list with two elements: the element `main` is a `data.frame` containing the generated experiment design and the element `information` is an optional list that may be used to provide complementary information about the design process and results.

Furthermore, in order to give more advanced data reporting mechanism with the new method, users can redefine the generic functions:

```
summary(object, ...), plot(x, y, ...), print(x, ...)
```

Value

`invisible()`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# an example implementation of the method "MC" is held in the file
# "inst/extdata/montecarloDesigner.R"

rFile <- "montecarloDesigner.R"
rFile <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", rFile, sep = "")

# to convert this special version of the method "MC"
# to S4 classes compliant with the "mtk" package. The generated "mtk" compliant class
# is called "mtkXXXDesigner.R" where XXX corresponds to the name of the method.
mtk.designerAddons(where=rFile, authors="H. Monod, INRA", name="MC",
main="basicMonteCarlo")
```

```
# to use the method "MC" with the package "mtk",
# just source the generated new files

source("mtkMCDesigner.R")

## Use the "mtkMCDesigner" with the "mtk" package in a seamless way:

# 1) Define the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# 2) Specify a new workflow with the new method
ishiReg <- mtkExperiment(expFactors=ishi.factors,design="MC",
  model="Ishigami", analyze="Regression",
  designInfo=list(size=20))

# 3) Run the workflow and report the results
run(ishiReg)
summary(ishiReg)
```

mtk.evaluatorAddons

The mtk.evaluatorAddons function

Description

A function used to extend the "mtk" package with new models programmed as R functions. The `mtk.evaluatorAddons` function takes a R file as input and converts it into a `mtk` compliant class which can be seamlessly integrated into the `mtk` package.

Usage

```
mtk.evaluatorAddons(where = NULL, library = NULL,
  authors = NULL, name = NULL, main = NULL,
  summary = NULL, plot = NULL,
  print = NULL)
```

Arguments

<code>where</code>	NULL or a file holding the R function to convert.
<code>library</code>	NULL or the name of the library if the R function to convert is held in a library.
<code>authors</code>	NULL or information about the authors of the R function.
<code>name</code>	a string to name the model when used with the "mtk" package.
<code>main</code>	the R function which implements the model.
<code>summary</code>	NULL or a special version of the "summary" function provided with the model.

plot	NULL or a special version of the "plot" function provided with the model.
print	NULL or a special version of the "print" function provided with the model.

Details

The new model must be programmed according to the following syntax:

```
main <- function(X, ...) where X is a data.frame holding the experiment design used to
run the model simulation.
```

The function `main` returns a named list with two elements: `main` and `information`. The element `main` holds the result of the model simulation and the element `information` is optional, may be used to give supplementary information about the simulation process and its results.

Furthermore, users can redefine the following generic functions to report the results more precisely:

```
summary (object, ...), plot(x, y, ...), print(x, ...).
```

Value

`invisible()`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# an example implementation of the model "WW" is held
# in the file "inst/extdata/wwdm.R"

rFile <- "wwdm.R"
rFile <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", rFile, sep = "")

# to covert the model "WW" to a S4 classes compliant with the "mtk" package.
# The generated "mtk" compliant class is called "mtkXXxEvaluator.R" where XXX corresponds
# to the name of the model.

mtk.evaluatorAddons(where=rFile, authors="H. Monod, INRA", name="WW", main="wwdm.simule")

# to use the model evaluator "WW" with the package "mtk",
# just source the generated new files

source("mtkWWEvaluator.R")

## Use the "mtkWWEvaluator" with the "mtk" package in a seamless way:

# 1) Define the factors

Eb <- make.mtkFactor(name="Eb", distribName="unif",
```

```

        nominal=1.85, distribPara=list(min=0.9, max=2.8))
Eimax <- make.mtkFactor(name="Eimax", distribName="unif",
        nominal=0.94, distribPara=list(min=0.9, max=0.99))
K <- make.mtkFactor(name="K", distribName="unif", nominal=0.7,
        distribPara=list(min=0.6, max=0.8))
Lmax <- make.mtkFactor(name="Lmax", distribName="unif", nominal=7.5,
        distribPara=list(min=3, max=12))
A <- make.mtkFactor(name="A", distribName="unif", nominal=0.0065,
        distribPara=list(min=0.0035, max=0.01))
B <- make.mtkFactor(name="B", distribName="unif", nominal=0.00205,
        distribPara=list(min=0.0011, max=0.0025))
TI <- make.mtkFactor(name="TI", distribName="unif", nominal=900,
        distribPara=list(min=700, max=1100))

WW.factors <- mtkExpFactors(list(Eb,Eimax,K,Lmax,A,B,TI))

# 2) Build a workflow for the "WW" model

exp <- mtkExperiment(expFactors=WW.factors,
design="Morris",designInfo=list(type="oat",
r=10, levels=5, grid.jump=3),
model="WW", modelInfo=list(year=3),
analyze="Morris", analyzeInfo=list(type="oat",
r=10, levels=5, grid.jump=3))

## 3) Run the workflow and reports the results

run(exp)
summary(exp)

```

mtkAnalyser

The constructor of the class mtkAnalyser

Description

The constructor

Usage

```

mtkAnalyser(protocol = "R", site = "mtk", service = "",
parameters= NULL, parametersList = NULL, ready = TRUE,
state = FALSE, result = NULL)

```

Arguments

protocol	a string from "http", "system", "R" respectively representing if the process is implemented remotely, locally or as R function.
site	the site where the process is implemented if remotely or the package where the process is implemented if as a R function.
service	a string corresponding to the name of the method implemented in the package "mtk" or the service that implements the process if remotely.

parameters	a vector of [mtkParameter] representing the parameters necessary to run the process.
parametersList	a named list containing the parameters necessary to run the process. It gives another way to specify the parameters.
ready	a logical to indicate if the process is ready to run.
state	a logical to indicate if the process finished running and the results are available.
result	an object of a class derived from [mtkAnalyserResult] to hold the results produced by the analyser.

Value

an object of the [mtkAnalyser](#) class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Creates an analyser avec the method "Morris" implemented
# in the package "mtk"
analyser <- mtkAnalyser(service="Morris",
parametersList=list(nboot=20))
```

`mtkAnalyser-class` *The mtkAnalyser class*

Description

The `mtkAnalyser` class is a sub-class of the class [mtkProcess](#) used to manage the sensitivity analysis process. It provides all the slots and methods defined in the class [mtkProcess](#).

Class Hierarchy

Parent classes : [mtkProcess](#)

Direct Known Subclasses : [mtkNativeAnalyser](#), [mtkMorrisAnalyser](#), etc.

Constructor

[mtkAnalyser](#) signature(protocol="R", site="mtk", service="", parameters=NULL, parametersList=NULL, ready=TRUE, state=FALSE, result=NULL)

Slots

`name:` (`character`) a string to name the processing type. Here, it always takes "analyze".

`protocol:` (`character`) a string to name the protocol used to run the process: http, system, R, etc.

`site:` (`character`) a string to indicate where the service is located.

`service:` (`character`) a string to name the method or the service (if remotely) to invoke.

`parameters:` (`vector`) a vector of `mtkParameter` containing the parameters to pass while calling the service.

`ready:` (`logical`) a logical to tell if the process is ready to run.

`state:` (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

`result:` (`ANY`) NULL or an object of the class `mtkAnalyserResult` to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkAnalyser", `name` = "character"): Not used, just inherited from the parent class.

`setParameters` signature(`this` = "mtkAnalyser", `f` = "vector"): Assigns a new vector of parameters to the process.

`getParameters` signature(`this` = "mtkAnalyser"): Returns the parameters as a named list.

`is.ready` signature(`this` = "mtkAnalyser"): Tests if the process is ready to run.

`setReady` signature(`this` = "mtkAnalyser", `switch` = "logical"): Makes the process ready to run.

`is.ready` signature(`this` = "mtkAnalyser"): Tests if the results produced by the process are available.

`setReady` signature(`this` = "mtkAnalyser", `switch` = "logical"): Marks the process as already executed.

`getResult` signature(`this` = "mtkAnalyser"): Returns the results produced by the process as a `mtkAnalyserResult`.

`getData` signature(`this` = "mtkAnalyser"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(`this` = "mtkAnalyser"): Returns all data managed by the process as a named list.

`run` signature(`this` = "mtkAnalyser", `context` = "mtkExpWorkflow"): Runs the sensitivity analysis on the model defined in the context.

`summary` signature(`object` = "mtkAnalyser"): Provides a summary of the results produced by the process.

`print` signature(`x` = "mtkAnalyser"): Prints a report of the results produced by the process.

`plot` signature(`x` = "mtkAnalyser"): Builds a plot of the results produced by the process.

`report` signature(`this` = "mtkAnalyser"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Creates an analyser avec the method "Morris"
# implemented in the package "mtk".

analyser <- mtkAnalyser(service="Morris",
  parametersList=list(nboot=20))
```

`mtkAnalyserResult` *The constructor of the class `mtkAnalyserResult`*

Description

The constructor

Usage

```
mtkAnalyserResult(main = data.frame(), information = list())
```

Arguments

<code>main</code>	a <code>data.frame</code> to hold the results produced with the analyser.
<code>information</code>	a named list containing optional information about the managed data and process.

Value

an object of the `mtkAnalyserResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Construct an object of the \code{mtkAnalyserResult} class
# from a data.frame.
data <- data.frame()
result <- mtkAnalyserResult(main=data,
information = list(method="Morris", model="Ishigami"))
```

```
mtkAnalyserResult-class
```

The mtkAnalyserResult class

Description

A class to manage the results produced by the sensitivity analysis process.

Class Hierarchy

Parent classes : `mtkResult`

Direct Known Subclasses : `mtkMorrisAnalyserResult`, `mtkPLMMAAnalyserResult`, etc.

Constructor

```
{mtkAnalyserResult} signature(main = data.frame(), information = list())
```

Slots

main: (`data.frame`) a data.frame to hold the analysis results produced with the analyser.

information: (`list`) a named list containing optional information about the managed data and process.

Methods

`summary` signature(object = "mtkAnalyserResult"): Provides a summary of the analysis results produced with the analyser.

`print` signature(x = "mtkAnalyserResult"): Prints a report of the analysis results produced with the analyser.

`plot` signature(x = "mtkAnalyserResult"): Plots the analysis results produced with the analyser.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Construct an object of the \code{mtkAnalyserResult} class
# from a data.frame.
data <- data.frame()
result <- mtkAnalyserResult(main=data, information
= list(method="Morris", model="Ishigami"))
```

mtkBasicMonteCarloDesigner

The constructor of the class mtkBasicMonteCarloDesigner

Description

The constructor

Usage

```
mtkBasicMonteCarloDesigner(mtkParameters = NULL,
  listParameters = NULL)
```

Arguments

mtkParameters

a vector of [mtkParameter](#) representing the parameters necessary to run the process.

listParameters

a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkBasicMonteCarloDesigner](#) class

Details

See the `BasicMonteCarlo` method with `help(BasicMonteCarlo)`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(BasicMonteCarlo)
```

```
mtkBasicMonteCarloDesigner-class
```

```
The mtkBasicMonteCarloDesigner class
```

Description

The `mtkBasicMonteCarloDesigner` class is a sub-class of the class `mtkDesigner`. It implements the `BasicMonteCarlo` method for experiments design and provides all the slots and methods defined in the class `mtkDesigner`.

Class Hierarchy

Parent classes : `mtkDesigner`

Direct Known Subclasses :

Constructor

mtkBasicMonteCarloDesigner signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (`character`) always takes the string "design".

protocol: (`character`) always takes the string "R".

site: (`character`) always takes the string "mtk".

service: (`character`) always takes the string "BasicMonteCarlo".

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

setName signature(`this` = "mtkBasicMonteCarloDesigner", `name` = "character"): Method inherited from the parent class.

setParameters signature(`this` = "mtkBasicMonteCarloDesigner", `f` = "vector"): Assigns new parameters to the process.

getParameters signature(`this` = "mtkBasicMonteCarloDesigner"): Returns the parameters as a named list.

is.ready signature(= "mtkBasicMonteCarloDesigner"): Tests if the process is ready to run.

setReady signature(`this` = "mtkBasicMonteCarloDesigner", `switch` = "logical"): Makes the process ready to run.

is.ready signature(= "mtkBasicMonteCarloDesigner"): Tests if the results produced by the process are available.

setReady signature(this = "mtkBasicMonteCarloDesigner", switch = "logical"): Marks the process as already executed.

getResult signature(this = "mtkBasicMonteCarloDesigner"): Returns the results produced by the process as a [mtkBasicMonteCarloDesignerResult](#).

getData signature(this = "mtkBasicMonteCarloDesigner"): Returns the results produced by the process as a data.frame.

serializeOn signature(this = "mtkBasicMonteCarloDesigner"): Returns all data managed by the process as a named list.

run signature(this = "mtkBasicMonteCarloDesigner", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

summary signature(object = "mtkBasicMonteCarloDesigner"): Provides a summary of the results produced by the process.

print signature(x = "mtkBasicMonteCarloDesigner"): Prints a report of the results produced by the process.

plot signature(x = "mtkBasicMonteCarloDesigner"): Plots the results produced by the process.

report signature(this = "mtkBasicMonteCarloDesigner"): Reports the results produced by the process.

Details

See the `BasicMonteCarlo` method with `help(BasicMonteCarlo)`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the BasicMontecarlo method: help(basicMonteCarlo)
```

`mtkBasicMonteCarloDesignerResult`*The constructor of class* `mtkBasicMonteCarloDesignerResult`

Description

The constructor

Usage

```
mtkBasicMonteCarloDesignerResult(main, information=NULL)
```

Arguments

<code>main</code>	a <code>data.frame</code> holding the experimental design produced by the designer.
<code>information</code>	a named list containing the information about the managed data and the underlying process.

Value

an object of the `mtkBasicMonteCarloDesignerResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(BasicMonteCarlo)
```

`mtkBasicMonteCarloDesignerResult-class`*The mtkBasicMonteCarloDesignerResult class*

Description

A class to collect the experimental design produced by the designer implementing the method `BasicMonteCarlo`.

Class Hierarchy

Parent classes : `mtkDesignerResult`

Direct Known Subclasses :

Constructor

`mtkBasicMonteCarloDesignerResult` signature(main,information=NULL)

Slots

main: (`data.frame`) a data-frame holding the experimental design.

information: (`list`) a named list containing optional information about the managed data or the underlying process.

Methods

`summary` signature(object = "mtkBasicMonteCarloDesignerResult"): Provides a summary of the experimental design produced by the designer.

`print` signature(x = "mtkBasicMonteCarloDesignerResult"): Prints a report of the experimental design produced by the designer.

`plot` signature(x = "mtkBasicMonteCarloDesignerResult"): Plots the experimental design produced by the designer.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(BasicMonteCarlo)
```

mtkDefaultAnalyser *The constructor of the class mtkDefaultAnalyser*

Description

This class is used when both the experimental design and the sensitivity analysis are fulfilled with the same method.

Usage

```
mtkDefaultAnalyser()
```

Value

an object of the `mtkDefaultAnalyser` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# creates a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the "Morris" method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
```



```

expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)

```

mtkDefaultAnalyser-class

The mtkDefaultAnalyser class

Description

The `mtkDefaultAnalyser` class is a sub-class of the class `mtkAnalyser`. It provides all the slots and methods defined in the class `mtkAnalyser`. The `mtkDefaultAnalyser` class is used when the method used for the sensitivity analysis is the same as the method used for the experiment design.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkDefaultAnalyser` signature()

Slots

name: (`character`) always takes the string "analyze".

protocol: (`character`) a string to name the protocol used to run the process: http, system, R, etc.

site: (`character`) a string to indicate where the service is located.

service: (`character`) a string to name the service to invoke.

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

setName signature(this = "mtkDefaultAnalyser", name = "character"): Not used, method inherited from the parent class.

setParameters signature(this = "mtkDefaultAnalyser", f = "vector"): Assigns new parameters to the process.

getParameters signature(this = "mtkDefaultAnalyser"): Returns the parameters as a named list.

is.ready signature(= "mtkDefaultAnalyser"): Tests if the process is ready to run.

setReady signature(this = "mtkDefaultAnalyser", switch = "logical"): Makes the process ready to run.

is.ready signature(= "mtkDefaultAnalyser"): Tests if the results produced by the process are available.

setReady signature(this = "mtkDefaultAnalyser", switch = "logical"): Marks the process as already executed.

getResult signature(this = "mtkDefaultAnalyser"): Returns the results produced by the process as a [mtkAnalyserResult](#).

getData signature(this = "mtkDefaultAnalyser"): Returns the results produced by the process as a data.frame.

serializeOn signature(this = "mtkDefaultAnalyser"): Returns all data managed by the process as a named list.

run signature(this = "mtkDefaultAnalyser", context= "mtkExpWorkflow"): Runs the sensitivity analysis defined in the context.

summary signature(object = "mtkDefaultAnalyser"): Provides a summary of the results produced by the process.

print signature(x = "mtkDefaultAnalyser"): Prints a report of the results produced by the process.

plot signature(x = "mtkDefaultAnalyser"): Reports graphically the results produced by the process.

report signature(this = "mtkDefaultAnalyser"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))
# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design = "Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
```

```

expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the "Morris" method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)

```

mtkDesigner

*The constructor of the class mtkDesigner***Description**

The constructor

Usage

```

mtkDesigner(protocol = "R", site = "mtk", service = "",
  parameters = NULL, parametersList = NULL, ready = TRUE,
  state = FALSE, result = NULL)

```

Arguments

protocol	(character) a string from "http", "system", "R" respectively representing if the process is implemented remotely, locally or as R function.
site	(character) a string to indicate where the service is located.
service	(character) a string to name the method or the service (if remotely) to invoke.
parameters	a vector of [mtkParameter] representing the parameters necessary to run the process.
parametersList	a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.
ready	a logical to indicate if the process is ready to run.
state	a logical to indicate if the process finished running and the results are available.
result	an object of a class derived from [mtkDesignerResult] to hold the results produced by the designer.

Valuean object of the [mtkDesigner](#) class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a designer with the method "Morris"
# implemented in the package "mtk"
designer <- mtkDesigner(service="Morris",
parametersList=list(nboot=20))
```

mtkDesigner-class *The mtkDesigner class*

Description

The `mtkDesigner` class is a sub-class of the class `mtkProcess` used to manage the experiments design task. It provides all the slots and methods defined in the class `mtkProcess`.

Class Hierarchy

Parent classes : `mtkProcess`

Direct Known Subclasses : `mtkNativeDesigner`, `mtkMorrisDesigner`, etc.

Constructor

mtkDesigner signature(protocol = "R", site = "mtk", service = "", parameters = NULL, parametersList = NULL, ready = TRUE, state = FALSE, result = NULL)

Slots

name: (`character`) always takes the string "design".

protocol: (`character`) a string to name the protocol used to run the process: http, system, R, etc.

site the site where the process is implemented if remotely or the package where the process is implemented if as a R function.

service a string corresponding to the name of the method implemented in the package "mtk" or the service that implements the process if remotely.

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder from the class `mtkDesignerResult` to hold the results produced by the process.

Methods

setName signature(this = "mtkDesigner", name = "character"): Not used, method inherited from the parent class.

setParameters signature(this = "mtkDesigner", f = "vector"): Assigns new parameters to the process.

getParameters signature(this = "mtkDesigner"): Returns the parameters as a named list.

is.ready signature(= "mtkDesigner"): Tests if the process is ready to run.

setReady signature(this = "mtkDesigner", switch = "logical"): Makes the process ready to run.

is.ready signature(= "mtkDesigner"): Tests if the results produced by the process are available.

setReady signature(this = "mtkDesigner", switch = "logical"): Marks the process as already executed.

getResult signature(this = "mtkDesigner"): Returns the results produced by the process as mtkDesignerResult.

getData signature(this = "mtkDesigner"): Returns the results as a data.frame.

serializeOn signature(this = "mtkDesigner"): Returns all data managed by the process as a named list.

run signature(this = "mtkDesigner", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

summary signature(object = "mtkDesigner"): Provides a summary of the results produced by the process.

print signature(x = "mtkDesigner"): Prints a report of the results produced by the process.

plot signature(x = "mtkDesigner"): Reports graphically the results produced by the process.

report signature(this = "mtkDesigner"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a designer with the method "Morris"
# implemented in the package "mtk"
designer <- mtkDesigner(service="Morris",
  parametersList=list(nboot=20))
```

`mtkDesignerResult` *The constructor of the class `mtkDesignerResult`*

Description

The constructor

Usage

```
mtkDesignerResult(main=data.frame(), information=list())
```

Arguments

`main` a data.frame holding the experimental design produced by the designer.
`information` a named list containing the information about the experiments design.

Value

an object of the `mtkDesignerResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Construct an object of the \code{mtkDesignerResult}
# class from a data-frame.
data <- data.frame()
expDesign <- mtkDesignerResult(main=data,
  information = list(sampling="Fast"))
```

`mtkDesignerResult-class`
The `mtkDesignerResult` class

Description

A class to collect the experimental design produced by an experiments design process.

Class Hierarchy

Parent classes : `mtkResult`

Direct Known Subclasses : `mtkSobolDesignerResult`, `mtkMorrisDesignerResult`, etc.

Constructor

```
mtkDesignerResult signature(main=data.frame(),information=list())
```

Slots

main: (`data.frame`) a `data.frame` holding the experimental design produced by the process.

information: (`list`) a named list containing optional information about the experiments design.

Methods

summary signature(object = "mtkDesignerResult"): Provides a summary of the experimental design produced by the design process.

print signature(x = "mtkDesignerResult"): Prints a report of the experimental design produced by the design process.

plot signature(x = "mtkDesignerResult"): Plots the experimental design produced by the design process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Construct an object of the mtkDesignerResult class from a data-frame.
data <- data.frame()
expDesign <- mtkDesignerResult(main=data,
  information = list(sampling="Fast"))
```

mtkDomain

The constructor of the class `mtkDomain`

Description

The constructor of the class `mtkDomain`.

Usage

```
mtkDomain(distributionName="unknown", domainNominalValue=0,
  distributionParameters=list())
```

Arguments

- `distributionName`
a string corresponding to the distribution name associated with the domain.
- `domainNominalValue`
an object of the `mtkValue` class or information allowing to create an object of the `mtkValue` class, used to hold the nominal value of the domain.
- `distributionParameters`
a list to hold the parameters of the distribution associated with the domain.

Value

an object of the `mtkDomain` class

Examples

```
# creates a new domain with a continue distribution
d <- mtkDomain(distributionName="unif", domainNominalValue=0,
distributionParameters = list(max=3, min=0))

# creates a new domain with a discrete distribution
d <- mtkDomain(distributionName="discrete", domainNominalValue=3,
distributionParameters = list(type='categorical',
levels = c(1,2,3,4,5), weights=rep(0.2, 5)))
```

mtkDomain-class	<i>The mtkDomain class</i>
-----------------	----------------------------

Description

The `mtkDomain` class is a class used to manage the uncertainty domain associated with a factor.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

mtkDomain signature(`distributionName` = "unknown", `domainNominalValue` = 0, `distributionParameters` = list())

Slots

`distributionName`: (`character`) a string representing the distribution law.
`nominalValue`: (`mtkValue`) the nominal value of the domain.
`levels`: (`mtkLevels`) an object of `mtkLevels` class.
`distributionParameters`: (`list`) a list of `mtkParameter` objects.

Methods

`initialize` signature(.Object = "mtkDomain"): The initializer of the class `mtkDomain`.

`getDistributionName` signature(this = "mtkDomain"): Returns the distribution's name.

`getNominalValue` signature(this = "mtkDomain"): Returns the the nominal value.

`getNominalValueType` signature(this = "mtkDomain"): Returns the value type of the nominal value .

`getDiscreteDistributionType` signature(this = "mtkDomain"): Returns the type of the discrete distribution.

`getLevels` signature(this="mtkDomain"): Fetches the the levels managed by the domain.

`getWeights` signature(this="mtkDomain"): Fetches the the weights managed by the domain.

`getDistributionParameters` signature(this = "mtkDomain"): Fetches the parameters of the distributions associated with the domain.

`setLevels` signature(this="mtkDomain", levels = "vector"): Affects a new level to the domain where levels is a named list like `list (type='categorical', levels=c(1,2,3,4,5), weights=...)`

`setLevels` signature(this="mtkDomain", levels = "mtkLevels"): Affects a new level to the domain where levels is an object from the class `mtkLevels`.

`setDistributionParameters` signature(this = "mtkDomain", aDistParamList="list"): Affects a new list of parameters to the domain. For continue distributions, `aDistParamList` may be a list of objects of the class `mtkParameter` or a named list like `list (max=5, min=1)` . For discrete distributions, `aDistParamList` may be a named list containing an object of the class `mtkLevels` or a named list like `list (type='categorical', levels = c(1,2,3,4,5), weights=...)` from which we can build an object of the class `mtkLevels`.

`print` signature(x = "mtkDomain"): Prints the data managed by the domain.

`show` signature(object = "mtkDomain"): Displays the underlying object of the class `mtkDomain`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a new domain with a continue distribution
d <- mtkDomain(distributionName="unif", domainNominalValue=0,
distributionParameters = list(max=3, min=0))

# Create a new domain with a discrete distribution
d <- mtkDomain(distributionName="discrete", domainNominalValue=3,
distributionParameters = list(type='categorical',
levels = c(1,2,3,4,5), weights=rep(0.2, 5)))
# Change the levels to list(type='categorical', levels = c('a','b','c','d'), weights=rep(0.25, 4))
setLevels(d, list(type='categorical', levels = c('a','b','c','d'), weights=rep(0.25, 4)))
```

mtkEvaluator

The constructor of the class mtkEvaluator

Description

The constructor

Usage

```
mtkEvaluator(protocol = "R", site = "mtk", service = "",  
             parameters = NULL, parametersList = NULL, ready = TRUE,  
             state = FALSE, result = NULL)
```

Arguments

protocol	a string from "http", "system", "R" respectively representing if the process is implemented remotety, locally or as R function.
site	the site where the process is implemented if remotely or the package where the process is implemented if as a R function.
service	a string corresponding to the name of the method implemented in the package "mtk" or the service that implements the process if remotely.
parameters	a vector of [mtkParameter] representing the parameters necessary to run the process.
parametersList	a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.
ready	a logical to indicate if the process is ready to run.
state	a logical to indicate if the process finished running and the results are available.
result	an object of the class [mtkEvaluatorResult] to hold the results produced by the Evaluator.

Value

an object of the [mtkEvaluator](#) class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create an evaluator with the model "Ishigami" implemented in the package "mtk".

evaluator1 <- mtkEvaluator(service="Ishigami")

# Create an evaluator avec the model "WWDm" implemented in the package "mtk"
evaluator2 <- mtkEvaluator(service="WWDm",
  parametersList=list(year=3, tout=FALSE))
```

mtkEvaluator-class *The mtkEvaluator class*

Description

The `mtkEvaluator` class is a sub-class of the class `mtkProcess` used to manage the model simulation. It provides all the slots and methods defined in the class `mtkProcess`.

Class Hierarchy

Parent classes : `mtkProcess`

Direct Known Subclasses : `mtkNativeEvaluator`, `mtkWWDMEvaluator`, etc.

Constructor

mtkEvaluator signature(protocol = "R", site = "mtk", service = "", parameters = NULL, parametersList = NULL, ready = TRUE, state = FALSE, result = NULL)

Slots

name: (`character`) always takes the string "evaluate".

protocol: (`character`) a string to name the protocol used to run the process: http, system, R, etc.

site: (`character`) a string to indicate where the service is located.

service: (`character`) a string to name the service to invoke.

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

setName signature(this = "mtkEvaluator", name = "character"): Not used, method inherited from the parent class.

setParameters signature(this = "mtkEvaluator", f = "vector"): Assigns new parameters to the process.

getParameters signature(this = "mtkEvaluator"): Returns the parameters as a named list.

`is.ready` signature(= "mtkEvaluator"): Tests if the process is ready to run.

`setReady` signature(this = "mtkEvaluator", switch = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkEvaluator"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkEvaluator", switch = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkEvaluator"): Returns the results produced by the process as a `[mtkEvaluatorResult]`.

`getData` signature(this = "mtkEvaluator"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(this = "mtkEvaluator"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkEvaluator", context= "mtkExpWorkflow"): Runs the model with the experimental design defined in the context.

`summary` signature(object = "mtkEvaluator"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkEvaluator"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkEvaluator"): Plots the results produced by the process.

`report` signature(this = "mtkEvaluator"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create an evaluator with the model "Ishigami"
# implemented in the package "mtk".
evaluator1 <- mtkEvaluator(service="Ishigami")

# Create an evaluator with the model "WWDM"
# implemented in the package "mtk"
evaluator2 <- mtkEvaluator(service="WWDM",
  parametersList=list(year=3, tout=FALSE))
```

mtkEvaluatorResult *The constructor of the class mtkEvaluatorResult*

Description

The constructor

Usage

```
mtkEvaluatorResult(main=data.frame(), information=list())
```

Arguments

`main` a data.frame holding the data produced by the model simulation..
`information` a named list containing the information about the managed data or process.

Value

an object of the `mtkEvaluatorResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Construct an object of the \code{mtkEvaluatorResult}  
# class from a data-frame.  
data <- data.frame()  
simulation <- mtkEvaluatorResult(main=data,  
information = list(model="Ishigami"))
```

mtkEvaluatorResult-class

The mtkEvaluatorResult class

Description

A class to collect the results of the simulation produced with a model.

Class Hierarchy

Parent classes : `mtkResult`

Direct Known Subclasses : `mtkWWDMEvaluatorResult`, etc.

Constructor

```
mtkEvaluatorResult signature(main=data.frame(),information=list())
```

Slots

main: (`data.frame`) a `data.frame` holding the data produced by the model simulation.

information: (`list`) a named list containing information about the managed data and process.

Methods

`summary` signature(object = "mtkEvaluatorResult"): Provides a summary of the data produced with the model simulation.

`print` signature(x = "mtkEvaluatorResult"): Prints a report of the data produced with the model simulation.

`plot` signature(x = "mtkEvaluatorResult"): Plots the data produced with the model simulation.

See Also

`help(morris, sensitivity)` and `help(Regression)`

Examples

```
## See examples from help(mtkAnalyserResult)
```

mtkExperiment

The constructor of the class mtkExperiment

Description

A simple way to build a workflow for interactive use.

Usage

```
mtkExperiment(expFactors,
  design=NULL, designInfo=NULL,
  model=NULL, modelInfo=NULL,
  analyze=NULL, analyzeInfo=NULL,
  XY=NULL)
```

Arguments

expFactors (`mtkExpFactors`) an object of the `mtkExpFactors` class.

design (`NULL` or `character`) the name of the method used to build the experiment design. `NULL` means that the experiment design is produced off-line and should be imported through the parameter `XY$X`.

designInfo	(list) a named list to specify the parameters used to generate the experiments design.
model	(NULL or character) the name of the model to simulate. NULL means that the simulation is produced off-line and should be imported through the parameter XY\$Y.
modelInfo	(list) a named list to specify the parameters used to manage the model simulation.
analyze	(NULL or character) the name of the method used to compute the sensitivity index.
analyzeInfo	(list) a named list to specify the parameters used to carry out the analyses.
XY	(NULL or list) a named list with two elements X and Y: X allows importing the experiment design produced off-line and Y allows importing the model simulation produced off-line.

Value

an object of the [mtkExperiment](#) class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Compute the sensitivity index with the method "Regression"
# over the model "Ishigami" according to an experiment design
# generated with the method "BasicMonteCarlo"

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

ishiReg <- mtkExperiment(expFactors=ishi.factors,
  design="BasicMonteCarlo", designInfo=list(size=20),
  model="Ishigami",
  analyze="Regression", analyzeInfo=list(nboot=20))

run(ishiReg)
summary(ishiReg)
```

mtkExperiment-class

The mtkExperiment class

Description

The class `mtkExperiment` is a sub-class of the class `mtkExpWorkflow`. It provides more facilities and more flexible use for interactive manipulation of the workflow. Different behaviors may be expected by appropriately combining the parameters: `design` – the method used for the experiment design; `model` – the model used for the simulation; `analyze` – the method used for calculating the sensitivity index; `XY` – argument used to provide with data produced off-line;

For example, 1) if the experiment design is produced off-line, it will be imported with the help of the parameter "XY\$X" ; 2) if the model simulation is produced off-line, it will be imported through the parameter "XY\$Y";

Class Hierarchy

Parent classes : `mtkExpWorkflow`

Direct Known Subclasses :

Constructor

`mtkExperiment` signature(`expFactors`, `design=NULL`, `designInfo=NULL`, `model=NULL`, `modelInfo=NULL`, `analyze=NULL`, `analyzeInfo=NULL`, `XY=NULL`)

Slots

`expFactors`: (`mtkExpFactors`) an object of the `mtkExpFactors` class.

`processesVector`: (`vector`) a vector of objects from the class `mtkProcess` or its sub-classes.

Methods

`addProcess` signature(`this = "mtkExperiment"`, `p = "mtkProcess"`, `name = "character"`): Adds a process to the workflow.

`deleteProcess` signature(`this = "mtkExperiment"`, `name = "character"`): Deletes a process from the workflow.

`setProcess` signature(`this = "mtkExperiment"`, `p = "mtkProcess"`, `name = "character"`): Replaces a process into the workflow.

`getProcess` signature(`this = "mtkExperiment"`, `name = "character"`): Gets a process from the workflow.

`extractData` signature(`this = "mtkExperiment"`, `name = "list"`): Returns the results produced by the workflow as a `data.frame`. According to the processes specified with the argument "name", we can fetch the results produced by the process "design", "evaluate" or "analyze". i.e. `name=c("design")` gives the experimental design produced by the process "design" and `name=c("design","evaluate")` gives both the experimental design and the model simulation, etc.

reevaluate signature(this = "mtkExperiment", name = "character"): Re-evaluate the processes of the workflow to know if they should be re-run. This should be done after changing a process of the workflow. According to the order "design", "evaluate", "analyze", only the processes after the one given by the argument "name" will be re-evaluated.

run signature(this = "mtkExperiment", context= "missing"): Runs the ExpWorkflow.

serializeOn signature(this = "mtkExperiment"): Returns all data managed by the workflow as a named list.

summary signature(object = "mtkExperiment"): Provides a summary of the results produced by the workflow.

print signature(x = "mtkExperiment"): Prints a report of the results produced by the workflow.

plot signature(x = "mtkExperiment"): Plots the results produced by the workflow.

report signature(this = "mtkExperiment"): Reports the results produced by the workflow.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Compute the sensitivity index with the method "Regression"
# over the model "Ishigami" according to an experiment design
# generated with the method "BasicMonteCarlo"

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

exp <- mtkExperiment(
  factors,
  design = 'BasicMonteCarlo',
  designInfo=list(size=20),
  model = 'Ishigami',
  analyze = 'Regression',
  analyzeInfo = list(ntboot=20)
)
run(exp)
summary(exp)
```

mtkExpFactors

*The constructor of the class [mtkExpFactors](#)***Description**

This class is used to define the input factors for a simulation experiment.

Usage

```
mtkExpFactors(expFactorsList=list())
```

Arguments

expFactorsList
a list of [mtkFactor](#) objects.

Value

an object of the [mtkExpFactors](#) class

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of the class mtkExpFactor
x1 <- make.mtkFactor(name="x1", distribName="unif",
                     distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
                     distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
                     distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))
```

mtkExpFactors-class

*The mtkExpFactors class***Description**

The `mtkExpFactors` class is a class used to manage the factors involved in a sensitivity analysis.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

`mtkExpFactors` signature(`expFactorsList=list()`)

Slots

`expFactorsList`: (`list`) a list of `mtkFactor` objects.

Methods

initialize signature(`.Object="mtkExpFactors"`): The initializer.

setFactors signature(`this="mtkExpFactors"`,`aFactList="list"`): Assigns a new list of `mtkFactor` objects.

getFactors signature(`this="mtkExpFactors"`): Returns the factors as a list of `mtkFactor` objects.

getNames signature(`this = "mtkExpFactors"`): Returns the names of the managed factors.

getFactorNames signature(`this = "mtkExpFactors"`): Returns the names of the managed factors as the method `getNames`.

getDistributionNames signature(`this="mtkExpFactors"`): Gets a list of `mtkExpFactors` names.

getDistributionParameters signature(`this="mtkExpFactors"`): Gets the parameters.

getFeatures signature(`this = "mtkExpFactors"`): Returns the features associated with the managed factors.

getDistributionNominalValues signature(`this = "mtkExpFactors"`): Returns the nominal values associated with the distributions of the managed factors.

getDistributionNominalValueTypes signature(`this = "mtkExpFactors"`): Returns the data type of the nominal value associated with the managed factors.

`[[` signature(`x = "mtkExpFactors"`, `i="ANY"`): Extracts or replaces parts of an object of the class `mtkExpFactors`.

`[` signature(`x = "mtkExpFactors"`, `i="ANY"`): Extracts or replaces parts of an object of class `mtkExpFactors`.

`$` signature(`x = "mtkExpFactors"`): Extracts or replaces parts of an object of the class.

`print` signature(`x = "mtkExpFactors"`): Prints information about the managed factors.

`show` signature(`object = "mtkExpFactors"`): Displays the underlying object of the class `mtkExpFactors`.

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Define the factor
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors(list(x1,x2,x3))
```

mtkExpWorkflow

*The constructor of the class mtkExpWorkflow***Description**

The class `mtkExpWorkflow` is used to manage the processes involved in a sensitivity analysis. We can construct a workflow in two ways: either from pre-defined factors and processes or from a XML file.

Usage

```
mtkExpWorkflow(
  expFactors = NULL,
  processesVector = NULL,
  xmlFilePath = NULL
)
```

Arguments

`expFactors` (`mtkExpFactors`) an object of the `mtkExpFactors` class.
`processesVector` (`vector`) a vector of objects from the class `mtkProcess` or its sub-classes.
`xmlFilePath` (`character`) a string holding the name of the XML file and its path.

Value

an object of the `mtkExpWorkflow` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
#####
# Example 1: Construct a workflow
# from the factors and the processes
#####

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
```

```

x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

ishiReg <- mtkExpWorkflow(expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
)
run(ishiReg)
summary(ishiReg)

#####
##### Example 2: Construct a workflow from a XML file
#####
# Create a workflow from XML file
## Nota: If your XML file is a local file
## for example /var/tmp/X.xml", you should
## create the workflow as follows:
## workflow <- mtkExpWorkflow(
##   xmlFilePath="/var/tmp/X.xml"
## )

xmlFile <- "WWDM_morris.xml"

## If WWDM_morris.xml is a local file, the next line is not necessary.
xmlFilePath <- paste(path.package("mtk", quiet = TRUE),
"/extdata/",xmlFile,sep = "")

workflow <- mtkExpWorkflow(xmlFilePath=xmlFilePath)

# Run the workflow and report the results
run(workflow)
summary(workflow)

```

mtkExpWorkflow-class

The mtkExpWorkflow class

Description

The `mtkExpWorkflow` class is used to coordinate the processes involved in a sensitivity analysis. It controls the state of the processes and coordinates their chaining.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

`mtkExpWorkflow` signature(expFactors=NULL, processesVector=NULL, xmlFilePath=NULL)

Slots

`expFactors`: (`mtkExpFactors`) an object of the `mtkExpFactors` class.

`processesVector`: (`vector`) a vector of objects from the class `mtkProcess` or its sub-classes.

Methods

`addProcess` signature(this = "mtkExpWorkflow", p = "mtkProcess", name = "character"): Adds a process to the workflow.

`deleteProcess` signature(this = "mtkExpWorkflow", name = "character"): Deletes a process from the workflow.

`setProcess` signature(this = "mtkExpWorkflow", p = "mtkProcess", name = "character"): Replaces a process into the workflow.

`getProcess` signature(this = "mtkExpWorkflow", name = "character"): Gets a process from the workflow.

`extractData` signature(this = "mtkExpWorkflow", name = "list"): Returns the results produced by the workflow as a data.frame. According to the processes specified with the argument "name", we can fetch the results produced by the process "design", "evaluate" or "analyze". i.e. name=c("design") gives the experimental design produced by the process "design" and name=c("design","evaluate") gives both the experimental design and the model simulation, etc.

`reevaluate` signature(this = "mtkExpWorkflow", name = "character"): Re-evaluate the processes of the workflow to know if they should be re-run. This should be done after changing a process of the workflow. According to the order "design", "evaluate", "analyze", only the processes after the one given by the argument "name" will be re-evaluated.

`run` signature(this = "mtkExpWorkflow", context= "missing"): Runs the workflow.

`serializeOn` signature(this = "mtkExpWorkflow"): Returns all data managed by the workflow as a named list.

`summary` signature(object = "mtkExpWorkflow"): Provides a summary of the results produced by the workflow.

`print` signature(x = "mtkExpWorkflow"): Prints a report of the results produced by the workflow.

`plot` signature(x = "mtkExpWorkflow"): Plots the results produced by the workflow.

`report` signature(this = "mtkExpWorkflow"): Reports the results produced by the workflow.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
#####
# Example 1: Construct a workflow
# from the factors and the processes
#####

# Specify the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

# Define the processes
designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

# Build the workflow
ishiReg <- mtkExpWorkflow( expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
)

# Run the workflow and report the results
run(ishiReg)
summary(ishiReg)

#####
##### Example 2: Construct a workflow from a XML file
#####
# # XML file is held in the directory of the library: "inst/extdata/"

# Specify the XML file's name
xmlFile <- "WWDM_morris.xml"
## find where the examples are held.
xmlFilePath <- paste(path.package("mtk", quiet = TRUE),
  "/extdata/",xmlFile,sep = "")

# Create the workflow from the XML
## Nota: If your XML file is local
## file for example /var/tmp/X.xml", you should
## create the workflow as follows:
## workflow <- mtkExpWorkflow(
```

mtkFactor-class	<i>The mtkFactor class</i>
-----------------	----------------------------

Description

The class used to manage an input factor and its uncertainty distribution.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

`mtkFactor` signature(name="unkown", id="unkown", unit="", type="numeric", domain=mtkDomain(), featureList=list())

Slots

name: the name of the input factor.

id: the name of the factor in the simulation code, if different from `name`.

unit: the measurement units of the factor values. This can be used in graphics or reports, for example.

type: the data type of the factor's values.

domain: the `mtkDomain` object that describes the factor's uncertainty.

featureList: the list of features that may be associated with the factor.

Methods

`initialize` signature(.Object = "mtkFactor"): The initializer of the class `mtkFactor`.

`getName` signature(this="mtkFactor"): Fetches the name of the factor.

`getType` signature(this = "mtkFactor"): Returns the data type of the factor's levels.

`getDomain` signature(this="mtkFactor"): Fetches the domain associated with the factor. It returns an object of the class `mtkDomain`.

`getDistributionName` signature(this="mtkFactor"): Fetches the name of the distribution associated with the uncertainty domain.

`getDistributionNominalValue` signature(this="mtkFactor"): Fetches the nominal value of the distribution associated with the uncertainty domain.

`getDistributionNominalValueType` signature(this="mtkFactor"): Fetches the data type associated with the uncertainty domain.

`getDiscreteDistributionType` signature(this="mtkFactor"): Returns the discrete distribution type.

`getDiscreteDistributionLevels` signature(this="mtkFactor"): Returns the levels managed by a discrete distribution.

`getDiscreteDistributionWeights` signature(this="mtkFactor"): Returns the weights managed by a discrete distribution.

`getDistributionParameters` signature(this="mtkFactor"): The `getDistributionParameters` method.

`getFeatures` signature(this="mtkFactor"): Returns the features as a named list.

`getMTKFeatures` signature(this="mtkFactor"): Returns the features as a vector of objects from the class `mtkFeature`.

`setName` signature(this = "mtkFactor", name = "character"): Gives a new name to the factor.

`setDomain` signature(this = "mtkFactor", domain = "mtkDomain"): Associates a new domain with the factor.

`setType` signature(this = "mtkFactor", type = "character"): Names explicitly the data type managed by the factor.

`setFeatures` signature(this="mtkFactor",aFList="list"): Gives new features to the factor. `aFList` may be a vector of objects from the class `mtkFeature` or a named list from which we can build a list of features.

`print` signature(x = "mtkFactor"): Prints the data managed by the factor.

`show` signature(object = "mtkFactor"): Displays the underlying object of the class `mtkFactor`.

Author(s)

Juhui WANG and Hervé Monod, MIA-jouy, INRA, Hervé Richard, BioSP, INRA

Examples

```
# Manage a factor x1 with a mtkFactor object.

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
getName(x1)
getDomain(x1)
getDistributionName(x1)
getType(x1)
setType(x1, "double")
getType(x1); # 'double'
```

mtkFastAnalyser	<i>The constructor of the class mtkFastAnalyser</i>
-----------------	---

Description

The constructor

Usage

```
mtkFastAnalyser(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`
a vector of [`mtkParameter`] representing the parameters necessary to run the process.

`listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the `mtkFastAnalyser` class

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(fast, sensitivity)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Fast" method

# Input the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner(listParameters
  = list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)
```

`mtkFastAnalyser-class`

The mtkFastAnalyser class

Description

The `mtkFastAnalyser` class is a sub-class of the class `mtkAnalyser`. It implements the sensitivity analysis method 'Fast' and provides all the slots and methods defined in the class `mtkAnalyser`.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkFastAnalyser` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

`name`: (`character`): always takes the string "analyze".
`protocol`: (`character`): always takes the string "R".
`site`: (`character`): always takes the string "mtk".
`service`: (`character`): always takes the string "Fast".
`parameters`: (`vector`): a vector of [`mtkParameter`] containing the parameters to pass while calling the service.
`ready`: (`logical`): a logical to tell if the process is ready to run.
`state`: (`logical`): a logical to tell if the results produced by the process are available and ready to be consumed.
`result`: (`ANY`): a data holder to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkFastAnalyser", `name` = "character"): Not used, method inherited from the parent class.
`setParameters` signature(`this` = "mtkFastAnalyser", `f` = "vector"): Assigns new parameters to the process.
`getParameters` signature(`this` = "mtkFastAnalyser"): Returns the parameters as a named list.
`is.ready` signature(`this` = "mtkFastAnalyser"): Tests if the process is ready to run.
`setReady` signature(`this` = "mtkFastAnalyser", `switch` = "logical"): Makes the process ready to run.
`is.ready` signature(`this` = "mtkFastAnalyser"): Tests if the results produced by the process are available.
`setReady` signature(`this` = "mtkFastAnalyser", `switch` = "logical"): Marks the process as already executed.
`getResult` signature(`this` = "mtkFastAnalyser"): Returns the results produced by the process as a [`mtkAnalyserResult`].
`getData` signature(`this` = "mtkFastAnalyser"): Returns the results produced by the process as a data.frame.
`serializeOn` signature(`this` = "mtkFastAnalyser"): Returns all data managed by the process as a named list.
`run` signature(`this` = "mtkFastAnalyser", `context`= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.
`summary` signature(`object` = "mtkFastAnalyser"): Provides a summary of the results produced by the process.
`print` signature(`x` = "mtkFastAnalyser"): Prints a report of the results produced by the process.
`plot` signature(`x` = "mtkFastAnalyser"): Plots the results produced by the process.
`report` signature(`this` = "mtkFastAnalyser"): Reports the results produced by the process.

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(fast, sensitivity)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Fast" method

# Input the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner(listParameters
  = list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)
```

`mtkFastAnalyserResult`

The constructor of the class `mtkFastAnalyserResult`

Description

The constructor

Usage

```
mtkFastAnalyserResult(main, information=NULL)
```

Arguments

`main` a data.frame holding the results of the sensitivity analysis produced by the analyser.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkFastAnalyserResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Fast)
```

```
mtkFastAnalyserResult-class
```

```
The mtkFastAnalyserResult class
```

Description

A class to collect the results of the sensitivity analysis produced by the analyser implementing the method `Fast`.

Class Hierarchy

Parent classes : `mtkAnalyserResult`

Direct Known Subclasses :

Constructor

```
mtkFastAnalyserResult signature(main,information=NULL)
```

Slots

`main:` (`data.frame`) a data.frame holding the experimental design.

`information:` (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkFastAnalyserResult"): Provides a summary of the results produced by the analyser.

`print` signature(x = "mtkFastAnalyserResult"): Prints a report of the results produced by the analyser.

`plot` signature(x = "mtkFastAnalyserResult"): Plots the results produced by the analyser.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Fast)
```

mtkFastDesigner	<i>The constructor of the class mtkFastDesigner</i>
-----------------	---

Description

The constructor

Usage

```
mtkFastDesigner(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`
a vector of [`mtkParameter`] representing the parameters necessary to run the process.

`listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the `mtkFastDesigner` class

See Also

```
help(fast, sensitivity)
```

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Fast" method

# Input the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner(listParameters
  = list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)
```

mtkFastDesigner-class

The mtkFastDesigner class

Description

The `mtkFastDesigner` class is a sub-class of the class `mtkDesigner`. It implements the sampling method `Fast` and provides all the slots and methods defined in the class `mtkDesigner`.

Class Hierarchy

Parent classes : `mtkDesigner`

Direct Known Subclasses :

Constructor

`mtkFastDesigner` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (`character`) always takes the string "design".
protocol: (`character`) always takes the string "R".
site: (`character`) always takes the string "mtk".
service: (`character`) always takes the string "Fast".
parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.
ready: (`logical`) a logical to tell if the process is ready to run.
state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.
result: (`ANY`) a data holder to hold the results produced by the process

Methods

setName signature(`this` = "mtkFastDesigner", `name` = "character"): Not used, method inherited from the parent class.
setParameters signature(`this` = "mtkFastDesigner", `f` = "vector"): Assigns new parameters to the process.
getParameters signature(`this` = "mtkFastDesigner"): Returns the parameters as a named list.
is.ready signature(`this` = "mtkFastDesigner"): Tests if the process is ready to run.
setReady signature(`this` = "mtkFastDesigner", `switch` = "logical"): Makes the process ready to run.
is.ready signature(`this` = "mtkFastDesigner"): Tests if the results produced by the process are available.
setReady signature(`this` = "mtkFastDesigner", `switch` = "logical"): Marks the process as already executed.
getResult signature(`this` = "mtkFastDesigner"): Returns the results produced by the process as a [`mtkDesignerResult`].
getData signature(`this` = "mtkFastDesigner"): Returns the results produced by the process as a `data.frame`.
serializeOn signature(`this` = "mtkFastDesigner"): Returns all data managed by the process as a named list.
run signature(`this` = "mtkFastDesigner", `context` = "mtkExpWorkflow"): Generates the experimental design by sampling the factors.
summary signature(`object` = "mtkFastDesigner"): Provides a summary of the results produced by the process.
print signature(`x` = "mtkFastDesigner"): Prints a report of the results produced by the process.
plot signature(`x` = "mtkFastDesigner"): Plots the results produced by the process.
report signature(`this` = "mtkFastDesigner"): Reports the results produced by the process.

References

1. A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York.
2. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

```
help(fast, sensitivity)
```

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Fast" method

# Input the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkFastDesigner(listParameters
  = list(n=1000))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkFastAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and reports the results.
run(expl)
print(expl)
```

```
mtkFastDesignerResult
```

The constructor of the class mtkFastDesignerResult

Description

The constructor

Usage

```
mtkFastDesignerResult(main, information=NULL)
```

Arguments

<code>main</code>	a data.frame holding the experimental design produced by the designer.
<code>information</code>	a named list containing the information about the managed data.

Value

an object of the `mtkFastDesignerResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Fast)
```

```
mtkFastDesignerResult-class
```

```
The mtkFastDesignerResult class
```

Description

A class to collect the experimental design produced by the designer implementing the method `Fast`.

Class Hierarchy

Parent classes : `mtkDesignerResult`

Direct Known Subclasses :

Constructor

`mtkFastDesignerResult` signature(main,information=NULL)

Slots

main: (`data.frame`) a data.frame holding the experimental design.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkFastDesignerResult"): Provides a summary of the experimental design produced by the designer.

`print` signature(x = "mtkFastDesignerResult"): Prints a report of the experimental design produced by the designer.

`plot` signature(x = "mtkFastDesignerResult"): Plots the experimental design produced by the designer.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Fast)
```

mtkFeature	<i>The constructor of the class <code>mtkFeature</code></i>
------------	---

Description

The constructor of the class `mtkFeature`. See also `make.mtkFeatureList`.

Usage

```
mtkFeature(name='unknown', type='logical', val=NULL)
```

Arguments

name	(character) the name of the feature.
type	(character) the data type managed by the feature such as 'numeric', 'double', 'logical', etc..
val	(ANY) the value of the feature.

Value

an object of the `mtkFeature` class

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# creates a feature "he"
f <- mtkFeature(name='he', type='character', val='pekin')

# We usually use the 'make.mtkFeatureList()' function to define
# a list of 'mtkFeature' instead of the constructor
# of the 'mtkFeature' class

flist <- make.mtkFeatureList(list(min=-1,max=+1,shape="hello"))
```

mtkFeature-class *The mtkFeature class*

Description

The `mtkFeature` class is a class used to manage the features associated with a factor.

Class Hierarchy

Parent classes : `mtkValue`

Direct Known Subclasses :

Constructor

```
mtkFeature signature(name='unknown', type='logical', val=NULL)
make.mtkFeatureList signature(x=list())
```

Slots

```
name: (character) the name of the feature.
type: (character) the type of value managed by the feature.
val: (ANY) the value of the feature in the right type.
```

Methods

```
getName signature( this = "mtkFeature"): Returns the value of the slot "name".
getValue signature( this = "mtkFeature"): Returns the value of the slot "val".
getType signature(this = "mtkFeature"): Returns the value of the slot "type".
setName signature( this = "mtkFeature", name = "character"): Gives a new value to the slot
"name".
setType signature( this = "mtkFeature", type = "character"): Gives a new value to the slot "type".
setValue signature(this = "mtkFeature", val = "ANY"): Gives a new value to the slot "val".
show signature( object = "mtkFeature"): Prints a report of the data managed by the underlying
object.
print signature(x = "mtkFeature"): Prints the information managed by the underlying object.
```

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of the 'mtkFeature' class.

f <- mtkFeature(name="x", type="double", val=0.0)

# We usually use the make.mtkFeatureList function to define a list of mtkFeature
# instead of the constructor of the mtkFeature class

flist <- make.mtkFeatureList(list(min=-1,max=+1,shape="hello"))
```

`mtkIshigamiEvaluator`*The constructor of the class `mtkIshigamiEvaluator`*

Description

The constructor

Usage

```
mtkIshigamiEvaluator()
```

Value

an object of the `mtkIshigamiEvaluator` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Carry out a sensitivity analysis with the Ishigami model

## Input the factors
data(Ishigami.factors)

## Specify the experiments designer
designer <- mtkNativeDesigner ("BasicMonteCarlo",
information=list(size=20))

## Specify the model simulator
model <- mtkIshigamiEvaluator()

## Specify the sensitivity analyser
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

## Specify the workflow
ishiReg <- new("mtkExpWorkflow", expFactors=Ishigami.factors,
  processesVector=c(
    design=designer,
    evaluate=model,
    analyze=analyser
  )
)
## Run and report the results
run(ishiReg)
```

```
summary(ishiReg)
```

```
mtkIshigamiEvaluator-class
```

```
The mtkIshigamiEvaluator class
```

Description

The `mtkIshigamiEvaluator` class is a sub-class of the class `mtkEvaluator` used to manage the simulation of the model `Ishigami`.

Class Hierarchy

Parent classes : `mtkEvaluator`

Direct Known Subclasses :

Constructor

```
mtkIshigamiEvaluator signature()
```

Slots

name: (`character`) always takes the string "evaluate".

protocol: (`character`) a string to name the protocol used to run the process: http, system, R, etc. Here, it takes the character "R".

site: (`character`) a string to indicate where the service is located. Here, it always takes the string "mtk".

service: (`character`) a string to name the service to invoke. Here, it always takes the string "Ishigami".

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service. The "Ishigami" model does not need parameters.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkIshigamiEvaluator", `name` = "character"): non useful, method inherited from the parent class.

`setParameters` signature(`this` = "mtkIshigamiEvaluator", `f` = "vector"): Assigns new parameters to the process.

`getParameters` signature(`this` = "mtkIshigamiEvaluator"): Returns the parameters as a named list.

`is.ready` signature(= "mtkIshigamiEvaluator"): Tests if the process is ready to run.

`setReady` signature(`this` = "mtkIshigamiEvaluator", `switch` = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkIshigamiEvaluator"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkIshigamiEvaluator", switch = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkIshigamiEvaluator"): Returns the results produced by the process as a `[mtkEvaluatorResult]`.

`getData` signature(this = "mtkIshigamiEvaluator"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(this = "mtkIshigamiEvaluator"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkIshigamiEvaluator", context= "mtkExpWorkflow"): runs the simulation.

`summary` signature(object = "mtkIshigamiEvaluator"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkIshigamiEvaluator"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkIshigamiEvaluator"): Plots the results produced by the process.

`report` signature(this = "mtkIshigamiEvaluator"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Carry out a sensitivity analysis with the Ishigami model

## Input the factors
data(Ishigami.factors)

## Specify the experiments designer
designer <- mtkNativeDesigner ("BasicMonteCarlo",
information=list(size=20))

## Specify the model simulator
model <- mtkIshigamiEvaluator()

## Specify the sensitivity analyser
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

## Specify the workflow
ishiReg <- new("mtkExpWorkflow", expFactors=Ishigami.factors,
  processesVector=c(
    design=designer,
    evaluate=model,
```



```
        analyze=analyser)
    )
    ## Run and report the results
    run(ishiReg)
    summary(ishiReg)
```

mtkLevels

The constructor of the class [mtkLevels](#)

Description

The constructor of the class [mtkLevels](#).

Usage

```
mtkLevels(type = "categorical", levels=vector(), weights=numeric(0))
```

Arguments

type	a string to specify the type of the discrete distribution: categorical, qualitative, etc.
levels	a vector of levels for a discrete domain.
weights	a vector of numeric values used to weight the levels.

Value

an object of the [mtkLevels](#) class

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# creates an object of the class mtkLevel
l1 <- mtkLevels(type="qualitative", levels = c("x", "y"), weights=c(0.5, 0.5))
l2 <- mtkLevels(levels = c("a", "b", "c"))
l3 <- mtkLevels(levels = c("a", "b", "c"), weights=c(3, 5, 3))
```

mtkLevels-class *The mtkLevels class*

Description

The `mtkLevels` class is a class used to manage the weighting levels associated with a factor's domain.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

`mtkLevesl` signature(`type` = "categorical", `levels`=`vector()`, `weights`=`numeric(0)`)

Slots

`type`: (`character`) a string to give the type of the discrete distribution such as 'categorical', 'qualitative', etc.

`levels`: (`vector`) a vector to specify the levels.

`weights`: (`numeric`) a numeric vector used to weight the levels.

Methods

`getType` signature(`this` = "mtkLevels"): Returns the type of the discrete distribution such as 'categorical', 'qualitative', etc .

`setType` signature(`this` = "mtkLevels", `type`="character"): Assigns a new type to the underlying object.

`getLevels` signature(`this` = "mtkLevels"): Returns the vector of the levels.

`setLevels` signature(`this` = "mtkLevels", `levels` = "vector"): Assigns a new vector to the levels.

`getWeights` signature(`this` = "mtkLevels"): Returns the vector of the weights.

`setWeights` signature(`this` = "mtkLevels", `weights` = "numeric"): Assigns new vector to the weight.

`print` signature(`x` = "mtkLevel"): Prints a summarized report about the underlying object of the class `mtkLevels`.

`summary` signature(`object` = "mtkLevel"): Gives a summary about the underlying object.

`show` signature(`object` = "mtkLevel"): Displays informations about the underlying object.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of the class 'mtkLevels'

l <- mtkLevels(type='categorical', levels=seq(1:3), weight=rep(0.33, 3))

# Set the levels' name to ('a', 'b', 'c')

setLevels(l, levels=c('a', 'b', 'c'))
```

mtkMorrisAnalyser *The constructor of the class mtkMorrisAnalyser*

Description

The constructor

Usage

```
mtkMorrisAnalyser(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`
a vector of [[mtkParameter](#)] holding the parameters necessary to run the process.

`listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkMorrisAnalyser](#) class

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(morris, sensitivity)` and `help(Morris)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Morris" method

# Generate the factors
data(Ishigami.factors)
```

```
# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner( listParameters
  = list(r=20, type="oat", levels=4, grid.jump=2))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

mtkMorrisAnalyser-class

The mtkMorrisAnalyser class

Description

The `mtkMorrisAnalyser` class is a sub-class of the class `mtkAnalyser`. It implements the sensitivity analysis method `Morris` and provides all the slots and methods defined in the class `mtkAnalyser`.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkMorrisAnalyser` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (`character`) always takes the string "analyze".

protocol: (`character`) always takes the string "R".

site: (`character`) always takes the string "mtk".

service: (`character`) always takes the string "Morris".

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

`state`: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

`result`: (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkMorrisAnalyser", `name` = "character"): Not used, method inherited from the parent class.

`setParameters` signature(`this` = "mtkMorrisAnalyser", `f` = "vector"): Assigns new parameters to the process.

`getParameters` signature(`this` = "mtkMorrisAnalyser"): Returns the parameters as a named list.

`is.ready` signature(`this` = "mtkMorrisAnalyser"): Tests if the process is ready to run.

`setReady` signature(`this` = "mtkMorrisAnalyser", `switch` = "logical"): Makes the process ready to run.

`is.ready` signature(`this` = "mtkMorrisAnalyser"): Tests if the results produced by the process are available.

`setReady` signature(`this` = "mtkMorrisAnalyser", `switch` = "logical"): Marks the process as already executed.

`getResult` signature(`this` = "mtkMorrisAnalyser"): Returns the results produced by the process as a `[mtkMorrisAnalyserResult]`.

`getData` signature(`this` = "mtkMorrisAnalyser"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(`this` = "mtkMorrisAnalyser"): Returns all data managed by the process as a named list.

`run` signature(`this` = "mtkMorrisAnalyser", `context` = "mtkExpWorkflow"): Runs the process to generate the results.

`summary` signature(`object` = "mtkMorrisAnalyser"): Provides a summary of the results produced by the process.

`print` signature(`x` = "mtkMorrisAnalyser"): Prints a report of the results produced by the process.

`plot` signature(`x` = "mtkMorrisAnalyser"): Plots the results produced by the process.

`report` signature(`this` = "mtkMorrisAnalyser"): Reports the results produced by the process.

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(morris, sensitivity)` and `help(Morris)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Morris" method

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner( listParameters
  = list(r=20, type="oat", levels=4, grid.jump=2))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

```
mtkMorrisAnalyserResult
```

The constructor of the class mtkMorrisAnalyserResult

Description

The constructor

Usage

```
mtkMorrisAnalyserResult(main, information=NULL)
```

Arguments

<code>main</code>	a data.frame holding the results of the sensitivity analysis produced by the analyser.
<code>information</code>	a named list containing the information about the managed data.

Value

an object of the `mtkMorrisAnalyserResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Morris)
```

```
mtkMorrisAnalyserResult-class
```

```
The mtkMorrisAnalyserResult class
```

Description

A class to collect the results of the sensitivity analysis produced by the analyser implementing the method `Morris`.

Class Hierarchy

Parent classes : `mtkAnalyserResult`

Direct Known Subclasses :

Constructor

```
mtkMorrisAnalyserResult signature(main,information=NULL)
```

Slots

main: (`data.frame`) a `data.frame` holding the results produced by the "Morris" analyser.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkMorrisAnalyserResult"): Provides a summary of the results produced by the analyser.

`print` signature(x = "mtkMorrisAnalyserResult"): Prints a report of the results produced by the analyser.

`plot` signature(x = "mtkMorrisAnalyserResult"): Plots the results produced by the analyser.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Morris)
```

```
mtkMorrisDesigner The constructor of the class mtkMorrisDesigner
```

Description

The constructor

Usage

```
mtkMorrisDesigner(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`

a vector of [\[mtkParameter\]](#) representing the parameters necessary to run the process.

`listParameters`

a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkMorrisDesigner](#) class

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(morris, sensitivity)` and `help(Morris)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Morris" method

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner( listParameters
  = list(r=20, type="oat", levels=4, grid.jump=2))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

mtkMorrisDesigner-class

The mtkMorrisDesigner class

Description

The `mtkMorrisDesigner` class is a sub-class of the class `mtkDesigner`. It implements the method `Morris` and provides all the slots and methods defined in the class `mtkDesigner`.

Class Hierarchy

Parent classes : `mtkDesigner`

Direct Known Subclasses :

Constructor

`mtkMorrisDesigner` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (*character*) always takes the string "design".
protocol: (*character*) always takes the string "R".
site: (*character*) always takes the string "mtk".
service: (*character*) always takes the string "Morris".
parameters: (*vector*) a vector of [*mtkParameter*] containing the parameters to pass while calling the service.
ready: (*logical*) a logical to tell if the process is ready to run.
state: (*logical*) a logical to tell if the results produced by the process are available and ready to be consumed.
result: (*ANY*) a data holder to hold the results produced by the process

Methods

setName signature(this = "mtkMorrisDesigner", name = "character"): Not used, method inherited from the parent class.
setParameters signature(this = "mtkMorrisDesigner", f = "vector"): Assigns new parameters to the process.
getParameters signature(this = "mtkMorrisDesigner"): Returns the parameters as a named list.
is.ready signature(= "mtkMorrisDesigner"): Tests if the process is ready to run.
setReady signature(this = "mtkMorrisDesigner", switch = "logical"): Makes the process ready to run.
is.ready signature(= "mtkMorrisDesigner"): Tests if the results produced by the process are available.
setReady signature(this = "mtkMorrisDesigner", switch = "logical"): Marks the process as already executed.
getResult signature(this = "mtkMorrisDesigner"): Returns the results produced by the process as a [*mtkMorrisDesignerResult*].
getData signature(this = "mtkMorrisDesigner"): Returns the results produced by the process as a data.frame.
serializeOn signature(this = "mtkMorrisDesigner"): Returns all data managed by the process as a named list.
run signature(this = "mtkMorrisDesigner", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.
summary signature(object = "mtkMorrisDesigner"): Provides a summary of the results produced by the process.
print signature(x = "mtkMorrisDesigner"): Prints a report of the results produced by the process.
plot signature(x = "mtkMorrisDesigner"): Plots the results produced by the process.
report signature(this = "mtkMorrisDesigner"): Reports the results produced by the process.

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(morris, sensitivity)` and `help(Morris)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Morris" method

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkMorrisDesigner( listParameters
  = list(r=20, type="oat", levels=4, grid.jump=2))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkMorrisAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

mtkMorrisDesignerResult

The constructor of the class mtkMorrisDesignerResult

Description

The constructor

Usage

```
mtkMorrisDesignerResult(main, information=NULL)
```

Arguments

`main` a data.frame holding the experimental design produced by the designer.
`information` a named list containing the information about the managed data.

Value

an object of the `mtkMorrisDesignerResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Morris)
```

```
mtkMorrisDesignerResult-class
```

```
The mtkMorrisDesignerResult class
```

Description

A class to collect the experimental design produced by the designer implementing the method `Morris`.

Class Hierarchy

Parent classes : `mtkDesignerResult`

Direct Known Subclasses :

Constructor

`mtkMorrisDesignerResult` signature(main,information=NULL)

Slots

main: (`data.frame`) a data.frame holding the experimental design produced by the designer.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkMorrisDesignerResult"): Provides a summary of the experimental design produced by the designer.

`print` signature(x = "mtkMorrisDesignerResult"): Prints a report of the experimental design produced by the designer.

`plot` signature(x = "mtkMorrisDesignerResult"): Plots the experimental design produced by the designer.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# See examples from the help of the method: help(Morris)
```

```
mtkNativeAnalyser The constructor of the class mtkNativeAnalyser
```

Description

The constructor.

Usage

```
mtkNativeAnalyser(analyze=NULL, X=NULL, information=NULL)
```

Arguments

<code>analyze</code>	NULL, an R function or a string to specify the analyser to use.
<code>X</code>	NULL or a data.frame to load the results produced off-line.
<code>information</code>	a named list to provide with supplementary information about the analysis produced off-line or the parameters used by the analyser.

Value

an object of the `mtkNativeAnalyser` class

Details

We can construct an object of the `mtkNativeAnalyser` class in three manners:

- the analyser is provided within the package "mtk" The argument "analyze" takes a string giving the name of the method used to carry out the sensitivity analysis, the argument "information" gives the list of parameters used by the analyser.
- the analyser is available as an R function implemented outside the package "mtk" The argument "analyze" takes an R function implementing the analyser, the argument "information" may be used to give supplementary information about the R function.
- the results of the sensitivity analysis are already available as a data.frame. We use "mtk" only for reporting. The argument "X" takes the data.frame holding the available results, and the argument "information" may be omitted or simply used to give supplementary information about the analysis.

More examples for using this class, see `?class(mtkNativeEvaluator)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`?class(mtkNativeEvaluator)`

Examples

```
# Create a native analyser with the method "Morris" implemented in the package "mtk"

analyser <- mtkNativeAnalyser(
  analyze="Morris",
  information=list(nboot=20))
```

`mtkNativeAnalyser-class`

The mtkNativeAnalyser class

Description

The `mtkNativeAnalyser` class is a sub-class of the class `mtkAnalyser` used to manage the sensitivity analysis task implemented locally (i.e. tasks don't need to call services from the Web). It provides all the slots and methods defined in the class `mtkAnalyser`.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkNativeAnalyser` signature(analyze=NULL, X=NULL, information=NULL)

Slots

analyze: (*ANY*) a string, an R function, or NULL to inform the method to use for the sensitivity analysis.

name: (*character*) always takes the string "analyze".

protocol: (*character*) a string to name the protocol used to run the process: http, system, R, etc. Here, it always takes "R".

site: (*character*) a string to indicate where the service is located.

service: (*character*) a string to name the service to invoke. Here, it may be a R function or a method implemented in the package "mtk".

parameters: ([vector](#)) a vector of [[mtkParameter](#)] containing the parameters to pass while calling the service.

ready: ([logical](#)) a logical to tell if the process is ready to run.

state: ([logical](#)) a logical to tell if the results produced by the process are available and ready to be consumed.

result: ([ANY](#)) a data holder to hold the results produced by the process

Methods

[setName](#) signature(this = "mtkNativeAnalyser", name = "character"): Not used here, method inherited from the parent class.

[setParameters](#) signature(this = "mtkNativeAnalyser", f = "vector"): Assigns new parameters to the process.

[getParameters](#) signature(this = "mtkNativeAnalyser"): Returns the parameters as a named list.

[is.ready](#) signature(= "mtkNativeAnalyser"): Tests if the process is ready to run.

[setReady](#) signature(this = "mtkNativeAnalyser", switch = "logical"): Makes the process ready to run.

[is.ready](#) signature(= "mtkNativeAnalyser"): Tests if the results produced by the process are available.

[setReady](#) signature(this = "mtkNativeAnalyser", switch = "logical"): Marks the process as already executed.

[getResult](#) signature(this = "mtkNativeAnalyser"): Returns the results produced by the process as a [[mtkAnalyserResult](#)].

[getData](#) signature(this = "mtkNativeAnalyser"): Returns the results produced by the process as a data.frame.

[serializeOn](#) signature(this = "mtkNativeAnalyser"): Returns all data managed by the process as a named list.

[run](#) signature(this = "mtkNativeAnalyser", context= "mtkExpWorkflow"): Runs the Analyser.

[summary](#) signature(object = "mtkNativeAnalyser"): Provides a summary of the results produced by the process.

[print](#) signature(x = "mtkNativeAnalyser"): Prints a report of the results produced by the process.

[plot](#) signature(x = "mtkNativeAnalyser"): Plots the results produced by the process.

[report](#) signature(this = "mtkNativeAnalyser"): Reports the results produced by the process.

Details

We can construct an object of the [mtkNativeAnalyser](#) class from the following situations:

1. The analyser is provided within the package "mtk";
2. The analyser is provided as an R function implemented outside the package "mtk"; If so, the R function must produce a result as a named list with two elements: X and information, where X is a data.frame containing the analysis result and information is a named list containing supplementary information about the analysis process.
3. The results of the model exploration are produced off-line and available as a data.frame. We just want to use the "mtk" package for reporting.

For detail uses, see examples from `help(mtkNativeEvaluator)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a native analyser with the method "Morris" implemented in the package "mtk"

analyser <- mtkNativeAnalyser(
  analyze="Morris",
  information=list(nboot=20))
```

`mtkNativeDesigner` *The constructor of the class `mtkNativeDesigner`*

Description

The constructor.

Usage

```
mtkNativeDesigner(design=NULL, X=NULL, information=NULL)
```

Arguments

<code>design</code>	NULL, an R function or a string to specify the method used to generate the experiments design.
<code>X</code>	NULL or a <code>data.frame</code> to load the experimental design produced off-line.
<code>information</code>	a named list to provide with supplementary information about the experimental design produced off-line or the parameters used by the designer.

Value

an object of the `mtkNativeDesigner` class

Details

We can construct an object of the `mtkNativeDesigner` class from the following situations:

- the designer is provided within the package "mtk" The argument "design" takes a string giving the method used to generate the experimental design, and the argument "information" gives the list of parameters used by the designer. e.g. `designer <- mtkNativeDesigner(design="Morris", information = list(nboot=20))`.
- the designer is provided with an R function implemented outside the package "mtk" The argument "design" takes the R function, the argument "information" may be used to give supplementary information about the R function.

- the experimental design is produced off-line and available as a data.frame. The argument "design" is not used, the argument "X" takes the data.frame holding the available experimental design, and the argument "information" may be omitted or simply used to give supplementary information about the method used to generate the experimental design. e.g. `Designer <- mtkNativeDesigner(X = mcDesign, information = list(sampling = "Monte-Carlo"))`.

For details uses, see examples from `help(mtkNativeEvaluator)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(mtkNativeEvaluator)`

Examples

```
# Create a native designer with the method "Morris"
# implemented in the package "mtk"

designer <- mtkNativeDesigner(design="Morris", information=list(size=20))
```

`mtkNativeDesigner-class`

The mtkNativeDesigner class

Description

The `mtkNativeDesigner` class is a sub-class of the class `mtkDesigner` used to manage the sampling task implemented locally (i.e. tasks don't need to call services from the Web). By object inheriting, it provides all the slots and methods defined in the class `mtkDesigner`.

Class Hierarchy

Parent classes : `mtkDesigner`

Direct Known Subclasses :

Constructor

`mtkNativeDesigner` signature(design=NULL, X=NULL, information=NULL)

Slots

design: (*ANY*) a string, an R function, or NULL to inform the designer to use.

name: (*character*) always takes the string "design".

protocol: (*character*) a string to name the protocol used to run the process: http, system, R, etc. Here, it always takes "R".

site: (*character*) a string to indicate where the service is located. Here, it gives no sense.

service: (*character*) a string to name the service to invoke.

parameters: (*vector*) a vector of [*mtkParameter*] containing the parameters to pass while calling the service.

ready: (*logical*) a logical to tell if the process is ready to run.

state: (*logical*) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (*ANY*) a data holder to hold the results produced by the process

Methods

setName signature(this = "mtkNativeDesigner", name = "character"): Method inherited from the parent class. It gives no sense here.

setParameters signature(this = "mtkNativeDesigner", f = "vector"): Assigns new parameters vector to the process.

getParameters signature(this = "mtkNativeDesigner"): Returns the parameters vector as a named list.

is.ready signature(= "mtkNativeDesigner"): Tests if the process is ready to run.

setReady signature(this = "mtkNativeDesigner", switch = "logical"): Makes the process ready to run.

is.ready signature(= "mtkNativeDesigner"): Tests if the results produced by the process are available.

setReady signature(this = "mtkNativeDesigner", switch = "logical"): Marks the process as already executed.

getResult signature(this = "mtkNativeDesigner"): Returns the results produced by the process as a [*mtkDesignerResult*].

getData signature(this = "mtkNativeDesigner"): Returns the results produced by the process as a data.frame.

serializeOn signature(this = "mtkNativeDesigner"): Returns all data managed by the process as a named list.

run signature(this = "mtkNativeDesigner", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

summary signature(object = "mtkNativeDesigner"): Provides a summary of the results produced by the process.

print signature(x = "mtkNativeDesigner"): Prints a report of the results produced by the process.

plot signature(x = "mtkNativeDesigner"): Produces a graphical report of the results produced by the process.

report signature(this = "mtkNativeDesigner"): Reports the results produced by the process.

Details

We can construct an object of the `mtkNativeDesigner` class from the following situations:

1. The designer is provided within the package "mtk";
2. The designer is provided as an R function implemented outside the package "mtk"; If so, the R function must produce a result as a named list with two elements: `X` and `information`, where `X` is a `data.frame` containing the analysis result and `information` is a named list containing supplementary information about the analysis process.
3. The experiments design is produced off-line and available as a `data.frame`. We just want to use the "mtk" package for reporting.

For detail uses, see examples from `help(mtkNativeEvaluator)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a native designer with the method "Morris"
# implemented in the package "mtk"

designer <- mtkNativeDesigner(
  design = "Morris",
  information = list(size = 20)
)
```

`mtkNativeEvaluator` *The constructor of the class mtkNativeEvaluator*

Description

The constructor.

Usage

```
mtkNativeEvaluator(model=NULL, Y=NULL, information=NULL)
```

Arguments

<code>model</code>	NULL, an R function or a string to specify the model to simulate.
<code>Y</code>	NULL or a <code>data.frame</code> to load the results of model simulation produced off-line.
<code>information</code>	a named list to provide with supplementary information about the simulation produced off-line or the parameters used by the evaluator.

Value

an object of the `mtkNativeEvaluator` class

Details

We can construct an object of the `mtkNativeEvaluator` class from the following situations:

- The model is provided within the package "mtk" The argument "model" takes a string giving the model to simulate, and the argument "information" gives the list of parameters used for the model simulation. e.g. `model <- mtkNativeEvaluator(model="Ishigami")`.
- The model is provided with an R function implemented outside the package "mtk" The argument "model" takes the R function, the argument "information" may be used to give supplementary information about the R function.
- The simulation results are produced off-line and available as a data.frame The argument "model" is not used, the argument "Y" takes the data.frame holding the model simulation, and the argument "information" may be omitted or simply used to give supplementary information about the simulation process. e.g. `model <- mtkNativeDesigner(Y = simulatedData, information = list(model = "Ishigami"))`.

For details uses, see examples from `?class(mtkNativeEvaluator)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`?class(mtkNativeEvaluator)`

Examples

```
## 1) Create a model simulation with the model "Ishigami" implemented in the package "mtk"
evaluator <- mtkNativeEvaluator(model="Ishigami")

## 2) Create a model simulation with a R function implemented outside the package "mtk"

# a) Create a R function to represent the model of population

ME <- function(K, Y0, a, t=5, ...){

  res <- exp(-a*t)
  res <- Y0+res*(K-Y0)
  res <- K*Y0/res
  out <- as.integer(res)

  return(out)
}
```

```

# b) Do the sensitivity analysis for the function "ME"

K <- make.mtkFactor(name="K", nominal=400, distribName="unif",
distribPara=list(min=100, max=1000))
Y0 <- make.mtkFactor(name="Y0", nominal=20, distribName="unif",
distribPara=list(min=1, max=40))
a <- make.mtkFactor(name="a", nominal=0.1, distribName="unif",
distribPara=list(min=0.05, max=0.2))
factors <- mtkExpFactors(list(K,Y0,a))

plan <- mtkNativeDesigner ("BasicMonteCarlo",
information=c(size=500))

model <- mtkNativeEvaluator(model=ME, information=c(t=5))

index<- mtkNativeAnalyser("Regression", information=c(nboot=20) )

expt <- mtkExpWorkflow( expFactors=factors,
processesVector=c(
design= plan,
evaluate= model,
analyze= index)
)
run(expt)
summary(expt)

## 3) Import the results of model simulation produced off-line into
##      an object of mtkNativeEvaluator

data <- data.frame()
model <- mtkNativeEvaluator(Y=data,
information = list(model="Ishigami"))

```

mtkNativeEvaluator-class

The mtkNativeEvaluator class

Description

The `mtkNativeEvaluator` class is a sub-class of the class `mtkEvaluator` used to manage the simulation task implemented locally (i.e. tasks don't need to call services from the Web). It provides all the slots and methods defined in the class `mtkEvaluator`.

Class Hierarchy

Parent classes : `mtkEvaluator`

Direct Known Subclasses :

Constructor

`mtkNativeEvaluator` signature(model=NULL, Y=NULL, information=NULL)

Slots

model: (*ANY*) a string, an R function, or NULL to inform the model to simulate.
name: (*character*) always takes the string "evaluate".
protocol: (*character*) a string to name the protocol used to run the process: http, system, R, etc. Here, it always takes "R".
site: (*character*) a string to indicate where the service is located. Here, it always takes "mtk".
service: (*character*) a string to name the service to invoke.
parameters: (*vector*) a vector of [*mtkParameter*] containing the parameters to pass while calling the service.
ready: (*logical*) a logical to tell if the process is ready to run.
state: (*logical*) a logical to tell if the results produced by the process are available and ready to be consumed.
result: (*ANY*) a data holder to hold the results produced by the process

Methods

setName signature(this = "mtkNativeEvaluator", name = "character"): Not used, method inherited from the parent class.
setParameters signature(this = "mtkNativeEvaluator", f = "vector"): Assigns new parameters to the process.
getParameters signature(this = "mtkNativeEvaluator"): Returns the parameters as a named list.
is.ready signature(= "mtkNativeEvaluator"): Tests if the process is ready to run.
setReady signature(this = "mtkNativeEvaluator", switch = "logical"): Makes the process ready to run.
is.ready signature(= "mtkNativeEvaluator"): Tests if the results produced by the process are available.
setReady signature(this = "mtkNativeEvaluator", switch = "logical"): Marks the process as already executed.
getResult signature(this = "mtkNativeEvaluator"): Returns the results produced by the process as a [*mtkEvaluatorResult*].
getData signature(this = "mtkNativeEvaluator"): Returns the results produced by the process as a data.frame.
serializeOn signature(this = "mtkNativeEvaluator"): Returns all data managed by the process as a named list.
run signature(this = "mtkNativeEvaluator", context= "mtkExpWorkflow"): runs the simulation.
summary signature(object = "mtkNativeEvaluator"): Provides a summary of the results produced by the process.
print signature(x = "mtkNativeEvaluator"): Prints a report of the results produced by the process.
plot signature(x = "mtkNativeEvaluator"): Plots the results produced by the process.
report signature(this = "mtkNativeEvaluator"): Reports the results produced by the process.

Details

We can construct an object of the `mtkNativeEvaluator` class from the following situations: 1) 2) 3) the experimental design is produced off-line and available as a data.frame.

We can construct an object of the `mtkNativeEvaluator` class from the following situations:

1. The evaluator is provided within the package "mtk";
2. The evaluator is provided as an R function outside the package "mtk";
3. The simulation is carried out off-line. We just want to use the "mtk" package for reporting.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
## 1) Create a model simulation with the model "Ishigami" implemented in the package "mtk"
evaluator <- mtkNativeEvaluator(model="Ishigami")

## 2) Create a model simulation with a R function implemented outside the package "mtk"

# a) Create a R function to represent the model of population

ME <- function(K, Y0, a, t=5, ...){

  res <- exp(-a*t)
  res <- Y0+res*(K-Y0)
  res <- K*Y0/res
  out <- as.integer(res)

  return(out)
}

# b) Do the sensitivity analysis for the function "ME"

K <- make.mtkFactor(name="K", nominal=400, distribName="unif",
  distribPara=list(min=100, max=1000))
Y0 <- make.mtkFactor(name="Y0", nominal=20, distribName="unif",
  distribPara=list(min=1, max=40))
a <- make.mtkFactor(name="a", nominal=0.1, distribName="unif",
  distribPara=list(min=0.05, max=0.2))
factors <- mtkExpFactors(list(K,Y0,a))

plan <- mtkNativeDesigner ("BasicMonteCarlo",
  information=c(size=500))

model <- mtkNativeEvaluator(model=ME, information=c(t=5))
```

```

index<- mtkNativeAnalyser("Regression", information=c(nboot=20) )

expt <- mtkExpWorkflow( expFactors=factors,
  processesVector=c(
    design= plan,
    evaluate= model,
    analyze= index)
  )
run(expt)
summary(expt)

## 3) Import the results of model simulation produced off-line
##      into an object of mtkNativeEvaluator

data <- data.frame()
model <- mtkNativeEvaluator(Y=data,
  information = list(model="Ishigami"))

```

mtkParameter

*The constructor of the class [mtkParameter](#)***Description**

The constructor of the class [mtkParameter](#). See also [make.mtkParameterList](#)

Usage

```
mtkParameter(name='unknown', type='logical', val=NULL)
```

Arguments

name	(character) the name of the parameter.
type	(character) the type of the parameter such as 'numeric', 'double', 'logical', etc..
val	(ANY) the value of the parameter.

Value

an object of the [mtkParameter](#) class

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```

# Create an object of the 'mtkParameter' class.

p <- mtkParameter(name="x", type="double", val=0.0)

# We usually use the 'make.mtkParameterList()' function to define
# a list of 'mtkParameter' instead of the constructor
# of the 'mtkParameter' class
flist <- make.mtkParameterList(x=list(min=-1,max=+1))

```

mtkParameter-class *The mtkParameter class*

Description

The `mtkParameter` class is a class used to manage the parameter concept.

Class Hierarchy

Parent classes : `mtkValue`

Direct Known Subclasses :

Constructor

```
mtkParameter signature(name='unknown', type='logical', val=NULL)
make.mtkParameterList signature(x=list())
```

Slots

name: (`character`) the name of the parameter.

type: (`character`) the type of the parameter.

val: (`ANY`) the value of the parameter.

Methods

```
getName signature( this = "mtkParameter"): Returns the value of the slot "name".
getValue signature( this = "mtkParameter"): Returns the value of the slot "val".
getType signature(this = "mtkParameter"): Returns the value of the slot "type".
setName signature( this = "mtkParameter", name="character"): Gives a new value to the slot
" name".
setValue signature( this = "mtkParameter", val="ANY"): Gives a new value to the slot "val".
setType signature(this = "mtkParameter", type="character"): Gives a new value to the slot "type".
show signature( object = "mtkParameter"): Prints a report of the data managed by the underlying
object.
print signature(x = "mtkParameter"): Prints the information managed by the underlying object.
```

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of the 'mtkParameter' class.

p <- mtkParameter(name="x", type="double", val=0.0)

# We usually use the 'make.mtkParameterList()' function to define a list of
# 'mtkParameter' instead of the constructor
# of the 'mtkParameter' class
plist <- make.mtkParameterList(list(min=-1,max=+1,shape="hello"))
```

`mtkParsor`*The constructor of the class `mtkParsor`*

Description

The constructor

Usage

```
mtkParsor(xmlPath=" ")
```

Arguments

`xmlPath` a string to specify the XML file to parse.

Value

an object of the `mtkParsor` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a parser with the file "inst/extdata/WWDM.xml".

# Specify the XML file's name
xmlFile <- "WWDM_morris.xml"

# find where the examples are held.
# This is only necessary for the example since the system does
# not know where the file "WWDM.xml" is kept.
xmlFilePath <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", xmlFile, sep = "")

## Create a parser from the xml file
parser <- mtkParsor(xmlFilePath)

# Create an empty workflow.
workflow <- mtkExpWorkflow()

# Parse the XML file and initialize the workflow
# with the data extracted from the XML file.
run(parser, workflow)

# Run the workflow and report the results of the sensitivity analysis
```

```
run(workflow)
summary(workflow)
```

mtkParsor-class	<i>The mtkParsor class</i>
-----------------	----------------------------

Description

The `mtkParsor` class is the main class used to parse the XML files used in the "mtk" package. It provides a generic way to communicate with the plate-form of model simulation.

Class Hierarchy

Parent classes :

Direct Known Subclasses :

Constructor

```
mtkParsor signature(xmlPath="")
```

Slots

`xmlPath`: (`character`) the XML file's path and name.

Methods

```
setXMLFilePath signature(this = "mtkParsor", xmlPath = "character"): Sets the xml File.
```

```
run signature(this = "mtkParsor", context = "mtkExpWorkflow"): Parses the XML file and fills
the workflow defined in the "context" argument with the data extracted from the XML file.
```

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a parsor with the file "inst/extdata/WWDM.xml".

# Specify the XML file's name
xmlFile <- "WWDM_morris.xml"

# find where the examples are held.
# This is only necessary for the example since the system does
# not know where the file "WWDM.xml" is kept.
xmlFilePath <- paste(path.package("mtk", quiet = TRUE),
```

```

"/extdata/",xmlFile,sep = "")

## Create a parser from the xml file
parser <- mtkParser(xmlFilePath)

# Create an empty workflow.
workflow <- mtkExpWorkflow()

# Parse the XML file and initialize the workflow
# with the data extracted from the XML file.
run(parser, workflow)

# Run the workflow and report the results of the sensitivity analysis

run(workflow)
summary(workflow)

```

mtkPLMMAlyser	<i>The constructor of the class mtkPLMMAlyser</i>
---------------	---

Description

The constructor

Usage

```
mtkPLMMAlyser(mtkParameters = NULL, listParameters = NULL)
```

Arguments

<code>mtkParameters</code>	a vector of [mtkParameter] representing the parameters necessary to run the process.
<code>listParameters</code>	a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkPLMMAlyser](#) class

Author(s)

Rober Faivre, MIA-Toulouse, INRA, Contact: faivre@toulouse.inra.fr, Juhui WANG, MIA-Jouy, Inra,

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(PLMM)
```

```
mtkPLMMAlyser-class
```

```
The mtkPLMMAlyser class
```

Description

The mtkPLMMAlyser class is a sub-class of the class mtkAnalyser. It implements the sensitivity analysis method PLMM and provides all the slots and methods defined in the class mtkAnalyser.

Class Hierarchy

Parent classes : [mtkAnalyser](#)

Direct Known Subclasses :

Constructor

[mtkPLMMAlyser](#) signature(mtkParameters = NULL, listParameters = NULL)

Slots

name: ([character](#)) always takes the string "analyze".

protocol: ([character](#)) always takes the string "R".

site: ([character](#)) always takes the string "mtk".

service: ([character](#)) always takes the string "PLMM".

parameters: ([vector](#)) a vector of [[mtkParameter](#)] containing the parameters to pass while calling the service.

ready: ([logical](#)) a logical to tell if the process is ready to run.

state: ([logical](#)) a logical to tell if the results produced by the process are available and ready to be consumed.

result: ([ANY](#)) a data holder to hold the results produced by the process

Methods

[setName](#) signature(this = "mtkPLMMAlyser", name = "character"): Not used, method inherited from the parent class.

[setParameters](#) signature(this = "mtkPLMMAlyser", f = "vector"): Assigns new parameters to the process.

[getParameters](#) signature(this = "mtkPLMMAlyser"): Returns the parameters as a named list.

[is.ready](#) signature(= "mtkPLMMAlyser"): Tests if the process is ready to run.

[setReady](#) signature(this = "mtkPLMMAlyser", switch = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkPLMMAlyser"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkPLMMAlyser", switch = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkPLMMAlyser"): Returns the results produced by the process as a `[mtkPLMMAlyserResult]`.

`getData` signature(this = "mtkPLMMAlyser"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(this = "mtkPLMMAlyser"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkPLMMAlyser", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

`summary` signature(object = "mtkPLMMAlyser"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkPLMMAlyser"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkPLMMAlyser"): Plots the results produced by the process.

`report` signature(this = "mtkPLMMAlyser"): Reports the results produced by the process.

Author(s)

Rober Faivre, MIA-Toulouse, INRA, Contact: faivre@toulouse.inra.fr, Juhui WANG, MIA-Jouy, Inra,

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(PLMM)
```

```
mtkPLMMAlyserResult
```

The constructor of the class mtkPLMMAlyserResult

Description

The constructor

Usage

```
mtkPLMMAlyserResult(main, information=NULL)
```

Arguments

`main` a data.frame holding the results of the sensitivity analysis produced by the PLMM analyser.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkPLMMAlyserResult` class

Author(s)

Rober Faivre, MIA-Toulouse, INRA, Contact: faivre@toulouse.inra.fr, Juhui WANG, MIA-Jouy, Inra,

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(PLMM)
```

```
mtkPLMMAlyserResult-class
```

The mtkPLMMAlyserResult class

Description

A class to collect the results of the sensitivity analysis produced by the analyser implementing the method `PLMM`.

Class Hierarchy

Parent classes : `mtkAnalyserResult`

Direct Known Subclasses :

Constructor

`mtkPLMMAlyserResult` signature(main,information=NULL)

Slots

`main:` (`data.frame`) a data.frame holding the experimental design.

`information:` (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkPLMMAAnalyserResult"): Provides a summary of the experimental design produced by the analyser.

`print` signature(x = "mtkPLMMAAnalyserResult"): Prints a report of the experimental design produced by the analyser.

`plot` signature(x = "mtkPLMMAAnalyserResult"): Plots the experimental design produced by the analyser.

Author(s)

Rober Faivre, MIA-Toulouse, INRA, Contact: faivre@toulouse.inra.fr, Juhui WANG, MIA-Jouy, Inra,

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(PLMM)
```

mtkProcess

The constructor of the `mtkProcess` class

Description

The constructor

Usage

```
mtkProcess(
  name,
  protocol = "R",
  site = "mtk",
  service = "",
  parameters = NULL,
  ready = FALSE,
  state = FALSE,
  result = NULL
)
```


Arguments

name	the processing step associated with this process. It may be "design", "evaluate", or "analyze".
protocol	a string from "http", "system", "R" respectively representing if the process is implemented remotely, locally or as R function.
site	the site where the process is implemented if remotely or the package where the process is implemented if as a R function.
service	the service name or a system call that implements the process.
parameters	a vector of <code>[mtkParameter]</code> representing the parameters necessary to run the process.
ready	a logical to indicate if the process is ready to run.
state	a logical to indicate if the process finished running and the results are available.
result	an object of a class derived from <code>[mtkResult]</code> to hold the results produced by the process.

Value

an object of the `mtkProcess` class

Details

The `mtkProcess` class is a virtual class to manage the generic properties of processes involved in the "mtk" package.

For details uses, see examples from `help(mtkNativeDesigner)`, `help(mtkNativeEvaluator)`, `help(mtkNativeAnalyser)`, .

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(mtkNativeDesigner)
```

mtkProcess-class *The mtkProcess class*

Description

The `mtkProcess` is a class to represent the processes managed within the workflow. It provides a generic mechanism for conceptualizing the common behavior of the processes used in experimental design, model simulation and sensitivity analysis.

Class Hierarchy

Parent classes :

Direct Known Subclasses : `mtkDesigner`, `mtkEvaluator`, `mtkAnalyser`

Constructor

`mtkProcess` signature(name, protocol = "R", site = "mtk", service = "", parameters = NULL, ready = FALSE, state = FALSE, result = NULL)

Slots

name: (`character`) a string to name the step of the analysis: "design", "evaluate" or "analyze".

protocol: (`character`) a string to name the protocol used to run the process: "http", "system", "R", etc.

site: (`character`) a string to indicate where the service is located: "mtk", URI, etc.

service: (`character`) a string to name the service to invoke.

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to keep the results produced by the process

Methods

`setName` signature(this = "mtkProcess", name = "character"): Gives a name to the process.

`getName` signature(this = "mtkProcess"): Returns the name of the process.

`setParameters` signature(this = "mtkProcess", f = "vector"): Assigns new parameters to the process.

`getParameters` signature(this = "mtkProcess"): Returns the parameters as a named list.

`is.ready` signature(this = "mtkProcess"): Tests if the process is ready to run.

`setReady` signature(this = "mtkProcess", switch = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkProcess"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkProcess", state = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkProcess"): Returns the results produced by the process as a `mtkResult`.

`getData` signature(`this = "mtkProcess"`) : Returns the results produced by the process as a data frame.

`serializeOn` signature(`this = "mtkProcess"`): Returns all data managed by the process as a named list.

`run` signature(`this = "mtkProcess"`, `context= "mtkExpWorkflow"`): Runs the process.

`summary` signature(`object = "mtkProcess"`, ...): Displays a summary of the results produced by the process.

`print` signature(`x = "mtkProcess"`): Prints a report of the results produced by the process.

`plot` signature(`x = "mtkProcess"`, `y, ...`): Plots the results produced by the process.

`report` signature(`this = "mtkProcess"`): Reports the results produced by the process.

Details

The `mtkProcess` class is a virtual class to manage the generic properties of processes involved in the "mtk" package.

For details uses, see examples from `help(mtkNativeDesigner)`, `help(mtkNativeEvaluator)`, `help(mtkNativeAnalyser)`,.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples with help(mtkNativeDesigner)
```

`mtkRandLHSDesigner` *The constructor of the class mtkRandLHSDesigner*

Description

The constructor

Usage

```
mtkRandLHSDesigner(mtkParameters = NULL, listParameters = NULL)
```

Arguments

- `mtkParameters`
a vector of [`mtkParameter`] representing the parameters necessary to run the process.
- `listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the `mtkRandLHSDesigner` class

See Also

`package?lsh`, `help(LHS)`

Examples

```
# To do, example for LHS method
```

```
mtkRandLHSDesigner-class
```

The mtkRandLHSDesigner class

Description

The `mtkRandLHSDesigner` class is a sub-class of the class `mtkDesigner`. It implements the method `RandLHS` and provides all the slots and methods defined in the class `mtkDesigner`.

Class Hierarchy

Parent classes : `mtkDesigner`

Direct Known Subclasses :

Constructor

`mtkRandLHSDesigner` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

- `name:` (`character`) always takes the string "design".
- `protocol:` (`character`) always takes the string "R".
- `site:` (`character`) always takes the string "mtk".
- `service:` (`character`) always takes the string "RandLHS".
- `parameters:` (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.
- `ready:` (`logical`) a logical to tell if the process is ready to run.
- `state:` (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.
- `result:` (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this = "mtkRandLHSDesigner"`, `name = "character"`): Not used, method inherited from the parent class.

`setParameters` signature(`this = "mtkRandLHSDesigner"`, `f = "vector"`): Assigns new parameters to the process.

`getParameters` signature(`this = "mtkRandLHSDesigner"`): Returns the parameters as a named list.

`is.ready` signature(`= "mtkRandLHSDesigner"`): Tests if the process is ready to run.

`setReady` signature(`this = "mtkRandLHSDesigner"`, `switch = "logical"`): Makes the process ready to run.

`is.ready` signature(`= "mtkRandLHSDesigner"`): Tests if the results produced by the process are available.

`setReady` signature(`this = "mtkRandLHSDesigner"`, `switch = "logical"`): Marks the process as already executed.

`getResult` signature(`this = "mtkRandLHSDesigner"`): Returns the results produced by the process as a `[mtkRandLHSDesignerResult]`.

`getData` signature(`this = "mtkRandLHSDesigner"`): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(`this = "mtkRandLHSDesigner"`): Returns all data managed by the process as a named list.

`run` signature(`this = "mtkRandLHSDesigner"`, `context= "mtkExpWorkflow"`): Generates the experimental design by sampling the factors.

`summary` signature(`object = "mtkRandLHSDesigner"`): Provides a summary of the results produced by the process.

`print` signature(`x = "mtkRandLHSDesigner"`): Prints a report of the results produced by the process.

`plot` signature(`x = "mtkRandLHSDesigner"`): Plots the results produced by the process.

`report` signature(`this = "mtkRandLHSDesigner"`): Reports the results produced by the process.

See Also

`package?lsh, help(LHS)`

Examples

```
# To do, example for LHS method
```

```
mtkRandLHSDesignerResult
```

The constructor of the class mtkRandLHSDesignerResult

Description

The constructor

Usage

```
mtkRandLHSDesignerResult (main, information=NULL)
```

Arguments

`main` a data.frame holding the experimental design produced by the designer.
`information` a named list containing the information about the managed data.

Value

an object of the `mtkRandLHSDesignerResult` class

See Also

`package?lsh`, `help(LHS)`

Examples

```
# To do, example for LHS method
```

```
mtkRandLHSDesignerResult-class
```

The mtkRandLHSDesignerResult class

Description

A class to collect the experimental design produced by the designer implementing the method `RandLHS`.

Class Hierarchy

Parent classes : `mtkDesignerResult`

Direct Known Subclasses :

Constructor

```
mtkRandLHSDesignerResult signature(main,information=NULL)
```

Slots

`main:` (`data.frame`) a data.frame holding the experimental design.
`information:` (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkRandLHSDesignerResult"): Provides a summary of the experimental design produced by the designer.

`print` signature(x = "mtkRandLHSDesignerResult"): Prints a report of the experimental design produced by the designer.

`plot` signature(x = "mtkRandLHSDesignerResult"): Plots the experimental design produced by the designer.

See Also

package?lsh, help(LHS)

Examples

```
# To do, example for LHS method
```

mtkReadFactors-methods

The mtkReadFactor method

Description

a list of factors

Usage

```
mtkReadFactors(file, path)
```

Arguments

file	the name of the file to read.
path	the path to the file to read.

Value

an object of the class `mtkDomain`

Author(s)

Hervé Richard, BioSP, INRA, Domaine Saint paul, 84914 Avignon Cedex 9

Examples

```
# see examples for the \code{\linkS4class{mtkExpFactors}} class.
```

mtkRegressionAnalyser

The constructor of the class mtkRegressionAnalyser

Description

The constructor

Usage

```
mtkRegressionAnalyser(  
  mtkParameters = NULL,  
  listParameters = NULL  
)
```

Arguments

- `mtkParameters`
a vector of [`mtkParameter`] representing the parameters necessary to run the process.
- `listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the `mtkRegressionAnalyser` class

See Also

`help(morris, sensitivity)` and `help(Regression)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Monte-Carlo" and "Regression" m

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
exp.designer <- mtkBasicMonteCarloDesigner (listParameters=list(size=20))

# 2) the simulation process
exp.evaluator <- mtkIshigamiEvaluator()

# 3) the analysis process
exp.analyser <- mtkRegressionAnalyser(listParameters=list(nboot=20) )

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=exp.designer,
    evaluate=exp.evaluator, analyze=exp.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

`mtkRegressionAnalyser-class`

The mtkRegressionAnalyser class

Description

The `mtkRegressionAnalyser` class is a sub-class of the class `mtkAnalyser`. It implements the sensitivity analysis method `Regression` and provides all the slots and methods defined in the class `mtkAnalyser`.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkRegressionAnalyser` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

`name:` (`character`) always takes the string "analyze".
`protocol:` (`character`) always takes the string "R".
`site:` (`character`) always takes the string "mtk".
`service:` (`character`) always takes the string "Regression".
`parameters:` (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.
`ready:` (`logical`) a logical to tell if the process is ready to run.
`state:` (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.
`result:` (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkRegressionAnalyser", `name` = "character"): Not used, method inherited from the parent class.
`setParameters` signature(`this` = "mtkRegressionAnalyser", `f` = "vector"): Assigns new parameters to the process.
`getParameters` signature(`this` = "mtkRegressionAnalyser"): Gets the parameters as a named list.
`is.ready` signature(= "mtkRegressionAnalyser"): Tests if the process is ready to run.
`setReady` signature(`this` = "mtkRegressionAnalyser", `switch` = "logical"): Makes the process ready to run.
`is.ready` signature(= "mtkRegressionAnalyser"): Tests if the results produced by the process are available.
`setReady` signature(`this` = "mtkRegressionAnalyser", `switch` = "logical"): Marks the process as already executed.
`getResult` signature(`this` = "mtkRegressionAnalyser"): Returns the results produced by the process as a [`mtkRegressionAnalyserResult`].
`getData` signature(`this` = "mtkRegressionAnalyser"): Returns the results produced by the process as a `data.frame`.
`serializeOn` signature(`this` = "mtkRegressionAnalyser"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkRegressionAnalyser", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

`summary` signature(object = "mtkRegressionAnalyser"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkRegressionAnalyser"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkRegressionAnalyser"): Plots the results produced by the process.

`report` signature(this = "mtkRegressionAnalyser"): Reports the results produced by the process.

See Also

`help(morris, sensitivity)` and `help(Regression)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Monte-Carlo" and "Regression" m

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
exp.designer <- mtkBasicMonteCarloDesigner (listParameters=list(size=20))

# 2) the simulation process
exp.evaluator <- mtkIshigamiEvaluator()

# 3) the analysis process
exp.analyser <- mtkRegressionAnalyser(listParameters=list(nboot=20) )

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=exp.designer,
    evaluate=exp.evaluator, analyze=exp.analyser))

# Run the workflow and report the results.
run(expl)
print(expl)
```

mtkRegressionAnalyserResult

The constructor of the class mtkRegressionAnalyserResult

Description

The constructor

Usage

```
mtkRegressionAnalyserResult (main, information=NULL)
```

Arguments

`main` a data.frame holding the results of the sensitivity analysis produced by the analyser.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkRegressionAnalyserResult` class

See Also

`help(morris, sensitivity)` and `help(Regression)`

Examples

```
## See examples from help(mtkAnalyserResult)
```

```
mtkRegressionAnalyserResult-class
```

The mtkRegressionAnalyserResult class

Description

A class to collect the results of the sensitivity analysis produced by the analyser implementing the method `Regression`.

Class Hierarchy

Parent classes : `mtkAnalyserResult`

Direct Known Subclasses :

Constructor

`mtkRegressionAnalyserResult` signature(main,information=NULL)

Slots

`main:` (`data.frame`) a data.frame holding the experimental design.

`information:` (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkRegressionAnalyserResult"): Provides a summary of the experimental design produced by the analyser.

`print` signature(x = "mtkRegressionAnalyserResult"): Prints a report of the experimental design produced by the analyser.

`plot` signature(x = "mtkRegressionAnalyserResult"): Plots the experimental design produced by the analyser.

See Also

`help(morris, sensitivity)` and `help(Regression)`

Examples

```
## See examples from help(mtkAnalyserResult)
```

mtkResult

The constructor of the class mtkResult

Description

The constructor

Usage

```
mtkResult(information=list())
```

Arguments

`information` a named list containing the information about the managed data.

Value

an object of the `mtkResult` class

Details

The `mtkResult` class is a virtual class to manage the generic properties of results produced by the processes involved in the "mtk" package.

For details uses, see examples from `help(mtkAnalyserResult)`, `help(mtkDesignerResult)`, `help(mtkEvaluatorResult)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(mtkAnalyserResult)`, `help(mtkDesignerResult)`, `help(mtkEvaluatorResult)`

Examples

```
## See examples from help(mtkAnalyserResult), help(mtkDesignerResult), help(mtkEvaluatorResult)
```

<code>mtkResult-class</code>	<i>The mtkResult class</i>
------------------------------	----------------------------

Description

A general and simple class to collect the results produced by diverse processes involved in the "mtk" package.

Class Hierarchy

Parent classes :

Direct Known Subclasses : `mtkDesignerResult`, `mtkEvaluatorResult`, etc.

Constructor

`mtkResult` signature(`information=list()`)

Slots

information: (`list`) a named list containing information about the managed data.

Methods

`summary` signature(`object = "mtkResult"`): Provides a summary report about the managed data.

`serializeOn` signature(`this = "mtkResult"`): Returns all managed data as a named list.

Details

The `mtkResult` class is a virtual class to manage the generic properties of results produced by the processes involved in the "mtk" package.

For details uses, see examples from `help(mtkAnalyserResult)`, `help(mtkDesignerResult)`, `help(mtkEvaluatorResult)`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(mtkAnalyserResult)`, `help(mtkDesignerResult)`, `help(mtkEvaluatorResult)`

Examples

```
## See examples from help(mtkAnalyserResult), help(mtkDesignerResult), help(mtkEvaluatorResult)
```

`mtkSobolAnalyser` *The constructor of the class `mtkSobolAnalyser`*

Description

The constructor

Usage

```
mtkSobolAnalyser(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`

a vector of [[mtkParameter](#)] representing the parameters necessary to run the process.

`listParameters`

a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkSobolAnalyser](#) class

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(sobol2002, sensitivity)` and `help(Sobol)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Sobol" method
```

```
mtkSobolAnalyser-class
```

The mtkSobolAnalyser class

Description

The `mtkSobolAnalyser` class is a sub-class of the class `mtkAnalyser`. It implements the sensitivity analysis method `Sobol` and provides all the slots and methods defined in the class `mtkAnalyser`.

Class Hierarchy

Parent classes : `mtkAnalyser`

Direct Known Subclasses :

Constructor

`mtkSobolAnalyser` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (`character`) always takes the string "analyze".

protocol: (`character`) always takes the string "R".

site: (`character`) always takes the string "mtk".

service: (`character`) always takes the string "Sobol".

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this` = "mtkSobolAnalyser", `name` = "character"): Not used, method inherited from the parent class.

`setParameters` signature(`this` = "mtkSobolAnalyser", `f` = "vector"): Assigns new parameters to the process.

`getParameters` signature(`this` = "mtkSobolAnalyser"): Returns the parameters as a named list.

`is.ready` signature(= "mtkSobolAnalyser"): Tests if the process is ready to run.

`setReady` signature(this = "mtkSobolAnalyser", switch = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkSobolAnalyser"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkSobolAnalyser", switch = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkSobolAnalyser"): Returns the results produced by the process as a `[mtkSobolAnalyserResult]`.

`getData` signature(this = "mtkSobolAnalyser"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(this = "mtkSobolAnalyser"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkSobolAnalyser", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

`summary` signature(object = "mtkSobolAnalyser"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkSobolAnalyser"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkSobolAnalyser"): Plots the results produced by the process.

`report` signature(this = "mtkSobolAnalyser"): Reports the results produced by the process.

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(sobol, sensitivity)` and `help(Sobol)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Sobol" method
```

```
mtkSobolAnalyserResult
```

The constructor of the class mtkSobolAnalyserResult

Description

The constructor

Usage

```
mtkSobolAnalyserResult(main, information=NULL)
```


Arguments

`main` a data.frame holding the results of the sensitivity analysis produced by the analyser.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkSobolAnalyserResult` class

See Also

`help(mtkAnalyserResult)` and `help(Sobol)`

Examples

```
## See examples from help(mtkAnalyserResult).
```

```
mtkSobolAnalyserResult-class
```

The mtkSobolAnalyserResult class

Description

A class to collect the results of the sensitivity analysis produced by the analyser implementing the method `Sobol`.

Class Hierarchy

Parent classes : `mtkAnalyserResult`

Direct Known Subclasses :

Constructor

`mtkSobolAnalyserResult` signature(main,information=NULL)

Slots

`main:` (`data.frame`) a data.frame holding the experimental design.

`information:` (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkSobolAnalyserResult"): Provides a summary of the experimental design produced by the analyser.

`print` signature(x = "mtkSobolAnalyserResult"): Prints a report of the experimental design produced by the analyser.

`plot` signature(x = "mtkSobolAnalyserResult"): Plots the experimental design produced by the analyser.

See Also

`help(mtkAnalyserResult)` and `help(Sobol)`

Examples

```
## See examples from help(mtkAnalyserResult).
```

`mtkSobolDesigner` *The constructor of the class mtkSobolDesigner*

Description

The constructor

Usage

```
mtkSobolDesigner(mtkParameters = NULL, listParameters = NULL)
```

Arguments

`mtkParameters`

a vector of [[mtkParameter](#)] representing the parameters necessary to run the process.

`listParameters`

a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkSobolDesigner](#) class

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(sobol2002, sensitivity)` and `help(Sobol)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Sobol" method
```

mtkSobolDesigner-class

The mtkSobolDesigner class

Description

This class is a sub-class of the class [mtkDesigner](#). It implements the sampling method 'Sobol' and provides all the slots and methods defined in the class [mtkDesigner](#).

Class Hierarchy

Parent classes : [mtkDesigner](#)

Direct Known Subclasses :

Constructor

[mtkSobolDesigner](#) signature(mtkParameters = NULL, listParameters = NULL)

Slots

name: ([character](#)) always takes the string "design".

protocol: ([character](#)) always takes the string "R".

site: ([character](#)) always takes the string "mtk".

service: ([character](#)) always takes the string "Sobol".

parameters: ([vector](#)) a vector of [[mtkParameter](#)] containing the parameters to pass while calling the service.

ready: ([logical](#)) a logical to tell if the process is ready to run.

state: ([logical](#)) a logical to tell if the results produced by the process are available and ready to be consumed.

result: ([ANY](#)) a data holder to hold the results produced by the process

Methods

[setName](#) signature(this = "mtkSobolDesigner", name = "character"): Not used, method inherited from the parent class.

[setParameter](#) signature(this = "mtkSobolDesigner", f = "vector"): Assigns new parameters to the process.

[getParameter](#) signature(this = "mtkSobolDesigner"): Returns the parameters as a named list.

[is.ready](#) signature(= "mtkSobolDesigner"): Tests if the process is ready to run.

[setReady](#) signature(this = "mtkSobolDesigner", switch = "logical"): Makes the process ready to run.

[is.ready](#) signature(= "mtkSobolDesigner"): Tests if the results produced by the process are available.

[setReady](#) signature(this = "mtkSobolDesigner", switch = "logical"): Marks the process as already executed.

[getResult](#) signature(this = "mtkSobolDesigner"): Returns the results produced by the process as a [[mtkSobolDesignerResult](#)].

`getData` signature(this = "mtkSobolDesigner"): Returns the results produced by the process as a data.frame.

`serializeOn` signature(this = "mtkSobolDesigner"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkSobolDesigner", context= "mtkExpWorkflow"): Generates the experimental design by sampling the factors.

`summary` signature(object = "mtkSobolDesigner"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkSobolDesigner"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkSobolDesigner"): Plots the results produced by the process.

`report` signature(this = "mtkSobolDesigner"): Reports the results produced by the process.

References

1. Campolongo, F., J. Cariboni, and A. Saltelli (2007). An effective screening design for sensitivity analysis of large models. *Environmental Modelling and Software*, 22, 1509–1518.
2. A. Saltelli, K. Chan and E. M. Scott (2000). *Sensitivity Analysis*. Wiley, New York

See Also

`help(sobol, sensitivity)` and `help(Sobol)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Sobol" method
```

```
mtkSobolDesignerResult
```

The constructor of the class mtkSobolDesignerResult

Description

The constructor

Usage

```
mtkSobolDesignerResult(main, information=NULL)
```

Arguments

`main` a data.frame holding the experimental design produced by the designer.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkSobolDesignerResult` class

See Also

`help(mtkDesignerResult)` and `help(Sobol)`

Examples

```
## See examples from help(mtkDesignerResult).
```

mtkSobolDesignerResult-class

The mtkSobolDesignerResult class

Description

A class to collect the experimental design produced by the Designer implementing the method Sobol.

Class Hierarchy

Parent classes : `mtkDesignerResult`

Direct Known Subclasses :

Constructor

`mtkSobolDesignerResult` signature(main,information=NULL)

Slots

main: (`data.frame`) a data.frame holding the experimental design.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkSobolDesignerResult"): Provides a summary of the experimental design produced by the designer.

`print` signature(x = "mtkSobolDesignerResult"): Prints a report of the experimental design produced by the designer.

`plot` signature(x = "mtkSobolDesignerResult"): Plots the experimental design produced by the designer.

See Also

`help(mtkDesignerResult)` and `help(Sobol)`

Examples

```
## See examples from help(mtkDesignerResult).
```

mtkSystemEvaluator *The constructor of the class mtkSystemEvaluator*

Description

The constructor

Usage

```
mtkSystemEvaluator(  
  service = "",  
  mtkParameters = NULL,  
  listParameters = NULL  
)
```

Arguments

`service` a string specifying the way to invoke the application implementing the model.

`mtkParameters` a vector of [[mtkParameter](#)] representing the parameters necessary to run the process.

`listParameters` a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the [mtkSystemEvaluator](#) class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples
```

mtkSystemEvaluator-class

The mtkSystemEvaluator class

Description

The `mtkSystemEvaluator` class is a sub-class of the class `mtkEvaluator` used to manage the simulation of the model implemented as a system application.

Class Hierarchy

Parent classes : `mtkEvaluator`

Direct Known Subclasses :

Constructor

`mtkSystemEvaluator` signature(service="",mtkParameters=NULL,listParameters = NULL)

Slots

name: (`character`) always takes the string "evaluate".

protocol: (`character`) always takes the string "system".

site: (`character`) not used here.

service: (`character`) a string to invoke the system command implementing the model.

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while invoking the system command.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(this = "mtkSystemEvaluator", name = "character"): Not used, method inherited from the parent class.

`setParameters` signature(this = "mtkSystemEvaluator", f = "vector"): Assigns new parameters to the process.

`getParameters` signature(this = "mtkSystemEvaluator"): Returns the parameters as a named list.

`is.ready` signature(= "mtkSystemEvaluator"): Tests if the process is ready to run.

`setReady` signature(this = "mtkSystemEvaluator", switch = "logical"): Makes the process ready to run.

`is.ready` signature(= "mtkSystemEvaluator"): Tests if the results produced by the process are available.

`setReady` signature(this = "mtkSystemEvaluator", switch = "logical"): Marks the process as already executed.

`getResult` signature(this = "mtkSystemEvaluator"): Returns the results produced by the process as a `[mtkEvaluatorResult]`.

`getData` signature(this = "mtkSystemEvaluator"): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(this = "mtkSystemEvaluator"): Returns all data managed by the process as a named list.

`run` signature(this = "mtkSystemEvaluator", context= "mtkExpWorkflow"): runs the simulation.

`summary` signature(object = "mtkSystemEvaluator"): Provides a summary of the results produced by the process.

`print` signature(x = "mtkSystemEvaluator"): Prints a report of the results produced by the process.

`plot` signature(x = "mtkSystemEvaluator"): Plots the results produced by the process.

`report` signature(this = "mtkSystemEvaluator"): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples
```

```
mtkSystemEvaluatorResult
```

The constructor of the class mtkSystemEvaluatorResult

Description

The constructor

Usage

```
mtkSystemEvaluatorResult(main, information=NULL)
```

Arguments

`main` a `data.frame` holding the results produced by the evaluator.

`information` a named list containing the information about the managed data.

Value

an object of the `mtkSystemEvaluatorResult` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

Examples

```
# See examples
```

```
mtkSystemEvaluatorResult-class
```

```
The mtkSystemEvaluatorResult class
```

Description

A class to collect the results produced by the evaluator implemented as a system application.

Class Hierarchy

Parent classes : `mtkEvaluatorResult`

Direct Known Subclasses :

Constructor

```
mtkSystemEvaluatorResult signature(main,information=NULL)
```

Slots

main: (`data.frame`) a data.frame holding the results produced by the model simulation.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkSystemEvaluatorResult"): Provides a summary of the results produced by the evaluator.

`print` signature(x = "mtkSystemEvaluatorResult"): Prints a report of the results produced by the evaluator.

`plot` signature(x = "mtkSystemEvaluatorResult"): Plots the results produced by the evaluator.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

Examples

```
# See examples
```

mtkValue

*The constructor of the class [mtkValue](#)***Description**

The constructor

Usage

```
mtkValue(name='unknown', type='', val=NULL)
```

Arguments

name	the name of the variable.
type	the type of the variable, i.e. double, integer, character, logical, null, etc.
val	the value of the variable. It may be a single or a vector of values.

Valuean object of the [mtkValue](#) class**Author(s)**

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create an object of 'mtkValue'

triple <- mtkValue('a', 'double', c(2.5, 3.0))
```

mtkValue-class

*The mtkValue class***Description**

The mtkValue class is a virtual class used to manage a triple (name, type, value).

Class Hierarchy**Parent classes :****Direct Known Subclasses :** [mtkParameter](#), [code](#)[mtkFeature](#)**Constructor**

[mtkValue](#) signature(name='unknown', type='', val=NULL)

Slots

name: (`character`) the name of the variable.

type: (`character`) the type of the variable.

val: (`ANY`) the value of the variable in the right type. It may be a single value or a vector of values

Methods

`getName` signature(this = "mtkValue"): Returns the value of the slot "name".

`getValue` signature(this = "mtkValue"): Returns the value of the slot "val".

`getType` signature(this = "mtkValue"): Returns the value of the slot "type".

`setName` signature(this = "mtkValue", name = "character"): Gives a new value to the slot "name".

`setValue` signature(this = "mtkValue", type = "ANY"): Gives a new value to the slot "val".

`setType` signature(this = "mtkValue", type = "character"): Gives a new value to the slot "type".

`show` signature(object = "mtkValue"): Prints a report of the data managed by the underlying object.

`print` signature(x = "mtkValue"): Prints the information managed by the underlying object.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a new object of 'mtkValue'
d <- mtkValue("a", "double", c(0,1))
getType(d) # gives "double"
getName(d) # gives "a"
getValue(d) # gives (0, 1)

setType(d, 'character')
getValue(d) # gives ("0", "1")

setValue(d, "3.14")
getValue(d) # gives "3.14"
```

mtkWWDMEvaluator *The constructor of the class mtkWWDMEvaluator*

Description

The constructor

Usage

```
mtkWWDMEvaluator(mtkParameters = NULL, listParameters = NULL)
```

Arguments

- `mtkParameters`
a vector of [`mtkParameter`] representing the parameters necessary to run the process.
- `listParameters`
a named list containing the parameters to pass while calling the process. This gives another way to specify the parameters.

Value

an object of the `mtkWWDMEvaluator` class

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.
2. R. Faivre, D. Makowski, J. Wang, H. Richard, R. Monod (2013). Exploration numérique d'un modèle agronomique avec le package `mtk`. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(WWDM)`

Examples

```
# Carry out a sensitivity analysis with the WWDM model

## Input the factors
data(WWDM.factors)

## Specify the experiments designer
designer <- mtkMorrisDesigner (
  listParameters = list(type="oat", levels=5, grid.jump=3, r=10)
)

## Specify the model simulator
model <- mtkWWDMEvaluator(
  listParameters = list(year=3, tout=FALSE)
)

## Specify the sensiticity analyser
analyser <- mtkMorrisAnalyser()

## Specify the workflow
exp <- new("mtkExpWorkflow", expFactors=WWDM.factors,
```

```

        processesVector=c(
            design=designer,
            evaluate=model,
            analyze=analyser)
    )
    ## Run and report the results
    run(exp)
    summary(exp)

```

mtkWWDMEvaluator-class

The mtkWWDMEvaluator class

Description

The `mtkWWDMEvaluator` class is a sub-class of the class `mtkEvaluator` used to manage the simulation of the model WWDM.

Class Hierarchy

Parent classes : `mtkEvaluator`

Direct Known Subclasses :

Constructor

`mtkWWDMEvaluator` signature(`mtkParameters` = NULL, `listParameters` = NULL)

Slots

name: (`character`) always takes the string "evaluate".

protocol: (`character`) a string to name the protocol used to run the process: http, system, R, etc. Here, it always takes the character "R".

site: (`character`) a string to indicate where the service is located. Here, it always takes the string "mtk".

service: (`character`) a string to name the service to invoke. Here, it always takes the string "WWDM".

parameters: (`vector`) a vector of [`mtkParameter`] containing the parameters to pass while calling the service. The WWDM model does not need parameters.

ready: (`logical`) a logical to tell if the process is ready to run.

state: (`logical`) a logical to tell if the results produced by the process are available and ready to be consumed.

result: (`ANY`) a data holder to hold the results produced by the process

Methods

`setName` signature(`this = "mtkWWDMEvaluator"`, `name = "character"`): Not used, method inherited from the parent class.

`setParameters` signature(`this = "mtkWWDMEvaluator"`, `f = "vector"`): Assigns new parameters to the process.

`getParameters` signature(`this = "mtkWWDMEvaluator"`): Returns the parameters as a named list.

`is.ready` signature(`= "mtkWWDMEvaluator"`): Tests if the process is ready to run.

`setReady` signature(`this = "mtkWWDMEvaluator"`, `switch = "logical"`): Makes the process ready to run.

`is.ready` signature(`= "mtkWWDMEvaluator"`): Tests if the results produced by the process are available.

`setReady` signature(`this = "mtkWWDMEvaluator"`, `switch = "logical"`): Marks the process as already executed.

`getResult` signature(`this = "mtkWWDMEvaluator"`): Returns the results produced by the process as a [`mtkWWDMEvaluatorResult`].

`getData` signature(`this = "mtkWWDMEvaluator"`): Returns the results produced by the process as a `data.frame`.

`serializeOn` signature(`this = "mtkWWDMEvaluator"`): Returns all data managed by the process as a named list.

`run` signature(`this = "mtkWWDMEvaluator"`, `context= "mtkExpWorkflow"`): runs the simulation.

`summary` signature(`object = "mtkWWDMEvaluator"`): Provides a summary of the results produced by the process.

`print` signature(`x = "mtkWWDMEvaluator"`): Prints a report of the results produced by the process.

`plot` signature(`x = "mtkWWDMEvaluator"`): Plots the results produced by the process.

`report` signature(`this = "mtkWWDMEvaluator"`): Reports the results produced by the process.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

1. J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.
2. R. Faivre, D. Makowski, J. Wang, H. Richard, R. Monod (2013). Exploration numérique d'un modèle agronomique avec le package `mtk`. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

See Also

`help(WWDM)`

Examples

```
# Carry out a sensitivity analysis with the WWDM model

## Input the factors
data(WWDM.factors)

## Specify the experiments designer
designer <- mtkMorrisDesigner (
  listParameters = list(type="oat", levels=5, grid.jump=3, r=10)
)

## Specify the model simulator
model <- mtkWWDMEvaluator(
  listParameters = list(year=3)
)

## Specify the sensitivity analyser
analyser <- mtkMorrisAnalyser()

## Specify the workflow
exp <- new("mtkExpWorkflow", expFactors=WWDM.factors,
  processesVector=c(
    design=designer,
    evaluate=model,
    analyze=analyser)
)
## Run and report the results
run(exp)
summary(exp)
```

mtkWWDMEvaluatorResult

The constructor of the class mtkWWDMEvaluatorResult

Description

The constructor

Usage

```
mtkWWDMEvaluatorResult(main, information=NULL)
```

Arguments

`main` a data.frame holding the results produced by the evaluator.
`information` a named list containing the information about the managed data.

Value

an object of the `mtkWWDMEvaluatorResult` class

See Also

`help(mtkEvaluatorResult)` and `help(WWDM)`

Examples

```
## See examples from help(mtkEvaluatorResult).
```

mtkWWDMEvaluatorResult-class

The mtkWWDMEvaluatorResult class

Description

A class to collect the results produced by the evaluator implementing the model WWDM.

Class Hierarchy

Parent classes : `mtkEvaluatorResult`

Direct Known Subclasses :

Constructor

`mtkWWDMEvaluatorResult` signature(main,information=NULL)

Slots

main: (`data.frame`) a data.frame holding the results produced by the model simulation.

information: (`NULL`) a named list containing optional information about the managed data.

Methods

`summary` signature(object = "mtkWWDMEvaluatorResult"): Provides a summary of the results produced by the evaluator.

`print` signature(x = "mtkWWDMEvaluatorResult"): Prints a report of the results produced by the evaluator.

`plot` signature(x = "mtkWWDMEvaluatorResult"): Plots the results produced by the evaluator.

See Also

`help(mtkEvaluatorResult)` and `help(WWDM)`

Examples

```
## See examples from help(mtkEvaluatorResult).
```


Description

A `mtk` compliant implementation of the PLMM method for sensitivity analysis using polynomial linear metamodeling.

Usage

- `mtkPLMMAnalyser(listParameters = NULL)`
- `mtkNativeAnalyser(analyze="PLMM", information=NULL)`

Parameters

`degree.pol`: the maximum degree of polynomials (the sum of the degrees of cross products of polynomials is lower or equal to `degree.pol`). See details.

`rawX`: orthogonal polynomials (default value FALSE) or raw polynomials (TRUE). See `poly`, `polym`.

`numY`: the column number of the dependent variable (default is the first column of the dataframe of outputs).

`listex`: the column numbers of the dependent variables (default is all the dependent variables).

Parameters for auxiliary functions

`all`: all the specific summaries and plots are displayed if TRUE (default is FALSE). Else, see the `which` option.

`which`: when `all=FALSE`, the name of the specific summary or plot. Options are "best" (default), "full", "best.adjustedR2", "full.adjustedR2". See details.

`lang`: language of the summary and plot ("en" (default) for english, "fr" for french).

`digits`: number of digits in the summary (default = `options()$digits`).

`colors`: colors used in plot (default = `c("red", "orange", "blue")`).

`legend.loc`: location of the legend in plot (default no legend(NULL), options are "topleft", "topright", ... See `help(legend)`).

Details

1. The PLMM metamodeling approach consists in estimating 3 models and comparing the percentage of variance (coefficient of determination) explained by these 3 models. The 3 models are `polym(A, B, C)`, `poly(A)`, `polym(B, C)` where `polym` computes orthogonal polynomials. `polym(A, B, C)` gives the total variance explained by the full metamodel, `poly(A)` gives the variance that can be explained by factor A only (in the sense of polynomials of A) and `polym(B, C)` gives the variance not explained by factor A. Total sensitivity index of factor A is computed as $\max(R^2(\text{poly}(A)), 1 - R^2(\text{polym}(A, B, C)) - R^2(\text{polym}(B, C)))$ where $R^2(M)$ is the coefficient of determination of model M, and first order sensitivity index as $\min(R^2(\text{poly}(A)), 1 - R^2(\text{polym}(A, B, C)) - R^2(\text{polym}(B, C)))$. The PLMM function computes a best model in the sense of stepwise model selection starting with the constant model with direction fixed to both (see `stepAIC` for more details). Total sensitivity and first order indices are computed in the same. Additional results are given when using adjusted R2 for both best and full models. Names of the results (needed in `which` option) are: `best`, `full`, `best.adjustedR2`, `full.adjustedR2`.

2. Computational aspects: PLMM does not use the `polym` function (as `polym` needs time to orthogonalize when the number of factors and the degree of the polynomials are high). The cross products are computed as cross products of one dimensional orthogonal polynomials `poly(A) * poly(B) * poly(C)`. So we have to take care with the selected components of the best model (obtained with a stepwise model selection). Care should be taken for interpreting them because the dependent variables are orthogonalized. This not the case when the `rawX` option is set to `TRUE`. To prevent from computational side effects, the input factors are first scaled.
3. The `mtk` implementation of the PLMM method includes the following classes:
 - `mtkPLMMAlyser`: for PLMM analysis processes.
 - `mtkPLMMAlyserResult`: to store and manage the analysis results.
4. The `mtk` implementation of the PLMM method includes the following generic functions:
 - `summary`: to display summary of analysis results. See parameters for auxiliary functions.
 - `plot`: to plot analysis results. See parameters for auxiliary functions.
5. Many ways to create a PLMM analyser are available in `mtk`, but we recommend the following class constructors: `mtkPLMMAlyser` or `mtkNativeAnalyser`.

References

1. Faivre R., 2013. Exploration par construction de métamodèles. In Faivre R., Iooss B., Mahévas S., Makowski D., Monod H., editors. Analyse de sensibilité et exploration de modèles. Applications aux modèles environnementaux. Collection « Savoir Faire », Quae, Versailles, 37p.

See Also

`help(polym, stepAIC)`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "PLMM" method

# Generates the factors
data(Ishigami.factors)

# Builds the processes and workflow:

# 1) the experimental design process with the method "BasicMonteCarlo".
expl.designer <- mtkNativeDesigner("BasicMonteCarlo", information=list(size=100))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkNativeAnalyser("PLMM", information = list(degree.pol=3,numY=1))

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
```

```

        analyze=expl.analyser)
    )

# Runs the workflow and reports the results.
run(expl)
summary(expl)
summary(getProcess(expl,name="analyze"), lang="fr")
summary(getProcess(expl,name="analyze"), lang="fr",
  which="full", all=FALSE, digit=4)
extractData(expl,name="analyze")$best$call
plot(getProcess(expl,name="analysis"), lang="fr", legend.loc="topleft")
plot(getProcess(expl,name="analysis"), which="full",
  all=FALSE, legend.loc="topright")

## Example II: comparing metamodels of the WWDM model

# Generates the factors
data(WWDM.factors)

# 1) to create a sampler with the Monte-Carlo method

sampler <- mtkNativeDesigner("BasicMonteCarlo", information = list(size=100) )

# 2) to create a simulator with the WWDM model
model <- mtkNativeEvaluator("WWDM" , information = list(year=3))

# 3) to create a partial workflow (design and evaluation)

experience1 <- mtkExpWorkflow(expFactors=WWDM.factors,
  processesVector=c(design=sampler, evaluate=model) )
run(experience1)

# 4) to create an "analyser" with the Regression method

analyser1 <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

# to add to the workflow the analyser "Regression"

addProcess(experience1, p = analyser1, name = "analyze")
run(experience1)

# 4bis) to create new analysers PLMM and to add them to the workflow

experience2 <- experience1

analyser2 <- mtkNativeAnalyser("PLMM")

setProcess(experience2, p = analyser2, name = "analyze")
run(experience2) ;

## to comment out the following lines to compare others analysers
## with 'analyser1' and 'analyser2'
# experience4 <- experience3 <- experience2
# analyser3 <- mtkNativeAnalyser("PLMM", information = list(degree.pol = 3))
# analyser4 <- mtkNativeAnalyser("PLMM",
# information = list(degree.pol = 3, rawX = TRUE))

```

```
# setProcess(experience3, p = analyser3, name = "analyze")
# setProcess(experience4, p = analyser4, name = "analyze")
# run(experience3) ; run(experience4)

summary(getProcess(experience1,name="analyze"))
      summary(getProcess(experience2,name="analyze"))
# summary(getProcess(experience3,name="analyze"))
# summary(getProcess(experience4,name="analyze"), digi=3)
```

plot,mtkProcess-method

The plot method

Description

Plots graphically the results produced by the process.

Usage

```
plot(x, y, ...)
```

Arguments

x	the underlying object of class <code>mtkProcess</code>
y	see <code>par</code> for details about the graphical parameter arguments
...	see <code>par</code> for details about the graphical parameter arguments

Value

`invisible()`

Details

1. The behavior of the `plot` depends on the sub-class where the method is implemented.
2. See the documentation of the particular sub-class for details of what is produced. Use `methods("plot")` to get all the methods for the `plot` generic.
3. See `par` for details about the graphical parameter arguments.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

See Also

`help(plot`

Examples

```
# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the Morris method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))
# Run the workflow and plot the results.
run(expl)
plot(expl)

# Extract a process and report its results

p <- getProcess(expl, "analyze")
plot(p)
```

```
print,mtkProcess-method
```

The print method

Description

Prints a report of the results produced by the process.

Usage

```
print(x, ...)
```

Arguments

x	the underlying object of class <code>mtkProcess</code> .
...	see the documentation of the function: <code>base::print()</code> .

Value

invisible()

Details

1. The behavior of the `print` depends on the sub-class where the method is implemented.
2. See the documentation of the particular sub-class for details of what is produced.
3. Use `methods("print")` to get all the methods for the `print` generic.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

See Also

`help(print)`

Examples

```
# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the Morris method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))
# Run the workflow and plot the results.
run(expl)
print(expl)

# Extract a process and report its results

p <- getProcess(expl, "analyze")
print(p)
```

Quantiles

*The Quantiles function***Description**

Calculates the quantiles of a univariate distribution.

Usage

```
Quantiles(pvalues, distribName, distribParameters, shrink=0.95)
```

Arguments

`pvalues` a vector of probability values.

`distribName` a string giving the name of a probability distribution.

`distribParameters` a list of parameters of the distribution.

`shrink` a scalar eqn ≤ 1 to determine how to shrink the pvalues(used when the quantiles are infinite for pvalues equal to 0 or 1).

Value

the q-values

Author(s)

Hervé Monod, MIA-Jouy, Inra, Domaine de Vilvert, 78352 Jouy en Josas, France

Examples

```
Quantiles(seq(0,1,length=11),"unif",list(min=8,max=10))
Quantiles(seq(0,1,length=11),"unif",list(min=8,max=10),shrink=0.5)
Quantiles(seq(0,1,length=11),"norm",list(mean=0, sd=1),shrink=0.5)
```

RandLHS

*The RandLHS Method***Description**

A mtk compliant implementation of the method for drawing Random Latin Hypercube Design.

Usage

- `mtkRandLHSDesigner(listParameters = NULL)`
- `mtkNativeDesigner(design="RandLHS", information=NULL)`

Parameters used to manage the method

size: The number of partitions (simulations or design points).

preserveDraw: logical (default FALSE). Ensures that two subsequent draws with the same *n*, but one with *k* and one with *m* variables ($k < m$), will have the same first *k* columns if the seed is the same.

Details

1. The `mtk` implementation uses the `randomLHS` function of the package `lhs`. For further details on the arguments and the behavior, see `help(randomLHS, lhs)`.
2. The implementation of the `RandLHS` method includes the class `mtkRandLHSDesigner` to manage the sampling task and the class `mtkRandLHSDesignerResult` to manage the results produced by the sampling process.

References

Stein, M. (1987) Large Sample Properties of Simulations Using Latin Hypercube Sampling. *Technometrics*. 29, 143–151.

See Also

`help(randomLHS, lhs)`

Examples

```
# uses the RandLHS method
## Random Latin Hypercube draws for the "Ishigami" model

# Example I: by using the class constructors: mtkRandLHSDesigner()

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkRandLHSDesigner( listParameters = list(size=10) )

# 2) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer) )

# Run the workflow and reports the results.
run(expl)
print(expl)
plot(expl)
```

reevaluate-methods *The reevaluate method*

Description

Re-evaluates the processes of the workflow to know if they should be re-run. This must be done after changing a process in the workflow. The argument "name" gives the process from which the workflow should be reevaluated. i.e. if name="design", we tell the workflow that all the processes after the process "design" should be reevaluated. If name="evaluate", we tell the workflow that only the processes after the process "evaluate" should be re-evaluated, etc.

Usage

```
reevaluate(this, name)
```

Arguments

this	the underlying object of class <code>mtkExpWorkflow</code> .
name	a string from "design", "evaluate", or "analyze" to specify the process from which we re-evaluate the workflow.

Value

```
invisible()
```

Details

This function is only useful for the kernel programming.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# see examples.
```

Description

A `mtk` compliant implementation of the `src` method for computing the sensitivity index based on standardized (rank) regression coefficients.

Usage

- `mtkRegressionAnalyser(listParameters = NULL)`
- `mtkNativeAnalyser(analyze="Regression", information=NULL)`

Parameters used to manage the method

rank: logical. If TRUE, the analysis is done on the ranks (default is FALSE). See the help on function `src` in the package `sensitivity`.

nboot: the number of bootstrap replicates (default 100). See the help on function `src` in the package `sensitivity`.

conf: the confidence level for bootstrap confidence intervals (default 0.95). See the help on function `src` in the package `sensitivity`.

Details

1. The `mtk` implementation uses the `src` function of the package `sensitivity`. For further details on the arguments and the behavior, see `help(src, sensitivity)`.
2. The implementation of the "Regression" method includes the class `mtkRegressionAnalyser` to manage the analysis task and the class `mtkRegressionAnalyserResult` to manage the results produced by the analysis process.

References

A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis, Edition Wiley

See Also

`help(src, sensitivity)`

Examples

```
# Uses the method "Regression" to analyze the model "Ishigami":

# Generate the factors
data(Ishigami.factors)

# Builds experiment design with the Monte-Carlo method
designer <- mtkBasicMonteCarloDesigner( listParameters=list(size=20) )

# Builds a simulator for the model "Ishigami" with the defined factors
model <- mtkNativeEvaluator("Ishigami" )

# Builds an analyser with the method "Regression" implemented in the package "mtk"
```

```

    analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

# Builds a workflow to manage the processes scheduling.
ishiReg <- mtkExpWorkflow( expFactors=Ishigami.factors,
    processesVector=c(design=designer, evaluate=model, analyze=analyser) )

# Runs the workflow et reports the results
run(ishiReg)
summary(ishiReg)
plot(ishiReg)

```

report-methods	<i>The report method</i>
----------------	--------------------------

Description

Returns a detail report of the results produced by the process.

Usage

```
report(this)
```

Arguments

`this` the underlying object of class `mtkProcess`

Value

The form of the value returned by `report` depends on the sub-class where the method is implemented.

See the documentation of the particular sub-class for details of what is produced.

By default, it prints the report on the display device and return `invisible()`.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```

# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
    distribPara=list(min=-pi, max=pi))

```

```

x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the Morris method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))
# Run the workflow and plot the results.
run(expl)
report(expl)

# Extract a process and report its results

p <- getProcess(expl, "analyze")
report(p)

```

run-methods

The run method

Description

Runs a task defined in a process or workflow. Examples classes in which this function is implemented are the following: [\[mtkParsor\]](#), [\[mtkExpWorkflow\]](#), [\[mtkProcess\]](#) and their sub-classes. Examples of "run" are:

- `run(this, context)` "this" is an object of class [\[mtkNativeDesigner\]](#), and "context" is an object of class [\[mtkExpWorkflow\]](#).
- `run(this, context)` "this" is an object of class [\[mtkParsor\]](#), and "context" is an object of class [\[mtkExpWorkflow\]](#).

Usage

```
run(this, context)
```

Arguments

`this` an object corresponding to the task to launch. It may be an object of the following classes: [\[mtkParsor\]](#), [\[mtkExpWorkflow\]](#), [\[mtkProcess\]](#) or their sub-classes.

context missing or an object specifying the context which manages the task. It may be an object of the following classes: [mtkExpWorkflow](#) or its sub-classes.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a designer and an analyser avec the method "Morris"
# to analyze the model "Ishigami":

# Specify the factors to analyze:
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
factors <- mtkExpFactors(list(x1,x2,x3))

# Build the processes:
# 1) the experimental design process with the method "Morris".
expl.designer <- mtkNativeDesigner(design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2))

# 2) the model simulation process with the model "Ishigami".
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method.
# Here, it is the Morris method.
expl.analyser <- mtkDefaultAnalyser()

# Build the workflow with the processes defined previously.
expl <- mtkExpWorkflow(expFactors=factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator, analyze=expl.analyser))
# Run the workflow and plot the results.
run(expl)
print(expl)
```

serializeOn-methods

The serializeOn method

Description

Returns all data and informations managed by an object as a named list.

Usage

```
serializeOn(this)
```

Arguments

`this` the underlying object

Value

a named list

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

Examples

```
# Function not used yet in the current release.
```

```
setDistributionParameters-methods
```

The setDistributionParameters method

Description

Sets the parameters of the distribution associated with a factor's domain.

Usage

```
setDistributionParameters(this, aDistParamList)
```

Arguments

`this` the underlying object of the class `mtkDomain`.
`aDistParamList` a list of objects of class `mtkParameter` or a named list from which we can
 build a list of objects of class `mtkParameter` .

Value

`invisible()`

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# 1) Build an object of the "mtkDomain" class
d <- mtkDomain(distributionName="unif", domainNominalValue=0)

## Define the parameters
p <- make.mtkParameterList(list(min=-pi, max=pi))

## Assign the parameters to the mtkDomain's object

setDistributionParameters(d, p)
# 2) Build an object of the "mtkDomain" class
d <- mtkDomain(distributionName="unif", domainNominalValue=0)

## Assign the parameters to the mtkDomain's object

setDistributionParameters(d, list(min=-pi, max=pi))

# 3) Build an object of the "mtkDomain" class with a discrete distribution
d <- mtkDomain(distributionName="discrete", domainNominalValue=0)

## Assign the parameters to the mtkDomain's object

setDistributionParameters(d, list(type='categorical', levels=seq(1:3), weights=rep(0.33,3)))
```

setDomain-methods *The setDomain method*

Description

Associates a new domain with the factor.

Usage

```
setDomain(this, domain)
```

Arguments

this	an object of the class <code>mtkFactor</code> .
domain	an object of the class <code>mtkDomain</code> .

Value

`invisible()`

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1")

# Define a domain
d <- mtkDomain(distributionName="unif",
  domainNominalValue=0, distributionParameters = list(max=3, min=0))

# Use the setDomain to change the domain of the factor
setDomain(x1,d)
```

setFactors-methods *The setFactors method*

Description

Assigns a list of objects of the class `mtkFactor` to the underlying object.

Usage

```
setFactors(this, aFactList)
```

Arguments

`this` the underlying object of the class `mtkExpFactors`.
`aFactList` a list of objects of the class `mtkFactor`.

Value

`invisible()`

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Build an object of the "mtkExpFactors" class
ishi.factors <- mtkExpFactors()

# Define the factors
x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
# Assign the factors to the mtkExpFactors' object

setFactors(ishi.factors, list(x1,x2,x3))
```

`setFeatures-methods`*The setFeatures method*

Description

Sets the features to an object of the `mtkFactor` class.

Usage

```
setFeatures(this, aFList)
```

Arguments

<code>this</code>	an object of the class <code>mtkFactor</code>
<code>aFList</code>	a list of <code>mtkFeature</code> objects.

Value

invisible

Author(s)

Hervé Richard, BioSP, Inra, Herve.Richard@avignon.inra.fr, Hervé Monod and Juhui WANG, MIA-jouy, INRA

Examples

```
# Build an object of the "mtkFactor" class
x1 <- make.mtkFactor(name="x1", type="double", nominal=0, distribName="unif",
  distribPara=list(min=-pi, max=pi))
# Define the list of features
f <- make.mtkFeatureList(list(f=4.5, c=+6, shape="parabolic"))

# Assign the features to the factor

setFeatures(x1, f)
```

`setLevels-methods` *The setLevels method*

Description

Sets new levels to a discrete distribution.

Usage

```
setLevels(this, levels)
```

Arguments

`this` an object of the class `mtkDomain` or `mtkLevels`.
`levels` an object of the class `mtkLevels` or a list from which we can create an object of the class `mtkLevels`.

Value

invisible

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a new mtkLevels for a discrete distribution

l <- mtkLevels(type='categorical', levels = c(1,2,3,4,5), weights=rep(0.2, 5))
# Change the levels' name to ('a','b','c','d','e')
setLevels(l, c('a','b','c','d','e'))

# Create a new domain with a discrete distribution
d <- mtkDomain(distributionName="discrete", domainNominalValue=3,
distributionParameters = list(type='categorical',
  levels = c(1,2,3,4,5), weights=rep(0.2, 5)))

# Create a new mtkLevels for a discrete distribution and assign it to the domain

l <- mtkLevels(type='categorical', levels = c('a','b','c','d','e'), weights=rep(0.2, 5))
setLevels(d, l)

# Change the domain's levels to type='categorical', levels = c(5,4,3,2,1), weights=rep(0.2, 5))

setLevels(d, levels=list(type='categorical', levels = c(5,4,3,2,1), weights=rep(0.2, 5)))
```

setName-methods

The setName method

Description

Gives a new name to the underlying object

Usage

```
setName(this, name)
```

Arguments

`this` the underlying object
`name` a string indicating the new name.

Value

invisible()

Details

Used by many classes. The behavior depends on the underlying class.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", type="double", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Change the numeric value of the factor to "numeric" type.

setName(x1, name="mit")

# Create a new object of mtkValue
d <- mtkValue("a", "double", 0)

# Change the name of the object to "x" type.
setName(d, "x")
```

setParameters-methods

The setParameters method

Description

Assigns a vector of parameters to the process.

Usage

```
setParameters(this, f)
```

Arguments

<code>this</code>	the underlying object of class <code>mtkProcess</code>
<code>f</code>	a vector of <code>mtkParameter</code> .

Value

invisible()

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a process for experiments design

designer <- mtkNativeDesigner(design ="Morris")

# Create a list of mtkParameter for the parameters: min, max, shape.
p <- make.mtkParameterList(list(size=20))

# Assign the parameters to the process

setParameter(designer, p)
```

setProcess-methods *The setProcess method*

Description

Places or replaces a process into the workflow.

Usage

```
setProcess(this, p, name)
```

Arguments

<code>this</code>	the underlying object of the class <code>mtkExpWorkflow</code> .
<code>p</code>	an object of the class <code>mtkProcess</code> .
<code>name</code>	a string from "design", "evaluate", or "analyze" to specify the process to place or replace.

Value

`invisible()`

Details

This method is especially useful when we need to compare different methods or models.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Analyze the "Ishigami" model with the "Regression" method

x1 <- make.mtkFactor(name="x1", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x2 <- make.mtkFactor(name="x2", distribName="unif",
  distribPara=list(min=-pi, max=pi))
x3 <- make.mtkFactor(name="x3", distribName="unif",
  distribPara=list(min=-pi, max=pi))
ishi.factors <- mtkExpFactors(list(x1,x2,x3))

designer <- mtkNativeDesigner("BasicMonteCarlo",
  information=list(size=20))
model <- mtkNativeEvaluator("Ishigami" )
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

ishiReg <- mtkExpWorkflow( expFactors=ishi.factors,
  processesVector=c( design=designer,
    evaluate=model,
    analyze=analyser)
)
run(ishiReg)
summary(ishiReg)

# Re-analyzes the model "Ishigami" with the method "Morris"

# 1) Build a designer with the method "Morris" and put it into the workflow
morris.designer <- mtkNativeDesigner(
  design="Morris",
  information=list(r=20,type="oat",levels=4,grid.jump=2)
)
setProcess(ishiReg, morris.designer, "design")

# 2) Build an analysis process with the default method and put it
# into the workflow
default.analyser <- mtkDefaultAnalyser()
setProcess(ishiReg, default.analyser, "analyze")
# 3) Run the new workflow

run(ishiReg)
summary(ishiReg)
```

Description

Makes the process ready to run.

Usage

```
setReady(this, switch)
```

Arguments

<code>this</code>	the underlying object of the class <code>mtkProcess</code>
<code>switch</code>	a logical (TRUE or FALSE).

Value

`invisible()`

Details

This function is only useful for the programmers who need to program the mtk's internal functions.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# This function is only useful for the programmers
# who need to program the mtk's internal functions.
```

setState-methods *The setState method*

Description

Marks the state of the process as TRUE when the results produced by the process are available.

Usage

```
setState(this, state)
```

Arguments

<code>this</code>	the underlying object of the <code>mtkProcess</code> class
<code>state</code>	a logical (TRUE or FALSE).

Value

invisible()

Details

This function is only useful for the programmers who need to program the mtk's internal functions.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In*: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# This function is only useful for the programmers
# who need to program the mtk's internal functions.
```

setType-methods	<i>The setType method</i>
-----------------	---------------------------

Description

Gives a new type to the underlying object.

Usage

```
setType(this, type)
```

Arguments

<code>this</code>	the underlying object
<code>type</code>	a string indicating the new type for the data. It may be "numeric", "integer", "double", etc.

Value

invisible()

Details

Used by many classes. The behavior depends on the underlying class.

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Define a factor
x1 <- make.mtkFactor(name="x1", type="double", distribName="unif",
  distribPara=list(min=-pi, max=pi))

# Change the numeric value of the factor to "numeric" type.

setType(x1, type="numeric")

# Create a new object of mtkValue
d <- mtkValue("a", "double", 0)

# Change the numeric value of the object to "numeric" type.
setType(d, "numeric")
```

setValue-methods *The setValue method*

Description

Gives a new value to the underlying object

Usage

```
setValue(this, val)
```

Arguments

<code>this</code>	the underlying object of the corresponding class.
<code>val</code>	a new value.

Value

invisible()

Details

Used by many classes. The behavior depends on the underlying class.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Create a new object of mtkValue
d <- mtkValue("a", "double", 0)
getValue(d) # gives 0.0

setValue(d, 3.14)
getValue(d) # gives 3.14
```

setWeights-methods *The setWeights method*

Description

Gives new weights to the discrete distribution associated with the factor's domain.

Usage

```
setWeights(this, weights)
```

Arguments

this	the underlying object of the class to proceed (mtkLevels).
weights	a vector of numeric value.

Value

invisible

Author(s)

Juhui WANG, MIA-jouy, INRA

Examples

```
# Create a mtkLevels object

l <- mtkLevels(type='categorical', levels=c(1,2,3,4))

setWeights(l, weights=rep(0.25,4))
```

setXMLFilePath-methods

The setXMLFilePath function

Description

Specifies the XML file to parse.

Usage

```
setXMLFilePath(this, xmlPath)
```

Arguments

<code>this</code>	the underlying object of class <code>mtkParsor</code>
<code>xmlPath</code>	a string indicating the XML file to parse.

Value

`invisible()`

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Specify the XML file's name
xmlFile <- "WWDM_morris.xml"

## Find where the example XML file is held in the 'mtk' package.
## (This line is nit useful for real life example!)
xmlFile <- paste(path.package("mtk", quiet = TRUE),
"/extdata/", xmlFile, sep = "")

# Create a XML parsor.
parsor <- mtkParsor(xmlFile)

# Create an empty workflow.
workflow <- mtkExpWorkflow()

# Parse the XML file and initialize the workflow
# with the data extracted from the XML file.
run(parsor, workflow)

# Run the workflow
```

```

run(workflow)

# If you want to parse another XML file with the same parsor,
# just changes the XML file to "inst/extdata/ishigami_fast.xml".

xmlFile <- "ishigami_fast.xml"

# Find where the example XML file is held in the 'mtk' package.
# (This line is nit useful for real life example!)
xmlFile <- paste(path.package("mtk", quiet = TRUE),
"/extdata/",xmlFile,sep = "")

# Change the XML file to the new one
setXMLFilePath(parsor, xmlFile)

# Parse the new XML file and initialize the workflow
# with the data extracted from the XML file.
run(parsor, workflow)

# Run the workflow
run(workflow)

```

Sobol

The Sobol Method

Description

A mtk compliant implementation of the Sobol' method for design of experiments and sensitivity analysis.

Usage

- `mtkSobolDesigner(listParameters = NULL)`
- `mtkNativeDesigner(design="Sobol", information=NULL)`
- `mtkSobolAnalyser(listParameters = NULL)`
- `mtkNativeAnalyser(analyze="Sobol", information=NULL)`

Parameters

N: the size of the basic samples; the final sample size will be $N \cdot (k+2)$ where k is the number of the factors to analyze.

nboot: the number of bootstrap replicates (default 0). See the help on function `sobol2002` in the package `sensitivity`.

conf: the confidence level for bootstrap confidence intervals (default 0.95). See the help on function `sobol2002` in the package `sensitivity`.

sampling: character string specifying the type of sampling method: "MC" (default) for Monte Carlo sampling, "LHS" for Latin Hypercube sampling.

shrink: a scalar or a vector of scalars between 0 and 1 (default 1), specifying shrinkage to be used on the probabilities before calculating the quantiles.

Details

1. The `mtk` implementation uses the `sobol2002` function of the `sensitivity` package. For further details on the arguments and the behavior, see `help(sobol2002, sensitivity)`.
2. The `mtk` implementation of the Sobol' method includes the following classes:
 - `mtkSobolDesigner`: for the Sobol design processes.
 - `mtkSobolAnalyser`: for Sobol analysis processes.
 - `mtkSobolDesignerResult`: to store and manage the design.
 - `mtkSobolAnalyserResult`: to store and manage the analysis results.
3. Many ways to create a Sobol designer are available in `mtk`, but we recommend the following class constructors: `mtkSobolDesigner` or `mtkNativeDesigner`.
4. Many ways to create a Sobol analyser are available in `mtk`, but we recommend the following class constructors: `mtkSobolAnalyser` or `mtkNativeAnalyser`.
5. The Sobol' method is usually used both to build the experiment design and to carry out the sensitivity analysis. In such case, we can use the `mtkDefaultAnalyser` instead of naming explicitly the method for sensitivity analysis (see example III in the examples section)

References

A. Saltelli, K. Chan and E. M. Scott (2000). Sensitivity Analysis. Wiley, New York

See Also

`help(sobol2002, sensitivity)`, `Quantiles`

Examples

```
## Sensitivity analysis of the "Ishigami" model with the "Sobol" method

# Example I: by using the class constructors: mtkSobolDesigner() and mtkSobolAnalyser()

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkSobolDesigner( listParameters = list(N=100))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process
expl.analyser <- mtkSobolAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
    analyze=expl.analyser))

# Run the workflow and reports the results.
```

```
run(exp1)
print(exp1)
plot(exp1)

## Example II: by using the class constructors: mtkNativeDesigner() and mtkSobolAnalyse

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkNativeDesigner(design = "Sobol", information = list(N=10))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkSobolAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
    analyze=expl.analyser))

# Run the workflow and reports the results.
run(exp1)
print(exp1)
plot(exp1)

## Example III: by using the class constructors: mtkSobolDesigner() and mtkDefaultAnaly

# Generate the factors
data(Ishigami.factors)

# Build the processes and workflow:

# 1) the design process
expl.designer <- mtkSobolDesigner( listParameters = list(N=10))

# 2) the simulation process
expl.evaluator <- mtkNativeEvaluator(model="Ishigami")

# 3) the analysis process with the default method
expl.analyser <- mtkDefaultAnalyser()

# 4) the workflow

expl <- mtkExpWorkflow(expFactors=Ishigami.factors,
  processesVector = c(design=expl.designer,
    evaluate=expl.evaluator,
    analyze=expl.analyser))

# Run the workflow and reports the results.
```

```
run(expl)
print(expl)
plot(expl)
```

```
summary,mtkProcess-method
```

The summary method

Description

Returns a summary report of the results produced by the process.

Usage

```
summary(object, ...)
```

Arguments

<code>object</code>	the underlying object of class <code>mtkProcess</code> .
<code>...</code>	see the help for the function: <code>base::summary()</code> .

Value

The form of the value returned by `summary` depends on the sub-class where the method is implemented.

By default, it prints the report on the display device.

Details

1. The behavior of the `print` depends on the sub-class where the method is implemented.
2. See the documentation of the particular sub-class for details of what is produced.
3. Use `methods("summary")` to get all the methods for the `summary` generic.

Author(s)

Juhui WANG, MIA-Jouy, Inra, Juhui.Wang@jouy.inra.fr

References

J. Wang, H. Richard, R. Faivre, H. Monod (2013). Le package `mtk`, une bibliothèque R pour l'exploration numérique des modèles. *In: Analyse de sensibilité et exploration de modèles : Application aux sciences de la nature et de l'environnement* (R. Faivre, B. Iooss, S. Mahévas, D. Makowski, H. Monod, Eds). Editions Quae, Versailles.

Examples

```
# Carry out a sensitivity analysis with the Ishigami model

## Input the factors
data(Ishigami.factors)

## Specify the experiments designer
designer <- mtkNativeDesigner ("BasicMonteCarlo",
information=list(size=20))

## Specify the model simulator
model <- mtkIshigamiEvaluator()

## Specify the sensitivity analyser
analyser <- mtkNativeAnalyser("Regression", information=list(nboot=20) )

## Specify the workflow
ishiReg <- new("mtkExpWorkflow", expFactors=Ishigami.factors,
  processesVector=c(
    design=designer,
    evaluate=model,
    analyze=analyser)
)
## Run and report a summary of the results produced by the workflow
run(ishiReg)
summary(ishiReg)
```

WWDM

The WWDM model

Description

The WWDM (Winter Wheat Dry Matter Model) is a very simple dynamic crop model with a daily time step. It has been developed at INRA (France) by David Makowski, Marie-Hélène Jeuffroy and Martine Guérif.

The behavior of the model is influenced by seven factors:

Eb: Radiation use efficiency

Eimax: Maximal ratio of intercepted to incident radiation

K: Coefficient of extinction

Lmax: Maximal value of the Leaf Area Index (LAI)

A: Coefficient of LAI increase

B: Coefficient of LAI decrease

TI: Temperature threshold

Details

1. The implementation of the WWDM model includes the object `WWDM.factors` on the input factors, the class `mtkWWDMEvaluator` to run the simulations, and the data frame `wwdm.climates` containing the climate data.
2. In `mtk`, there are a few ways to build an evaluator of the WWDM model, but we usually recommend the following class constructors: `mtkWWDMEvaluator`, `mtkNativeEvaluator`.

Usage

- `mtkWWDMEvaluator(listParameters=NULL)`
- `mtkNativeEvaluator(model="WWDM",information=NULL)`
- `mtkEvaluator(protocol = "R", site = "mtk", service = "WWDM", parametersList=NULL)`

Parameters used to manage the simulation

`year` Either NULL or a number between 1 and 14 to specify the number of years to simulate. A database with 14 yearly sequences of meteorological data are included in the environment (data frame `wwdm.climates`).

References

1. Makowski, D., Jeuffroy, M.-H., Guérif, M., 2004. Bayesian methods for updating crop model predictions, applications for predicting biomass and grain protein content. In: Bayesian Statistics and Quality Modelling in the Agro-Food Production Chain (van Boekel et al. eds), pp. 57-68. Kluwer, Dordrecht.
2. Monod, H., Naud, C., Makowski, D., 2006. Uncertainty and sensitivity analysis for crop models. In: Working with Dynamic Crop Models (Wallach D., Makowski D. and Jones J. eds), pp. 55-100. Elsevier, Amsterdam.

See Also

`help(WWDM.factors)`

Examples

```
## Evaluation of the "WWDM" model

# Example I: by using the class constructors: mtkWWDMEvaluator()

# Generate the factors
data(WWDM.factors)

# Build the workflow:
# 1) specify the design process
designer <- mtkNativeDesigner("BasicMonteCarlo", information = list(size=50) )

# 2) specify the evaluation process;
model <- mtkWWDMEvaluator(listParameters = list(year=3) )

# 3) specify the workflow with the processes defined previously

exp <- mtkExpWorkflow( expFactors=WWDM.factors,
  processesVector=c( design=designer, evaluate=model) )
```



```

# Run the workflow and report the results.
run(exp)
summary(exp)

# Personalize the data reporting

designData <- extractData(exp,name="design")

simulationData <- extractData(exp,name="evaluate")

plot(designData$Eb, simulationData$Biomass, xlab="Eb",ylab="Biomass")

## Example II: by using the class constructor: mtkNativeEvaluator()

# Generate the input factors
data(WWDM.factors)

# Build the workflow:
# 1) specify the design process
designer <- mtkNativeDesigner("BasicMonteCarlo", information = list(size=20) )

# 2) specify the evaluation process;
model <- mtkNativeEvaluator(model="WWDM", information=list(year=3) )

# 3) specify the workflow with the processes defined previously

exp <- mtkExpWorkflow(expFactors=WWDM.factors,
  processesVector=c( design=designer, evaluate=model) )

# Run the workflow and report the results.
run(exp)
summary(exp)
plot(exp)

```

wwdm.climates

Dataset used with the [WWDM model](#)

Description

This dataset gives climatic data needed by the [WWDM](#) crop model model.

ANNEE numeric, year of weather data: from 1 to 14.

RG Global Radiation

Tmin Minimal temperature

Tmax Maximal temperature

References

1. Makowski, D., Jeuffroy, M.-H., Gu'erif, M., 2004. Bayesian methods for updating crop model predictions, applications for predicting biomass and grain protein content. In: Bayesian Statistics and Quality Modelling in the Agro-Food Production Chain (van Boeakel et al. eds), pp. 57-68. Kluwer, Dordrecht.

2. Monod, H., Naud, C., Makowski, D., 2006. Uncertainty and sensitivity analysis for crop models. In: Working with Dynamic Crop Models (Wallach D., Makowski D. and Jones J. eds), pp. 55-100. Elsevier, Amsterdam.

See Also

`help(WWDM)`

Examples

```
data(wwdm.climates)
summary(wwdm.climates)
wwdm.climates[1:20,]
par(mfrow=c(3,1)) ;
for(i in 1:3) ts.plot(wwdm.climates[,1]==1,1+i),
  ylab=names(wwdm.climates[1+i])
)
```

WWDM.factors

The input factors of the [WWDM](#) model

Description

This dataset gives the input factors and their uncertainty domains involved in the [WWDM](#) model.

Eb Radiation use efficiency

Eimax Maximal ratio of intercepted to incident radiation

K Coefficient of extinction

Lmax Maximal value of the Leaf Area Index (LAI)

A Coefficient of LAI increase

B Coefficient of LAI decrease

TI Temperature threshold

Usage

```
data(WWDM.factors)
```

Format

an object of the class [mtkExpFactors](#).

References

1. Makowski, D., Jeuffroy, M.-H., Gu'érif, M., 2004. Bayesian methods for updating crop model predictions, applications for predicting biomass and grain protein content. In: Bayesian Statistics and Quality Modelling in the Agro-Food Production Chain (van Boeakel et al. eds), pp. 57-68. Kluwer, Dordrecht.
2. Monod, H., Naud, C., Makowski, D., 2006. Uncertainty and sensitivity analysis for crop models. In: Working with Dynamic Crop Models (Wallach D., Makowski D. and Jones J. eds), pp. 55-100. Elsevier, Amsterdam.

See Also

```
help(WWDM)
```

Examples

```
# The code used to generate the WWDM.factors is as follows:
Eb <- make.mtkFactor(name="Eb", distribName="unif",
  nominal=1.85, distribPara=list(min=0.9, max=2.8), unit="g/MJ")
Eimax <- make.mtkFactor(name="Eimax", distribName="unif",
  nominal=0.94, distribPara=list(min=0.9, max=0.99))
K <- make.mtkFactor(name="K", distribName="unif",
  nominal=0.7, distribPara=list(min=0.6, max=0.8))
Lmax <- make.mtkFactor(name="Lmax", distribName="unif",
  nominal=7.5, distribPara=list(min=3, max=12), unit="m\u00b2/m\u00b2")
A <- make.mtkFactor(name="A", distribName="unif",
  nominal=0.0065, distribPara=list(min=0.0035, max=0.01))
B <- make.mtkFactor(name="B", distribName="unif",
  nominal=0.00205, distribPara=list(min=0.0011, max=0.0025))
TI <- make.mtkFactor(name="TI", distribName="unif",
  nominal=900, distribPara=list(min=700, max=1100), unit="\u00b0C")

WWDM.factors <- mtkExpFactors(list(Eb,Eimax,K,Lmax,A,B,TI))

# To import the WWDM.factors, just use the following line
data(WWDM.factors)
```

Index

*Topic **datasets**

Ishigami.factors, [42](#)

*Topic **dataset**

wwdm.climates, [201](#)

WWDm.factors, [202](#)

[, mtkExpFactors-method
(*mtkExpFactors-class*), [82](#)

[[, mtkExpFactors-method
(*mtkExpFactors-class*), [82](#)

\$, mtkExpFactors-method
(*mtkExpFactors-class*), [82](#)

addProcess, [80](#), [86](#)

addProcess (addProcess-methods), [7](#)

addProcess, mtkExperiment, mtkProcess, character-method
(*mtkExperiment-class*), [80](#)

addProcess, mtkExpWorkflow, mtkProcess, character-method
(*mtkExpWorkflow-class*), [85](#)

addProcess-methods, [7](#)

ANY, [8](#), [56](#), [60](#), [65](#), [68](#), [75](#), [92](#), [97](#), [100](#), [101](#),
[103](#), [109](#), [114](#), [118](#), [119](#), [122](#), [126](#),
[128](#), [129](#), [133](#), [138](#), [140](#), [145](#), [151](#),
[155](#), [159](#), [163](#), [165](#)

BasicMonteCarlo, [9](#)

character, [56](#), [60](#), [65](#), [67](#), [68](#), [72](#), [75](#), [78](#),
[79](#), [84](#), [92](#), [97](#), [100](#), [101](#), [103](#), [106](#),
[108](#), [114](#), [118](#), [122](#), [126](#), [128](#), [129](#),
[131](#), [133](#), [138](#), [140](#), [145](#), [151](#), [155](#),
[159](#), [163](#), [165](#)

data.frame, [58](#), [63](#), [71](#), [78](#), [94](#), [99](#), [111](#),
[116](#), [135](#), [142](#), [147](#), [153](#), [157](#), [161](#),
[168](#)

deleteProcess, [80](#), [86](#)

deleteProcess
(deleteProcess-methods), [10](#)

deleteProcess, mtkExperiment, character-method
(*mtkExperiment-class*), [80](#)

deleteProcess, mtkExpWorkflow, character-method
(*mtkExpWorkflow-class*), [85](#)

deleteProcess-methods, [10](#)

extractData, [80](#), [86](#)

extractData
(extractData-methods), [12](#)

extractData, mtkExperiment, character-method
(*mtkExperiment-class*), [80](#)

extractData, mtkExpWorkflow, character-method
(*mtkExpWorkflow-class*), [85](#)

extractData-methods, [12](#)

Fast, [13](#)

getData, [56](#), [76](#), [92](#), [97](#), [104](#), [109](#), [114](#), [119](#),
[122](#), [126](#), [134](#), [139](#), [141](#), [145](#), [152](#),
[156](#), [160](#), [166](#)

getData (getData-methods), [15](#)

getData, mtkAnalys
(*mtkAnalyser-class*), [55](#)

getData, mtkBasicMonteCarloDesigner-method
(*mtkBasicMonteCarloDesigner-class*),
[60](#)

getData, mtkDefaultAnalyser-method
(*mtkDefaultAnalyser-class*),
[65](#)

getData, mtkDesigner-method
(*mtkDesigner-class*), [68](#)

getData, mtkEvaluator-method
(*mtkEvaluator-class*), [75](#)

getData, mtkFastAnalyser-method
(*mtkFastAnalyser-class*), [91](#)

getData, mtkFastDesigner-method
(*mtkFastDesigner-class*), [96](#)

getData, mtkIshigamiEvaluator-method
(*mtkIshigamiEvaluator-class*),
[103](#)

getData, mtkMorrisAnalyser-method
(*mtkMorrisAnalyser-class*),
[108](#)

getData, mtkMorrisDesigner-method
(*mtkMorrisDesigner-class*),
[113](#)

getData, mtkNativeAnalyser-method
(*mtkNativeAnalyser-class*),
[118](#)

getData, mtkNativeDesigner-method
(*mtkNativeDesigner-class*),

- 121
- getData, mtkNativeEvaluator-method
(*mtkNativeEvaluator-class*),
125
- getData, mtkPLMMAAnalyser-method
(*mtkPLMMAAnalyser-class*),
133
- getData, mtkProcess-method
(*mtkProcess-class*), 138
- getData, mtkRandLHSDesigner-method
(*mtkRandLHSDesigner-class*),
140
- getData, mtkRegressionAnalyser-method
(*mtkRegressionAnalyser-class*),
144
- getData, mtkSobolAnalyser-method
(*mtkSobolAnalyser-class*),
151
- getData, mtkSobolDesigner-method
(*mtkSobolDesigner-class*),
155
- getData, mtkSystemEvaluator-method
(*mtkSystemEvaluator-class*),
159
- getData, mtkWWDMEvaluator-method
(*mtkWWDMEvaluator-class*),
165
- getData-methods, 15
- getDiscreteDistributionLevels, 89
- getDiscreteDistributionLevels
(*getDiscreteDistributionLevels-methods*),
17
- getDiscreteDistributionLevels, mtkFactor-method
(*mtkFactor-class*), 89
- getDiscreteDistributionLevels-methods, 17
- getDiscreteDistributionType, 73,
89
- getDiscreteDistributionType
(*getDiscreteDistributionType-methods*),
17
- getDiscreteDistributionType, mtkDomain-method
(*mtkDomain-class*), 72
- getDiscreteDistributionType, mtkFactor-method
(*mtkFactor-class*), 89
- getDiscreteDistributionType-methods,
17
- getDiscreteDistributionWeights,
89
- getDiscreteDistributionWeights
(*getDiscreteDistributionWeights-methods*),
18
- getDiscreteDistributionWeights, mtkFactor-method
(*mtkFactor-class*), 89
- getDiscreteDistributionWeights-methods,
18
- getDistributionName, 73, 89
- getDistributionName
(*getDistributionName-methods*),
19
- getDistributionName, mtkDomain-method
(*mtkDomain-class*), 72
- getDistributionName, mtkFactor-method
(*mtkFactor-class*), 89
- getDistributionName-methods, 19
- getDistributionNames
(*getDistributionNames-methods*),
20
- getDistributionNames, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getDistributionNames-methods, 20
- getDistributionNominalValue, 89
- getDistributionNominalValue
(*getDistributionNominalValue-methods*),
21
- getDistributionNominalValue, mtkFactor-method
(*mtkFactor-class*), 89
- getDistributionNominalValue-methods,
21
- getDistributionNominalValues
(*getDistributionNominalValues-methods*),
21
- getDistributionNominalValues, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getDistributionNominalValues-methods,
21
- getDistributionNominalValueType,
89
- getDistributionNominalValueType
(*getDistributionNominalValueType-methods*),
22
- getDistributionNominalValueType, mtkFactor-method
(*mtkFactor-class*), 89
- getDistributionNominalValueType-methods,
22
- getDistributionNominalValueTypes
(*getDistributionNominalValueTypes-methods*),
23
- getDistributionNominalValueTypes, mtkExpFactors
(*mtkExpFactors-class*), 82
- getDistributionNominalValueTypes-methods,
23
- getDistributionParameters, 73, 90
- getDistributionParameters

- (getDistributionParameters-methods)*, 24
- getDistributionParameters*, mtkDomain-method
(*mtkDomain-class*), 72
- getDistributionParameters*, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getDistributionParameters*, mtkFactor-method
(*mtkFactor-class*), 89
- getDistributionParameters-methods*, 24
- getDomain*, 89
- getDomain* (*getDomain-methods*), 24
- getDomain*, mtkFactor-method
(*mtkFactor-class*), 89
- getDomain-methods*, 24
- getFactorFeatures*
(*getFactorFeatures-methods*), 25
- getFactorFeatures*, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getFactorFeatures-methods*, 25
- getFactorNames*
(*getFactorNames-methods*), 26
- getFactorNames*, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getFactorNames-methods*, 26
- getFactors* (*getFactors-methods*), 27
- getFactors*, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getFactors-methods*, 27
- getFeatures*, 90
- getFeatures*
(*getFeatures-methods*), 28
- getFeatures*, mtkFactor-method
(*mtkFactor-class*), 89
- getFeatures-methods*, 28
- getLevels*, 73, 106
- getLevels* (*getLevels-methods*), 28
- getLevels*, mtkDomain-method
(*mtkDomain-class*), 72
- getLevels*, mtkLevels-method
(*mtkLevels-class*), 106
- getLevels-methods*, 28
- getMTKFeatures*, 90
- getMTKFeatures*
(*getMTKFeatures-methods*), 29
- getMTKFeatures*, mtkFactor-method
(*mtkFactor-class*), 89
- getMTKFeatures-methods*, 29
- getName*, 89, 101, 129, 138, 163
- getName* (*getName-methods*), 30
- getName*, mtkFactor-method
(*mtkFactor-class*), 89
- getName*, mtkFeature-method
(*mtkFeature-class*), 101
- getName*, mtkParameter-method
(*mtkParameter-class*), 129
- getName*, mtkProcess-method
(*mtkProcess-class*), 138
- getName*, mtkValue-method
(*mtkValue-class*), 162
- getName-methods*, 30
- getNames* (*getNames-methods*), 30
- getNames*, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- getNames-methods*, 30
- getNominalValue*, 73
- getNominalValue*
(*getNominalValue-methods*), 31
- getNominalValue*, mtkDomain-method
(*mtkDomain-class*), 72
- getNominalValue-methods*, 31
- getNominalValueType*, 73
- getNominalValueType*
(*getNominalValueType-methods*), 32
- getNominalValueType*, mtkDomain-method
(*mtkDomain-class*), 72
- getNominalValueType-methods*, 32
- getParameters*, 56, 75, 92, 97, 103, 109, 114, 119, 122, 126, 133, 138, 141, 145, 151, 155, 159, 166
- getParameters*
(*getParameters-methods*), 33
- getParameters*, mtkAnalyser-method
(*mtkAnalyser-class*), 55
- getParameters*, mtkBasicMonteCarloDesigner-method
(*mtkBasicMonteCarloDesigner-class*), 60
- getParameters*, mtkDefaultAnalyser-method
(*mtkDefaultAnalyser-class*), 65
- getParameters*, mtkDesigner-method
(*mtkDesigner-class*), 68
- getParameters*, mtkEvaluator-method
(*mtkEvaluator-class*), 75
- getParameters*, mtkFastAnalyser-method
(*mtkFastAnalyser-class*), 91
- getParameters*, mtkFastDesigner-method
(*mtkFastDesigner-class*), 96

- getParameters, mtkIshigamiEvaluator-method 152, 155, 160, 166
(*mtkIshigamiEvaluator-class*), 103
- getParameters, mtkMorrisAnalyser-method
(*mtkMorrisAnalyser-class*), 108
- getParameters, mtkMorrisDesigner-method
(*mtkMorrisDesigner-class*), 113
- getParameters, mtkNativeAnalyser-method
(*mtkNativeAnalyser-class*), 118
- getParameters, mtkNativeDesigner-method
(*mtkNativeDesigner-class*), 121
- getParameters, mtkNativeEvaluator-method
(*mtkNativeEvaluator-class*), 125
- getParameters, mtkPLMMAAnalyser-method
(*mtkPLMMAAnalyser-class*), 133
- getParameters, mtkProcess-method
(*mtkProcess-class*), 138
- getParameters, mtkRandLHSDesigner-method
(*mtkRandLHSDesigner-class*), 140
- getParameters, mtkRegressionAnalyser-method
(*mtkRegressionAnalyser-class*), 144
- getParameters, mtkSobolAnalyser-method
(*mtkSobolAnalyser-class*), 151
- getParameters, mtkSobolDesigner-method
(*mtkSobolDesigner-class*), 155
- getParameters, mtkSystemEvaluator-method
(*mtkSystemEvaluator-class*), 159
- getParameters, mtkWWDMEvaluator-method
(*mtkWWDMEvaluator-class*), 165
- getParameters-methods, 33
- getProcess, 80, 86
- getProcess (*getProcess-methods*), 34
- getProcess, mtkExperiment, character-method
(*mtkExperiment-class*), 80
- getProcess, mtkExpWorkflow, character-method
(*mtkExpWorkflow-class*), 85
- getProcess-methods, 34
- getResult, 56, 76, 92, 97, 104, 109, 114, 119, 122, 126, 134, 138, 141, 145, 152, 155, 160, 166
- getResult (*getResult-methods*), 35
- getResult, mtkAnalyser-method
(*mtkAnalyser-class*), 55
- getResult, mtkBasicMonteCarloDesigner-method
(*mtkBasicMonteCarloDesigner-class*), 60
- getResult, mtkDefaultAnalyser-method
(*mtkDefaultAnalyser-class*), 65
- getResult, mtkDesigner-method
(*mtkDesigner-class*), 68
- getResult, mtkEvaluator-method
(*mtkEvaluator-class*), 75
- getResult, mtkFastAnalyser-method
(*mtkFastAnalyser-class*), 91
- getResult, mtkFastDesigner-method
(*mtkFastDesigner-class*), 96
- getResult, mtkIshigamiEvaluator-method
(*mtkIshigamiEvaluator-class*), 103
- getResult, mtkMorrisAnalyser-method
(*mtkMorrisAnalyser-class*), 108
- getResult, mtkMorrisDesigner-method
(*mtkMorrisDesigner-class*), 113
- getResult, mtkNativeAnalyser-method
(*mtkNativeAnalyser-class*), 118
- getResult, mtkNativeDesigner-method
(*mtkNativeDesigner-class*), 121
- getResult, mtkNativeEvaluator-method
(*mtkNativeEvaluator-class*), 125
- getResult, mtkPLMMAAnalyser-method
(*mtkPLMMAAnalyser-class*), 133
- getResult, mtkProcess-method
(*mtkProcess-class*), 138
- getResult, mtkRandLHSDesigner-method
(*mtkRandLHSDesigner-class*), 140
- getResult, mtkRegressionAnalyser-method
(*mtkRegressionAnalyser-class*), 144
- getResult, mtkSobolAnalyser-method
(*mtkSobolAnalyser-class*), 151
- getResult, mtkSobolDesigner-method
(*mtkSobolDesigner-class*), 155

- 155
- getResult, mtkSystemEvaluator-method
(*mtkSystemEvaluator-class*),
159
- getResult, mtkWWDMEvaluator-method
(*mtkWWDMEvaluator-class*),
165
- getResult-methods, 35
- getType, 89, 101, 106, 129, 163
- getType (*getType-methods*), 36
- getType, mtkFactor-method
(*mtkFactor-class*), 89
- getType, mtkFeature-method
(*mtkFeature-class*), 101
- getType, mtkLevels-method
(*mtkLevels-class*), 106
- getType, mtkParameter-method
(*mtkParameter-class*), 129
- getType, mtkValue-method
(*mtkValue-class*), 162
- getType-methods, 36
- getValue, 101, 129, 163
- getValue (*getValue-methods*), 37
- getValue, mtkFeature-method
(*mtkFeature-class*), 101
- getValue, mtkParameter-method
(*mtkParameter-class*), 129
- getValue, mtkValue-method
(*mtkValue-class*), 162
- getValue-methods, 37
- getWeights, 73, 106
- getWeights (*getWeights-methods*),
38
- getWeights, mtkDomain-method
(*mtkDomain-class*), 72
- getWeights, mtkLevels-method
(*mtkLevels-class*), 106
- getWeights-methods, 38
- initialize, 89
- initialize, mtkDomain-method
(*mtkDomain-class*), 72
- initialize, mtkExpFactors-method
(*mtkExpFactors-class*), 82
- initialize, mtkFactor-method
(*mtkFactor-class*), 89
- is.finished
(*is.finished-methods*), 38
- is.finished, mtkAnalyser-method
(*mtkAnalyser-class*), 55
- is.finished, mtkBasicMonteCarloDesigner-method
(*mtkBasicMonteCarloDesigner-class*),
60
- is.finished, mtkDefaultAnalyser-method
(*mtkDefaultAnalyser-class*),
65
- is.finished, mtkDesigner-method
(*mtkDesigner-class*), 68
- is.finished, mtkEvaluator-method
(*mtkEvaluator-class*), 75
- is.finished, mtkFastAnalyser-method
(*mtkFastAnalyser-class*), 91
- is.finished, mtkFastDesigner-method
(*mtkFastDesigner-class*), 96
- is.finished, mtkIshigamiEvaluator-method
(*mtkIshigamiEvaluator-class*),
103
- is.finished, mtkMorrisAnalyser-method
(*mtkMorrisAnalyser-class*),
108
- is.finished, mtkMorrisDesigner-method
(*mtkMorrisDesigner-class*),
113
- is.finished, mtkNativeAnalyser-method
(*mtkNativeAnalyser-class*),
118
- is.finished, mtkNativeDesigner-method
(*mtkNativeDesigner-class*),
121
- is.finished, mtkNativeEvaluator-method
(*mtkNativeEvaluator-class*),
125
- is.finished, mtkPLMMAAnalyser-method
(*mtkPLMMAAnalyser-class*),
133
- is.finished, mtkProcess-method
(*mtkProcess-class*), 138
- is.finished, mtkRandLHSDesigner-method
(*mtkRandLHSDesigner-class*),
140
- is.finished, mtkRegressionAnalyser-method
(*mtkRegressionAnalyser-class*),
144
- is.finished, mtkSobolAnalyser-method
(*mtkSobolAnalyser-class*),
151
- is.finished, mtkSobolDesigner-method
(*mtkSobolDesigner-class*),
155
- is.finished, mtkSystemEvaluator-method
(*mtkSystemEvaluator-class*),
159
- is.finished, mtkWWDMEvaluator-method
(*mtkWWDMEvaluator-class*),
165

- `is.finished-methods`, 38
- `is.ready`, 56, 76, 92, 97, 103, 104, 109, 114, 119, 122, 126, 133, 134, 138, 141, 145, 151, 152, 155, 159, 166
- `is.ready(is.ready-methods)`, 39
- `is.ready, mtkAnalyser-method`
(*mtkAnalyser-class*), 55
- `is.ready, mtkBasicMonteCarloDesigner-method`
(*mtkBasicMonteCarloDesigner-class*), 60
- `is.ready, mtkDefaultAnalyser-method`
(*mtkDefaultAnalyser-class*), 65
- `is.ready, mtkDesigner-method`
(*mtkDesigner-class*), 68
- `is.ready, mtkEvaluator-method`
(*mtkEvaluator-class*), 75
- `is.ready, mtkFastAnalyser-method`
(*mtkFastAnalyser-class*), 91
- `is.ready, mtkFastDesigner-method`
(*mtkFastDesigner-class*), 96
- `is.ready, mtkIshigamiEvaluator-method`
(*mtkIshigamiEvaluator-class*), 103
- `is.ready, mtkMorrisAnalyser-method`
(*mtkMorrisAnalyser-class*), 108
- `is.ready, mtkMorrisDesigner-method`
(*mtkMorrisDesigner-class*), 113
- `is.ready, mtkNativeAnalyser-method`
(*mtkNativeAnalyser-class*), 118
- `is.ready, mtkNativeDesigner-method`
(*mtkNativeDesigner-class*), 121
- `is.ready, mtkNativeEvaluator-method`
(*mtkNativeEvaluator-class*), 125
- `is.ready, mtkPLMMAAnalyser-method`
(*mtkPLMMAAnalyser-class*), 133
- `is.ready, mtkProcess-method`
(*mtkProcess-class*), 138
- `is.ready, mtkRandLHSDesigner-method`
(*mtkRandLHSDesigner-class*), 140
- `is.ready, mtkRegressionAnalyser-method`
(*mtkRegressionAnalyser-class*), 144
- `is.ready, mtkSobolAnalyser-method`
(*mtkSobolAnalyser-class*), 151
- `is.ready, mtkSobolDesigner-method`
(*mtkSobolDesigner-class*), 155
- `is.ready, mtkSystemEvaluator-method`
(*mtkSystemEvaluator-class*), 159
- `is.ready, mtkWWDMEvaluator-method`
(*mtkWWDMEvaluator-class*), 165
- `is.ready-methods`, 39
- Ishigami, 40, 42
- `Ishigami.factors`, 41, 42
- `list`, 58, 63, 71, 72, 78, 79, 83, 149
- `logical`, 56, 60, 65, 68, 75, 92, 97, 103, 108, 109, 114, 119, 122, 126, 133, 138, 140, 145, 151, 155, 159, 165
- `make.mtkFactor`, 43, 88
- `make.mtkFeatureList`, 44, 100, 101
- `make.mtkParameterList`, 45, 128, 129
- Morris, 45
- `mtk-package`, 5
- `mtk.analyserAddons`, 48
- `mtk.designerAddons`, 50
- `mtk.evaluatorAddons`, 52
- `mtkAnalyser`, 54, 55, 65, 91, 92, 108, 118, 133, 138, 145, 151
- `mtkAnalyser-class`, 55
- `mtkAnalyserResult`, 55, 56, 57, 57, 66, 92, 94, 111, 119, 135, 147, 153
- `mtkAnalyserResult-class`, 58
- `mtkBasicMonteCarloDesigner`, 9, 59, 59
- `mtkBasicMonteCarloDesigner-class`, 60
- `mtkBasicMonteCarloDesignerResult`, 9, 61, 62, 62, 63
- `mtkBasicMonteCarloDesignerResult-class`, 63
- `mtkDefaultAnalyser`, 14, 46, 64, 64, 65, 196
- `mtkDefaultAnalyser-class`, 65
- `mtkDesigner`, 35, 60, 67, 67, 96, 113, 121, 138, 140, 155
- `mtkDesigner-class`, 68
- `mtkDesignerResult`, 35, 63, 67, 68, 70, 70, 71, 97, 99, 116, 122, 142, 149, 157
- `mtkDesignerResult-class`, 70
- `mtkDomain`, 19, 24, 28, 31, 32, 38, 71, 71–73, 88, 89, 182, 183, 186

- mtkDomain-class, [72](#)
- mtkEvaluator, [74](#), [74](#), [103](#), [125](#), [138](#), [159](#), [165](#)
- mtkEvaluator-class, [75](#)
- mtkEvaluatorResult, [74](#), [76](#), [77](#), [77](#), [78](#), [104](#), [126](#), [149](#), [160](#), [161](#), [168](#)
- mtkEvaluatorResult-class, [77](#)
- mtkExperiment, [78](#), [79](#), [80](#)
- mtkExperiment-class, [80](#)
- mtkExpFactors, [20](#), [21](#), [23–25](#), [27](#), [30](#), [43](#), [78](#), [80](#), [82](#), [82–84](#), [86](#), [184](#), [202](#)
- mtkExpFactors-class, [82](#)
- mtkExpWorkflow, [7](#), [11](#), [12](#), [34](#), [80](#), [84](#), [84](#), [86](#), [177](#), [180](#), [181](#), [188](#)
- mtkExpWorkflow-class, [85](#)
- mtkFactor, [17–19](#), [21](#), [22](#), [24](#), [25](#), [27–29](#), [44](#), [82](#), [83](#), [88](#), [88–90](#), [183–185](#)
- mtkFactor-class, [89](#)
- mtkFastAnalyser, [13](#), [14](#), [90](#), [91](#), [92](#)
- mtkFastAnalyser-class, [91](#)
- mtkFastAnalyserResult, [13](#), [93](#), [94](#)
- mtkFastAnalyserResult-class, [94](#)
- mtkFastDesigner, [13](#), [95](#), [95](#), [96](#)
- mtkFastDesigner-class, [96](#)
- mtkFastDesignerResult, [13](#), [98](#), [99](#)
- mtkFastDesignerResult-class, [99](#)
- mtkFeature, [29](#), [44](#), [90](#), [100](#), [100](#), [101](#), [162](#), [185](#)
- mtkFeature-class, [101](#)
- mtkIshigamiEvaluator, [41](#), [102](#), [102](#), [103](#)
- mtkIshigamiEvaluator-class, [103](#)
- mtkLevels, [28](#), [38](#), [72](#), [73](#), [105](#), [105](#), [106](#), [186](#), [193](#)
- mtkLevels-class, [106](#)
- mtkLevesl, [106](#)
- mtkMorrisAnalyser, [46](#), [55](#), [107](#), [107](#), [108](#)
- mtkMorrisAnalyser-class, [108](#)
- mtkMorrisAnalyserResult, [46](#), [58](#), [109](#), [110](#), [110](#), [111](#)
- mtkMorrisAnalyserResult-class, [111](#)
- mtkMorrisDesigner, [46](#), [68](#), [112](#), [112](#), [113](#)
- mtkMorrisDesigner-class, [113](#)
- mtkMorrisDesignerResult, [46](#), [114](#), [115](#), [116](#)
- mtkMorrisDesignerResult-class, [116](#)
- mtkNativeAnalyser, [14](#), [46](#), [55](#), [117](#), [117–119](#), [170](#), [196](#)
- mtkNativeAnalyser-class, [118](#)
- mtkNativeDesigner, [9](#), [13](#), [46](#), [68](#), [120](#), [120](#), [121](#), [123](#), [180](#), [196](#)
- mtkNativeDesigner-class, [121](#)
- mtkNativeEvaluator, [41](#), [75](#), [123](#), [124](#), [125](#), [127](#), [200](#)
- mtkNativeEvaluator-class, [125](#)
- mtkParameter, [45](#), [55](#), [56](#), [59](#), [60](#), [65](#), [67](#), [68](#), [72](#), [74](#), [75](#), [90](#), [92](#), [95](#), [97](#), [103](#), [107](#), [108](#), [112](#), [114](#), [119](#), [122](#), [126](#), [128](#), [128](#), [129](#), [132](#), [133](#), [137](#), [138](#), [140](#), [144](#), [145](#), [150](#), [151](#), [154](#), [155](#), [158](#), [159](#), [162](#), [164](#), [165](#), [182](#), [187](#)
- mtkParameter-class, [129](#)
- mtkParsor, [130](#), [130](#), [131](#), [180](#), [194](#)
- mtkParsor-class, [131](#)
- mtkPLMMAAnalyser, [132](#), [132](#), [133](#), [170](#)
- mtkPLMMAAnalyser-class, [133](#)
- mtkPLMMAAnalyserResult, [58](#), [134](#), [134](#), [135](#), [170](#)
- mtkPLMMAAnalyserResult-class, [135](#)
- mtkProcess, [7](#), [16](#), [33–35](#), [38](#), [39](#), [55](#), [68](#), [75](#), [80](#), [84](#), [86](#), [136](#), [136](#), [137](#), [139](#), [172](#), [173](#), [179](#), [180](#), [187](#), [188](#), [190](#), [198](#)
- mtkProcess-class, [138](#)
- mtkRandLHSDesigner, [139](#), [140](#), [176](#)
- mtkRandLHSDesigner-class, [140](#)
- mtkRandLHSDesignerResult, [141](#), [141](#), [142](#), [176](#)
- mtkRandLHSDesignerResult-class, [142](#)
- mtkReadFactors
(*mtkReadFactors-methods*), [143](#)
- mtkReadFactors-methods, [143](#)
- mtkRegressionAnalyser, [143](#), [144](#), [145](#), [178](#)
- mtkRegressionAnalyser-class, [144](#)
- mtkRegressionAnalyserResult, [145](#), [146](#), [147](#), [178](#)
- mtkRegressionAnalyserResult-class, [147](#)
- mtkResult, [35](#), [58](#), [70](#), [77](#), [137](#), [148](#), [148](#), [149](#)
- mtkResult-class, [149](#)
- mtkSobolAnalyser, [150](#), [150](#), [151](#), [196](#)
- mtkSobolAnalyser-class, [151](#)
- mtkSobolAnalyserResult, [152](#), [152](#), [153](#), [196](#)
- mtkSobolAnalyserResult-class, [153](#)
- mtkSobolDesigner, [154](#), [154](#), [155](#), [196](#)

- mtkSobolDesigner-class, [155](#)
- mtkSobolDesignerResult, [155](#), [156](#), [156](#), [157](#), [196](#)
- mtkSobolDesignerResult-class, [157](#)
- mtkSystemEvaluator, [158](#), [158](#), [159](#)
- mtkSystemEvaluator-class, [159](#)
- mtkSystemEvaluatorResult, [160](#), [160](#), [161](#)
- mtkSystemEvaluatorResult-class, [161](#)
- mtkValue, [37](#), [72](#), [101](#), [129](#), [162](#), [162](#)
- mtkValue-class, [162](#)
- mtkWWDMEvaluator, [75](#), [163](#), [164](#), [165](#), [200](#)
- mtkWWDMEvaluator-class, [165](#)
- mtkWWDMEvaluatorResult, [77](#), [166](#), [167](#), [167](#), [168](#)
- mtkWWDMEvaluatorResult-class, [168](#)

- NULL, [94](#), [99](#), [111](#), [116](#), [135](#), [142](#), [147](#), [153](#), [157](#), [161](#), [168](#)
- numeric, [13](#), [106](#)

- PLMM, [169](#)
- plmm (PLMM), [169](#)
- plot, [56](#), [58](#), [63](#), [71](#), [76](#), [78](#), [81](#), [86](#), [92](#), [95](#), [97](#), [99](#), [104](#), [109](#), [111](#), [114](#), [116](#), [119](#), [122](#), [126](#), [134](#), [136](#), [139](#), [141](#), [142](#), [146](#), [148](#), [152](#), [153](#), [156](#), [157](#), [160](#), [161](#), [166](#), [168](#)
- plot (plot, mtkProcess-method), [172](#)
- plot, mtkAnalyser-method
(mtkAnalyser-class), [55](#)
- plot, mtkAnalyserResult-method
(mtkAnalyserResult-class), [58](#)
- plot, mtkBasicMonteCarloDesigner-method
(mtkBasicMonteCarloDesigner-class), [60](#)
- plot, mtkBasicMonteCarloDesignerResult-method (mtkBasicMonteCarloDesignerResult-class), [63](#)
- plot, mtkDefaultAnalyser-method
(mtkDefaultAnalyser-class), [65](#)
- plot, mtkDesigner-method
(mtkDesigner-class), [68](#)
- plot, mtkDesignerResult-method
(mtkDesignerResult-class), [70](#)
- plot, mtkEvaluator-method
(mtkEvaluator-class), [75](#)
- plot, mtkEvaluatorResult-method
(mtkEvaluatorResult-class), [77](#)
- plot, mtkExperiment-method
(mtkExperiment-class), [80](#)
- plot, mtkExpWorkflow-method
(mtkExpWorkflow-class), [85](#)
- plot, mtkFastAnalyser-method
(mtkFastAnalyser-class), [91](#)
- plot, mtkFastAnalyserResult-method
(mtkFastAnalyserResult-class), [94](#)
- plot, mtkFastDesigner-method
(mtkFastDesigner-class), [96](#)
- plot, mtkFastDesignerResult-method
(mtkFastDesignerResult-class), [99](#)
- plot, mtkIshigamiEvaluator-method
(mtkIshigamiEvaluator-class), [103](#)
- plot, mtkMorrisAnalyser-method
(mtkMorrisAnalyser-class), [108](#)
- plot, mtkMorrisAnalyserResult-method
(mtkMorrisAnalyserResult-class), [111](#)
- plot, mtkMorrisDesigner-method
(mtkMorrisDesigner-class), [113](#)
- plot, mtkMorrisDesignerResult-method
(mtkMorrisDesignerResult-class), [116](#)
- plot, mtkNativeAnalyser-method
(mtkNativeAnalyser-class), [118](#)
- plot, mtkNativeDesigner-method
(mtkNativeDesigner-class), [121](#)
- plot, mtkNativeEvaluator-method
(mtkNativeEvaluator-class), [125](#)
- plot, mtkPLMMAAnalyser-method
(mtkPLMMAAnalyser-class), [133](#)
- plot, mtkPLMMAAnalyserResult-method
(mtkPLMMAAnalyserResult-class), [135](#)
- plot, mtkProcess-method, [172](#)
- plot, mtkRandLHSDesigner-method
(mtkRandLHSDesigner-class), [140](#)
- plot, mtkRandLHSDesignerResult-method

<i>(mtkRandLHSDesignerResult-class)</i> , 142	<i>(mtkDefaultAnalyser-class)</i> , 65
plot, mtkRegressionAnalyser-method <i>(mtkRegressionAnalyser-class)</i> , 144	print, mtkDesigner-method <i>(mtkDesigner-class)</i> , 68
plot, mtkRegressionAnalyserResult-method <i>(mtkRegressionAnalyserResult-class)</i> , 147	print, mtkDesignerResult-method <i>(mtkDesignerResult-class)</i> , 70
plot, mtkSobolAnalyser-method <i>(mtkSobolAnalyser-class)</i> , 151	print, mtkDomain-method <i>(mtkDomain-class)</i> , 72
plot, mtkSobolAnalyserResult-method <i>(mtkSobolAnalyserResult-class)</i> , 153	print, mtkEvaluator-method <i>(mtkEvaluator-class)</i> , 75
plot, mtkSobolDesigner-method <i>(mtkSobolDesigner-class)</i> , 155	print, mtkEvaluatorResult-method <i>(mtkEvaluatorResult-class)</i> , 77
plot, mtkSobolDesignerResult-method <i>(mtkSobolDesignerResult-class)</i> , 157	print, mtkExperiment-method <i>(mtkExperiment-class)</i> , 80
plot, mtkSystemEvaluator-method <i>(mtkSystemEvaluator-class)</i> , 159	print, mtkExpFactors-method <i>(mtkExpFactors-class)</i> , 82
plot, mtkSystemEvaluatorResult-method <i>(mtkSystemEvaluatorResult-class)</i> , 161	print, mtkExpWorkflow-method <i>(mtkExpWorkflow-class)</i> , 85
plot, mtkWWDMEvaluator-method <i>(mtkWWDMEvaluator-class)</i> , 165	print, mtkFactor-method <i>(mtkFactor-class)</i> , 89
plot, mtkWWDMEvaluatorResult-method <i>(mtkWWDMEvaluatorResult-class)</i> , 168	print, mtkFastAnalyser-method <i>(mtkFastAnalyser-class)</i> , 91
print, 56, 58, 63, 71, 73, 76, 78, 81, 83, 86, 90, 92, 95, 97, 99, 101, 104, 106, 109, 111, 114, 116, 119, 122, 126, 129, 134, 136, 139, 141, 142, 146, 148, 152, 153, 156, 157, 160, 161, 163, 166, 168	print, mtkFastAnalyserResult-method <i>(mtkFastAnalyserResult-class)</i> , 94
print (<i>print, mtkProcess-method</i>), 173	print, mtkFastDesigner-method <i>(mtkFastDesigner-class)</i> , 96
print, mtkAnalyser-method <i>(mtkAnalyser-class)</i> , 55	print, mtkFastDesignerResult-method <i>(mtkFastDesignerResult-class)</i> , 99
print, mtkAnalyserResult-method <i>(mtkAnalyserResult-class)</i> , 58	print, mtkFeature-method <i>(mtkFeature-class)</i> , 101
print, mtkBasicMonteCarloDesigner-method <i>(mtkBasicMonteCarloDesigner-class)</i> , 60	print, mtkIshigamiEvaluator-method <i>(mtkIshigamiEvaluator-class)</i> , 103
print, mtkBasicMonteCarloDesignerResult-method <i>(mtkBasicMonteCarloDesignerResult-class)</i> , 63	print, mtkLevels-method <i>(mtkLevels-class)</i> , 106
print, mtkDefaultAnalyser-method	print, mtkMorrisAnalyser-method <i>(mtkMorrisAnalyser-class)</i> , 108
	print, mtkMorrisAnalyserResult-method <i>(mtkMorrisAnalyserResult-class)</i> , 111
	print, mtkMorrisDesigner-method <i>(mtkMorrisDesigner-class)</i> , 113
	print, mtkMorrisDesignerResult-method <i>(mtkMorrisDesignerResult-class)</i> , 116
	print, mtkNativeAnalyser-method

- (mtkNativeAnalyser-class)*, 118
- print, *mtkNativeDesigner-method* (*mtkNativeDesigner-class*), 121
- print, *mtkNativeEvaluator-method* (*mtkNativeEvaluator-class*), 125
- print, *mtkParameter-method* (*mtkParameter-class*), 129
- print, *mtkPLMMAAnalyser-method* (*mtkPLMMAAnalyser-class*), 133
- print, *mtkPLMMAAnalyserResult-method* (*mtkPLMMAAnalyserResult-class*), 135
- print, *mtkProcess-method*, 173
- print, *mtkRandLHSDesigner-method* (*mtkRandLHSDesigner-class*), 140
- print, *mtkRandLHSDesignerResult-method* (*mtkRandLHSDesignerResult-class*), 142
- print, *mtkRegressionAnalyser-method* (*mtkRegressionAnalyser-class*), 144
- print, *mtkRegressionAnalyserResult-method* (*mtkRegressionAnalyserResult-class*), 147
- print, *mtkSobolAnalyser-method* (*mtkSobolAnalyser-class*), 151
- print, *mtkSobolAnalyserResult-method* (*mtkSobolAnalyserResult-class*), 153
- print, *mtkSobolDesigner-method* (*mtkSobolDesigner-class*), 155
- print, *mtkSobolDesignerResult-method* (*mtkSobolDesignerResult-class*), 157
- print, *mtkSystemEvaluator-method* (*mtkSystemEvaluator-class*), 159
- print, *mtkSystemEvaluatorResult-method* (*mtkSystemEvaluatorResult-class*), 161
- print, *mtkValue-method* (*mtkValue-class*), 162
- print, *mtkWWDMEvaluator-method* (*mtkWWDMEvaluator-class*), 165
- print, *mtkWWDMEvaluatorResult-method* (*mtkWWDMEvaluatorResult-class*), 168
- Quantiles, 175
- RandLHS, 175
- reevaluate, 81, 86
- reevaluate (*reevaluate-methods*), 177
- reevaluate, *mtkExperiment, character-method* (*mtkExperiment-class*), 80
- reevaluate, *mtkExpWorkflow, character-method* (*mtkExpWorkflow-class*), 85
- reevaluate-methods, 177
- Regression, 178
- report, 56, 76, 81, 86, 92, 97, 104, 109, 114, 119, 122, 126, 134, 139, 141, 146, 152, 156, 160, 166
- report (*report-methods*), 179
- report, *mtkAnalyser-method* (*mtkAnalyser-class*), 55
- report, *mtkBasicMonteCarloDesigner-method* (*mtkBasicMonteCarloDesigner-class*), 60
- report, *mtkDefaultAnalyser-method* (*mtkDefaultAnalyser-class*), 65
- report, *mtkDesigner-method* (*mtkDesigner-class*), 68
- report, *mtkEvaluator-method* (*mtkEvaluator-class*), 75
- report, *mtkExperiment-method* (*mtkExperiment-class*), 80
- report, *mtkExpWorkflow-method* (*mtkExpWorkflow-class*), 85
- report, *mtkFastAnalyser-method* (*mtkFastAnalyser-class*), 91
- report, *mtkFastDesigner-method* (*mtkFastDesigner-class*), 96
- report, *mtkIshigamiEvaluator-method* (*mtkIshigamiEvaluator-class*), 103
- report, *mtkMorrisAnalyser-method* (*mtkMorrisAnalyser-class*), 108
- report, *mtkMorrisDesigner-method* (*mtkMorrisDesigner-class*), 113
- report, *mtkNativeAnalyser-method* (*mtkNativeAnalyser-class*), 118

- report, mtkNativeDesigner-method
(*mtkNativeDesigner-class*), [121](#)
- report, mtkNativeEvaluator-method
(*mtkNativeEvaluator-class*), [125](#)
- report, mtkPLMMAlyser-method
(*mtkPLMMAlyser-class*), [133](#)
- report, mtkProcess-method
(*mtkProcess-class*), [138](#)
- report, mtkRandLHSDesigner-method
(*mtkRandLHSDesigner-class*), [140](#)
- report, mtkRegressionAnalyser-method
(*mtkRegressionAnalyser-class*), [144](#)
- report, mtkSobolAnalyser-method
(*mtkSobolAnalyser-class*), [151](#)
- report, mtkSobolDesigner-method
(*mtkSobolDesigner-class*), [155](#)
- report, mtkSystemEvaluator-method
(*mtkSystemEvaluator-class*), [159](#)
- report, mtkWWDMEvaluator-method
(*mtkWWDMEvaluator-class*), [165](#)
- report-methods, [179](#)
- run, [56](#), [76](#), [81](#), [86](#), [92](#), [97](#), [104](#), [109](#), [114](#),
[119](#), [122](#), [126](#), [131](#), [134](#), [139](#), [141](#),
[146](#), [152](#), [156](#), [160](#), [166](#)
- run (run-methods), [180](#)
- run, mtkAnalyser, mtkExpWorkflow-method
(*mtkAnalyser-class*), [55](#)
- run, mtkBasicMonteCarloDesigner, mtkExpWorkflow-method
(*mtkBasicMonteCarloDesigner-class*), [60](#)
- run, mtkDefaultAnalyser, mtkExpWorkflow-method
(*mtkDefaultAnalyser-class*), [65](#)
- run, mtkDesigner, mtkExpWorkflow-method
(*mtkDesigner-class*), [68](#)
- run, mtkEvaluator, mtkExpWorkflow-method
(*mtkEvaluator-class*), [75](#)
- run, mtkExperiment, missing-method
(*mtkExperiment-class*), [80](#)
- run, mtkExpWorkflow, missing-method
(*mtkExpWorkflow-class*), [85](#)
- run, mtkFastAnalyser, mtkExpWorkflow-method
(*mtkFastAnalyser-class*), [91](#)
- run, mtkFastDesigner, mtkExpWorkflow-method
(*mtkFastDesigner-class*), [96](#)
- run, mtkIshigamiEvaluator, mtkExpWorkflow-method
(*mtkIshigamiEvaluator-class*), [103](#)
- run, mtkMorrisAnalyser, mtkExpWorkflow-method
(*mtkMorrisAnalyser-class*), [108](#)
- run, mtkMorrisDesigner, mtkExpWorkflow-method
(*mtkMorrisDesigner-class*), [113](#)
- run, mtkNativeAnalyser, mtkExpWorkflow-method
(*mtkNativeAnalyser-class*), [118](#)
- run, mtkNativeDesigner, mtkExpWorkflow-method
(*mtkNativeDesigner-class*), [121](#)
- run, mtkNativeEvaluator, mtkExpWorkflow-method
(*mtkNativeEvaluator-class*), [125](#)
- run, mtkParsor, mtkExpWorkflow-method
(*mtkParsor-class*), [131](#)
- run, mtkPLMMAlyser, mtkExpWorkflow-method
(*mtkPLMMAlyser-class*), [133](#)
- run, mtkProcess, mtkExpWorkflow-method
(*mtkProcess-class*), [138](#)
- run, mtkRandLHSDesigner, mtkExpWorkflow-method
(*mtkRandLHSDesigner-class*), [140](#)
- run, mtkRegressionAnalyser, mtkExpWorkflow-method
(*mtkRegressionAnalyser-class*), [144](#)
- run, mtkSobolAnalyser, mtkExpWorkflow-method
(*mtkSobolAnalyser-class*), [151](#)
- run, mtkSobolDesigner, mtkExpWorkflow-method
(*mtkSobolDesigner-class*), [155](#)
- run, mtkSystemEvaluator, mtkExpWorkflow-method
(*mtkSystemEvaluator-class*), [159](#)
- run, mtkWWDMEvaluator, mtkExpWorkflow-method
(*mtkWWDMEvaluator-class*), [165](#)
- run-methods, [180](#)
- serializeOn, [56](#), [76](#), [81](#), [86](#), [92](#), [97](#), [104](#),
[109](#), [114](#), [119](#), [122](#), [126](#), [134](#), [139](#),
[141](#), [145](#), [149](#), [152](#), [156](#), [160](#), [166](#)
- serializeOn
(serializeOn-methods), [181](#)

- `serializeOn, mtkAnalyser-method`
(*mtkAnalyser-class*), [55](#)
- `serializeOn, mtkBasicMonteCarloDesigner-method`
(*mtkBasicMonteCarloDesigner-class*), [60](#)
- `serializeOn, mtkDefaultAnalyser-method`
(*mtkDefaultAnalyser-class*), [65](#)
- `serializeOn, mtkDesigner-method`
(*mtkDesigner-class*), [68](#)
- `serializeOn, mtkEvaluator-method`
(*mtkEvaluator-class*), [75](#)
- `serializeOn, mtkExperiment-method`
(*mtkExperiment-class*), [80](#)
- `serializeOn, mtkExpWorkflow-method`
(*mtkExpWorkflow-class*), [85](#)
- `serializeOn, mtkFastAnalyser-method`
(*mtkFastAnalyser-class*), [91](#)
- `serializeOn, mtkFastDesigner-method`
(*mtkFastDesigner-class*), [96](#)
- `serializeOn, mtkIshigamiEvaluator-method`
(*mtkIshigamiEvaluator-class*), [103](#)
- `serializeOn, mtkMorrisAnalyser-method`
(*mtkMorrisAnalyser-class*), [108](#)
- `serializeOn, mtkMorrisDesigner-method`
(*mtkMorrisDesigner-class*), [113](#)
- `serializeOn, mtkNativeAnalyser-method`
(*mtkNativeAnalyser-class*), [118](#)
- `serializeOn, mtkNativeDesigner-method`
(*mtkNativeDesigner-class*), [121](#)
- `serializeOn, mtkNativeEvaluator-method`
(*mtkNativeEvaluator-class*), [125](#)
- `serializeOn, mtkPLMMAAnalyser-method`
(*mtkPLMMAAnalyser-class*), [133](#)
- `serializeOn, mtkProcess-method`
(*mtkProcess-class*), [138](#)
- `serializeOn, mtkRandLHSDesigner-method`
(*mtkRandLHSDesigner-class*), [140](#)
- `serializeOn, mtkRegressionAnalyser-method`
(*mtkRegressionAnalyser-class*), [144](#)
- `serializeOn, mtkResult-method`
(*mtkResult-class*), [149](#)
- `serializeOn, mtkSobolAnalyser-method`
(*mtkSobolAnalyser-class*), [151](#)
- `serializeOn, mtkSobolDesigner-method`
(*mtkSobolDesigner-class*), [155](#)
- `serializeOn, mtkSystemEvaluator-method`
(*mtkSystemEvaluator-class*), [159](#)
- `serializeOn, mtkWWDMEvaluator-method`
(*mtkWWDMEvaluator-class*), [165](#)
- `serializeOn-methods`, [181](#)
- `setDistributionParameters, 73`
`setDistributionParameters`
(*setDistributionParameters-methods*), [182](#)
- `setDistributionParameters, mtkDomain, list-method`
(*mtkDomain-class*), [72](#)
- `setDistributionParameters-methods`, [182](#)
- `setDomain, 90`
`setDomain` (*setDomain-methods*), [183](#)
- `setDomain, mtkFactor, mtkDomain-method`
(*mtkFactor-class*), [89](#)
- `setDomain-methods`, [183](#)
- `setFactors` (*setFactors-methods*), [184](#)
- `setFactors, mtkExpFactors, list-method`
(*mtkExpFactors-class*), [82](#)
- `setFactors-methods`, [184](#)
- `setFeatures, 90`
`setFeatures`
(*setFeatures-methods*), [185](#)
- `setFeatures, mtkFactor, list-method`
(*mtkFactor-class*), [89](#)
- `setFeatures-methods`, [185](#)
- `setLevels, 73, 106`
`setLevels` (*setLevels-methods*), [185](#)
- `setLevels, mtkDomain, list-method`
(*mtkDomain-class*), [72](#)
- `setLevels, mtkDomain, mtkLevels-method`
(*mtkDomain-class*), [72](#)
- `setLevels, mtkLevels, vector-method`
(*mtkLevels-class*), [106](#)
- `setLevels-methods`, [185](#)
- `setName, 56, 75, 90, 92, 97, 101, 103, 109, 114, 119, 122, 126, 129, 133, 138, 141, 145, 151, 155, 159, 163, 166`
`setName` (*setName-methods*), [186](#)
- `setName, mtkAnalyser, character-method`
(*mtkAnalyser-class*), [55](#)
- `setName, mtkBasicMonteCarloDesigner, character-`

(*mtkBasicMonteCarloDesigner-class*), 60
 setName, *mtkDefaultAnalyser*, character-method (*mtkDefaultAnalyser-class*), 65
 setName, *mtkDesigner*, character-method (*mtkDesigner-class*), 68
 setName, *mtkEvaluator*, character-method (*mtkEvaluator-class*), 75
 setName, *mtkFactor*, character-method (*mtkFactor-class*), 89
 setName, *mtkFastAnalyser*, character-method (*mtkFastAnalyser-class*), 91
 setName, *mtkFastDesigner*, character-method (*mtkFastDesigner-class*), 96
 setName, *mtkFeature*, character-method (*mtkFeature-class*), 101
 setName, *mtkIshigamiEvaluator*, character-method (*mtkIshigamiEvaluator-class*), 103
 setName, *mtkMorrisAnalyser*, character-method (*mtkMorrisAnalyser-class*), 108
 setName, *mtkMorrisDesigner*, character-method (*mtkMorrisDesigner-class*), 113
 setName, *mtkNativeAnalyser*, character-method (*mtkNativeAnalyser-class*), 118
 setName, *mtkNativeDesigner*, character-method (*mtkNativeDesigner-class*), 121
 setName, *mtkNativeEvaluator*, character-method (*mtkNativeEvaluator-class*), 125
 setName, *mtkParameter*, character-method (*mtkParameter-class*), 129
 setName, *mtkPLMMAAnalyser*, character-method (*mtkPLMMAAnalyser-class*), 133
 setName, *mtkProcess*, character-method (*mtkProcess-class*), 138
 setName, *mtkRandLHSDesigner*, character-method (*mtkRandLHSDesigner-class*), 140
 setName, *mtkRegressionAnalyser*, character-method (*mtkRegressionAnalyser-class*), 144
 setName, *mtkSobolAnalyser*, character-method (*mtkSobolAnalyser-class*), 151
 setName, *mtkSobolDesigner*, character-method (*mtkSobolDesigner-class*), 155
 setName, *mtkSystemEvaluator*, character-method (*mtkSystemEvaluator-class*), 159
 setName, *mtkValue*, character-method (*mtkValue-class*), 162
 setName, *mtkWWDMEvaluator*, character-method (*mtkWWDMEvaluator-class*), 165
 setName-methods, 186
 setParameters, 56, 75, 92, 97, 103, 109, 114, 119, 122, 126, 133, 138, 141, 145, 151, 155, 159, 166
 setParameters (*setParameters-methods*), 187
 setParameters, *mtkAnalyser*, vector-method (*mtkAnalyser-class*), 55
 setParameters, *mtkBasicMonteCarloDesigner*, vector-method (*mtkBasicMonteCarloDesigner-class*), 60
 setParameters, *mtkDefaultAnalyser*, vector-method (*mtkDefaultAnalyser-class*), 65
 setParameters, *mtkDesigner*, vector-method (*mtkDesigner-class*), 68
 setParameters, *mtkEvaluator*, vector-method (*mtkEvaluator-class*), 75
 setParameters, *mtkFastAnalyser*, vector-method (*mtkFastAnalyser-class*), 91
 setParameters, *mtkFastDesigner*, vector-method (*mtkFastDesigner-class*), 96
 setParameters, *mtkIshigamiEvaluator*, vector-method (*mtkIshigamiEvaluator-class*), 103
 setParameters, *mtkMorrisAnalyser*, vector-method (*mtkMorrisAnalyser-class*), 108
 setParameters, *mtkMorrisDesigner*, vector-method (*mtkMorrisDesigner-class*), 113
 setParameters, *mtkNativeAnalyser*, vector-method (*mtkNativeAnalyser-class*), 118
 setParameters, *mtkNativeDesigner*, vector-method (*mtkNativeDesigner-class*), 121
 setParameters, *mtkNativeEvaluator*, vector-method (*mtkNativeEvaluator-class*), 125
 setParameters, *mtkPLMMAAnalyser*, vector-method (*mtkPLMMAAnalyser-class*), 133

- (*mtkPLMMAAnalyser-class*), 133
- setParameters, *mtkProcess*, vector-method (*mtkProcess-class*), 138
- setParameters, *mtkRandLHSDesigner*, vector-method (*mtkRandLHSDesigner-class*), 140
- setParameters, *mtkRegressionAnalyser*, vector-method (*mtkRegressionAnalyser-class*), 144
- setParameters, *mtkSobolAnalyser*, vector-method (*mtkSobolAnalyser-class*), 151
- setParameters, *mtkSobolDesigner*, vector-method (*mtkSobolDesigner-class*), 155
- setParameters, *mtkSystemEvaluator*, vector-method (*mtkSystemEvaluator-class*), 159
- setParameters, *mtkWWDMEvaluator*, vector-method (*mtkWWDMEvaluator-class*), 165
- setParameters-methods, 187
- setProcess, 80, 86
- setProcess (*setProcess-methods*), 188
- setProcess, *mtkExperiment*, *mtkProcess*, character (*mtkExperiment-class*), 80
- setProcess, *mtkExpWorkflow*, *mtkProcess*, character (*mtkExpWorkflow-class*), 85
- setProcess-methods, 188
- setReady, 56, 76, 92, 97, 103, 104, 109, 114, 119, 122, 126, 133, 134, 138, 141, 145, 152, 155, 159, 166
- setReady (*setReady-methods*), 189
- setReady, *mtkAnalyser*, logical-method (*mtkAnalyser-class*), 55
- setReady, *mtkBasicMonteCarloDesigner*, logical-method (*mtkBasicMonteCarloDesigner-class*), 60
- setReady, *mtkDefaultAnalyser*, logical-method (*mtkDefaultAnalyser-class*), 65
- setReady, *mtkDesigner*, logical-method (*mtkDesigner-class*), 68
- setReady, *mtkEvaluator*, logical-method (*mtkEvaluator-class*), 75
- setReady, *mtkFastAnalyser*, logical-method (*mtkFastAnalyser-class*), 91
- setReady, *mtkFastDesigner*, logical-method (*mtkFastDesigner-class*), 96
- setReady, *mtkIshigamiEvaluator*, logical-method (*mtkIshigamiEvaluator-class*), 103
- setReady, *mtkMorrisAnalyser*, logical-method (*mtkMorrisAnalyser-class*), 108
- setReady, *mtkMorrisDesigner*, logical-method (*mtkMorrisDesigner-class*), 113
- setReady, *mtkNativeAnalyser*, logical-method (*mtkNativeAnalyser-class*), 118
- setReady, *mtkNativeDesigner*, logical-method (*mtkNativeDesigner-class*), 121
- setReady, *mtkNativeEvaluator*, logical-method (*mtkNativeEvaluator-class*), 125
- setReady, *mtkPLMMAAnalyser*, logical-method (*mtkPLMMAAnalyser-class*), 133
- setReady, *mtkProcess*, logical-method (*mtkProcess-class*), 138
- setReady, *mtkRandLHSDesigner*, logical-method (*mtkRandLHSDesigner-class*), 140
- setReady, *mtkRegressionAnalyser*, logical-method (*mtkRegressionAnalyser-class*), 144
- setReady, *mtkSobolAnalyser*, logical-method (*mtkSobolAnalyser-class*), 151
- setReady, *mtkSobolDesigner*, logical-method (*mtkSobolDesigner-class*), 155
- setReady, *mtkSystemEvaluator*, logical-method (*mtkSystemEvaluator-class*), 159
- setReady, *mtkWWDMEvaluator*, logical-method (*mtkWWDMEvaluator-class*), 165
- setReady-methods, 189
- setState (*setState-methods*), 190
- setState, *mtkAnalyser*, logical-method (*mtkAnalyser-class*), 55
- setState, *mtkBasicMonteCarloDesigner*, logical-method (*mtkBasicMonteCarloDesigner-class*), 60
- setState, *mtkDefaultAnalyser*, logical-method (*mtkDefaultAnalyser-class*), 65
- setState, *mtkDesigner*, logical-method (*mtkDesigner-class*), 68

- setState, mtkEvaluator, logical-method (mtkEvaluator-class), 75
- setState, mtkFastAnalyser, logical-method (mtkFastAnalyser-class), 91
- setState, mtkFastDesigner, logical-method (mtkFastDesigner-class), 96
- setState, mtkIshigamiEvaluator, logical-method (mtkIshigamiEvaluator-class), 103
- setState, mtkMorrisAnalyser, logical-method (mtkMorrisAnalyser-class), 108
- setState, mtkMorrisDesigner, logical-method (mtkMorrisDesigner-class), 113
- setState, mtkNativeAnalyser, logical-method (mtkNativeAnalyser-class), 118
- setState, mtkNativeDesigner, logical-method (mtkNativeDesigner-class), 121
- setState, mtkNativeEvaluator, logical-method (mtkNativeEvaluator-class), 125
- setState, mtkPLMMAAnalyser, logical-method (mtkPLMMAAnalyser-class), 133
- setState, mtkProcess, logical-method (mtkProcess-class), 138
- setState, mtkRandLHSDesigner, logical-method (mtkRandLHSDesigner-class), 140
- setState, mtkRegressionAnalyser, logical-method (mtkRegressionAnalyser-class), 144
- setState, mtkSobolAnalyser, logical-method (mtkSobolAnalyser-class), 151
- setState, mtkSobolDesigner, logical-method (mtkSobolDesigner-class), 155
- setState, mtkSystemEvaluator, logical-method (mtkSystemEvaluator-class), 159
- setState, mtkWWDMEvaluator, logical-method (mtkWWDMEvaluator-class), 165
- setState-methods, 190
- setType, 90, 101, 106, 129, 163
- setType (setType-methods), 191
- setType, mtkFeature, character-method (mtkFeature-class), 101
- setType, mtkLevels, character-method (mtkLevels-class), 106
- setType, mtkParameter, character-method (mtkParameter-class), 129
- setType, mtkValue, character-method (mtkValue-class), 162
- setType-methods, 191
- setValue, 101, 129, 163
- setValue (setValue-methods), 192
- setValue, mtkFeature, ANY-method (mtkFeature-class), 101
- setValue, mtkParameter, ANY-method (mtkParameter-class), 129
- setValue, mtkValue, ANY-method (mtkValue-class), 162
- setValue, mtkValue-method (mtkValue-class), 162
- setValue-methods, 192
- setWeights, 106
- setWeights (setWeights-methods), 193
- setWeights, mtkLevels, numeric-method (mtkLevels-class), 106
- setWeights-methods, 193
- setXMLFilePath, 131
- setXMLFilePath (setXMLFilePath-methods), 194
- setXMLFilePath, mtkParsor, character-method (mtkParsor-class), 131
- show, 73, 83, 90, 101, 106, 129, 163
- show, mtkDomain-method (mtkDomain-class), 72
- show, mtkExpFactors-method (mtkExpFactors-class), 82
- show, mtkFactor-method (mtkFactor-class), 89
- show, mtkFeature-method (mtkFeature-class), 101
- show, mtkLevels-method (mtkLevels-class), 106
- show, mtkParameter-method (mtkParameter-class), 129
- show, mtkValue-method (mtkValue-class), 162
- Sobol, 195
- summary, 56, 58, 63, 71, 76, 78, 81, 86, 92, 95, 97, 99, 104, 106, 109, 111, 114, 116, 119, 122, 126, 134, 136, 139,

- 141, 142, 146, 148, 149, 152, 153,
156, 157, 160, 161, 166, 168
- summary
(*summary*, *mtkProcess*-method),
198
- summary, *mtkAnalyser*-method
(*mtkAnalyser*-class), 55
- summary, *mtkAnalyserResult*-method
(*mtkAnalyserResult*-class),
58
- summary, *mtkBasicMonteCarloDesigner*-method
(*mtkBasicMonteCarloDesigner*-class),
60
- summary, *mtkBasicMonteCarloDesignerResult*-method
(*mtkBasicMonteCarloDesignerResult*-class),
63
- summary, *mtkDefaultAnalyser*-method
(*mtkDefaultAnalyser*-class),
65
- summary, *mtkDesigner*-method
(*mtkDesigner*-class), 68
- summary, *mtkDesignerResult*-method
(*mtkDesignerResult*-class),
70
- summary, *mtkEvaluator*-method
(*mtkEvaluator*-class), 75
- summary, *mtkEvaluatorResult*-method
(*mtkEvaluatorResult*-class),
77
- summary, *mtkExperiment*-method
(*mtkExperiment*-class), 80
- summary, *mtkExpWorkflow*-method
(*mtkExpWorkflow*-class), 85
- summary, *mtkFastAnalyser*-method
(*mtkFastAnalyser*-class), 91
- summary, *mtkFastAnalyserResult*-method
(*mtkFastAnalyserResult*-class),
94
- summary, *mtkFastDesigner*-method
(*mtkFastDesigner*-class), 96
- summary, *mtkFastDesignerResult*-method
(*mtkFastDesignerResult*-class),
99
- summary, *mtkIshigamiEvaluator*-method
(*mtkIshigamiEvaluator*-class),
103
- summary, *mtkLevels*-method
(*mtkLevels*-class), 106
- summary, *mtkMorrisAnalyser*-method
(*mtkMorrisAnalyser*-class),
108
- summary, *mtkMorrisAnalyserResult*-method
(*mtkMorrisAnalyserResult*-class),
111
- summary, *mtkMorrisDesigner*-method
(*mtkMorrisDesigner*-class),
113
- summary, *mtkMorrisDesignerResult*-method
(*mtkMorrisDesignerResult*-class),
116
- summary, *mtkNativeAnalyser*-method
(*mtkNativeAnalyser*-class),
118
- summary, *mtkNativeDesigner*-method
(*mtkNativeDesigner*-class),
121
- summary, *mtkNativeEvaluator*-method
(*mtkNativeEvaluator*-class),
125
- summary, *mtkPLMMAAnalyser*-method
(*mtkPLMMAAnalyser*-class),
133
- summary, *mtkPLMMAAnalyserResult*-method
(*mtkPLMMAAnalyserResult*-class),
135
- summary, *mtkProcess*-method, 198
- summary, *mtkRandLHSDesigner*-method
(*mtkRandLHSDesigner*-class),
140
- summary, *mtkRandLHSDesignerResult*-method
(*mtkRandLHSDesignerResult*-class),
142
- summary, *mtkRegressionAnalyser*-method
(*mtkRegressionAnalyser*-class),
144
- summary, *mtkRegressionAnalyserResult*-method
(*mtkRegressionAnalyserResult*-class),
147
- summary, *mtkResult*-method
(*mtkResult*-class), 149
- summary, *mtkSobolAnalyser*-method
(*mtkSobolAnalyser*-class),
151
- summary, *mtkSobolAnalyserResult*-method
(*mtkSobolAnalyserResult*-class),
153
- summary, *mtkSobolDesigner*-method
(*mtkSobolDesigner*-class),
155
- summary, *mtkSobolDesignerResult*-method
(*mtkSobolDesignerResult*-class),
157
- summary, *mtkSystemEvaluator*-method
(*mtkSystemEvaluator*-class),

[159](#)
summary, `mtkSystemEvaluatorResult`-method
 (`mtkSystemEvaluatorResult`-class),
 [161](#)
summary, `mtkWWDMEvaluator`-method
 (`mtkWWDMEvaluator`-class),
 [165](#)
summary, `mtkWWDMEvaluatorResult`-method
 (`mtkWWDMEvaluatorResult`-class),
 [168](#)

vector, [56](#), [60](#), [65](#), [68](#), [75](#), [80](#), [84](#), [86](#), [92](#), [97](#),
 [103](#), [106](#), [108](#), [114](#), [119](#), [122](#), [126](#),
 [133](#), [138](#), [140](#), [145](#), [151](#), [155](#), [159](#),
 [165](#)

WWDM, [199](#), [201](#), [202](#)
WWDM.climates (`wwdm.climates`), [201](#)
wwdm.climates, [201](#)
WWDM.factors, [200](#), [202](#)