



# SeqinR 1.0–6






Figure 1: The march of progress icon is very common in popular press. This example is from page 46 of a 1984 summer issue of the Czech edition of *Playboy*.

## The march of progress icon

The cover, an artwork created<sup>1</sup> by Lionel Humblot, is an allusion to what Stephen J. Gould considered as a canonical icon of "[t]he most serious and pervasive of all misconceptions about evolution equates the concept with some notion of progress, usually inherent and predictable, and leading to a human pinnacle" [14]. Some examples of the so-called "march of progress" out of hundreds in S.J. Gould's collection from popular press are given in the beginning of his famous book *Wonderful life* [13].

Note that the underlying conception predates Darwin [37]. We know now that evolution doesn't equal progress, and this is illustrated here in the cover by the unusual **decreasing** size from the initial character (on the left) to the last one (on the right).



*L'île aux enfants.*

## The character on the left

The character on the left is called Casimir, the cult character of the French TV show *l'île aux enfants* (literally Kid's island, a French adaptation of *Sesame Street* from 1974 to 1975 and then an autonomous production until 1982 when it eventually ended). Casimir was a puppet, human-sized, with an actor playing inside, representing an orange dinosaur (the exact taxonomy has never been published) with yellow and red spots. Casimir was symbolically chosen here for two reasons. First, its birth corresponds to one of the earliest papers from our

<sup>1</sup> with Canvas from ACD Systems.

lab about molecular evolution [16]. If you dig into **seqinR** you will find that the data from this more than 30 years old paper are still available<sup>2</sup>:

```
data(aaindex)
grth <- which(sapply(aaindex, function(x) length(grep("Grantham",
  x$A)) != 0))
lapply(aaindex[grth], "[", "D")
```

```
$GRAR740101
[1] "Composition (Grantham, 1974)"
```


```
$GRAR740102
[1] "Polarity (Grantham, 1974)"
```

```
$GRAR740103
[1] "Volume (Grantham, 1974)"
```

Second, Casimir's life span correspond more or less to the time during which the sequence analysis software called ANALSEQ<sup>3</sup> [22] was under development in our lab. ANALSEQ has never been published as a regular paper (although it is mentioned in one of the ACNUC paper [15]), there is only a reference manual in french [22] also available on-line at <http://biomserv.univ-lyon1.fr/doclogi/docanals/manuel.html>. ANALSEQ was entirely written in FORTRAN 77, and although you won't find any fossil code from it within **seqinR**, we wanted to credit symbolically ANALSEQ as a kind of spiritual ancestor of **seqinR** with the cover.

## The character on the right

The character on the right is called Kirikou. He is the main character of the animated film *Kirikou et la sorcière* (Kirikou and the sorceress, 1998) and *Kirikou et les bêtes sauvages* (Kirikou and the Wild Beasts, 2005). Kirikou was chosen as a symbol of **seqinR** development time. **SeqinR** started in september 2002 as part of the work of Delphine Charif's master of sciences. The first public presentation of **seqinR** was a seminar (2-JUL-2003, Lausanne University, Swiss) and the first public release on the CRAN<sup>4</sup> was in october 2004.



Kirikou and the sorceress, a film by Michel Ocelot with original music by Youssou N'Dour.

## Technical details

The cover was saved from Canvas into an EPS<sup>5</sup> file. This file was then manually edited to remove non-ASCII characters. It was then converted into RGML<sup>6</sup> format with the following **R** code based on **grid** [46], **XML** [5] and **grImport** [39]:

```
library(grid)
library(XML)
library(grImport)
PostScriptTrace("../figs/couverture.eps", "../figs/couverture.rgml")
```

<sup>2</sup> thanks to **aaindex** database [26, 56, 40].

<sup>3</sup> not to be confused with the ANALYSEQ program by Rodger Staden [53].

<sup>4</sup> Comprehensive R Archive Network.

<sup>5</sup> Encapsulated Postscript.

<sup>6</sup> RDF (Resource Description Framework) Graph Modeling Language (<http://www.cs.rpi.edu/~puninj/RGML/>).


The picture was then edited to add automatically the current **seqinR** release number:

```
cover <- readPicture("../figs/couverture.rgml")
pdf(file = "../figs/cover.pdf", width = 21/2.54, height = 29.7/2.54)
pushViewport(plotViewport(margins = c(0, 0, 0, 0)))
grid.rect()
grid.picture(cover)
grid.text(paste("SeqinR", packageDescription("seqinr")$Version),
  gp = gpar(cex = 5), y = unit(0.72, "npc"))
popViewport()
dev.off()
```


And finally inserted at the beginning of the L<sup>A</sup>T<sub>E</sub>X file with:

```
\atxy(0cm,0cm){
  \includegraphics[width=\paperwidth,height=\paperheight]{../figs/cover}
}
```

## Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), powerpc-apple-darwin8.6.0
- Base packages: base, datasets, grDevices, graphics, grid, methods, stats, utils
- Other packages: MASS 7.2-27.1, XML 0.99-8, ade4 1.4-1, ape 1.8-2, gee 4.13-10, grImport 0.2, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0

**SeqinR** 1.0-6: a contributed package to the  
 project for statistical computing devoted to  
biological sequences retrieval and analysis

Charif, D.      Humblot, L.      Lobry, J.R.      Palmeira, L.

September 1, 2006



---

# CONTENTS

<b>Licence of this document</b>	<b>i</b>
<b>1 Introduction</b>	<b>1</b>
1.1 About ACNUC	1
1.2 About R and CRAN	3
1.3 About this document	3
1.4 About sequin and <b>sequinR</b>	3
1.5 About getting started	3
1.6 About running R in batch mode	4
1.7 About the learning curve	4
1.7.1 Wheel (the)	4
1.7.2 Hotline	5
1.7.3 Automation	5
1.7.4 Reproducibility	5
1.7.5 Fine tuning	5
1.7.6 Data as fast moving targets	8
1.7.7 <b>Sweave()</b> and <b>xtable()</b>	9
1.8 Session Informations	10
<b>2 Importing sequences from flat files</b>	<b>11</b>
2.1 Importing raw sequence data from FASTA files	11
2.1.1 FASTA files examples	11
2.1.2 The function <b>read.fasta()</b>	12
2.1.3 The function <b>write.fasta()</b>	14
2.1.4 Big room examples	15
2.2 Importing aligned sequence data	26
2.2.1 Aligned sequences files examples	26
2.2.2 The function <b>read.alignment()</b>	30
2.2.3 A simple example with the louse-gopher data	31
2.3 Session Informations	34

<b>3</b>	<b>Importing sequences from ACNUC databases</b>	<b>35</b>
3.1	Choose a bank . . . . .	35
3.2	Make your query . . . . .	38
3.3	Extract sequences of interest . . . . .	42
3.4	Session Informations . . . . .	44
<b>4</b>	<b>How to deal with sequences</b>	<b>45</b>
4.1	Sequence classes . . . . .	45
4.2	Generic methods for sequences . . . . .	45
4.3	Internal representation of sequences . . . . .	46
4.3.1	Sequences as vectors of characters . . . . .	46
4.3.2	Sequences as strings . . . . .	49
4.4	Session Informations . . . . .	50
<b>5</b>	<b>Multivariate analyses</b>	<b>51</b>
5.1	Correspondence analysis . . . . .	51
5.2	Synonymous and non-synonymous analyses . . . . .	60
5.3	Session Informations . . . . .	70
<b>6</b>	<b>Nonparametric statistics</b>	<b>73</b>
6.1	Introduction . . . . .	73
6.2	Determining dinucleotides over- and under-representation . . . . .	73
6.2.1	The <i>rho</i> statistic . . . . .	73
6.2.2	The <i>zscore</i> statistic . . . . .	75
6.2.3	Comparing statistics on a sequence . . . . .	75
6.3	UV exposure and dinucleotide content . . . . .	77
6.3.1	The expected impact of UV light on genomic content . . . . .	77
6.3.2	The measured impact of UV light on genomic content . . . . .	79
6.4	Session Informations . . . . .	81
<b>A</b>	<b>FAQ: Frequently Asked Questions</b>	<b>83</b>
A.1	How do I compute a score on my sequences? . . . . .	83
A.2	Why do I have not exactly the same G+C content as in <code>codonW</code> ? . . . . .	84
A.3	How do I get a sequence from its name? . . . . .	90
A.4	Session Informations . . . . .	91
<b>B</b>	<b>GNU Free Documentation License</b>	<b>93</b>
B.1	APPLICABILITY AND DEFINITIONS . . . . .	93
B.2	VERBATIM COPYING . . . . .	95
B.3	COPYING IN QUANTITY . . . . .	95
B.4	MODIFICATIONS . . . . .	96
B.5	COMBINING DOCUMENTS . . . . .	98
B.6	COLLECTIONS OF DOCUMENTS . . . . .	98
B.7	AGGREGATION WITH INDEPENDENT WORKS . . . . .	98
B.8	TRANSLATION . . . . .	99
B.9	TERMINATION . . . . .	99
B.10	FUTURE REVISIONS OF THIS LICENSE . . . . .	99



<b>C Genetic codes</b>	<b>101</b>
C.1 Standard genetic code . . . . .	101
C.2 Available genetic code numbers . . . . .	101
C.3 Session Informations . . . . .	102
<b>D Release notes</b>	<b>111</b>
D.1 release 1.0-6 . . . . .	111
D.2 release 1.0-5 . . . . .	111
D.3 release 1.0-4 . . . . .	112
D.4 release 1.0-3 . . . . .	113
D.5 Session Informations . . . . .	114
<b>Bibliography</b>	<b>115</b>



---

# Licence of this document

## Licence

Copyright ©2003-2006 J.R. Lobry. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License", that is in appendix B page 93.

## Using and contributing

If you want to re-use or contribute to this document, some indications are given in the appendix (*under construction*)



---

---

# CHAPTER 1

---

## Introduction

Lobry, J.R.

### Contents

1.1	About ACNUC . . . . .	1
1.2	About R and CRAN . . . . .	3
1.3	About this document . . . . .	3
1.4	About sequin and sequinR . . . . .	3
1.5	About getting started . . . . .	3
1.6	About running R in batch mode . . . . .	4
1.7	About the learning curve . . . . .	4
1.8	Session Informations . . . . .	10

### 1.1 About ACNUC

ACNUC<sup>1</sup> was first a database of nucleic acids developed in the early 80's in the same lab (Lyon, France) that issued **sequinR**. ACNUC was first published as a printed book in two volumes [11, 12] whose covers are reproduced in margin there. At about the same time, two other databases were created, one in the USA (GenBank, at Los Alamos and now managed by the NCBI<sup>2</sup>), and another one in Germany (created in Köln by K. Stüber). To avoid duplication of efforts at the european level, a single repository database was initiated in Germany yielding the EMBL<sup>3</sup> database that moved from Köln to Heidelberg, and then to its current location at the EBI<sup>4</sup> near Cambridge. The DDBJ<sup>5</sup> started in 1986

---


<sup>1</sup> A contraction of ACides NUcléiques, that is *NUcleic ACids* in french (<http://pbil.univ-lyon1.fr/databases/acnuc/acnuc.html>)

<sup>2</sup>National Center for Biotechnology Information


<sup>3</sup>European Molecular Biology Laboratory

<sup>4</sup>European Bioinformatic Institute

<sup>5</sup>DNA Data Bank of Japan



Cover of ACNUC book vol. 1



Cover of ACNUC book vol. 2

at the NIG<sup>6</sup> in Mishima. These three main repository DNA databases are now collaborating to maintain the INSD<sup>7</sup> and are sharing data on a daily basis.

The sequences present in the ACNUC books [11, 12] were all the published nucleic acid sequences of about 150 or more continuous unambiguous nucleotides up to May or June 1981 from the journal given in table 1.1.

Journal name
<i>Biochimie</i>
<i>Biochemistry (ACS)</i>
<i>Cell</i>
<i>Comptes Rendus de l'Académie des Sciences, Paris</i>
<i>European Journal of Biochemistry</i>
<i>FEBS Letters</i>
<i>Gene</i>
<i>Journal of Bacteriology</i>
<i>Journal of Biological Chemistry</i>
<i>Journal of Molecular Biology</i>
<i>Molecular and General Genetics</i>
<i>Nature</i>
<i>Nucleic Acids Research</i>
<i>Proceedings of the National Academy of Sciences of the United States of America</i>
<i>Science</i>

Table 1.1: The list of journals that were manually scanned for nucleic sequences that were included in the ACNUC books [11, 12]



ACNUC books are about 4.5 cm width

The total number of base pair was 474,439 in the two books. They were about 4.5 cm width. We can then compute of much place would it take to print the last GenBank release with the same format as the ACNUC book:

```
acnucbooksize <- 4.5
acnucbp <- 474439
mybank <- choosebank("genbank")
mybank$details
```

```
[1] "GenBank Rel. 155 (15 August 2006) Last Updated: Sep 1, 2006"
[2] "66,009,892,298 bases; 61,704,148 sequences; 3,242,595 subseqs; 435,242 refers."
[3] "Software by M. Gouy, Lab. Biometrie et Biologie Evolutive, Universite Lyon I"
```

```
bpbk <- unlist(strsplit(mybank$details[2], split = " "))[1]
bpbk
```

```
[1] "66,009,892,298"
```

```
bpbk <- as.numeric(paste(unlist(strsplit(bpbk, split = ",")),
collapse = ""))
widthcm <- acnucbooksize * bpbk/acnucbp
(widthkm <- widthcm/10^5)
```

```
[1] 6.260963
```

It would be about 6.3 kilometer long in ACNUC book format to print to print GenBank today (September 1, 2006).

<sup>6</sup>National Institute of Genetics

<sup>7</sup> International Nucleotide Sequence Database (<http://www.insdc.org/>)

## 1.2 About R and CRAN

R [21, 47] is a *libre* language and environment for statistical computing and graphics which provides a wide variety of statistical and graphical techniques: linear and nonlinear modelling, statistical tests, time series analysis, classification, clustering, etc. Please consult the R project homepage at <http://www.R-project.org/> for further information.

The Comprehensive R Archive Network, CRAN, is a network of servers around the world that store identical, up-to-date, versions of code and documentation for R. At compilation time of this document, there were 63 mirrors available from 26 countries. Please use the CRAN mirror nearest to you to minimize network load, they are listed at <http://cran.r-project.org/mirrors.html>, and can be directly selected with the function `chooseCRANmirror()`.

## 1.3 About this document

In the terminology of the R project [21, 47], this document is a package *vignette*. The examples given thereafter were run under Version 2.3.1 (2006-06-01) on Fri Sep 1 23:35:01 2006 with Sweave [31]. The last compiled version of this document is distributed along with the **seqinR** package in the `/doc` folder. Once **seqinR** has been installed, the full path to the package is given by the following R code :

```
.find.package("seqinr")  
  
[1] "/Users/lobry/Library/R/library/seqinr"
```

## 1.4 About sequin and seqinR

Sequin is the well known software used to submit sequences to GenBank, **seqinR** has definitively no connection with sequin. **seqinR** is just a shortcut, with no google hit, for "Sequences in R".

However, as a mnemotechnic tip, you may think about the **seqinR** package as the **R**eciprocal function of sequin: with sequin you can submit sequences to Genbank, with **seqinR** you can **R**etrieve sequences from Genbank. This is a very good summary of a major functionality of the **seqinR** package: to provide an efficient access to sequence databases under R.

## 1.5 About getting started

You need a computer connected to the Internet. First, install R on your computer. There are distributions for Linux, Mac and Windows users on the CRAN (<http://cran.r-project.org>). Then, install the **ape**, **ade4** and **seqinr** packages. This can be done directly in an R console with for instance the command `install.packages("seqinr")`. Last, load the **seqinR** package with:

```
library(seqinr)
```

The command `lseqinr()` lists all what is defined in the package **seqinR**:

```
lseqinr()[1:9]
```

```
[1] "AAstat"      "EXP"         "GC"          "GC1"         "GC2"
[6] "GC3"        "SEQINR.UTIL" "a"           "aaa"
```

We have printed here only the first 9 entries because they are too numerous. To get help on a specific function, say `aaa()`, just prefix its name with a question mark, as in `?aaa` and press enter.

## 1.6 About running R in batch mode

Although R is usually run in an interactive mode, some data pre-processing and analyses could be too long. You can run your R code in batch mode in a shell with a command that typically looks like :

```
unix$ R CMD BATCH input.R results.out &
```

where `input.R` is a text file with the R code you want to run and `results.out` a text file to store the outputs. Note that in batch mode, the graphical user interface is not active so that some graphical devices (*e.g.* `x11`, `jpeg`, `png`) are not available (see the R FAQ [19] for further details).

It's worth noting that R uses the XDR representation of binary objects in binary saved files, and these are portable across all R platforms. The `save()` and `load()` functions are very efficient (because of their binary nature) for saving and restoring any kind of R objects, in a platform independent way. To give a striking real example, at a given time on a given platform, it was about 4 minutes long to import a numeric table with 70000 lines and 64 columns with the defaults settings of the `read.table()` function. Turning it into binary format, it was then about 8 *seconds* to restore it with the `load()` function. It is therefore advisable in the `input.R` batch file to save important data or results (with something like `save(mybigdata, file = "mybigdata.RData")`) so as to be able to restore them later efficiently in the interactive mode (with something like `load("mybigdata.RData")`).

## 1.7 About the learning curve

### Introduction

If you are used to work with a purely graphical user interface, you may feel frustrated in the beginning of the learning process because apparently simple things are not so easily obtained (*ce n'est que le premier pas qui coûte !*). In the long term, however, you are a winner for the following reasons.

#### 1.7.1 Wheel (the)

Do not re-invent (there's a patent [27] on it anyway). At the compilation time of this document there were 798 contributed packages available. Even if you don't want to be spoon-feed *à bouche ouverte*, it's not a bad idea to look around there just to check what's going on in your own application field. Specialists all around the world are there.



### 1.7.2 Hotline

There is a very reactive discussion list to help you, just make sure to read the posting guide there: <http://www.R-project.org/posting-guide.html> before posting. Because of the high traffic on this list, we strongly suggest to answer *yes* at the question *Would you like to receive list mail batched in a daily digest?* when subscribing at <https://stat.ethz.ch/mailman/listinfo/r-help>. Some *bons mots* from the list are archived in the `R` `fortunes` package.

### 1.7.3 Automation

Consider the 178 pages of figures in the additional data file 1 (<http://genomebiology.com/2002/3/10/research/0058/suppl/S1>) from [36]. They were produced in part automatically (with a proprietary software that is no more maintained) and manually, involving a lot of tedious and repetitive manipulations (such as italicising species names by hand in subtitles). In few words, a waste of time. The advantage of the `R` environment is that once you are happy with the outputs (including graphical outputs) of an analysis for species *x*, it's very easy to run the same analysis on *n* species.


### 1.7.4 Reproducibility

If you do not consider the reproducibility of scientific results to be a serious problem in practice, then the paper by Jonathan Buckheit and David Donoho [2] is a must read. Molecular data are available in public databases, this is a necessary but not sufficient condition to allow for the reproducibility of results. Publishing the `R` source code that was used in your analyses is a simple way to greatly facilitate the reproduction of your results at the expense of no extra cost. At the expense of a little extra cost, you may consider to set up a `RWeb` server so that even the laziest reviewer may reproduce your results just by clicking on the "do it again" button in his web browser (*i.e.* without installing any software on his computer). For an example involving the `seqinR` package, follow this link <http://pbil.univ-lyon1.fr/members/lobry/repro/bioinfo04/> to reproduce on-line the results from [3].

### 1.7.5 Fine tuning

You have full control on everything, even the source code for all functions is available. The following graph was specifically designed to illustrate the first experimental evidence [48] that, on average, we have also  $[A]=[T]$  and  $[C]=[G]$  in single-stranded DNA. These data from Chargaff's lab give the base composition of the L (Ligth) strand for 7 bacterial chromosomes.

```
example(chargaff)
```



This is a very specialised graph. The filled areas correspond to non-allowed values because the sum of the four bases frequencies cannot exceed 100 %. The white areas correspond to possible values (more exactly to the projection from  $\mathbb{R}^4$  to the corresponding  $\mathbb{R}^2$  planes of the region of allowed values). The lines correspond to the very small subset of allowed values for which we have in addition  $[A]=[T]$  and  $[C]=[G]$ . Points represent observed values in the 7 bacterial chromosomes. The whole graph is entirely defined by the code given in the example of the `chargaff` dataset (`?chargaff` to see it).

Another example of highly specialised graph is given by the function `tablecode()` to display a genetic code as in textbooks :

```
tablecode()
```

Genetic code 1 : standard							
TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTT	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

It's very convenient in practice to have a genetic code at hand, and moreover here, all genetic code variants are available :

```
tablecode(numcode = 2)
```

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Trp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Thr	CCT	Pro	CAT	His	CGT	Arg
CTC	Thr	CCC	Pro	CAC	His	CGC	Arg
CTA	Thr	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Thr	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Met	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table 1.2: Genetic code number 3: yeast.mitochondrial.

---

<b>Genetic code 2 : vertebrate.mitochondrial</b>							
TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Trp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Met	ACA	Thr	AAA	Lys	AGA	Stp
ATG	Met	ACG	Thr	AAG	Lys	AGG	Stp
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

As from **seqinR** 1.0-4, it is possible to export the table of a genetic code into a  $\text{\LaTeX}$  document, for instance table 1.2 and table 1.3 were automatically generated with the following R code:

```
tablecode(numcode = 3, latexfile = "../tables/code3.tex",
           size = "small")
tablecode(numcode = 4, latexfile = "../tables/code4.tex",
           size = "small")
```

The tables were then inserted in the  $\text{\LaTeX}$  file with:

```
\input{../tables/code3.tex}
```

---


TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Trp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table 1.3: Genetic code number 4: protozoan.mitochondrial+mycoplasma.

```
\input{../tables/code4.tex}
```

### 1.7.6 Data as fast moving targets

In research area, data are not always stable. Consider figure 1 from [33] which is reproduced here in figure 1.1. Data have been updated since then, but we can re-use the same  code<sup>8</sup> to update the figure:

```
data <- get.db.growth()
scale <- 1
ltymoore <- 1
date <- data$date
Nucleotides <- data$Nucleotides
Month <- data$Month
plot.default(date, log10(Nucleotides), main = "Update of Fig. 1 from Lobry (2004) LNCS, 3039:679:\nThe e
          xlab = "Year", ylab = "Log10 number of nucleotides", pch = 19,
          cex = scale/2, cex.axis = scale, cex.lab = scale)
abline(lm(log10(Nucleotides) ~ date), lwd = 2)
lm1 <- lm(log(Nucleotides) ~ date)
mu <- lm1$coef[2]
dbt <- log(2)/mu
dbt <- 12 * dbt
x <- mean(date)
y <- mean(log10(Nucleotides))
a <- log10(2)/1.5
b <- y - a * x
lm10 <- lm(log10(Nucleotides) ~ date)
for (i in seq(-10, 10, by = 1)) if (i != 0) abline(coef = c(b +
  i, a), col = "black", lty = ltymoore)
```

---

<sup>8</sup> This code was copy/pasted from <http://pbil.univ-lyon1.fr/members/lobry/repro/lncs04/>.






Figure 1.1: Screenshot of figure 1 from [33]. The exponential growth of genomic sequence data mimics Moore's law. The source of data is the december 2003 release note (realnote.txt) from the EMBL database available at <http://www.ebi.ac.uk/>. External lines correspond to what would be expected with a doubling time of 18 months. The central line through points is the best least square fit, corresponding to a doubling time of 16.9 months.



The doubling time is now 16.6 months.

### 1.7.7 Sweave() and xtable()

For  $\text{\LaTeX}$  users, it's worth mentioning the fantastic tool contributed by Friedrich Leish [31] called `Sweave()` that allows for the automatic insertion of  outputs

(including graphics) in a  $\text{\LaTeX}$  document. In the same spirit, there is a package called `xtable` [4] to coerce  $\text{\R}$  data into  $\text{\LaTeX}$  tables.

## 1.8 Session Informations

This part was compiled under the following  $\text{\R}$  environment:

- Version 2.3.1 (2006-06-01), `powerpc-apple-darwin8.6.0`
- Base packages: `base`, `datasets`, `grDevices`, `graphics`, `methods`, `stats`, `utils`
- Other packages: `MASS` 7.2-27.1, `ade4` 1.4-1, `ape` 1.8-2, `gee` 4.13-10, `lattice` 0.13-8, `nlme` 3.1-73, `seqinr` 1.0-6, `xtable` 1.3-0

---

---

## CHAPTER 2

---

# Importing sequences from flat files

Charif, D. Lobry, J.R.

### Contents

---

2.1	Importing raw sequence data from FASTA files . .	11
2.2	Importing aligned sequence data . . . . .	26
2.3	Session Informations . . . . .	34

---

## 2.1 Importing raw sequence data from FASTA files

### 2.1.1 FASTA files examples

The FASTA format is very simple and widely used for simple import of biological sequences. It was used originally by the FASTA program [43]. It begins with a single-line description starting with a character >, followed by lines of sequence data of maximum 80 character each. Examples of files in FASTA format are distributed with the **seqinR** package in the **sequences** directory:

```
list.files(path = system.file("sequences", package = "seqinr"),
           pattern = ".fasta")

[1] "ATH1_pep_cm_20040228.fasta" "Anouk.fasta"
[3] "bb.fasta"                  "bordetella.fasta"
[5] "ct.fasta"                  "ecolicgpe5.fasta"
[7] "gopher.fasta"              "louse.fasta"
[9] "malM.fasta"                "ortho.fasta"
[11] "seqAA.fasta"               "smallAA.fasta"
```

Here is an example of a FASTA file:

```
cat(readLines(system.file("sequences/seqAA.fasta", package = "seqinr")),
     sep = "\n")
```

```
>A06852                                183 residues
MPRLFSYLLGVWLLLSQLPREIPGQSTNDFIKACGRELVRWLWEICGSVSWGRITALSLEE
PQLETGPPAETMPSSITKDAEILKMMLEFVFNLPQELKATLSERQPSLRQLQSSASKDSN
LNFEEFKIILNRQNEAEDKSLLELKNLGLDKHSRKKRLFRMTLSEKCCQVGCIRKDIAR
LC*
```

## 2.1.2 The function read.fasta()

The function `read.fasta()` imports sequences from FASTA files into your workspace.

### DNA file example

The example file looks like:

```
dnafile <- system.file("sequences/malM.fasta", package = "seqinr")
cat(readLines(dnafile), sep = "\n")
```

```
>XYLEECOM.MALM 921 bp ACCESSION E00218, X04477
ATGAAAATGAATAAAAGTCTCATCGTCTCTGTTTATCAGCAGGGTTACTGGCAAGCGCG
CCTGGAATTAGCCTTGCCGATGTTAACTACGTACCGCAAAACACACGCGACGCGCCAGCC
ATTCCATCTGCTGCGCTGCAACAACCTCACCTGGACACCGGTCGATCAATCTAAAACCCAG
ACCACCAACTGGCGACCGCGCGCAACAACCTGAACGTTCCCGGCATCAGTGGTCCGGTT
GCTGCGTACAGCGTCCCGCAAAACATTGGCGAACTGACCCGACGCTGACACGCGAAGTG
AACAAAACAAACCGCGTTTTTGGCGCCGAACGTGCTGATTCTTGATCAGAACATGACCCCA
TCAGCCTTCTTCCCGCAGCTTATTTACCTACCAGGAACACGCGGTGATGAGTGCAGAT
CGGCTGGAAGGCGTTATGCGCCTGACACCGGCGTTGGGGCAGCAAAAACCTTATGTTCTG
GTCTTTACCGCAAAAGATCTCCAGCAGACGCCAACTGCTCGACCCGCGCTAAAGCC
TATGCCAAGGGCGTCGGTAACCTCGATCCCGGATATCCCGATCCGGTTGCTCGTCATACC
ACCGATGGCTTACTGAACTGAAAGTGAACGAACCTCCAGCTCCAGCGTGTGGTAGGA
CCCTTATTTGGTTCTCCGCTCCAGCTCCGGTTACGGTAGGTAAACACGGCGGCACCGGT
GTGGCTGCACCCGCTCCGGCACCGGTGAAGAAAAGCGAGCCGATGCTCAACGACACGGAA
AGTTATTTTAATACCGCGATCAAAAACGCTGTGCGGAAAGGTGATGTTGATAAGGCGTTA
AAACTGCTTGATGAAGCTGAACGCTTGGGATCGACATCTGCCCGTTCCACCTTTATCAGC
AGTGTAAGGCAAGGGTAA
```

With default arguments the output looks like:

```
read.fasta(file = dnafile)
```

```
$XYLEECOM.MALM
[1] "a" "t" "g" "a" "a" "a" "a" "t" "g" "a" "a" "t" "a" "a" "a" "a" "g" "t"
[19] "c" "t" "c" "a" "t" "c" "g" "t" "c" "c" "t" "c" "t" "g" "t" "t" "t" "a"
[37] "t" "c" "a" "g" "c" "a" "g" "g" "t" "t" "a" "c" "t" "g" "g" "a" "c" "a"
[55] "a" "g" "c" "g" "c" "g" "c" "c" "t" "g" "g" "a" "a" "t" "t" "a" "g" "c"
[73] "c" "t" "t" "g" "c" "c" "g" "a" "t" "g" "t" "t" "a" "a" "c" "t" "a" "c"
[91] "g" "t" "a" "c" "c" "g" "c" "a" "a" "a" "a" "c" "a" "c" "c" "a" "g" "c"
[109] "g" "a" "c" "g" "c" "g" "c" "c" "a" "g" "c" "c" "a" "t" "t" "c" "a" "a"
[127] "t" "c" "t" "g" "c" "t" "g" "c" "g" "c" "t" "g" "c" "a" "a" "c" "a" "a"
[145] "c" "t" "c" "a" "c" "c" "t" "g" "g" "a" "c" "a" "c" "c" "g" "g" "t" "c"
[163] "g" "a" "t" "c" "a" "a" "a" "t" "c" "t" "a" "a" "a" "c" "c" "c" "a" "g"
[181] "a" "c" "c" "a" "c" "c" "c" "a" "a" "c" "t" "g" "g" "c" "g" "a" "c" "c"
[199] "g" "g" "c" "g" "g" "c" "c" "a" "a" "c" "a" "a" "c" "t" "g" "a" "a" "c"
[217] "g" "t" "t" "c" "c" "c" "g" "c" "a" "t" "c" "a" "g" "t" "g" "g" "t"
[235] "c" "c" "g" "g" "t" "t" "g" "c" "t" "g" "c" "g" "t" "a" "c" "a" "g" "c"
[253] "g" "t" "c" "c" "c" "g" "g" "c" "a" "a" "a" "c" "a" "t" "t" "g" "g" "c"
[271] "g" "a" "a" "c" "t" "g" "a" "c" "c" "c" "t" "g" "a" "c" "g" "c" "t" "g"
[289] "a" "c" "c" "a" "g" "c" "g" "a" "a" "g" "t" "g" "a" "a" "c" "a" "a" "a"
[307] "c" "a" "a" "a" "c" "c" "a" "g" "c" "g" "t" "t" "t" "t" "t" "g" "c" "g"
[325] "c" "c" "g" "a" "c" "c" "t" "g" "c" "t" "g" "a" "t" "t" "c" "c" "t" "t"
[343] "g" "a" "t" "c" "a" "g" "a" "a" "c" "a" "t" "g" "a" "c" "c" "c" "c" "a"
[361] "t" "c" "a" "g" "c" "c" "t" "t" "c" "t" "t" "c" "c" "c" "c" "a" "g" "c"
[379] "a" "g" "t" "a" "t" "t" "c" "t" "c" "a" "c" "t" "a" "a" "c" "c" "g" "g"
[397] "g" "a" "a" "c" "c" "a" "g" "g" "c" "g" "t" "g" "a" "t" "g" "a" "g" "t"
[415] "g" "c" "a" "g" "a" "t" "c" "g" "g" "c" "t" "g" "g" "a" "a" "g" "g" "c"
[433] "g" "t" "t" "a" "t" "g" "c" "g" "c" "t" "g" "a" "c" "a" "c" "c" "g"
[451] "g" "c" "g" "t" "t" "g" "g" "g" "c" "a" "g" "c" "a" "a" "a" "a" "a" "a"
```



```

[469] "c" "t" "t" "t" "a" "t" "g" "t" "t" "c" "t" "g" "g" "t" "c" "t" "t" "t"
[487] "a" "c" "c" "a" "c" "g" "g" "a" "a" "a" "a" "g" "a" "t" "c" "t" "c"
[505] "c" "a" "g" "c" "a" "g" "a" "c" "g" "a" "c" "c" "c" "a" "c" "t" "g"
[523] "c" "t" "c" "g" "a" "c" "c" "c" "g" "g" "c" "t" "a" "a" "a" "g" "c" "c"
[541] "t" "a" "t" "g" "c" "c" "a" "a" "g" "g" "c" "g" "t" "c" "g" "g" "t"
[559] "a" "a" "c" "t" "c" "g" "a" "t" "c" "c" "c" "g" "g" "a" "t" "a" "t" "c"
[577] "c" "c" "c" "g" "a" "t" "c" "c" "g" "g" "t" "t" "g" "c" "t" "c" "g" "t"
[595] "c" "a" "t" "a" "c" "c" "a" "c" "c" "g" "a" "t" "g" "c" "t" "t" "a"
[613] "c" "t" "g" "a" "a" "a" "c" "t" "g" "a" "a" "a" "g" "t" "g" "a" "a" "a"
[631] "a" "c" "g" "a" "a" "c" "t" "c" "c" "a" "g" "c" "t" "c" "a" "g" "c"
[649] "g" "t" "g" "t" "t" "g" "g" "a" "g" "c" "a" "c" "c" "t" "t" "a"
[667] "t" "t" "g" "g" "t" "t" "c" "c" "c" "c" "g" "c" "t" "c" "c" "a"
[685] "g" "c" "t" "c" "c" "g" "g" "t" "t" "a" "c" "g" "g" "t" "a" "g" "g" "t"
[703] "a" "a" "c" "a" "c" "g" "g" "c" "g" "g" "c" "c" "c" "c" "a" "g" "c" "t"
[721] "g" "t" "g" "c" "c" "t" "g" "c" "c" "c" "c" "g" "t" "c" "c" "g"
[739] "g" "c" "a" "c" "c" "g" "g" "t" "g" "a" "a" "g" "a" "a" "a" "g" "c"
[757] "g" "a" "g" "c" "c" "g" "a" "t" "g" "c" "t" "c" "a" "a" "g" "a" "c"
[775] "g" "c" "g" "a" "a" "a" "a" "g" "t" "a" "t" "t" "t" "a" "a" "t"
[793] "a" "c" "c" "g" "c" "g" "a" "t" "c" "a" "a" "a" "a" "c" "g" "c" "t"
[811] "g" "t" "c" "g" "c" "g" "a" "a" "a" "g" "g" "t" "g" "a" "t" "g" "t" "t"
[829] "g" "a" "t" "a" "a" "g" "g" "c" "g" "t" "t" "a" "a" "a" "c" "t" "g"
[847] "c" "t" "t" "g" "a" "t" "g" "a" "a" "g" "c" "t" "g" "a" "a" "c" "g" "c"
[865] "t" "t" "g" "g" "a" "t" "c" "g" "a" "c" "a" "t" "c" "t" "g" "c" "c"
[883] "c" "g" "t" "t" "c" "c" "a" "c" "t" "t" "a" "t" "c" "a" "g" "c"
[901] "a" "g" "t" "g" "t" "a" "a" "a" "a" "g" "g" "c" "a" "a" "g" "g" "g"
[919] "t" "a" "a"
attr(,"name")
[1] "XYLEECOM.MALM"
attr(,"Annot")
[1] ">XYLEECOM.MALM 921 bp ACCESSION E00218, X04477"
attr(,"class")
[1] "SeqFastadna"

```

As from **seqinR** 1.0-5 the automatic conversion of sequences into vector of single characters can be neutralized, for instance:

```

read.fasta(file = dnafile, as.string = TRUE)

$XYLEECOM.MALM
[1] "atgaaaatgaataaaagtctcatcgctcctctgtttatcagcagggttactggcaagcgcgcctggaattagccttgccgatgttaactacgtaccgcaaaacaccagcgacg"
attr(,"name")
[1] "XYLEECOM.MALM"
attr(,"Annot")
[1] ">XYLEECOM.MALM 921 bp ACCESSION E00218, X04477"
attr(,"class")
[1] "SeqFastadna"

```

Forcing to lower case letters can be disabled this way:

```

read.fasta(file = dnafile, as.string = TRUE, forcedDNAtolower = FALSE)

$XYLEECOM.MALM
[1] "ATGAAAATGAATAAAAGTCTCATCGTCCTCTGTTTATCAGCAGGGTTACTGGCAAGCGCGCCTGGAATTAGCCTTGCCGATGTTAACACTACGTACCGCAAAACACCAGCGACG"
attr(,"name")
[1] "XYLEECOM.MALM"
attr(,"Annot")
[1] ">XYLEECOM.MALM 921 bp ACCESSION E00218, X04477"
attr(,"class")
[1] "SeqFastadna"

```

## Protein file example

The example file looks like:

```

aafile <- system.file("sequences/seqAA.fasta", package = "seqinr")
cat(readLines(aafile), sep = "\n")

```

```
>A06852                                183 residues
MPRLFSYLLGVWLLLSQLPREIPGQSTNDFIKACGRELVRWLWEICGSVSWGRTALSLEE
PQLETGPPAETMPSSITKDAEILKMMLEFVFNLPQELKATLSEKQPSLRELQQSASKDSN
LNFEEFKIILNRQNEAEDKSLELKNLGLDKHSRKKRLFRMTLSEKCCQVGCIRKDIAR
LC*
```

Read the protein sequence file, looks like:

```
read.fasta(aafile, seqtype = "AA")

$A06852
 [1] "M" "P" "R" "L" "F" "S" "Y" "L" "L" "G" "V" "W" "L" "L" "L" "S" "Q" "L"
[19] "P" "R" "E" "I" "P" "G" "Q" "S" "T" "N" "D" "F" "I" "K" "A" "C" "G" "R"
[37] "E" "L" "V" "R" "L" "W" "V" "E" "I" "C" "G" "S" "V" "S" "W" "G" "R" "T"
[55] "A" "L" "S" "L" "E" "E" "P" "Q" "L" "E" "T" "G" "P" "P" "A" "E" "T" "M"
[73] "P" "S" "S" "I" "T" "K" "D" "A" "E" "I" "L" "K" "M" "M" "L" "E" "F" "V"
[91] "P" "N" "L" "P" "Q" "E" "L" "K" "A" "T" "L" "S" "E" "R" "Q" "P" "S" "L"
[109] "R" "E" "L" "Q" "S" "A" "S" "K" "D" "S" "N" "L" "N" "F" "E" "E" "F"
[127] "K" "K" "I" "I" "L" "N" "R" "Q" "N" "E" "A" "E" "D" "K" "S" "L" "I" "E"
[145] "L" "K" "N" "G" "L" "D" "K" "H" "S" "R" "K" "K" "R" "L" "F" "I" "M"
[163] "T" "L" "S" "E" "K" "C" "C" "Q" "V" "G" "C" "I" "R" "K" "D" "I" "A" "R"
[181] "L" "C" "*"
attr(,"name")
[1] "A06852"
attr(,"Annot")
[1] ">A06852                                183 residues"
attr(,"class")
[1] "SeqFastaAA"
```

The same, but as string and without attributes setting, looks like:

```
read.fasta(aafile, seqtype = "AA", as.string = TRUE, set.attributes = FALSE)

$A06852
[1] "MPRLFSYLLGVWLLLSQLPREIPGQSTNDFIKACGRELVRWLWEICGSVSWGRTALSLEE"
[2] "PQLETGPPAETMPSSITKDAEILKMMLEFVFNLPQELKATLSEKQPSLRELQQSASKDSN"
[3] "LNFEEFKIILNRQNEAEDKSLELKNLGLDKHSRKKRLFRMTLSEKCCQVGCIRKDIAR"
[4] "LC"
```

### 2.1.3 The function write.fasta()

This function writes sequences to a file in FASTA format. Read 3 coding sequences from a FASTA file:

```
ortho <- read.fasta(file = system.file("sequences/ortho.fasta",
package = "seqinr"))
length(ortho)
```

```
[1] 3
```

```
ortho[[1]][1:12]
```

```
[1] "a" "t" "g" "g" "c" "t" "c" "a" "g" "c" "g" "g"
```

Select only third codon positions:

```
ortho3 <- lapply(ortho, function(x) x[seq(from = 3, to = length(x),
by = 3)])
ortho3[[1]][1:4]
```

```
[1] "g" "t" "g" "g"
```

Write the modified sequences to a file:

```
tmpf <- tempfile()
write.fasta(sequences = ortho3, names = names(ortho3), nbchar = 80,
file.out = tmpf)
```

Read them again from the same file and check that sequences are preserved:

```
ortho3bis <- read.fasta(tmpf, set.attributes = FALSE)
identical(ortho3bis, ortho3)
```


```
[1] TRUE
```

### 2.1.4 Big room examples

#### Oriloc example (*Chlamydia trachomatis* complete genome)


A more consequent example is given in the fasta file `ct.fasta` which contains the complete genome of *Chlamydia trachomatis* that was used in [7]. You should be able to reproduce figure 1b from this paper with the following code:

```
out <- oriloc(seq.fasta = system.file("sequences/ct.fasta",
  package = "seqinr"), g2.coord = system.file("sequences/ct.coord",
  package = "seqinr"), oldoriloc = TRUE)
plot(out$st, out$sk/1000, type = "l", xlab = "Map position in Kb",
  ylab = "Cumulated composite skew in Kb", main = expression(italic(Chlamydia ~
  ~trachomatis) ~ ~complete ~ ~genome), las = 1)
abline(h = 0, lty = 2)
text(400, -4, "Terminus")
text(850, 9, "Origin")
```



Note that the algorithm has been improved since then and that it's more advisable to use the default option `oldoriloc = FALSE` if you are interested in the prediction of origins and terminus of replication from base composition biases (more on this at <http://pbil.univ-lyon1.fr/software/oriloc.html>). See also [38] for a recent review on this topic.

```
out <- oriloc(seq.fasta = system.file("sequences/ct.fasta",
  package = "seqinr"), g2.coord = system.file("sequences/ct.coord",
  package = "seqinr"))
plot(out$st, out$sk/1000, type = "l", xlab = "Map position in Kb",
  ylab = "Cumulated composite skew in Kb", main = expression(italic(Chlamydia ~
  ~trachomatis) ~ ~complete ~ ~genome), las = 1)
mtext("New version")
abline(h = 0, lty = 2)
text(400, -4, "Terminus")
text(850, 9, "Origin")
```



*Arabidopsis thaliana*. Source: wikipedia.

### Example with 21,161 proteins from *Arabidopsis thaliana*

As from `seqinR` 1.0-5 the automatic conversion of sequences into vector of single characters and the automatic attribute settings can be neutralized, for instance :

```
smallAA <- system.file("sequences/smallAA.fasta", package = "seqinr")
read.fasta(smallAA, seqtype = "AA", as.string = TRUE, set.attributes = FALSE)
```

```
$smallAA
[1] "SEQINRSEQINRSEQINRSEQINR*"
```

This is interesting to save time and space when reading large FASTA files. Let's give a practical example. In their paper [17], Matthew Hannah, Arnd Heyer and Dirk Hinchin were working on *Arabidopsis thaliana* genes in order to detect those involved in cold acclimation. They were interested by the detection of proteins called hydrophilins, that had a mean hydrophilicity of over 1 and glycine content of over 0.08 [9], because they are thought to be important for freezing tolerance. The starting point was a FASTA file called `ATH1_pep_cm_20040228` downloaded from the Arabidopsis Information Ressource (TAIR at <http://www.arabidopsis.org/>) which contains the sequences of 21,161 proteins.

```
athfile <- system.file("sequences/ATH1_pep_cm_20040228.fasta",
  package = "seqinr")
system.time(ath <- read.fasta(athfile, seqtype = "AA", as.string = TRUE,
  set.attributes = FALSE))
```

```
[1] 28.222 0.461 29.937 0.000 0.000
```

It's about one minute here to read 21,161 protein sequences. We save them in XDR binary format to read them faster later at will:

```
save(ath, file = "ath.RData")

system.time(load("ath.RData"))

[1] 0.655 0.048 1.009 0.000 0.000
```

Now it's about one second to load the whole data set thanks to the XDR format. The object size is about 15 Mo in RAM, that is something very close to the flat file size on disk:

```
object.size(ath)/2^20


[1] 14.94021

file.info(athfile)$size/2^20

[1] 15.89863
```

Using strings for sequence storage is very comfortable when there is an efficient function to compute what you want. For instance, suppose that you are interested by the distribution of protein size in *Arabidopsis thaliana*. There is an efficient vectorized function called `nchar()` that will do the job, we just have to remove one unit because of the stop codon which is translated as a star (\*) in this data set. This is a simple and direct task under R:

```
nres <- nchar(ath) - 1
hist(log10(nres), col = grey(0.7), xlab = "Protein size (log10 scale)",
     ylab = "Protein count", main = expression(italic(Arabidopsis ~
~thaliana)))
```



However, sometimes it is more convenient to work with the single character vector representation of sequences. For instance, to count the number of glycine (G), we first play with one sequence, let's take the smallest one in the data set:

```
which.min(nres)

[1] 9523

ath[[9523]]

[1] "MAGSQREKLKPRTKGSTRC*"

s2c(ath[[9523]])

[1] "M" "A" "G" "S" "Q" "R" "E" "K" "L" "K" "P" "R" "T" "K" "G" "S" "T" "R"
[19] "C" "*"

s2c(ath[[9523]]) == "G"

[1] FALSE FALSE TRUE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
[13] FALSE FALSE TRUE FALSE FALSE FALSE FALSE FALSE

sum(s2c(ath[[9523]]) == "G")

[1] 2
```

We can now easily define a vectorised function to count the number of glycine:

```
ngly <- function(data) {
  res <- sapply(data, function(x) sum(s2c(x) == "G"))
  names(res) <- NULL
  return(res)
}
```

Now we can use `ngly()` in the same way that `nchar()` so that computing glycine frequencies is very simple:


```
ngly(ath[1:10])

[1] 25 5 29 128 8 27 27 26 21 18

fgly <- ngly(ath)/nres
```


And we can have a look at the distribution:

```
hist(fgly, col = grey(0.7), main = "Distribution of Glycine frequency",
     xlab = "Glycine content", ylab = "Protein count")
abline(v = 0.08, col = "red")
legend("topright", inset = 0.01, lty = 1, col = "red", legend = "Threshold for hydrophilines")
```



Let's use a boxplot instead:

```
boxplot(fgly, horizontal = TRUE, col = grey(0.7), main = "Distribution of Glycine frequency",  
        xlab = "Glycine content", ylab = "Protein count")  
abline(v = 0.08, col = "red")  
legend("topright", inset = 0.01, lty = 1, col = "red", legend = "Threshold for hydrophilines")
```



The threshold value for the glycine content in hydrophilines is therefore very close to the third quartile of the distribution:

```
summary(fgly)
```

```
      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
0.00000 0.04907 0.06195 0.06475 0.07639 0.59240
```

We want now to compute something relatively more complex, we want the Kyte and Doolittle[29] hydropathy score of our proteins (aka GRAVY score). This is basically a linear form on amino acid frequencies:

$$s = \sum_{i=1}^{20} \alpha_i f_i$$

where  $\alpha_i$  is the coefficient for amino acid number  $i$  and  $f_i$  the relative frequency of amino acid number  $i$ . The coefficients  $\alpha_i$  are given in the KD component of the data set EXP:

```
data(EXP)
EXP$KD
```

```
[1] -3.9 -3.5 -3.9 -3.5 -0.7 -0.7 -0.7 -0.7 -4.5 -0.8 -4.5 -0.8 4.5 4.5
[15] 1.9 4.5 -3.5 -3.2 -3.5 -3.2 -1.6 -1.6 -1.6 -1.6 -4.5 -4.5 -4.5 -4.5
[29] 3.8 3.8 3.8 3.8 -3.5 -3.5 -3.5 -3.5 1.8 1.8 1.8 1.8 -0.4 -0.4
[43] -0.4 -0.4 4.2 4.2 4.2 4.2 0.0 -1.3 0.0 -1.3 -0.8 -0.8 -0.8 -0.8
[57] 0.0 2.5 -0.9 2.5 3.8 2.8 3.8 2.8
```

This is for codons in lexical order, that is:

```
words()
```



```

[1] "aaa" "aac" "aag" "aat" "aca" "acc" "acg" "act" "aga" "agc" "agg" "agt"
[13] "ata" "atc" "atg" "att" "caa" "cac" "cag" "cat" "cca" "ccc" "ccg" "cct"
[25] "cga" "cgc" "cgg" "cgt" "cta" "ctc" "ctg" "ctt" "gaa" "gac" "gag" "gat"
[37] "gca" "gcc" "gcg" "gct" "gga" "ggc" "ggg" "ggg" "ggt" "gta" "gtc" "gtg" "gtt"
[49] "taa" "tac" "tag" "tat" "tca" "tcc" "tcg" "tct" "tga" "tgc" "tgg" "tgt"
[61] "tta" "ttc" "ttg" "ttt"

```

But since we are working with protein sequences here we name the coefficient according to their amino acid :

```
names(EXP$KD) <- sapply(words(), function(x) translate(s2c(x)))
```

We just need one value per amino acid, we sort them in the lexical order, and we reverse the scale so as to have positive values for hydrophilic proteins as in [17] :

```

kdc <- EXP$KD[unique(names(EXP$KD))]
kdc <- -kdc[order(names(kdc))]
kdc

```

```

*      A      C      D      E      F      G      H      I      K      L      M      N      P      Q
0.0 -1.8 -2.5  3.5  3.5 -2.8  0.4  3.2 -4.5  3.9 -3.8 -1.9  3.5  1.6  3.5
R      S      T      V      W      Y
4.5  0.8  0.7 -4.2  0.9  1.3

```

Now that we have the vector of coefficient  $\alpha_i$ , we need the amino acid relative frequencies  $f_i$ , let's play with one protein first:

```
ath[[9523]]
```

```
[1] "MAGSQREKLPRTKGSTRC*"
```

```
s2c(ath[[9523]])
```

```

[1] "M" "A" "G" "S" "Q" "R" "E" "K" "L" "K" "P" "R" "T" "K" "G" "S" "T" "R"
[19] "C" "*"

```

```
table(s2c(ath[[9523]]))
```

```

* A C E G K L M P Q R S T
1 1 1 1 2 3 1 1 1 1 3 2 2

```

```
table(factor(s2c(ath[[9523]]), levels = names(kdc)))
```

```

* A C D E F G H I K L M N P Q R S T V W Y
1 1 1 0 1 0 2 0 0 3 1 1 0 1 1 3 2 2 0 0 0

```

Now that we know how to count amino acids it's relatively easy thanks to R's matrix operator `%*%` to define a vectorised function to compute a linear form on amino acid frequencies:


```

linform <- function(data, coef) {
  f <- function(x) {
    aaseq <- s2c(x)
    freq <- table(factor(aaseq, levels = names(coef)))/length(aaseq)
    return(coef %*% freq)
  }
  res <- sapply(data, f)
  names(res) <- NULL
  return(res)
}
kdath <- linform(ath, kdc)

```

Let's have a look at the distribution:

```
boxplot(kdath, horizontal = TRUE, col = grey(0.7), main = "Distribution of Hydropathy index",
        xlab = "Kyte and Doolittle GRAVY score")
abline(v = 1, col = "red")
legend("topleft", inset = 0.01, lty = 1, col = "red", legend = "Threshold for hydrophilines")
```



The threshold is therefore much more stringent here than the previous one on glycine content. Let's define a vector of logicals to select the hydrophilines:

```
hydrophilines <- fgly > 0.08 & kdath > 1
names(ath)[hydrophilines]
```

```
[1] "At1g02840.1" "At1g02840.2" "At1g02840.3" "At1g03320.1" "At1g03820.1"
[6] "At1g04450.1" "At1g12810.1" "At1g13020.1" "At1g13290.1" "At1g13890.1"
[11] "At1g15270.1" "At1g15280.1" "At1g15280.2" "At1g15400.1" "At1g15400.2"
[16] "At1g20220.1" "At1g21520.1" "At1g23530.1" "At1g23860.1" "At1g23860.2"
[21] "At1g26210.1" "At1g27650.1" "At1g31750.1" "At1g42430.1" "At1g44478.1"
[26] "At1g47970.1" "At1g48920.1" "At1g49680.1" "At1g50300.1" "At1g51510.1"
[31] "At1g52300.1" "At1g52690.1" "At1g52690.2" "At1g52710.1" "At1g53160.1"
[36] "At1g53160.2" "At1g53260.1" "At1g53645.1" "At1g54410.1" "At1g54926.1"
[41] "At1g55310.1" "At1g56085.1" "At1g60650.1" "At1g60650.2" "At1g62045.1"
[46] "At1g63310.1" "At1g64360.1" "At1g64370.1" "At1g67325.1" "At1g67870.1"
[51] "At1g72050.1" "At1g72080.1" "At1g73350.1" "At1g75560.1" "At1g76010.1"
[56] "At1g77030.1" "At1g77765.1" "At1g80000.1" "At1g80000.2" "At2g02160.1"
[61] "At2g03440.1" "At2g04380.1" "At2g04870.1" "At2g07675.1" "At2g11910.1"
[66] "At2g11910.2" "At2g13125.1" "At2g17950.1" "At2g19750.1" "At2g20430.1"
[71] "At2g20760.1" "At2g21490.1" "At2g22080.1" "At2g22100.1" "At2g22820.1"
[76] "At2g23110.1" "At2g24590.1" "At2g25990.1" "At2g27100.1" "At2g32710.1"
[81] "At2g32710.2" "At2g33460.1" "At2g33690.1" "At2g34310.1" "At2g34310.2"
[86] "At2g34310.3" "At2g35230.2" "At2g37340.1" "At2g37340.2" "At2g37340.3"
[91] "At2g39855.2" "At2g40040.1" "At2g40080.1" "At2g40170.1" "At2g41730.1"
[96] "At2g42190.1" "At2g43370.1" "At2g43970.2" "At2g44710.1" "At2g44820.1"
[101] "At2g44820.2" "At2g46270.2" "At3g02480.1" "At3g05220.1" "At3g05220.2"
[106] "At3g07195.1" "At3g10020.1" "At3g13570.1" "At3g13780.1" "At3g15270.1"
[111] "At3g16040.1" "At3g16080.1" "At3g17160.1" "At3g17190.1" "At3g20910.1"
```

```

[116] "At3g21270.1" "At3g21290.1" "At3g22660.1" "At3g23140.1" "At3g23380.1"
[121] "At3g23390.1" "At3g24100.1" "At3g24740.1" "At3g25590.1" "At3g26400.1"
[126] "At3g26420.1" "At3g29075.1" "At3g29470.1" "At3g29600.1" "At3g47120.1"
[131] "At3g48180.1" "At3g49430.1" "At3g50320.1" "At3g50610.1" "At3g50670.1"
[136] "At3g50690.1" "At3g50970.1" "At3g50980.1" "At3g51810.1" "At3g51940.1"
[141] "At3g53500.1" "At3g53500.2" "At3g55460.1" "At3g56720.1" "At3g57930.1"
[146] "At3g58070.1" "At3g60230.1" "At3g62790.1" "At3g63100.1" "At3g63400.1"
[151] "At3g63400.2" "At4g02425.1" "At4g02430.2" "At4g07940.1" "At4g09840.1"
[156] "At4g09850.1" "At4g09980.1" "At4g12610.1" "At4g12670.1" "At4g13560.1"
[161] "At4g13615.1" "At4g14020.1" "At4g14320.1" "At4g16830.1" "At4g17520.1"
[166] "At4g22740.1" "At4g22740.2" "At4g24500.1" "At4g24500.2" "At4g24680.1"
[171] "At4g25340.1" "At4g25500.1" "At4g25500.2" "At4g26640.1" "At4g26640.2"
[176] "At4g28870.1" "At4g28990.1" "At4g29390.1" "At4g31580.1" "At4g36600.1"
[181] "At4g36730.1" "At4g36730.2" "At4g38710.1" "At5g02020.1" "At5g03990.1"
[186] "At5g04290.1" "At5g11260.1" "At5g11970.1" "At5g12840.1" "At5g12840.2"
[191] "At5g12840.3" "At5g12840.4" "At5g16470.1" "At5g17650.1" "At5g19960.1"
[196] "At5g22040.1" "At5g22650.1" "At5g22650.2" "At5g26890.1" "At5g27690.1"
[201] "At5g28610.1" "At5g28630.1" "At5g44200.1" "At5g47210.1" "At5g50830.1"
[206] "At5g51840.1" "At5g52200.1" "At5g52310.1" "At5g52530.1" "At5g52530.2"
[211] "At5g53820.1" "At5g55430.1" "At5g55640.1" "At5g55670.1" "At5g56670.1"
[216] "At5g58040.1" "At5g58470.1" "At5g58470.2" "At5g59080.1" "At5g59950.1"
[221] "At5g59950.3" "At5g60800.1" "At5g60880.1" "At5g61890.1" "At5g64130.1"
[226] "At5g66400.1" "At5g66780.1" "At5g67190.1" "At5g67490.1" "AtMg00880"


```

Check with a simple graph that there is no mistake here:

```

library(MASS)
dst <- kde2d(kdath, fgly, n = 50)
filled.contour(x = dst, color.palette = topo.colors, plot.axes = {
  axis(1)
  axis(2)
  title(xlab = "Kyte and Doolittle GRAVY score", ylab = "Glycine content",
    main = "Hydrophilines location")
  abline(v = 1, col = "yellow")
  abline(h = 0.08, col = "yellow")
  points(kdath[hydrophilines], fgly[hydrophilines], col = "white")
  legend("topleft", inset = 0.02, lty = 1, col = "yellow",
    bg = "white", legend = "Threshold for hydrophilines",
    cex = 0.8)
})

```



Everything seems to be OK, we can save the results in a data frame:

```
athres <- data.frame(list(name = names(ath), KD = kdath, Gly = fgly))
head(athres)
```

	name	KD	Gly
1	At1g01010.1	0.7297674	0.05827506
2	At1g01020.1	-0.1674419	0.03906250
3	At1g01030.1	0.8136490	0.08100559
4	At1g01040.1	0.4159686	0.06705081
5	At1g01050.1	0.4460094	0.03773585
6	At1g01060.1	0.7444272	0.04186047

We want to check now that the results are consistent with those reported previously. The following table is extracted from the file `pgen.0010026.st003.xls` provided as the supplementary material table S3 in [17] and available at <http://www.pubmedcentral.nih.gov/picrender.fcgi?artid=1189076&blobname=pgen.0010026.st003.xls>. Only the protein names, the hydrophilicity and the glycine content were extracted:

```
hannah <- read.table(system.file("sequences/hannah.txt", package = "seqinr"),
  sep = "\t", header = TRUE)
head(hannah)
```

	AGI	Hydrophilicity	Glycine
1	At2g19570	-0.10	0.07
2	At2g45290	-0.25	0.09
3	At4g29570	-0.05	0.07
4	At4g29580	-0.10	0.06
5	At4g29600	-0.14	0.06
6	At5g28050	-0.11	0.08

The protein names are not exactly the same because they have no extension. As explained in [17], when multiple gene models were predicted only the first was one used. Then:

```
hannah$AGI <- paste(hannah$AGI, "1", sep = ".")
head(hannah)
```

```
      AGI Hydrophilicity Glycine
1 At2g19570.1      -0.10    0.07
2 At2g45290.1      -0.25    0.09
3 At4g29570.1      -0.05    0.07
4 At4g29580.1      -0.10    0.06
5 At4g29600.1      -0.14    0.06
6 At5g28050.1      -0.11    0.08
```


We join now the two data frames thanks to their common key:

```
join <- merge(hannah, athres, by.x = "AGI", by.y = "name")
head(join)
```

```
      AGI Hydrophilicity Glycine      KD      Gly
1 At1g01120.1      -0.10    0.06 0.10699433 0.05871212
2 At1g01390.1       0.02    0.06 0.00914761 0.06458333
3 At1g01390.1       0.02    0.06 0.00914761 0.06458333
4 At1g01420.1      -0.05    0.07 0.06203320 0.07276507
5 At1g01420.1      -0.05    0.07 0.06203320 0.07276507
6 At1g01480.1      -0.20    0.07 0.20080483 0.06653226
```

Let's compare the glycine content :

```
plot(join$Glycine, join$Gly, xlab = "Glycine content in Hannah et al. (2005)",
      ylab = "Glycine content here", main = "Comparison of Glycine content results")
abline(c(0, 1), col = "red")
```




The results are consistent, we have just lost some resolution because there are only two figures after the decimal point in the Excel<sup>1</sup> file. Let's have a look at the GRAVY score now:

<sup>1</sup> this software is a real **pain** for the reproducibility of results. This is well documented, see [http://www.burns-stat.com/pages/Tutor/spreadsheet\\_addiction.html](http://www.burns-stat.com/pages/Tutor/spreadsheet_addiction.html) and references therein.

```

plot(join$Hydrophilicity, join$KD, xlab = "GRAVY score in Hannah et al. (2005)",
     ylab = "GRAVY score here", main = "Comparison of hydropathy score results",
     las = 1)
abline(c(0, -1), col = "red")
abline(v = 0, lty = 2)
abline(h = 0, lty = 2)

```



The results are consistent, it's hard to say whether the small differences are due to Excel rounding errors or because the method used to compute the GRAVY score was not exactly the same (in [17] they used the mean over a sliding window).

## 2.2 Importing aligned sequence data

### 2.2.1 Aligned sequences files examples

#### mase

Mase format is a flatfile format use by the SeaView multiple alignment editor [8], developed by Manolo Gouy and available at <http://pbil.univ-lyon1.fr/software/seaview.html>. The mase format is used to store nucleotide or protein multiple alignments. The beginning of the file must contain a header containing at least one line (but the content of this header may be empty). The header lines must begin by ;;. The body of the file has the following structure: First, each entry must begin by one (or more) commentary line. Commentary lines begin by the character ;. Again, this commentary line may be empty. After the commentaries, the name of the sequence is written on a separate line. At last, the sequence itself is written on the following lines.




Figure 2.1: The file `test.mase` under SeaView. This is a graphical multiple sequence alignment editor developed by Manolo Gouy [8]. SeaView is able to read and write various alignment formats (NEXUS, MSF, CLUSTAL, FASTA, PHYLIP, MASE). It allows to manually edit the alignment, and also to run DOT-PLOT or CLUSTALW programs to locally improve the alignment.

```
masef <- system.file("sequences/test.mase", package = "seqinr")
cat(readLines(masef), sep = "\n")
```

```
;;Aligned by clustal on Tue Jun 30 17:36:11 1998
;empty description
;Langur
-KIFERCELARTLKKLGLDGYKGVSLANWVCLAKWESGYNTEATNYPGDESTDYGIFQINSRYWCNNGKPGAVDACHISCSALLQNNIADAVACAKRVVSDQGIRAWAWRNHCQN
;
;Baboon
-KIFERCELARTLKKLGLDGYRGISLANWVCLAKWESDYNTQATNYPGQSTDYGFQINSRYWCNDGKPGAVNACHISCNALLQDNITDAVACAKRVVSDQGIRAWAWRNHCQN
;
;Human
-KVFERCELARTLKKLGLDGYRGISLANWVCLAKWESGYNTRATNYPGDRSTDYGFQINSRYWCNDGKPGAVNACHLSCSALLQDNIADAVACAKRVVSDQGIRAWAWRNHCQN
;
;Rat
-KTYERCEFARTLKRNGMSGYGVSLADWVCLAQHSNYNTQARNYPGQSTDYGFQINSRYWCNDGKPRKNACGIPCSALLQDDITQAIQCAKRVVSDQGIRAWAWRHCQN
;
;Cow
-KVFERCELARTLKKLGLDGYKGVSLANWVCLAKWESDYNTQATNYPGQSTDYGFQINSRYWCNDGKPGAVNACHLSCSALLQDNIADAVACAKRVVSDQGIRAWAWRNHCQN
;
;Horse
-KVFSKCELAHKLKAQEMDGGYSLANWVCLAKWESDYNTQATNYPGQSTDYGFQINSRYWCNDGKPGAVNACHLSCSALLQDNIADAVACAKRVVSDQGIRAWAWRNHCQN
```

A screenshot copy of the same file as seen under SeaView is given in figure 2.1.

### clustal

The CLUSTAL format (\*.aln) is the format of the ClustalW multialignment tool output [18, 57]. It can be described as follows. The word CLUSTAL is on the first line of the file. The alignment is displayed in blocks of a fixed length, each line in the block corresponding to one sequence. Each line of each block starts with the sequence name (maximum of 10 characters), followed by at least one space character. The sequence is then displayed in upper or lower cases, '-' denotes gaps. The residue number may be displayed at the end of the first line of each block.

```
clustalf <- system.file("sequences/test.aln", package = "seqinr")
cat(readLines(clustalf), sep = "\n")
```

CLUSTAL W (1.82) multiple sequence alignment

```

FOSB_MOUSE      MFQAFPGDYDSGSRCSSSPSAESQYLSSVDSFGSPPTAAASQECAGLGEMPGSFVPTVTA  60
FOSB_HUMAN      MFQAFPGDYDSGSRCSSSPSAESQYLSSVDSFGSPPTAAASQECAGLGEMPGSFVPTVTA  60
*****

FOSB_MOUSE      ITTSQDLQWLVPQTLISSMAQSQGQPLASQPPAVDPYDMPGTSYSTPGLSAYSTGGASGS 120
FOSB_HUMAN      ITTSQDLQWLVPQTLISSMAQSQGQPLASQPPVVDPYDMPGTSYSTPGMSGYSSGGASGS 120
*****

FOSB_MOUSE      GGPSTSTTSGPVSARPARARPRRPREETLTPEEEEEKRRVRRERNKLAALKCRNRREL 180
FOSB_HUMAN      GGPSTSGTTS GP PARPARARPRRPREETLTPEEEEEKRRVRRERNKLAALKCRNRREL 180
*****

FOSB_MOUSE      DRLQAETDQLEEEKAELESEIAELQKEKERLEFVLVAHKPGCKIPYEEGPGPGPLAEVRD 240
FOSB_HUMAN      DRLQAETDQLEEEKAELESEIAELQKEKERLEFVLVAHKPGCKIPYEEGPGPGPLAEVRD 240
*****

FOSB_MOUSE      LPGSTSAKEDGFGWLLPPPPPPPLPFQSSRDAPPNLTASLFTHSEVQVLGDPFPVVPSPSY 300
FOSB_HUMAN      LPGSAPAKEDGFSWLLPPPPPPPLPFQTSQDAPPNLTASLFTHSEVQVLGDPFPVVPSPSY 300
****:*****:*****:*****:*****:*****:*****:*****:*****

FOSB_MOUSE      TSSFVLTCEVSAFAGAQRSTSGSEQSDPLNPSLLAL 338
FOSB_HUMAN      TSSFVLTCEVSAFAGAQRSTSGSDQPSDPLNPSLLAL 338
*****

```

## phylip

PHYLIP is a tree construction program [6]. The format is as follows: the number of sequences and their length (in characters) is on the first line of the file. The alignment is displayed in an interleaved or sequential format. The sequence names are limited to 10 characters and may contain blanks.

```

phylipf <- system.file("sequences/test.phylip", package = "seqinr")
cat(readLines(phylipf), sep = "\n")

```

```

5      42
Turkey      AAGCTNNGGC  ATTTCAGGGT
Salmo gairdneri AAGCCTTGGC AGTGCAGGGT
H. Sapiens   ACCGGTTGGC  CGTTCAGGGT
Chimp        AAACCCCTGC   CGTTACGCTT
Gorilla      AAACCCCTGC   CGGTACGCTT

GAGCCCGGGC  AATACAGGGT  AT
GAGCCGTGGC  CGGGCACGGT  AT
ACAGGTTGGC  CGTTCAGGGT  AA
AAACCGAGGC  CGGGCACTC   AT
AAACCATGCT  CGGTACGCTT  AA

```

## msf

MSF is the multiple sequence alignment format of the GCG sequence analysis package (<http://www.accelrys.com/products/gcg/index.html>). It begins with the line (all uppercase) !!NA\_MULTIPLE\_ALIGNMENT 1.0 for nucleic acid sequences or !!AA\_MULTIPLE\_ALIGNMENT 1.0 for amino acid sequences. Do not edit or delete the file type if its present (optional). A description line which contains informative text describing what is in the file. You can add this information to the top of the MSF file using a text editor (optional). A dividing line which contains the number of bases or residues in the sequence, when the file was created, and importantly, two dots (..) which act as a divider between the descriptive information and the following sequence information (required). msf files contain some other information: the Name/Weight, a Separating Line which must include two slashes (//) to divide the name/weight



information from the sequence alignment (required) and the multiple sequence alignment.

```
msff <- system.file("sequences/test.msff", package = "seqinr")
cat(readLines(msff), sep = "\n")

PileUp of: @Pi3k.Fil

Symbol comparison table: GenRunData:Pileuppep.Cmp  CompCheck: 1254

          GapWeight: 3.000
          GapLengthWeight: 0.100

Pi3k.Msf  MSF: 377  Type: P  July 12, 1996 10:40  Check: 167 ..

Name: Tor1_Yeast      Len: 377  Check: 7773  Weight: 1.00
Name: Tor2_Yeast      Len: 377  Check: 8562  Weight: 1.00
Name: Frap_Human       Len: 377  Check: 9129  Weight: 1.00
Name: Esr1_Yeast       Len: 377  Check: 8114  Weight: 1.00
Name: Tel1_Yeast       Len: 377  Check: 1564  Weight: 1.00
Name: Pi4k_Human       Len: 377  Check: 8252  Weight: 1.00
Name: Stt4_Yeast       Len: 377  Check: 9117  Weight: 1.00
Name: Pik1_Yeast       Len: 377  Check: 3455  Weight: 1.00
Name: P3k1_Soybn       Len: 377  Check: 4973  Weight: 1.00
Name: P3k2_Soybn       Len: 377  Check: 4632  Weight: 1.00
Name: Pi3k_Arath       Len: 377  Check: 3585  Weight: 1.00
Name: Vp34_Yeast       Len: 377  Check: 5928  Weight: 1.00
Name: P11a_Human       Len: 377  Check: 6597  Weight: 1.00
Name: P11b_Human       Len: 377  Check: 8486  Weight: 1.00

//

1                                     50
Tor1_Yeast .....GHE DIRQDSLVMQ LFGLVNTLLK NDSECFKRHL DIQQYPAIPL
Tor2_Yeast .....GHE DIRQDSLVMQ LFGLVNTLLQ NDAECFRRHL DIQQYPAIPL
Frap_Human .....GHE DLRQDERVMQ LFGLVNTLLA NDPTSLRKNL SIQRYAVIPL
Esr1_Yeast .....KKE DVRQDNQYMQ FATTMDFLLS KDIASRKRSI GINIYSVLSL
Tel1_Yeast .KALMKGSND DLRQDAIMEQ VFQQVNVKVLQ NDKVLRNLDL GIRTYKVVPL
Pi4k_Human ..AAIFKVG DCRQDMLALQ IIDLFKNIFQ LV....GLDL FVFPYRVVAT
Stt4_Yeast ..AAIFKVG DCRQDVLALQ LISLFRTIWS SI....GLDV YVFPYRVVAT
Pik1_Yeast ...VIAKTGD DLRQEAFAYQ MIQAMANIWV KE....KVDV WVKRMKILIT
P3k1_Soybn TCKIIFKKGD DLRQDQLVVQ MVSLMDRLK LE....NLDL HLTPYKVLAT
P3k2_Soybn ....IFKKGD DIRQDQLVVQ MVSLMDRLK LE....NLDL HLTPYKVLAT
Pi3k_Arath ...KLIFKKGD DLRQDQLVVQ MVWLMDRLLK LE....NLDL CLTPYKVLAT
Vp34_Yeast .YHLMFKVG DLRQDQLVVQ IISLMNELLK NE....NVDL KLTPYKILAT
P11a_Human ...IIFKNGD DLRQDMLTLQ IIRIMENIWQ NQ....GLDL RMLPYGCLSI
P11b_Human ...VIFKNGD DLRQDMLTLQ MLRLMDLLWK EA....GLDL RMLPYGCLAT

51                                     100
Tor1_Yeast SPKSGLLGWV PNSDTFHVLI REHRDAKKIP LNIEHWVWLQ MAPDYENLTL
Tor2_Yeast SPKSGLLGWV PNSDTFHVLI REHREAKKIP LNIEHWVWLQ MAPDYDNLTL
Frap_Human STNSGLIGWV PHCDTLHALI RDYREKKKIL LNIEHRIMLR MAPDYDHLTL
Esr1_Yeast REDCGILEMV PNVTTLRSIL STKYESLKIK Y....SLKS LHDRWQHTAV
Tel1_Yeast GPKAGIIEFV ANSTSLHQIL SKLHTNDKIT FDQARKGMKA VQTKSN....
Pi4k_Human APGCGVIECI PDCTS..... RDQLGRQTFD GMYDYFTRQY
Stt4_Yeast APGCGVIDVL PNSVS..... RDMLGREAVN GLYEYFTSKF
Pik1_Yeast SANTGLVETI TNAMSVHSIK KALTKKMIED AELDDKGGIA SLNDHFLRAF
P3k1_Soybn GQDEGMLEFI P.SRSLAQI. .... LSENRSII SYLQ.....
P3k2_Soybn GQDEGMLEFI P.SRSLAQI. .... LSENRSII SYLQ.....
Pi3k_Arath GHDEGMLEFI P.SRSLAQI. .... LSEHRSIT SYLQ.....
Vp34_Yeast GPQEGAIEFI P.NDTLASI. .... LSKYHGIL GYLK.....
P11a_Human GDCVGLIEV RNSHTIMQI. .... Q.CKGGLK GALQFNSHTL
P11b_Human GDRSGLIEV STSETIADI. .... QLNSSNVA AAAAFNKDAL
```

## FASTA

Sequence in fasta format begins with a single-line description (distinguished by a greater-than (>) symbol), followed by sequence data on the next line.

```
fastaf <- system.file("sequences/Anouk.fasta", package = "seqinr")
cat(readLines(fastaf), sep = "\n")
```

```

>LmjF01.0030
ATGATGTGCGGCCGAGCCGCGTCTGTCGAGCCGTACATCAGCGACGTGCTGCGGCGGTAC
CAGCTGGAGCGCTTTTCAGTGTGCTTTGTCATCGAGCATGACCATCAAGGACCTCCTCGCC
CTGCAGCCAGAGGACTTCAACCGCTACGGCGTCTAGAGGCGATGGACATTTTGGGGCTG
CGTGACGCCATCGAGTACATCAAGGCTAATCCGCTCCCGGCTCGCGCTCTGGCAGTGAAC
GTGCTCGACAACGAGCGGACGCGGACGAGTACGAGTACGCGCGGAGGGGAAGGAGGGG
TGCTCGAGCGGAGCGCGGCGGAGTACACAGCAGCGGAACACAGTCTTTGCGGGTGC
ACCGACACCGCGGAGGAGGTGAAGCGCAAGAGCGCATCCTCGTGGCATTGCGAAGCGT
CCGCTCAGCGCGGGGAGCAGACGAACGGCTTCACGGACATCATGGACGCGGACAAACAGC
GGCGAGATTGTGCTGAAGGAGCCAAAGGTGAAGTTCGACCTCCGCAAGTACACCCACGTG
CACCGCTTCTTCTTCGACGAGGTTTTCGACGAGGCTGCGACAACGTGACGTGTACAAC
CGCGCTCCCGCGCGCTGATCGACACCGTCTTCGACGCGGCTGCGGACATGCTTCGCC
TATGGACAGACAGGGAGCGGCAAGACACACAGTGTGGGCAAGGGCCCGAGCGGGC
CTCTACGCACTCGCGCGCAAGACATGTTTGACCGCTCAGGAGGACACGCGCATCGTC
GTTTCTCTTTACGAGTCTACAGCGGGAAGCTCTTTGACTTGCTGAACGGCGCGGACCC
CTCGGAGCCTCGAGGACGACAAGGGCGGGTGAACATCCGCGGCTCACCGAACACTGC
TCTACAGCGTGGAGGACCTCATGACGATCATCGACAGGCGAGCGGTGTTGCGAGCTGC
GGCTCCACCGCGCGCAATGACACAAGCTCCCGCTCCACGCCATTCTCGAGATCAAGCTC
AAGCGCAACGAGGAGCTGAAGCAGAGCGGCAAGTTACGTTTCATCGACCTCGTGGAAGC
GAGCGCGCGGCTGACACGGTGGACTGCGCGGACAGACACGCGCTCGAAGGGCGGAGATC
AACAGGAGCCTACTCGCGCTGAAGGAGTGCATTGTTTTAGATCAGAACAGGAAGCAC
GTCCGTTCCGCGGCTCGAAGCTGACTGAGGTGCTCCGCGACTCGTTTATCGGCAACTGC
CGCACGCTGATGATCGCGCGCTCTCTCCGTCGAACAACAATGCCGAGCACAGCTGAAC
ACGCTCGGCTACGCGGATCGTGTCAAGGAGCTGAAGCGCAACGCCACGGAGCGGCGACT
GTGTGATGCCCCAGCAGGAGGAAGGCGCTTCTTGACAGCAGCGAGAGCAGGCCACCG
TGCGGAGGAGCACAACCTCGCTTCTACGCGCGCGGCTTTTCTCGGCTCTTCGAGC
GTCGCGGACGACTTAGAAGCAGCTACTCAGCAGCGGCTCCGTCACACACTCTCGCGG
TCGTGCGAGCGCAAGTCACTCTCGTCAACCGAAGCGCGCTGCGGCTCGGACTCGG
GACATGTTGTGACTAAGCGGCGCGGACTCAGACAGAAGCGGCGAGGACGAAGTGGTA
CGCGCGCGAGTGGGCGCCCAAGCTTCAAGCGCTTCGAGAGCGGCGCGAGCTTGTGCGG
GCCAGCGAGTCTCGCTCATTTGACCAATACAACGCTACCTCGAGACGACATGAACGTG
ATCAAGGAGGAGTACAGGTGAAGTACGACGAGAGCAGATGAACGCCAACACGCGCAGC
TTTGTGAGGCGGCGACGCTCTGCTGGTGAGCGAGAAGCGGCGCGGATGGAGTCTTCTTA
ACGCGAGCTGGAGGAGCTCGACAAGATCGCGCAGCAGGTGCGCGACATCACCGCTTTCAG
CAGCAGCTGCGCGCAACG
>LinJ01.0030
ATGATGTGCGGCCGAGCCGCGTCTGTCGAGCCGTACATCAGCGACGTGCTGCGGCGGTAC
CAGCTGGAGCGCTTTTCAGAGTTCTTTGTCATCGAGCATGACCATCAAGGACCTCCTCGCC
CTGCAGCCGAGGACTTCAACCGCTACGGCGTCTAGAGGCAATGGACATTTTGGGGCTG
CGCGACGCCATCGAGTACATCAAGGCAACCGGCTCCCGGCTCGCGCTCGGCGAGTGAAC
GTGCTCGACAACGAGCGGACGCGGACGCGGACGACAGTACGCGGAGGGGAAGGAGGGG
TGCTCGAGCGAGCGCGGACGCGAGTACACAGCAGCGGGAACACCGTCTTTGCGGGTGC
ACCGACACCGCGGAGGAGGTGAAGCGCAAGAGCGCATCATCGTGGCATTGCGAAGCGT
CCGCTCAGCGCGGGGAGCAGACGAACGGCTTCACGGACATCATGGACGCGGACAAAC
GGCGAGATTGTGCTGAAGGAGCCAAAGGTGAAGTTCGACCTCCGCAAGTACACCCACGTG
CACCGCTTCTTCTTCGACGAGGTTTTCGACGAGGCGTGCAGACAACGTGACGTGTACAAC
CGCGCTGCCCGCGCGTGTGTCGACACCGTCTTCGACGCGGCTGCGGACATGCTTCGCC
TATGGGCGTACAGGGAGCGGCAAGACACACAGTGTCTCGGCAAGGGCCCGAGCGGGC
CTGTACGCACTCGCGCGCAAGACATGTTTGACCGCTCAGGAGGACACGCGCATCGTT
GTTTCTCTTTACGAGTCTACAGCGGGAAGCTCTTTGACTTGCTGAACGGCGCGGACCA
CTGCGAGCCCTCGAGGACGACAAGGGGAGGTGAACATCCGCGGCTCACCGAACACTGC
TCTACAGCGTGGAGGACCTCATGACGATCATCGACAGGCGAGCGGCTTGCAGCTGC
GGCTCCACCGCGGCAACGACACGAGTCTCCGCTCCACGCCATTCTCGAGATCAAGCTC
AAGGCGAAACGGAGCTCGAAGCAGAGCGGCAAGTTACATTTCATCGACCTCGTGGAGC
GAGCGCGGCGCGGACGCGTGGATTGCGCGGACAGACACGCTCGAAGGGCGGAGATT
AACAGAGCCTACTCGCTCTGAAGGAGTGCATTGTTTTAGATCAGAACAGGAAGCAC
GTCCCGTTCCGCGGCTCGAAGCTGACTGAGGTGCTCCGCGACTCGTTTATCGGCAACTGC
CGCACGCTGATGATCGGCGCGTCTCTCCGTCACAACAATGCCGAGCACACGCTGAAC
ACGTTGCGCTACGCGGATCGGCTCAAGGAGTGAAGCGCAACGCCACGGAGCGGCGCAC
GTGTGCTGTGCCAAGCAGGAGGAGGCTTCTTTGACAGCGGAGGACAGGCGACCG
GCCAGCGCAGTCTGTCATTGACCAATACAACGCTACCTCGAGACGACATGAACGTG
ATCAAGGAGGAGTACAGGTGAAGTACGACGAGAGCAGATGAACGCCAACACGCGCAGC
TTTGTGAGGCGGCGACGCTGCTGGTGAGCGAGAAGCGGCGCGGATGGAGTCTTCTTA
ACGCGAGCTGGAGGAGCTCGACAAGATCGCGCAGCAGGTGCGCGACATCACCGCTTTCAG
CAGCAGCTGCGCGCAACG

```

### 2.2.2 The function `read.alignment()`

Aligned sequence data are very important in evolutionary studies, in this representation all vertically aligned positions are supposed to be homologous, that is sharing a common ancestor. This is a mandatory starting point for comparative studies. There is a function in **seqinR** called `read.alignment()` to read

aligned sequences data from various formats (`mase`, `clustal`, `phylip`, `fasta` or `msf`) produced by common external programs for multiple sequence alignment.

```
example(read.alignment)

rd.lgn> mase <- read.alignment(File = system.file("sequences/test.mase",
  package = "seqinr"), format = "mase")

rd.lgn> clustal <- read.alignment(File = system.file("sequences/test.aln",
  package = "seqinr"), format = "clustal")

rd.lgn> phylip <- read.alignment(File = system.file("sequences/test.phylip",
  package = "seqinr"), format = "phylip")

rd.lgn> msf <- read.alignment(File = system.file("sequences/test.msf",
  package = "seqinr"), format = "msf")

rd.lgn> fasta <- read.alignment(File = system.file("sequences/Anouk.fasta",
  package = "seqinr"), format = "fasta")
```

### 2.2.3 A simple example with the louse-gopher data


Let's give an example. The gene coding for the mitochondrial cytochrome oxidase I is essential and therefore often used in phylogenetic studies because of its ubiquitous nature. The following two sample tests of aligned sequences of this gene (extracted from ParaFit [30]), are distributed along with the `seqinR` package:

```
louse <- read.alignment(system.file("sequences/louse.fasta",
  package = "seqinr"), format = "fasta")
louse$nam

[1] "gi|548117|gb|L32667.1|GYDCYTOXIB" "gi|548119|gb|L32668.1|GYDCYTOXIC"
[3] "gi|548121|gb|L32669.1|GYDCYTOXID" "gi|548125|gb|L32671.1|GYDCYTOXIF"
[5] "gi|548127|gb|L32672.1|GYDCYTOXIG" "gi|548131|gb|L32675.1|GYDCYTOXII"
[7] "gi|548133|gb|L32676.1|GYDCYTOXIJ" "gi|548137|gb|L32678.1|GYDCYTOXIL"

gopher <- read.alignment(system.file("sequences/gopher.fasta",
  package = "seqinr"), format = "fasta")
gopher$nam

[1] "gi|548223|gb|L32683.1|PPGCYTOXIA" "gi|548197|gb|L32686.1|OGOCYTOXIA"
[3] "gi|548199|gb|L32687.1|OGOCYTOXIB" "gi|548201|gb|L32691.1|OGOCYTOXIC"
[5] "gi|548203|gb|L32692.1|OGOCYTOXID" "gi|548229|gb|L32693.1|PPGCYTOXID"
[7] "gi|548231|gb|L32694.1|PPGCYTOXIE" "gi|548205|gb|L32696.1|OGOCYTOXIE"
```

The aligned sequences are now imported in your  environment. The 8 genes of the first sample are from various species of louse (insects parasitics on warm-blooded animals) and the 8 genes of the second sample are from their corresponding gopher hosts (a subset of rodents), see figure 2.2 :

```
l.names <- readLines(system.file("sequences/louse.names",
  package = "seqinr"))
l.names

[1] "G.chapini " "G.cherriei " "G.costaric " "G.ewingi " "G.geomydis "
[6] "G.oklahome " "G.panamens " "G.setzeri "
```



Figure 2.2: Louse (left) and gopher (right). Images are from the wikipedia (<http://www.wikipedia.org/>). The picture of the chewing louse *Damalinia limbata* found on Angora goats was taken by Fiorella Carnevali (ENEA, Italy). The gopher drawing is from Gustav Mützel, Brehms Tierleben, Small Edition 1927.

```
g.names <- readLines(system.file("sequences/gopher.names",
                                package = "seqinr"))
g.names
```

```
[1] "G.brevicep " "O.cavator " "O.cherriei " "O.underwoo " "O.hispidus "
[6] "G.burs1 " "G.burs2 " "O.heterodu"
```

**SeqinR** has very few methods devoted to phylogenetic analyses but many are available in the **ape** package. This allows for a very fine tuning of the graphical outputs of the analyses thanks to the power of the R facilities. For instance, a natural question here would be to compare the topology of the tree of the hosts and their parasites to see if we have congruence between host and parasite evolution. In other words, we want to display two phylogenetic trees face to face. This would be tedious with a program devoted to the display of a single phylogenetic tree at time, involving a lot of manual copy/paste operations, hard to reproduce, and then boring to maintain with data updates.

How does it looks under R? First, we need to *infer* the tree topologies from data. Let's try as an *illustration* the famous neighbor-joining tree estimation of Saitou and Nei [49] with Jukes and Cantor's correction [24] for multiple substitutions.


```
library(ape)
louse.JC <- dist.dna(x = lapply(louse$seq, s2c), model = "JC69")
gopher.JC <- dist.dna(x = lapply(gopher$seq, s2c), model = "JC69")
l <- nj(louse.JC)
g <- nj(gopher.JC)
```

Now we have an estimation for *illustrative* purposes of the tree topology for the parasite and their hosts. We want to plot the two trees face to face, and for this we must change R graphical parameters. The first thing to do is to save the current graphical parameter settings so as to be able to restore them later:

```
op <- par(no.readonly = TRUE)
```

The meaning of the `no.readonly = TRUE` option here is that graphical parameters are not all settable, we just want to save those we can change at will. Now, we can play with graphics :

```
g$tip.label <- paste(1:8, g.names)
l$tip.label <- paste(1:8, l.names)
layout(matrix(data = 1:2, nrow = 1, ncol = 2), width = c(1.4,
1))
par(mar = c(2, 1, 2, 1))
plot(g, adj = 0.8, cex = 1.4, use.edge.length = FALSE, main = "gopher (host)",
cex.main = 2)
plot(l, direction = "l", use.edge.length = FALSE, cex = 1.4,
main = "louse (parasite)", cex.main = 2)
```




We now restore the old graphical settings that were previously saved:


```
par(op)
```


OK, this may look a little bit obscure if you are not fluent in programming, but please try the following experiment. In your current working directory, that is in the directory given by the `getwd()` command, create a text file called `essai.r` with your favourite text editor, and copy/paste the previous R commands, that is :


```
louse <- read.alignment(system.file("sequences/louse.fasta", package = "seqinr"), format = "fasta")
gopher <- read.alignment(system.file("sequences/gopher.fasta", package = "seqinr"), format = "fasta")
l.names <- readLines("http://pbil.univ-lyon1.fr/software/SeqinR/Datasets/louse.names")
g.names <- readLines("http://pbil.univ-lyon1.fr/software/SeqinR/Datasets/gopher.names")
louse.JC <- dist.dna(x = laply(louse$seq, s2c), model = "JC69")
gopher.JC <- dist.dna(x = laply(gopher$seq, s2c), model = "JC69")
l <- nj(louse.JC)
g <- nj(gopher.JC)
g$tip.label <- paste(1:8, g.names)
l$tip.label <- paste(1:8, l.names)
layout(matrix(data = 1:2, nrow = 1, ncol = 2), width=c(1.4, 1))
par(mar=c(2,1,2,1))
plot(g, adj = 0.8, cex = 1.4, use.edge.length=FALSE,
main = "gopher (host)", cex.main = 2)
plot(l,direction="l", use.edge.length=FALSE, cex = 1.4,
main = "louse (parasite)", cex.main = 2)
```

Make sure that your text has been saved and then go back to  console to enter the command :

```
source("essai.r")
```

This should reproduce the previous face-to-face phylogenetic trees in your  graphical device. Now, your boss is unhappy with working with the Jukes and


Cantor's model [24] and wants you to use the Kimura's 2-parameters distance [28] instead. Go back to the text editor to change `model = "JC69"` by `model = "K80"`, save the file, and in the  console `source("essai.r")` again, you should obtain the following graph :




Nice congruence, isn't it? Now, something even worse, there was a error in the aligned sequence set : the first base in the first sequence in the file `louse.fasta` is not a C but a T. To locate the file on your system, enter the following command:

```
system.file("sequences/louse.fasta", package = "seqinr")
```

```
[1] "../../../seqinr.Rcheck/seqinr/sequences/louse.fasta"
```

Open the `louse.fasta` file in your text editor, fix the error, go back to the  console to `source("essai.r")` again. That's all, your graph is now consistent with the updated dataset.

## 2.3 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), `powerpc-apple-darwin8.6.0`
- Base packages: `base`, `datasets`, `grDevices`, `graphics`, `methods`, `stats`, `utils`
- Other packages: `MASS` 7.2-27.1, `ade4` 1.4-1, `ape` 1.8-2, `gee` 4.13-10, `lattice` 0.13-8, `nlme` 3.1-73, `seqinr` 1.0-6, `xtable` 1.3-0

---

---

## CHAPTER 3

---


# Importing sequences from ACNUC databases

Charif, D. Lobry, J.R.

### Contents

3.1	Choose a bank . . . . .	35
3.2	Make your query . . . . .	38
3.3	Extract sequences of interest . . . . .	42
3.4	Session Informations . . . . .	44

### Introduction

As a rule of thumb, after compression one nucleotide needs one octet of disk space storage (because you need also the annotations corresponding to the sequences), so that most likely you won't have enough space on your computer to work with a local copy of a complete DNA database. The idea is to import under  only the subset of sequences you are interested in. This is done in three steps detailed thereafter.

### 3.1 Choose a bank

Select the database from which you want to extract sequences with the `choosebank()` function. This function initiates a remote access to an ACNUC database. Called without arguments, `choosebank()` returns the list of available databases:

```
choosebank()
```

```
[1] "genbank"      "embl"         "emblwgs"      "swissprot"
[5] "ensemblold"  "ensembl"      "emglib"       "nrsub"
```

```
[9] "nbrf"          "hobacnucl"  "hobacprot"  "hovernucl"
[13] "hoverprot"      "hogennucl"  "hogenprot"  "hoverclnu"
[17] "hoverclpr"      "homolensprot" "homolensnucl" "HAMAPnucl"
[21] "HAMAPprot"      "hoppsigen"  "nurebnucl"  "nurebprot"
[25] "taxobacgen"     "greview"    "hogendnucl"  "hogendprot"
[29] "refseq"
```

Biological sequence databases are fast moving targets, and for publication purposes it is recommended to specify on which release you were working on when you made the job. To get more informations about available databases on the server, just set the `infobank` parameter to `TRUE`. For instance, here is the result for the three first databases on the default server at the compilation time (September 1, 2006) of this document:

```
choosebank(infobank = TRUE)[1:3, ]
```

```
      bank status
1 genbank      on
2  embl       on
3 emblwgs      on
      info
1 GenBank Rel. 155 (15 August 2006) Last Updated: Sep  1, 2006
2      EMBL Library Release 87 (June 2006)
3  EMBL Whole Genome Shotgun sequences Release 87 (June 2006)
```

Note that there is a `status` column because a database could be unavailable for a while during updates. If you try call `choosebank(bank = "bankname")` when the bank called `bankname` is off from server, you will get an explicit error message stating that this bank is temporarily unavailable, for instance:

```
choosebank("off")
```

```
Error in choosebank("off") : Database with name -->off<-- is currently off for maintenance,
please try again later.
```

Some special purpose databases are not listed by default. These are *tagged* databases that are only listed if you provide an explicit `tagbank` argument to the `choosebank()` function. Of special interest for teaching purposes is the TP tag, an acronym for *Travaux Pratiques* which means "practicals", and corresponds to *frozen* databases so that you can set up a practical whose results are stable from year to year. Currently available frozen databases at the default server are:

```
choosebank(tagbank = "TP", infobank = TRUE)
```

```
      bank status
1  emblTP      on
2 swissprotTP  on
3 hoverprotTP  on
4 hovernuclTP  on
5  trypano     on
      info
1      EMBL Library Release 78 WITHOUT ESTs (March 2004)
2 UniProt Rel. 1 (SWISS-PROT 43 + TrEMBL 26 + NEW): Last Updated: May  3, 2004
3      HOVERGEN - Release 45 (Jan 22 2004) Last Updated: Jan 22, 2004
4      HOVERGEN - Release 45 (Jan 22 2004) Last Updated: Jan 22, 2004
5      trypano Rel. 1 (27 Janvier 2004) Last Updated: Jan 27, 2004
```

Now, if you want to work with a given database, say GenBank, just call `choosebank()` with `"genbank"` as its first argument and store the result in a variable in the workspace, called for instance `mybank` in the example thereafter:



```
mybank <- choosebank("genbank")
str(mybank)
```

```
List of 8
 $ socket :Classes 'sockconn', 'connection' int 8
 $ bankname: chr "genbank"
 $ totseqs : chr "64946744"
 $ totspscs: chr "393311"
 $ totkeys : chr "2109217"
 $ release : chr "GenBank Rel. 155 (15 August 2006) Last Updated: Sep 1, 2006"
 $ status :Class 'AsIs' chr "on"
 $ details : chr [1:3] "GenBank Rel. 155 (15 August 2006) Last Updated: Sep 1, 2006" "66,009,892,298 bases; 61,704,1
```

The list returned by `choosebank()` here means that in the database called `genbank` at the compilation time of this document there were 64,946,744 sequences from 393,311 species and a total of 2,109,217 keywords. The status of the bank was `on`, and the release information was `GenBank Rel. 155 (15 August 2006) Last Updated: Sep 1, 2006`. For specialized databases, some relevant informations are also given in the `details` component, for instance:

```
choosebank("taxobacgen")$details

[1] "TaxoBacGen Rel. 7 (September 2005)"
[2] "1,151,149,763 bases; 254,335 sequences; 847,767 subseqs; 63,879 refers."
[3] "Data compiled from GenBank by Gregory Devulder"
[4] "Laboratoire de Biometrie & Biologie Evolutive, Univ Lyon I"
[5] "-----"
[6] "This database is a taxonomic genomic database."
[7] "It results from an expertise crossing the data nomenclature database DSMZ"
[8] "[http://www.dsmz.de/species/bacteria.htm Deutsche Sammlung von"
[9] "Mikroorganismen und Zellkulturen GmbH, Braunschweig, Germany]"
[10] "and GenBank."
[11] "- Only contains sequences described under species present in"
[12] "Bacterial Nomenclature Up-to-date."
[13] "- Names of species and genus validly published according to the"
[14] "Bacteriological Code (names with standing in nomenclature) is"
[15] "added in field \"DEFINITION\"."
[16] "- A keyword \"type strain\" is added in field \"FEATURES/source/strain\" in"
[17] "GenBank format definition to easily identify Type Strain."
[18] "Taxobacgen is a genomic database designed for studies based on a strict"
[19] "respect of up-to-date nomenclature and taxonomy."
```


The previous command has a side-effect that is worth mentioning. As from `seqinR` 1.0-3, the result of the `choosebank()` function is automatically stored in a global variable named `banknameSocket`, so that if no socket argument is given to the `query()` function, the last opened database will be used by default for your requests. This is just a matter of convenience so that you don't have to explicitly specify the details of the socket connection when working with the last opened database. You have, however, full control of the process since `choosebank()` returns (invisibly) all the required details. There is no trouble to open *simultaneously* many databases. You are just limited by the number of simultaneous connections your build of R is allowed<sup>1</sup>.

For advanced users who may wish to access to more than one database at time, a good advice is to close them with the function `closebank()` as soon as possible so that the maximum number of simultaneous connections is never reached. In the example below, we want to display the number of taxa (*i.e.*

<sup>1</sup> There is a very convenient function called `closeAllConnections()` in the R base package if you want to close all open connections at once.

the number of nodes) in the species taxonomy associated with each available database (including frozen databases). For this, we loop over available databases and close them as soon as the information has been retrieved.

```
banks <- c(choosebank(), choosebank(tagbank = "TP"))
ntaxa <- numeric(0)
for (i in banks) {
  ntaxa[i] <- as.numeric(choosebank(i)$totspecs)
  closebank()
}
dotchart(log10(ntaxa[order(ntaxa)]), pch = 19, main = "Number of taxa in available databases",
  xlab = "Log10(number of taxa)")
```



## 3.2 Make your query

For this section, set up the default bank to GenBank, so that you don't have to provide the sockets details for the `query()` function:

```
choosebank("genbank")
```

Then, you have to say what you want, that is to compose a query to select the subset of sequences you are interested in. The way to do this is documented under `?query`, we just give here a simple example. In the query below, we want to select all the coding sequences (`t=cds`) from cat (`sp=felis catus`) that are not (`et no`) partial sequences (`k=partial`). We want the result to be stored in an object called `completeCatsCDS`.

```
query("completeCatsCDS", "sp=felis catus et t=cds et no k=partial")
```

Now, there is in the workspace an object called `completeCatsCDS`, which does not contain the sequences themselves but the *sequence names* (and various relevant informations such as the genetic code and the frame) that fit the query. They are stored in the `req` component of the object, let's see the name of the first ten of them:

```
sapply(completeCatsCDS$req[1:10], getName)
```

```
[1] "AB000483.PE1" "AB000484.PE1" "AB000485.PE1" "AB004237"
[5] "AB004238" "AB009279.PE1" "AB009280.PE1" "AB010872.UGT1A1"
[9] "AB011965.SDF-1A" "AB011966.SDF-1B"
```

The first sequence that fit our request is `AB000483.PE1`, the second one is `AB000484.PE1`, and so on. Note that the sequence name may have an extension, this corresponds to *subsequences*, a specificity of the ACNUC system that allows to handle easily a subsequence with a biological meaning, typically a gene. The list of available subsequences in a given database is given by the function `getType()`, for example the list of available subsequences in GenBank is given in table 3.1.



	Type	Description
1	CDS	.PE protein coding region
2	LOCUS	sequenced DNA fragment
3	MISC_RNA	.RN other structural RNA coding region
4	RRNA	.RR mature ribosomal RNA
5	SCRNA	.SC small cytoplasmic RNA
6	SNRNA	.SN small nuclear RNA
7	TRNA	.TR mature transfer RNA

Table 3.1: Available subsequences in genbank

The component `call` of `completeCatsCDS` keeps automatically a trace of the way you have selected the sequences:

```
completeCatsCDS$call
```

```
query(listname = "completeCatsCDS", query = "sp=felis catus et t=cds et no k=partial")
```

At this stage you can quit your  session saving the workspace image. The next time an  session is opened with the workspace image restored, there will be an object called `completeCatsCDS`, and looking into its `call` component will tell you that it contains the names of complete coding sequences from *Felis catus*.

In practice, queries for sequences are rarely done in one step and are more likely to be the result of an iterative, progressively refining, process. An important point is that a list of sequences can be re-used. For instance, we can re-use `completeCatsCDS` to get only the list of sequences that were published in 2004:

```
query("ccc2004", "completeCatsCDS et y=2004")
length(ccc2004$req)
```

```
[1] 57
```

Hence, there were 57 complete coding sequences published in 2004 for *Felis catus* in GenBank.

As from release 1.0-3 of the **seqinR** package, there is new parameter **virtual** which allows to disable the automatic retrieval of information for all list elements. This is interesting for list with many elements, for instance :

```
query("allcds", "t=cds", virtual = TRUE)
allcds$nelem
```

```
[1] 3494449
```

There are therefore 3,494,449 coding sequences in this version of GenBank<sup>2</sup>. It would be long to get all the informations for the elements of this list, so we have set the parameter **virtual** to **TRUE** and the **req** component of the list has not been documented:

```
allcds$req
```

```
[[1]]
[1] NA
```

However, the list can still be re-used<sup>3</sup>, for instance we may extract from this list all the sequences from, say, *Mycoplasma genitalium*:

```
query("small", "allcds et sp=mycoplasma genitalium", virtual = TRUE)
small$nelem
```

```
[1] 916
```

There are then 916 elements in the list **small**, so that we can safely repeat the previous query without asking for a virtual list:

```
query("small", "allcds et sp=mycoplasma genitalium")
sapply(small$req, getName)[1:10]
```

```
[1] "AY191424" "AY386807" "AY386808" "AY386809" "AY386810" "AY386811"
[7] "AY386812" "AY386813" "AY386814" "AY386815"
```

Here are some illustrations of using virtual list to answer simple questions about the current GenBank release.

**Man.** How many sequences are available for our species?

```
query("man", "sp=homo sapiens", virtual = T)
man$nelem
```

```
[1] 10649443
```

There are 10,649,443 sequences from *Homo sapiens*.

**Sex.** How many sequences are annotated with a keyword starting by sex?

<sup>2</sup> which is stored in the **release** component of the object **banknameSocket** and current value is today (September 1, 2006): **banknameSocket\$release = GenBank Rel. 155 (15 August 2006) Last Updated: Sep 1, 2006.**

<sup>3</sup> of course, as long as the socket connection with the server has not been lost: virtual lists details are only known by the server.

```
query("sex", "k=sex@", virtual = T)
sex$nelem
```

```
[1] 1080
```

There are 1,080 such sequences.

**tRNA.** How many complete tRNA sequences are available?

```
query("trna", "t=trna et no k=partial", virtual = T)
trna$nelem
```

```
[1] 179713
```

There are 179,713 complete tRNA sequences.

**Nature vs. Science.** In which journal were the more sequences published?

```
query("nature", "j=nature", virtual = T)
nature$nelem
```

```
[1] 1157543
```

```
query("science", "j=science", virtual = T)
science$nelem
```

```
[1] 1275773
```

There are 1,157,543 sequences published in *Nature* and 1,275,773 sequences published in *Science*, so that the winner is *Science*.

**Smith.** How many sequences have Smith (last name) as author?

```
query("smith", "au=smith", virtual = T)
smith$nelem
```

```
[1] 1393252
```

There are 1,393,252 such sequences.

**YK2.** How many sequences were published after year 2000 (included)?

```
query("yk2", "y>2000", virtual = T)
yk2$nelem
```

```
[1] 50248132
```

There are 50,248,132 sequences published after year 2000.

**Organelle contest.** Do we have more sequences from chloroplast genomes or from mitochondrion genomes?

```
query("chloro", "o=chloroplast", virtual = T)
chloro$nelem
```

```
[1] 117315
```

```
query("mito", "o=mitochondrion", virtual = T)
mito$nelem
```

```
[1] 390956
```

There are 117,315 sequences from chloroplast genomes and 390,956 sequences from mitochondrion genomes, so that the winner is mitochondrion.

### 3.3 Extract sequences of interest

The sequence itself is obtained with the function `getSequence()`. For example, the first 50 nucleotides of the first sequence of our request are:

```
myseq <- getSequence(completeCatsCDS$req[[1]])
myseq[1:50]

[1] "a" "t" "g" "a" "a" "t" "c" "a" "a" "g" "g" "a" "g" "c" "c" "g" "t" "t"
[19] "t" "t" "t" "a" "g" "g" "c" "a" "c" "c" "t" "g" "c" "t" "c" "c" "t" "g"
[37] "g" "t" "g" "c" "t" "g" "c" "a" "g" "c" "t" "g" "g" "t" "t"
```

They can also be coerced as string of character with the function `c2s()`:

```
c2s(myseq[1:50])

[1] "atgaatcaaggagccgttttttaggcacctgctcctggtgctgcagctggt"
```

Note that what is done by `getSequence()` is much more complex than a substring extraction because subsequences of biological interest are not necessarily contiguous or even on the same DNA strand. Consider for instance the following coding sequence from sequence AE003734:

```
AE003734.PE35      Location/Qualifiers      (length=1833 bp)
      CDS            join(complement(162997..163210),
                        complement(162780..162919),complement(161238..162090),
                        146568..146732,146806..147266)
                        /gene="mod(mdg4)"
                        /locus_tag="CG32491"
                        /note="CG32491 gene product from transcript CG32491-RT;
                        trans-splicing"
```

To get the coding sequence manually you would have join 5 different pieces from AE003734 and some of them are in the complementary strand. With `getSequence()` you don't have to think about this. Just make a query with the sequence name:

```
query("transspliced", "N=AE003734.PE35")
length(transspliced$req)
```

```
[1] 1
```

```
getName(transspliced$req[[1]])
```

```
[1] "AE003734.PE35"
```

Ok, now there is in your workspace an object called `transspliced` which `req` component is of length one (because you have asked for just one sequence) and the name of the single element of the `req` component is AE003734.PE35 (because this is the name of the sequence you wanted). Let see the first 50 base of this sequence:

```
getSequence(transspliced$req[[1]])[1:50]

[1] "a" "t" "g" "g" "c" "g" "g" "a" "c" "g" "a" "c" "g" "a" "g" "c" "a" "a"
[19] "t" "t" "c" "a" "g" "c" "t" "t" "g" "t" "g" "c" "t" "g" "g" "a" "a" "c"
[37] "a" "a" "c" "t" "t" "c" "a" "a" "c" "a" "c" "g" "a" "a"
```

All the complex transsplicing operations have been done here. You can check that there is no in-frame stop codons<sup>4</sup> with the `getTrans()` function to translate this coding sequence into protein:

```
getTrans(transspliced$req[[1]])[1:50]


[1] "M" "A" "D" "D" "E" "Q" "F" "S" "L" "C" "W" "N" "N" "F" "N" "T" "N" "L"
[19] "S" "A" "G" "F" "H" "E" "S" "L" "C" "R" "G" "D" "L" "V" "D" "V" "S" "L"
[37] "A" "A" "E" "G" "Q" "I" "V" "K" "A" "H" "R" "L" "V" "L"

table(getTrans(transspliced$req[[1]]))

*  A  C  D  E  F  G  H  I  K  L  M  N  P  Q  R  S  T  V  W  Y
1 55  9 38 50 22 28 11 20 40 36 10 21 35 57 22 54 50 38  1 13
```

In a more graphical way:

```
aaccount <- table(getTrans(transspliced$req[[1]]))
aaccount <- aaccount[order(aaccount)]
names(aaccount) <- aaa(names(aaccount))
dotchart(aaccount, pch = 19, xlab = "Stop and amino-acid counts",
         main = "There is only one stop codon in AE003734.PE35")
abline(v = 1, lty = 2)
```



Note that the relevant variant of the genetic code was automatically set up during the translation of the sequence into protein. This is because the `transspliced$req[[1]]` object belongs to the `SeqAcnucWeb` class:


```
class(transspliced$req[[1]])
```

<sup>4</sup> Stop codons are represented by the character \* when translated into protein.

[1] "SeqAcnucWeb"

Therefore, when you are using the `getTrans()` function, you are automatically redirected to the `getTrans.SeqAcnucWeb()` function which knows how to take into account the relevant frame and genetic code for your coding sequence.

### 3.4 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), `powerpc-apple-darwin8.6.0`
- Base packages: `base`, `datasets`, `grDevices`, `graphics`, `methods`, `stats`, `utils`
- Other packages: `MASS` 7.2-27.1, `ade4` 1.4-1, `ape` 1.8-2, `gee` 4.13-10, `lattice` 0.13-8, `nlme` 3.1-73, `seqinr` 1.0-6, `xtable` 1.3-0



---

---

# CHAPTER 4

---

## How to deal with sequences

Charif, D. Lobry, J.R.

### Contents

---

4.1	Sequence classes . . . . .	45
4.2	Generic methods for sequences . . . . .	45
4.3	Internal representation of sequences . . . . .	46
4.4	Session Informations . . . . .	50

---

### 4.1 Sequence classes

There are currently three classes of sequences, depending on the way they were obtained:


- **seqFasta** is the class for the sequences that were imported from a fasta file
- **seqAcnucWeb** is the class for the sequences coming from an ACNUC database server
- **seqFrag** is the class for the sequences that are fragments of other sequences

### 4.2 Generic methods for sequences


All sequence classes are sharing a common interface, so that there are very few method names we have to remember. In addition, all classes have their specific `as.ClassName` method that return an instance of the class, and `is.ClassName` method to check whether an object belongs or not to the class. Available methods are:

Methods	Result	Type of result
<b>getFrag</b>	a sequence fragment	a sequence fragment
<b>getSequence</b>	the sequence	vector of characters
<b>getName</b>	the name of a sequence	string
<b>getLength</b>	the length of a sequence	numeric vector
<b>getTrans</b>	translation into amino-acids	vector of characters
<b>getAnnot</b>	sequence annotations	vector of string
<b>getLocation</b>	position of a Sequence on its parent sequence	list of numeric vector

### 4.3 Internal representation of sequences

The current mode of sequence storage is done with vectors of characters instead of strings. This is very convenient for the user because all  tools to manipulate vectors are immediatly available. The price to pay is that this storage mode is extremly expensive in terms of memory. They are two utilities called `s2c()` and `c2s()` that allows to convert strings into vector of characters, and *vice versa*, respectively.

#### 4.3.1 Sequences as vectors of characters

In the vectorial representation mode, all the very convenient  tools for indexing vectors are at hand.

1. Vectors can be indexed by a vector of *positive* integers saying which elements are to be selected. As we have already seen, the first 50 elements of a sequence are easily extracted thanks to the binary operator `from:to`, as in:

```
dnafile <- system.file("sequences/malM.fasta", package = "seqinr")
myseq <- read.fasta(file = dnafile)[[1]]
1:50

[1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
[25] 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
[49] 49 50

myseq[1:50]

[1] "a" "t" "g" "a" "a" "a" "a" "t" "g" "a" "a" "t" "a" "a" "a" "g" "t"
[19] "c" "t" "c" "a" "t" "c" "g" "t" "c" "c" "t" "c" "t" "g" "t" "t" "t" "a"
[37] "t" "c" "a" "g" "c" "a" "g" "g" "t" "t" "a" "c" "t"
```

The `seq()` function allows to build more complexe integer vectors. For instance in coding sequences it is very common to focus on third codon positions where selection is weak. Let's extract bases from third codon positions:

```
tcp <- seq(from = 3, to = length(myseq), by = 3)
tcp[1:10]

[1] 3 6 9 12 15 18 21 24 27 30
```

```
myseqtcp <- myseq[tcp]
myseqtcp[1:10]
```

```
[1] "g" "a" "g" "t" "a" "t" "c" "c" "c" "c"
```

2. Vectors can also be indexed by a vector of *negative* integers saying which elements have to be removed. For instance, if we want to keep first and second codon positions, the easiest way is to remove third codon positions:

```
-tcp[1:10]
```

```
[1] -3 -6 -9 -12 -15 -18 -21 -24 -27 -30
```

```
myseqfscp <- myseq[-tcp]
myseqfscp[1:10]
```

```
[1] "a" "t" "a" "a" "a" "t" "a" "a" "a" "a"
```

3. Vectors are also indexable by a vector of *logicals* whose TRUE values say which elements to keep. Here is a different way to extract all third coding positions from our sequence. First, we define a vector of three logicals with only the last one true:

```
ind <- c(F, F, T)
ind
```

```
[1] FALSE FALSE TRUE
```

This vector seems too short for our purpose because our sequence is much more longer with its 921 bases. But under  $\mathbb{R}$  vectors are automatically *recycled* when they are not long enough:

```
(1:30)[ind]
```

```
[1] 3 6 9 12 15 18 21 24 27 30
```

```
myseqtcp2 <- myseq[ind]
```

The result should be the same as previously:

```
identical(myseqtcp, myseqtcp2)
```

```
[1] TRUE
```


This recycling rule is extremely convenient in practice but may have surprising effects if you assume (incorrectly) that there is a stringent dimension control for  $\mathbb{R}$  vectors as in linear algebra.

Another advantage of working with vector of characters is that most  $\mathbb{R}$  functions are vectorized so that many things can be done without explicit looping. Let's give some very simple examples:


```
tota <- sum(myseq == "a")
```

The total number of **a** in our sequence is 238. Let's compare graphically the different base counts in our sequence :


```
basecount <- table(myseq)
myseqname <- getName(myseq)
dotchart(basecount, xlim = c(0, max(basecount))), pch = 19,
  main = paste("Base count in", myseqname))
```




```
dinucldcount <- count(myseq, 2)
dotchart(dinucldcount[order(dinucldcount)], xlim = c(0, max(dinucldcount)),
  pch = 19, main = paste("Dinucleotide count in", myseqname))
```



```
codonusage <- uco(myseq)
dotchart.uco(codonusage, main = paste("Codon usage in", myseqname))
```



### 4.3.2 Sequences as strings

If you are interested in (fuzzy) pattern matching, then it is advisable to work with sequence as strings to take advantage of *regular expression* implemented in . The function `words.pos()` returns the positions of all occurrences of a given regular expression. Let's suppose we want to know where are the trinucleotides "cgt" in a sequence, that is the fragment CpGpT in the direct strand:

```
mystring <- c2s(myseq)
words.pos("cgt", mystring)
```

```
[1] 24 90 216 245 252 315 330 405 432 452 552 592 648 836 883
```

We can also look for the fragment CpGpTpY to illustrate fuzzy matching because Y (IUPAC code for pyrimidine) stands C or T:

```
words.pos("cgt[ct]", mystring)
```

```
[1] 24 216 252 315 432 452 552 592 836 883
```


To look for all CpC dinucleotides separated by 3 or 4 bases:

```
words.pos("cc.{3,4}cc", mystring)
```

```
[1] 72 119 176 177 539 577 578 638 677 682 730 731 736 881 882
```

Virtually any pattern is easily encoded with a regular expression. This is especially useful at the protein level because many functions can be attributed to short linear motifs.

## 4.4 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), powerpc-apple-darwin8.6.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: MASS 7.2-27.1, ade4 1.4-1, ape 1.8-2, gee 4.13-10, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0

---

---

# CHAPTER 5

---

## Multivariate analyses

Lobry, J.R.

### Contents

---

5.1	Correspondence analysis . . . . .	51
5.2	Synonymous and non-synonymous analyses . . . . .	60
5.3	Session Informations . . . . .	70

---

### 5.1 Correspondence analysis

This is the most popular multivariate data analysis technique for amino-acid and codon count tables, its application, however, is not without pitfalls [45]. Its primary goal is to transform a table of counts into a graphical display, in which each gene (or protein) and each codon (or amino-acid) is depicted as a point. Correspondence analysis (CA) may be defined as a special case of principal components analysis (PCA) with a different underlying metrics. The interest of the metrics in CA, that is the way we measure the distance between two individuals, is illustrated bellow with a very simple example (Table 5.1 inspired from [10]) with only three proteins having only three amino-acids, so that we can represent exactly on a map the consequences of the metric choice.

```
data(toyaa)
toyaa
```

```
Ala Val Cys
1 130 70 0
2 60 40 0
3 60 35 5
```

Let's first use the regular Euclidian metrics between two proteins  $i$  and  $i'$ ,

$$d^2(i, i') = \sum_{j=1}^J (n_{ij} - n_{i'j})^2 \quad (5.1)$$


51

	Ala	Val	Cys
1	130	70	0
2	60	40	0
3	60	35	5

Table 5.1: A very simple example of amino-acid counts in three proteins to be loaded with `data(toyaa)`.

to visualize this small data set:

```
library(ade4)
pco <- dudi.pco(dist(toyaa), scann = F, nf = 2)
myplot <- function(res, ...) {
  plot(res$li[, 1], res$li[, 2], ...)
  text(x = res$li[, 1], y = res$li[, 2], labels = 1:3, pos = ifelse(res$li[,
    2] < 0, 1, 3))
  perm <- c(3, 1, 2)
  lines(c(res$li[, 1], res$li[perm, 1]), c(res$li[, 2],
    res$li[perm, 2]))
}
myplot(pco, main = "Euclidian distance", asp = 1, pch = 19,
  xlab = "", ylab = "", las = 1)
```



From this point of view, the first individual is far away from the two others. But thinking about it, this is a rather trivial effect of protein size:

```
rowSums(toyaa)
```

```
  1  2  3
200 100 100
```



With 200 amino-acids, the first protein is two times bigger than the others so that when computing the Euclidian distance (5.1) its  $n_{ij}$  entries are on average bigger, sending it away from the others. To get rid of this trivial effect, the first obvious idea is to divide counts by protein lengths so as to work with *protein profiles*. The corresponding distance is,


$$d^2(i, i') = \sum_{j=1}^J \left( \frac{n_{ij}}{n_{i\bullet}} - \frac{n_{i'j}}{n_{i'\bullet}} \right)^2 \quad (5.2)$$

where  $n_{i\bullet}$  and  $n_{i'\bullet}$  are the total number of amino-acids in protein  $i$  and  $i'$ , respectively.

```
profile <- toyaa/rowSums(toyaa)
profile

  Ala  Val  Cys
1 0.65 0.35 0.00
2 0.60 0.40 0.00
3 0.60 0.35 0.05

pco1 <- dudi.pco(dist(profile), scann = F, nf = 2)
myplot(pco1, main = "Euclidian distance on protein profiles",
       asp = 1, pch = 19, xlab = "", ylab = "", ylim = range(pco1$li[,
       2]) * 1.2)
```




The pattern is now completely different with the three protein equally spaced. This is normal because in terms of relative amino-acid composition they are all differing two-by-two by 5% at the level of two amino-acids only. We have clearly removed the trivial protein size effect, but this is still not completely satisfactory. The proteins are differing by 5% for all amino-acids but the situation is

somewhat different for **Cys** because this amino-acid is very rare. A difference of 5% for a rare amino-acid has not the same significance than a difference of 5% for a common amino-acid such as **Ala** in our example. To cope with this, CA make use of a variance-standardizing technique to compensate for the larger variance in high frequencies and the smaller variance in low frequencies. This is achieved with the use of the *chi-square distance* ( $\chi^2$ ) which differs from the previous Euclidean distance on profiles (5.2) in that each square is weighted by the inverse of the frequency corresponding to each term,

$$d^2(i, i') = n_{\bullet\bullet} \sum_{j=1}^J \frac{1}{n_{\bullet j}} \left( \frac{n_{ij}}{n_{i\bullet}} - \frac{n_{i'j}}{n_{i'\bullet}} \right)^2 \quad (5.3)$$

where  $n_{\bullet j}$  is the total number of amino-acid of kind  $j$  and  $n_{\bullet\bullet}$  the total number of amino-acids. With this point of view, the map is now like this:

```
coa <- dudi.coa(toyaa, scann = FALSE, nf = 2)
myplot(coa, main = expression(paste(chi^2, " distance")),
       asp = 1, pch = 19, xlab = "", ylab = "")
```




The pattern is completely different with now protein number 3 which is far away from the others because it is enriched in the rare amino-acid **Cys** as compared to others.

The purpose of this small example was to demonstrate that the metric choice is not without dramatic effects on the visualisation of data. Depending on your objectives, you may agree or disagree with the  $\chi^2$  metric choice, that's not a problem, the important point is that you should be aware that there is an underlying model there, *chacun a son goût* ou *chacun à son goût*, it's up to you.

Now, if you agree with the  $\chi^2$  metric choice, there's a nice representation that may help you for the interpretation of results. This is a kind of "biplot" representation in which the lines and columns of the dataset are simultaneously represented, in the right way, that is as a graphical *translation* of a mathematical theorem, but let's see how does it look like in practice:


```
scatter(coa, clab.col = 0.8, clab.row = 0.8, posi = "none")
```



What is obvious is that the Cys content has a major effect on protein variability here, no scoop. Please note how the information is well summarised here: protein number 3 differs because it's enriched in Cys ; protein number 1 and 2 are almost the same but there is a small trend protein number 1 to be enriched in Ala. As compared to table 5.1 this graph is of poor information here, so let's try a more big-room-sized example (with 20 columns so as to illustrate the dimension reduction technique).


Data are from [35], a sample of the proteome of *Escherichia coli*. According to the title of this paper, the most important factor for the between-protein variability is hydrophilic - hydrophobic gradient. Let's try to reproduce this assertion :

```
download.file(url = "ftp://pbil.univ-lyon1.fr/pub/datasets/NAR94/data.txt",
  destfile = "data.txt")
ec <- read.table(file = "data.txt", header = TRUE, row.names = 1)
ec.coa <- dudi.coa(ec, scann = FALSE, nf = 1)
F1 <- ec.coa$li[, 1]
hist(F1, proba = TRUE, xlab = "First factor for amino-acid variability",
  col = grey(0.8), border = grey(0.5), las = 1, ylim = c(0,
  6), main = "Protein distribution on first factor")
lines(density(F1, adjust = 0.5), lwd = 2)
```



There is clearly a bimodal distribution of proteins on the first factor. What are the amino-acid coordinates on this factor?

```
aacoo <- ec.coa$co[, 1]
names(aacoo) <- rownames(ec.coa$co)
aacoo <- sort(aacoo)
dotchart(aacoo, pch = 19, xlab = "Coordinate on first factor",
  main = "Amino acid coordinates on first factor")
```



Aliphatic and aromatic amino-acids have positive values while charged amino-acids have negative values<sup>1</sup>. Let's try to compute the GRAVY score (*i.e.* the Kyte and Doolittle hydropathic index[29]) of our proteins to compare this with their coordinates on the first factor. We need first the amino-acid *relative* frequencies in the proteins, for this we divide the all the amino-acid counts by the total by row:

```
ecfr <- ec/rowSums(ec)
ecfr[1:5, 1:5]
```

	arg	leu	ser	thr	pro
FOLE	0.05829596	0.10313901	0.06278027	0.08520179	0.03587444
MSBA	0.06529210	0.10309278	0.08591065	0.06185567	0.02233677
NARV	0.06637168	0.12831858	0.06637168	0.05752212	0.03539823
NARW	0.05627706	0.16450216	0.05627706	0.03030303	0.04329004
NARY	0.06614786	0.06420233	0.05058366	0.03891051	0.06031128

We need also the coefficients corresponding to the GRAVY score:

```
gravy <- read.table(file = "ftp://pbil.univ-lyon1.fr/pub/datasets/NAR94/gravy.txt")
gravy[1:5, ]
```

	V1	V2
1 Ala	1.8	
2 Arg	-4.5	
3 Asn	-3.5	
4 Asp	-3.5	
5 Cys	2.5	

```
coef <- gravy$V2
```

The coefficient are given in the alphabetical order of the three letter code for the amino acids, that is in a different order than in the object `ecfr`:

```
names(ecfr)
```

```
[1] "arg" "leu" "ser" "thr" "pro" "ala" "gly" "val" "lys" "asn" "gln" "his"
[13] "glu" "asp" "tyr" "cys" "phe" "ile" "met" "trp"
```

We then re-order the columns of the data set and check that everthing is OK:

```
ecfr <- ecfr[, order(names(ecfr))]
ecfr[1:5, 1:5]
```

	ala	arg	asn	asp	cys
FOLE	0.08520179	0.05829596	0.04035874	0.05381166	0.008968610
MSBA	0.08247423	0.06529210	0.03608247	0.05154639	0.003436426
NARV	0.05309735	0.06637168	0.01769912	0.02212389	0.013274336
NARW	0.09090909	0.05627706	0.02597403	0.09090909	0.017316017
NARY	0.06225681	0.06614786	0.03891051	0.05642023	0.035019455

```
all(names(ecfr) == tolower(as.character(gravy$V1)))
```


```
[1] TRUE
```

---

<sup>1</sup>The physico-chemical classes for amino acids are given in the component `AA.PROPERTY` of the `SEQINR.UTIL` object.

Now, thanks to R build-in matrix multiplication, it's only one line to compute the GRAVY score:

```
gscores <- as.matrix(ecfr) %*% coef
plot(gscores, F1, xlab = "GRAVY Score", ylab = "F1 Score",
     las = 1, main = "The first factor is protein hydrophaty")
```



The proteins with high GRAVY scores are integral membrane proteins, and those with low scores are cytoplasmic proteins. Now, suppose that we want to adjust a mixture of two normal distributions to get an estimate of the proportion of cytoplasmic and integral membrane proteins. We first have a look on the predefined distributions (Table 5.2), but there is apparently not an out of the box solution. We then define our own probability density function and then use `fitdistr` from package `MASS` to get a maximum likelihood estimate of the parameters:


```
dmixnor <- function(x, p, m1, sd1, m2, sd2) {
  p * dnorm(x, m1, sd1) + (1 - p) * dnorm(x, m2, sd2)
}
library(MASS)
e <- fitdistr(F1, dmixnor, list(p = 0.88, m1 = -0.04, sd1 = 0.076,
  m2 = 0.34, sd2 = 0.07))$estimate
e
```

```
      p      m1      sd1      m2      sd2
0.88405009 -0.03989489 0.07632235 0.33579162 0.06632259
```

```
hist(F1, proba = TRUE, col = grey(0.8), main = "Ajustement with a mixture of two normal distributions",
     xlab = "First factor for amino-acid variability", las = 1)
xx <- seq(from = min(F1), to = max(F1), length = 200)
lines(xx, dmixnor(xx, e[1], e[2], e[3], e[4], e[5]), lwd = 2)
```

	d	p	q	r
beta	dbeta	pbeta	qbeta	rbeta
binom	dbinom	pbinom	qbinom	rbinom
cauchy	dcauchy	pcauchy	qcauchy	rcauchy
chisq	dchisq	pchisq	qchisq	rchisq
exp	dexp	pexp	qexp	rexp
f	df	pf	qf	rf
gamma	dgamma	pgamma	qgamma	rgamma
geom	dgeom	pgeom	qgeom	rgeom
hyper	dhyper	phyper	qhyper	rhyper
lnorm	dlnorm	plnorm	qlnorm	rlnorm
logis	dlogis	plogis	qlogis	rlogis
nbinom	dnbinom	pnbinom	qnbinom	rnbinom
norm	dnorm	pnorm	qnorm	rnorm
pois	dpois	ppois	qpois	rpois
signrank	dsignrank	psignrank	qsignrank	rsignrank
t	dt	pt	qt	rt
unif	dunif	punif	qunif	runif
weibull	dweibull	pweibull	qweibull	rweibull
wilcox	dwilcox	pwilcox	qwilcox	rwilcox


Table 5.2: Density, distribution function, quantile function and random generation for the predefined distributions under R



## 5.2 Synonymous and non-synonymous analyses

Genetic codes are surjective applications from the set codons ( $n = 64$ ) into the set of amino-acids ( $n = 20$ ) :

### The surjective nature of genetic codes Genetic code number 1



Adapted from insert 2 in Lobry & Chessel (2003) JAG 44:235

Two codons encoding the same amino-acid are said synonymous while two codons encoding a different amino-acid are said non-synonymous. The distinction between the synonymous and non-synonymous level are very important in evolutionary studies because most of the selective pressure is expected to work at the non-synonymous level, because the amino-acids are the components of the proteins, and therefore more likely to be subject to selection.

$K_s$  and  $K_a$  are an estimation of the number of substitutions per synonymous site and per non-synonymous site, respectively, between two protein-coding genes [32]. The  $\frac{K_a}{K_s}$  ratio is used as tool to evaluate selective pressure (see [20] for a nice back to basics). Let's give a simple illustration with three orthologous genes of the thioredoxin family from *Homo sapiens*, *Mus musculus*, and *Rattus norvegicus* species:

```
ortho <- read.alignment(system.file("sequences/ortho.fasta",
  package = "seqinr"), format = "fasta")
kaks.ortho <- kaks(ortho)
kaks.ortho$ka/kaks.ortho$ks
```



```

AK002358.PE1 HSU78678.PE1
HSU78678.PE1 0.1243472
RNU73525.PE1 0.1405012 0.1356036

```

The  $\frac{K_a}{K_s}$  ratios are less than 1, suggesting a selective pressure on those proteins during evolution.

For transversal studies (*i.e.* codon usage studies in a genome at the time it was sequenced) there is little doubt that the strong requirement to distinguish between synonymous and a non-synonymous variability was the source of many mistakes [45]. We have just shown here with a scholarship example that the metric choice is not neutral. If you consider that the  $\chi^2$  metric is not too bad, with respect to your objectives, and that you want to quantify the synonymous and a non-synonymous variability, please consider reading this paper [34], and follow this link <http://pbil.univ-lyon1.fr/members/lobry/repro/jag03/> for on-line reproducibility.

Let's now use the toy example given in table 5.3 to illustrate how to study synonymous and non-synonymous codon usage.

```

data(toycodon)
toycodon

```

```

   gca gcc gcg gct gta gtc gtg gtt tgt tgc
1  33  32  32  33  18  17  17  18   0   0
2  13  17  17  13   8  12  12   8   0   0
3  16  14  14  16   8   9  10   8   3   2

```

	gca	gcc	gcg	gct	gta	gtc	gtg	gtt	tgt	tgc
1	33	32	32	33	18	17	17	18	0	0
2	13	17	17	13	8	12	12	8	0	0
3	16	14	14	16	8	9	10	8	3	2


Table 5.3: A very simple example of codon counts in three coding sequences to be loaded with `data(toycodon)`.

Let's first have a look to global codon usage, we do not take into account the structure of the genetic code:

```

global <- dudi.coa(toycodon, scann = FALSE, nf = 2)
myplot(global, asp = 1, pch = 19, xlab = "", ylab = "", main = "Global codon usage")

```



From a global codon usage point of view, coding sequence number 3 is away. To take into account the genetic code structure, we need to know for which amino-acid the codons are coding. The codons are given by the names of the columns of the object `toycodon`:

```
names(toycodon)
```

```
[1] "gca" "gcc" "gcg" "gct" "gta" "gtc" "gtg" "gtt" "tgt" "tgc"
```

Put all codon names into a single string:

```
c2s(names(toycodon))
```

```
[1] "gcagccgcggctgtagtcgtggtttgttgc"
```

Transform this string as a vector of characters:

```
s2c(c2s(names(toycodon)))
```

```
[1] "g" "c" "a" "g" "c" "c" "g" "c" "g" "g" "c" "t" "g" "t" "a" "g" "t" "c"
[19] "g" "t" "g" "g" "t" "t" "t" "g" "t" "t" "g" "c"
```

Translate this into amino-acids using the default genetic code:

```
translate(s2c(c2s(names(toycodon))))
```

```
[1] "A" "A" "A" "A" "V" "V" "V" "V" "C" "C"
```

Use the three letter code for amino-acid instead:

```
aaa(translate(s2c(c2s(names(toycodon))))))
```

```
[1] "Ala" "Ala" "Ala" "Ala" "Val" "Val" "Val" "Val" "Cys" "Cys"
```


Make this a factor:

```
facaa <- factor(aaa(translate(s2c(c2s(names(toycodon))))))
facaa
```

```
[1] Ala Ala Ala Ala Val Val Val Val Cys Cys
Levels: Ala Cys Val
```

The non synonymous codon usage analysis is the between amino-acid analysis:

```
nonsynonymous <- t(between(dudi = t(global), fac = facaa,
  scann = FALSE, nf = 2))
myplot(nonsynonymous, asp = 1, pch = 19, xlab = "", ylab = "",
  main = "Non synonymous codon usage")
```



This is reminiscent of something, let's have a look at amino-acid counts:

```
by(t(toycodon), facaa, colSums)
```

```
INDICES: Ala
```

```
  1  2  3
130 60 60
```

```
INDICES: Cys
```


```
  1  2  3
  0  0  5
```

```
INDICES: Val
```

```
  1  2  3
 70 40 35
```


This is exactly the same data set that we used previously (table 5.1) at the amino-acid level. The non synonymous codon usage analysis is exactly the same as the amino-acid analysis. Coding sequence number 3 is far away because it codes for many Cys, a rare amino-acid. Note that at the global codon usage level, this is also the major visible structure. To get rid of this amino-acid effect, we use the synonymous codon usage analysis, that is the within amino-acid analysis:

```
synonymous <- t(within(dudi = t(global), fac = facaa, scann = FALSE,
  nf = 2))
myplot(synonymous, asp = 1, pch = 19, xlab = "", ylab = "",
  main = "Synonymous codon usage")
```



Now, coding sequence number 2 is away. When the amino-acid effect is removed, the pattern is then completely different. To interpret the result we look at the codon coordinates on the first factor of synonymous codon usage:

```
tmp <- synonymous$co[, 1, drop = FALSE]
tmp <- tmp[order(tmp$Axis1), , drop = FALSE]
colcod <- sapply(rownames(tmp), function(x) ifelse(substr(x,
  3, 3) == "c" || substr(x, 3, 3) == "g", "blue", "red"))
pchcod <- ifelse(colcod == "red", 1, 19)
dotchart(tmp$Axis1, labels = toupper(rownames(tmp)), color = colcod,
  pch = pchcod, main = "Codon coordinates on first factor\nfor synonymous codon usage")
legend("topleft", inset = 0.02, legend = c("GC ending codons",
  "AT ending codons"), text.col = c("blue", "red"), pch = c(19,
  1), col = c("blue", "red"), bg = "white")
```



At the synonymous level, coding sequence number 2 is different because it is enriched in GC-ending codons as compared to the two others. Note that this is hard to see at the global codon usage level because of the strong amino-acid effect.





Figure 5.1: Screenshot of figure 5 from [35]. Each point represents a protein. This was to show the correlation between the codon adaptation index (CAI Score) with the second factor of correspondence analysis at the amino-acid level (F2 Score). Highly expressed genes have a high CAI value.

To illustrate the interest of synonymous codon usage analyses, let's use now a more realistic example. In [35] there was an assertion stating that selection for translation optimisation in *Escherichia coli* was also visible at the amino-acid level. The argument was in figure 5 of the paper (*cf* fig 5.1), that can be reproduced<sup>2</sup> with the following R code:

```
ec <- read.table(file = "ftp://pbil.univ-lyon1.fr/pub/datasets/NAR94/data.txt",
  header = TRUE, row.names = 1)
ec.coa <- dudi.coa(ec, scann = FALSE, nf = 3)
tmp <- read.table(file = "ftp://pbil.univ-lyon1.fr/pub/datasets/NAR94/ecoli999.cai")
cai <- exp(tmp$V2)
plot(cai, ec.coa$li[, 2], pch = 20, xlab = "CAI Score", ylab = "F2 Score",
  main = "Fig 5 from Lobry & Gautier (1994) NAR 22:3174")
```

Fig 5 from Lobry & Gautier (1994) NAR 22:3174



So, there was a correlation between the CAI (Codon Adaptation Index [51]) and the second factor for amino-acid composition variability. However, this is not completely convincing because the CAI is not completely independent of the amino-acid composition of the protein. Let's use within amino-acid correspondence analysis to remove the amino-acid effect. Here is a commented step-by-step analysis:

```
data(ec999)
class(ec999)
```

```
[1] "list"
```

```
names(ec999)[1:10]
```

<sup>2</sup> the code to reproduce all figures from [35] is available at <http://pbil.univ-lyon1.fr/members/lobry/repro/nar94/>.

```
[1] "ECFOLE.FOLE"      "ECMSBAG.MSBA"      "ECNARZYW-C.NARV"  "ECNARZYW-C.NARW"
[5] "ECNARZYW-C.NARY"  "ECNARZYW-C.NARZ"  "ECNIRBC.NIRB"     "ECNIRBC.NIRD"
[9] "ECNIRBC.NIRC"     "ECNIRBC.CYSG"
```

```
ec999[[1]][1:50]
```

```
[1] "a" "t" "g" "c" "c" "a" "t" "c" "a" "c" "t" "c" "a" "g" "t" "a" "a"
[19] "g" "a" "a" "g" "c" "g" "g" "c" "c" "c" "t" "g" "g" "t" "t" "c" "a" "t"
[37] "g" "a" "a" "g" "c" "g" "t" "t" "a" "g" "t" "t" "g" "c"
```

This is to load the data from [35] which is available as `ec999` in the `seqinR` package. The letters `ec` are for the bacterium *Escherichia coli* and the number 999 means that there were 999 coding sequences available from this species at that time. The class of the object `ec999` is a list, which names are the coding sequence names, for instance the first coding sequence name is `ECFOLE.FOLE`. Each element of the list is a vector of character, we have listed just above the 50 first character of the first coding sequence of the list with `ec999[[1]][1:50]`, we can see that there is a start codon (ATG) at the beginning of the first coding sequence.

```
ec999.uco <- lapply(ec999, uco)
class(ec999.uco)
```

```
[1] "list"
```

```
class(ec999.uco[[1]])
```

```
[1] "table"
```

```
ec999.uco[[1]]
```

```
aaa aac aag aat aca acc acg act aga agc agg agt ata atc atg att caa cac cag
 9  5  2  4  2  8  8  1  0  2  0  4  0  9  8  6  2  3  7
cat cca ccc ccg cct cga cgc cgg cgt cta ctc ctg ctt gaa gac gag gat gca gcc
 7  1  1  6  0  1  7  1  4  1  3 13  3 12  3  1  9  1  6
gcg gct gga ggc ggg ggt gta gtc gtg gtt taa tac tag tat tca tcc tcg tct tga
 7  5  2  3  0  4  0  5  9  4  0  2  0  2  2  3  2  1  1
tgc tgg tgt tta ttc ttg ttt
 1  0  1  1  4  2  3
```

This is to compute the codon usage, that is how many times each codon is used in each coding sequence. Because `ec999` is a list, we use the function `lapply()` to apply the same function, `uco()`, to all the elements of the list and we store the result in the object `ec999.uco`. The object `ec999.uco` is a list too, and all its elements belong to the class `table`.

```
df <- as.data.frame(lapply(ec999.uco, as.vector))
dim(df)
```

```
[1] 64 999
```

```
df[1:5, 1:5]
```

	ECFOLE.FOLE	ECMSBAG.MSBA	ECNARZYW.C.NARV	ECNARZYW.C.NARW	ECNARZYW.C.NARY
1	9	15	2	6	23
2	5	18	2	4	16
3	2	8	1	3	4
4	4	3	2	2	4
5	2	3	1	1	0

This is to put the codon usage into a data.frame. Note that the codons are in row and the coding sequences are in columns. This is more convenient for the following because groups for within and between analyses are usually handled by row.

```
row.names(df) <- names(ec999.uco[[1]])
df[1:5, 1:5]
```

	ECFOLE.FOLE	ECMSBAG.MSBA	ECNARZYW.C.NARV	ECNARZYW.C.NARW	ECNARZYW.C.NARY
aaa	9	15	2	6	23
aac	5	18	2	4	16
aag	2	8	1	3	4
aat	4	3	2	2	4
aca	2	3	1	1	0

This is to keep a trace of codon names, just in case we would like to re-order the dataframe df. This is important because we can now play with the data at will without losing any critical information.

```
ec999.coa <- dudi.coa(df = df, scannf = FALSE)
ec999.coa
```

```
Duality diagramm
class: coa dudi
$call: dudi.coa(df = df, scannf = FALSE)

$nf: 2 axis-components saved
$rank: 63
eigen values: 0.05536 0.02712 0.02033 0.01884 0.01285 ...
vector length mode content
1 $cw 999 numeric column weights
2 $lw 64 numeric row weights
3 $eig 63 numeric eigen values

data.frame nrow ncol content
1 $tab 64 999 modified array
2 $li 64 2 row coordinates
3 $li 64 2 row normed scores
4 $co 999 2 column coordinates
5 $c1 999 2 column normed scores
other elements: N
```

This is to run global correspondence analysis of codon usage. We have set the `scannf` parameter to `FALSE` because otherwise the eigenvalue bar plot is displayed for the user to select manually the number of axes to be kept.

```
facaa <- as.factor(aaa(translate(s2c(c2s(rownames(df))))))
facaa
```

```
[1] Lys Asn Lys Asn Thr Thr Thr Thr Arg Ser Arg Ser Ile Ile Met Ile Gln His
[19] Gln His Pro Pro Pro Pro Arg Arg Arg Arg Leu Leu Leu Leu Glu Asp Glu Asp
[37] Ala Ala Ala Ala Gly Gly Gly Gly Val Val Val Val Stp Tyr Stp Tyr Ser Ser
[55] Ser Ser Stp Cys Trp Cys Leu Phe Leu Phe
21 Levels: Ala Arg Asn Asp Cys Gln Glu Gly His Ile Leu Lys Met Phe ... Val
```

This is to define a factor for amino-acids. The function `translate()` use by default the standard genetic code and this is OK for *E. coli*.



```
ec999.syn <- within(dudi = ec999.coa, fac = facaa, scannf = FALSE)
ec999.syn
```

```
Within analysis
call: within(dudi = ec999.coa, fac = facaa, scannf = FALSE)
class: within dudi

$nf (axis saved) : 2
$rank: 43
$ratio: 0.6438642

eigen values: 0.04855 0.0231 0.01425 0.007785 0.006748 ...

  vector length mode  content
1 $eig    43      numeric eigen values
2 $lw     64      numeric row weights
3 $cw    999      numeric col weights
4 $tabw   21      numeric table weights
5 $fac    64      numeric factor for grouping

 data.frame nrow ncol content
1 $tab      64   999 array class-variables
2 $li       64    2   row coordinates
3 $li       64    2   row normed scores
4 $co      999    2   column coordinates
5 $ci      999    2   column normed scores
6 $ls       64    2   supplementary row coordinates
7 $as        2    2   inertia axis onto within axis
```

This is to run the synonymous codon usage analysis. The value of the **ratio** component of the object **ec999.syn** shows that most of the variability is at the synonymous level, a common situation in codon usage studies.

```
ec999.btw <- between(dudi = ec999.coa, fac = facaa, scannf = FALSE)
ec999.btw
```

```
Between analysis
call: between(dudi = ec999.coa, fac = facaa, scannf = FALSE)
class: between dudi

$nf (axis saved) : 2
$rank: 20
$ratio: 0.3561358

eigen values: 0.01859 0.0152 0.01173 0.01051 0.008227 ...

  vector length mode  content
1 $eig    20      numeric eigen values
2 $lw     21      numeric group weights
3 $cw    999      numeric col weights

 data.frame nrow ncol content
1 $tab      21   999 array class-variables
2 $li       21    2   class coordinates
3 $li       21    2   class normed scores
4 $co      999    2   column coordinates
5 $ci      999    2   column normed scores
6 $ls       64    2   row coordinates
7 $as        2    2   inertia axis onto between axis
```


This is to run the non-synonymous codon usage analysis, or amino-acid usage analysis.

```
x <- ec999.syn$co[, 1]
y <- ec999.btw$co[, 2]
kxy <- kde2d(x, y, n = 100)
nlevels <- 25
breaks <- seq(from = min(kxy$z), to = max(kxy$z), length = nlevels +
1)
col <- cm.colors(nlevels)
image(kxy, breaks = breaks, col = col, xlab = "First synonymous factor",
      ylab = "Second non-synonymous factor", xlim = c(-0.5,
```

```

0.5), ylim = c(-0.3, 0.3), las = 1, main = "The second factor for amino-acid variability is\ncor
contour(kxy, add = TRUE, nlevels = nlevels, drawlabels = FALSE)
box()
abline(c(0, 1), lty = 2)
abline(lm(y ~ x))
legend("topleft", lty = c(2, 1), legend = c("y = x", "y = lm(y~x)"),
      inset = 0.01, bg = "white")


```



This is to plot the whole thing. We have extracted the coding sequences coordinates on the first synonymous factor and the second non-synonymous factor within  $x$  and  $y$ , respectively. Because we have many points, we use the two-dimensional kernel density estimation provided by the function `kde2d()` from package `MASS`.

*To be completed*

### 5.3 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), `powerpc-apple-darwin8.6.0`
- Base packages: `base`, `datasets`, `grDevices`, `graphics`, `methods`, `stats`, `utils`
- Other packages: `MASS` 7.2-27.1, `ade4` 1.4-1, `ape` 1.8-2, `gee` 4.13-10, `lattice` 0.13-8, `nlme` 3.1-73, `seqinr` 1.0-6, `xtable` 1.3-0

	aaa	a	prec	p	h	tot	gc
1	Ala	A	pyr	1	5	12	h
2	Cys	C	3pg	7	9	25	m
3	Asp	D	oaa	1	6	13	m
4	Glu	E	akg	3	6	15	m
5	Phe	F	2 pep, eryP	13	19	52	l
6	Gly	G	3pg	2	5	12	h
7	His	H	penP	20	9	38	m
8	Ile	I	pyr, oaa	4	14	32	l
9	Lys	K	oaa, pyr	4	13	30	l
10	Leu	L	2 pyr, acCoA	3	12	27	l
11	Met	M	oaa, Cys, -pyr	10	12	34	m
12	Asn	N	oaa	3	6	15	l
13	Pro	P	akg	4	8	20	h
14	Gln	Q	akg	4	6	16	m
15	Arg	R	akg	11	8	27	h
16	Ser	S	3pg	2	5	12	m
17	Thr	T	oaa	3	8	19	m
18	Val	V	2 pyr	2	11	23	m
19	Trp	W	2 pep, eryP, PRPP, -pyr	28	23	74	m
20	Tyr	Y	eryP, 2 pep	13	18	50	l

Table 5.4: Aerobic cost of amino-acids in *Escherichia coli* and G+C classes to be loaded with `data(aacost)`.



---

---

# CHAPTER 6

---

## Nonparametric statistics

Palmeira, L.

### Contents

<b>6.1</b>	<b>Introduction</b>	<b>73</b>
<b>6.2</b>	<b>Determining dinucleotides over- and under-representation</b>	<b>73</b>
<b>6.3</b>	<b>UV exposure and dinucleotide content</b>	<b>77</b>
<b>6.4</b>	<b>Session Informations</b>	<b>81</b>

### 6.1 Introduction

Nonparametric statistical methods were initially developed to study variables for which little or nothing is known concerning their distribution. This makes them particularly suitable for statistical analysis of biological sequences, in particular for the study of over- and under-representation of  $k$ -letter words.

We will briefly describe two statistics for the measure of dinucleotide over- and under-representation in sequences [25, 42], which can both be computed with **seqinR**. We will subsequently use them to answer the long-time controversial question concerning the relationship between UV exposure and genomic content in bacteria [52, 1].

### 6.2 Determining dinucleotides over- and under-representation

#### 6.2.1 The *rho* statistic

The  $\rho$  statistic (**rho()**), presented in [25], measures the over- and under-representation of two-letter words:

$$\rho(xy) = \frac{f_{xy}}{f_x \times f_y}$$

where  $f_{xy}$  and  $f_x$  are respectively the frequencies of dinucleotide  $xy$  and nucleotide  $x$  in the studied sequence. The underlying model of random generation considers dinucleotides to be formed according to the specific frequencies of the two nucleotides that compose it ( $\rho_{xy} = 1$ ). Departure from this value characterizes either over- or under-representation of dinucleotide  $xy$ .

We expect the  $\rho$  statistic of a randomly generated sequence to be neither over- nor under-represented. Indeed, when we compute the  $\rho$  statistic on 500 random sequences, we can fit a normal distribution which is centered on 1 (see Fig. 6.1)

```
rhoseq <- sapply(seq(n), function(x) {
  rho(sample(s2c("acgt"), 6000, rep = TRUE))
})
hist(rhoseq[di, ], freq = FALSE, xlab = "Rho statistic", main = paste("Distribution for dinucleotide",
  toupper(labels(rhoseq)[[1]][di]), "on", n, "random sequences"),
  las = 1, col = grey(0.8), border = grey(0.5))
abline(v = 1, lwd = 2, lty = 3)
min = min(rhoseq[di, ])
max = max(rhoseq[di, ])
x = seq(min, max, length.out = 1000)
lines(x, dnorm(x, mean = mean(rhoseq[di, ]), sd = sd(rhoseq[di,
  ])), lwd = 2, lty = 2)
```




Figure 6.1: Distribution of the  $\rho$  statistic computed on 500 random sequences. The vertical dotted line is centered on 1. The dashed curve draws the fitted normal distribution.

The downside of this statistic, is that the model against which we compare the sequence under study is fixed. For several types of sequences, dinucleotides

are far from being formed by mere chance (CDS, ...). In this case, the model used in the  $\rho$  statistic becomes trivial, and the over- or under-representations measured are mainly due to the strong constraints acting on those sequences.

### 6.2.2 The *zscore* statistic

The *zscore* statistic (`zscore()`) is inspired by the  $\rho$  statistic, and is defined so that several different models can be used for the determination of over- and under-representation [42]. It allows for a finer measure of over- and under-representation in sequences, according to the chosen model.

The *zscore* is defined as follows:

$$z_{score} = \frac{\rho_{xy} - E(\rho_{xy})}{\sqrt{Var(\rho_{xy})}}$$

where  $E(\rho_{xy})$  and  $Var(\rho_{xy})$  are the expected mean and variance of  $\rho_{xy}$  according to a given model that describes the sequence.

This statistic follows the standard normal distribution, and can be computed with several different models of random sequence generation based on permutations from the original sequence (`modele` argument). More details on those models can be obtained in the documentation for the `zscore()` function, by simply typing `?zscore`.

For instance, if we want to measure the over- and under-representation of dinucleotides in CDS sequences, we can use the `codon` model, which measures the over- and under-representations existing in the studied sequence once codon usage bias has been erased. For intergenic sequences, or sequences for which no good permutation model can be established, we can use the `base` model.

### 6.2.3 Comparing statistics on a sequence

Let's have a look at what these different statistics can show. First, we will extract a CDS sequence of *Escherichia coli*'s chromosome from the Genome Reviews database. We will first make a request to retrieve all available CDS from this bacteria:

```
choosebank("greview")
query("coli", "sp=escherichia coli et t=cds et no k=partial")
sequence <- getSequence(colibank$req[[448]])
```

From the 3684 sequences annotated as CDS in the Genome Reviews database, let's choose one coding sequence: say, for instance, number 448. We can see that this CDS encodes a maltose O-acetyltransferase protein (`getAnnot(colibank$req[[448]], 30)`). We will now compare the three following nonparametric statistics:

- the  $\rho$  statistic,
- the *zscore* statistic with `base` model,
- and the *zscore* statistic with `codon` model.

```
rhocoli = rho(sequence)
zcolibase = zscore(sequence, mod = "base")
zcolicodon = zscore(sequence, mod = "codon")
par(mfrow = c(1, 3))
plot(rhocoli - 1, ylim = c(-0.5, 0.5), las = 1, ylab = "rho")
plot(zcolibase, ylim = c(-2.5, 2.5), las = 1, ylab = "zscore with base model")
plot(zcolicodon, ylim = c(-2.5, 2.5), las = 1, ylab = "zscore with codon model")
```




Figure 6.2: Three different non-parametric statistics (from left to right:  $\rho$ ,  $zscore$  with **base** model,  $zscore$  with **codon** model), computed on the same sequence from *Escherichia coli*. In order to make the figures easily comparable, we subtracted 1 to the `rho()` results, so that all 3 statistics are centered on 0.

The first two figures are almost identical: this is due to the way the  $zscore$  statistic has been built. The statistic computed with the **base** model is a reflection of the  $\rho$  statistic. The difference being that the  $zscore$  follows a standard normal distribution, which makes easier the comparisons between the results from the **base** model and the ones from the **codon** model. The last figure ( $zscore$  with **codon** model), is completely different: almost all over- and under-representations have been erased. We can safely say that these over- and under-representations were due to codon usage bias.

On this last figure, four dinucleotides stand out: CC and TT seem rather under-represented, CT and TC rather over-represented. This means that, in this sequence, codons ending with a given pyrimidine tend to be more frequently followed by a codon starting with the other pyrimidine than expected by chance. This is not a universal feature of *Escherichia coli*, and is probably due to the amino-acid composition of this particular sequence. It seemed a funny example,



as the following part will also relate to pyrimidine dinucleotides. However, what we see on this CDS from *Escherichia coli* has nothing to do with what follows...

## 6.3 UV exposure and dinucleotide content

In the beginning of the 1970's, two contradictory papers considered the question of the impact of UV exposure on genomic content. Both papers had strong arguments for either side, and the question remained open until recently [42].

### 6.3.1 The expected impact of UV light on genomic content

On this controversy, the known facts are: pyrimidine dinucleotides (CC, TT, CT and TC) are the major DNA target for UV-light [50]; the sensitivities of the four pyrimidine dinucleotides to UV wavelengths differ and depend on the micro-organism [50]:

	G+C content	CC (%)	CT + TC (%)	TT (%)
<i>Haemophilus influenzae</i>	62	5	24	71
<i>Escherichia coli</i>	50	7	34	59
<i>Micrococcus lysodeikticus</i>	30	26	55	19

Table 6.1: Proportion of dimers formed in the DNA of three bacteria after irradiation with 265 nm UV light. Table adapted from [50].

The hypothesis presented by Singer and Ames [52] is that pyrimidine dinucleotides are avoided in light-exposed micro-organisms. At the time, only G+C content is available, and – based exclusively on the sensitivity of the four pyrimidine dinucleotides in an *Escherichia coli* chromosome – they hypothesize that a high G+C will result in less pyrimidine target. Indeed, they find that bacteria exposed to high levels of UV have higher G+C content than the others. Bak *et al.* [1] strongly criticize their methodology, but no clear cut answer is achieved.

In an *Escherichia coli* chromosome, it is true that a sequence with a high G+C content will contain few phototargets (see Fig. 6.3).




Figure 6.3: Density of phototargets, weighted by their frequency in the *Escherichia coli* chromosome, and calculated for different G+C contents and for three kinds of random genomes. The weights are as follows:  $0.59 * f_{tt} + 0.34 * (f_{tc} + f_{ct}) + 0.07 * f_{cc}$  (where  $f_{xy}$  is the frequency of dinucleotide  $xy$  in the specified genome). Three models of random genomes are analyzed. In the worst case (solid curve), the genome is the concatenation of a sequence of pyrimidines and a sequence of purines: all pyrimidines are involved in a pyrimidine dinucleotide. In the best case (dotted curve), the genome is an unbroken succession of pyrimidine-purine dinucleotides: no pyrimidine is involved in a pyrimidine dinucleotide. In the "random case" (dashed curve), the frequency of a pyrimidine dinucleotide is the result of chance ( $f_{xy} = f_x \times f_y$ ).

In a *Micrococcus lysodeikticus* sequence (see Fig. 6.4), we can see that this is no longer true...




Figure 6.4: Density of phototargets, weighted by their frequency in the *Micrococcus lysodeikticus* chromosome, and calculated for different G+C contents and for three kinds of random genomes. The weights are as follows:  $0.19 * f_{tt} + 0.55 * (f_{tc} + f_{ct}) + 0.26 * f_{cc}$ . See previous figure for more details.

These two figures show that the density of phototargets depends on:

- the degree of aggregation of pyrimidine dinucleotides in the sequence,
- the sensitivities of the four pyrimidine dinucleotides.

Instead of looking at G+C content, which is an indirect measure of the impact of UV exposure on genomic content, let us look at pyrimidine dinucleotide content.

Are CC, TT, CT and TC dinucleotides avoided in light-exposed bacteria?

### 6.3.2 The measured impact of UV light on genomic content

On all available genomes (as retrieved from Genome Reviews database on June 16, 2005), we have computed the mean of the *zscore* with the **base** model on all intergenic sequences, and the mean of the *zscore* with the **codon** model on all CDS:

```
data(dinucl)
```

The results show that there is no systematic under-representation of none of the four pyrimidine dinucleotides (see Fig. 6.5).




Figure 6.5: Plot of the mean *zscore* statistics for **intergenic sequences** (x-axis) and for **coding sequences** (y-axis), for each of the four pyrimidine dinucleotides. On each plot, a dot corresponds to the mean of these two statistics in a given prokaryote chromosome. The null x and y axis (dotted lines), and the 5% limits of significance for the standard normal distribution (dashed lines) are plotted as benchmarks. It should be noted that the variability within one chromosome is sometimes as great as that between different chromosomes.

However, we have little or no information on the exposure of this bacteria to UV light. In order to fully answer this question, let's do another analysis and look at *Prochlorococcus marinus* genome.

*Prochlorococcus marinus* seems to make an ideal model for investigating this hypothesis. Three completely sequenced strains are available in the Genome reviews database: two of these strains are adapted to living at a depth of more than 120 meters (accession numbers AE017126 and BX548175), and the other one at a depth of 5 meters (accession number BX548174).

Living at a depth of 5 meters, or at a depth of more than a 120 meters is totally different in terms of UV exposure: the residual intensity of 290 nm irradiation (UVb) in pure water can be estimated to 56% of its original intensity at 5 m depth and to less than 0.0001% at more than 120 m depth. For this reason, two of the *Prochlorococcus marinus* strains can be considered to be adapted to low levels of UV exposure, and the other one to much higher levels. Is pyrimidine dinucleotide content different in these three strains? And is it linked to their UV exposure?

We have computed the *zscore* with the `codon` model on all CDS from each of these three strains (as retrieved from Genome Reviews database on June 16, 2005):

```
data(prochlo)
```





Figure 6.6: Each figure shows the distributions of the *zscore* in all **coding sequences** corresponding to each of the three strains of *Prochlorococcus marinus*. In each figure, the distribution for the MED4 (a high-light adapted strain) is shown as a solid line; the distribution for the SS120 (a low-light adapted strain) is shown as a dashed line, and the distribution for the MIT 9313 (a low-light adapted strain) is shown as a dotted line. The 5% limits of significance for the standard normal distribution (dashed vertical lines) are plotted as benchmarks.

Figure 6.6 shows that there is no difference between the relative abundances of pyrimidine dinucleotides in these three strains. We can say that pyrimidine dinucleotides are not avoided, and that the hypothesis by Singer and Ames [52] no longer stands [42].

## 6.4 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), powerpc-apple-darwin8.6.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: MASS 7.2-27.1, ade4 1.4-1, ape 1.8-2, gee 4.13-10, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0



---

# APPENDIX A

---

## FAQ: Frequently Asked Questions

Lobry, J.R.

### A.1 How do I compute a score on my sequences?

In the example below we want to compute the G+C content in third codon positions for complete ribosomal CDS from *Escherichia coli*:

```
choosebank("emblTP")
query("ecribo", "sp=escherichia coli ET t=cds ET k=ribosom@ ET NO k=partial")
myseqs <- sapply(ecribo$req, getSequence)
(gc3 <- sapply(myseqs, GC3))
```

```
[1] 0.4946237 0.6046512 0.5000000 0.6194030 0.5772727 0.4838710 0.5980066
[8] 0.4974359 0.5031250 0.4324324 0.5000000 0.5113636 0.5290520 0.6142857
[15] 0.4904762 0.5714286 0.6191860 0.5906040 0.4880000 0.4880000 0.4946237
[22] 0.6046512 0.5000000 0.3522727 0.5076923 0.4343434 0.6194030 0.5522388
[29] 0.6104651 0.5661157 0.4946237 0.4946237 0.6079734 0.5000000 0.6343284
[36] 0.4659091 0.5789474 0.4946237 0.5000000 0.4974359 0.5689655 0.4611111
[43] 0.4611111 0.5303030 0.5303030 0.4482759 0.4201681 0.5915493 0.5000000
[50] 0.3829787 0.4519231 0.4302326 0.5696203 0.4285714 0.5689655 0.5000000
[57] 0.5224417 0.5661157 0.6057692 0.4444444 0.4659091 0.4130435 0.4946237
[64] 0.5661157 0.4946237 0.5680272
```

At the amino-acid level, we may get an estimate of the isoelectric point of the proteins this way:

```
sapply(sapply(myseqs, getTrans), computePI)
```

```
[1] 6.624309 7.801329 10.864793 5.931989 7.830476 6.624309 7.801329
[8] 9.203410 9.826485 5.674672 7.154423 6.060457 6.313741 5.571446
[15] 9.435422 4.310747 6.145496 4.876054 11.006424 10.876041 6.624309
[22] 7.801329 10.864793 9.346289 9.203410 5.877050 5.931989 9.934988
[29] 5.920490 6.612505 6.624309 6.624309 7.801329 10.864793 5.931989
[36] 11.182505 9.598944 6.624309 10.864793 9.203410 11.031938 5.858421
[43] 5.858421 11.777516 11.777511 10.619175 11.365738 9.460987 10.864793
[50] 13.002381 9.845859 10.584868 11.421257 10.248325 11.031938 10.402075
[57] 4.863862 6.612505 9.681066 11.150304 11.182505 11.043602 6.624309
[64] 6.612505 6.624309 4.310747
```

Note that some pre-defined vectors to compute linear forms on sequences are available in the EXP data.

As a matter of convenience, you may encapsulate the computation of your favorite score within a function this way:

```
GC3m <- function(list, ind = 1:list$nelem) sapply(sapply(list$req[ind],
  getSequence), GC3)
GC3m(ecribo)
```

```
[1] 0.4946237 0.6046512 0.5000000 0.6194030 0.5772727 0.4838710 0.5980066
[8] 0.4974359 0.5031250 0.4324324 0.5000000 0.5113636 0.5290520 0.6142857
[15] 0.4904762 0.5714286 0.6191860 0.5906040 0.4880000 0.4880000 0.4946237
[22] 0.6046512 0.5000000 0.3522727 0.5076923 0.4343434 0.6194030 0.5522388
[29] 0.6104651 0.5661157 0.4946237 0.4946237 0.6079734 0.5000000 0.6343284
[36] 0.4659091 0.5789474 0.4946237 0.5000000 0.4974359 0.5689655 0.4611111
[43] 0.4611111 0.5303030 0.5303030 0.4482759 0.4201681 0.5915493 0.5000000
[50] 0.3829787 0.4519231 0.4302326 0.5696203 0.4285714 0.5689655 0.5000000
[57] 0.5224417 0.5661157 0.6057692 0.4444444 0.4659091 0.4130435 0.4946237
[64] 0.5661157 0.4946237 0.5680272
```

```
GC3m(ecribo, 1:10)
```

```
[1] 0.4946237 0.6046512 0.5000000 0.6194030 0.5772727 0.4838710 0.5980066
[8] 0.4974359 0.5031250 0.4324324
```

## A.2 Why do I have not exactly the same G+C content as in codonW?

This question was raised (and solved) by Oliver Clay in an e-mail (23-AUG-2006). The program `codonW` was written in C as part of Jonh Peden's PhD thesis on Codon Usage [44] and is available at <http://codonw.sourceforge.net/>. The reason for the small differences in G+C content between the two programs is that the default behavior in `codonW` is to remove the stop codon before computations. Here is one way of removing the stop codon under  $\mathbb{R}$ :


```
gc3nos <- sapply(myseqs, function(s) GC3(s[1:(length(s) -
  3)]))
```

As compared with the previous result, the difference is small but visible:

```
plot(x = gc3, y = gc3nos, las = 1, main = "Stop codon removal effect on G+C content\nin third codon posi
  xlab = "With stop codon", ylab = "Stop codons removed")
abline(c(0, 1))
```




## A.2. WHY DO I HAVE NOT EXACTLY THE SAME G+C CONTENT AS IN CODONW?



CodonW was released with a test file called `input.dat`, here are the first 10 lines of the file copied from `CodonWSourceCode_1_4_4`:

```
inputdatfile <- system.file("sequences/input.dat", package = "seqinr")
cat(readLines(inputdatfile, n = 10), sep = "\n")

>YCG9 Probable      1377 residues Pha 0 Code 0
ATGAATATGCTCATTGTCGGTAGAGTTGTTGCTAGTGTGGGGGAAGCGGACTTCAAACG
CTTTGCTTTGTTATTGGTTGTACGATGGTTGGTGAAAGGTCACGTCCATTGGTGATTTC
ATCCTAAGTTGTGCATTTGCTGTAGCTGCTATCGTTGGTCCTATAATCGGAGGTGCCTTT
ACAACCCATGTTACCTGGAGGTGGTGTCTTCTATATCAATCTTCCTATCGGTGGTCTTGCC
ATTATTATGTTTTTACTCACATATAAGGCCGAGAATAAGGGTATACCTTCAACAAATAAA
GATGCTATAGGAACAATCTCGAGCTTTACTTTTAGTAAGTTCAGACACCAAGTTAATTTT
AAAAGACTTATGAATGGCATAATCTTCAAGTTTGACTTCTTTGGTTTGGCCTCTGCTCT
GCAGGGCTGGTCTTTTCTACTGGGGCTAACCTTTGGTGGTAATAAATATAGTTGGAAC
TCTGGCCAAGTCATCGCATATTTGGTTTGGGTGTCTTACTTTTTATTTTTCATTGGTG
```

This is a FASTA file that we import under  with:

```
input <- read.fasta(file = inputdatfile)
names(input)
```

[1]	"YCG9"	"YCG8"	"ALPHA2"	"ALPHA1"	"CHA1"	"KRR1"
[7]	"PRD1"	"KAR4"	"PBN1"	"LRE1"	"APA1"	"YCE9"
[13]	"YCE8"	"YCE7"	"YCE5"	"YCE6"	"YCE4"	"PDI1"
[19]	"GLK1"	"YCD8"	"SR09"	"YCD6"	"YCD5"	"YCD3"
[25]	"STE50"	"HIS4"	"BIK1"	"FUS1"	"YCO8"	"AGP1"
[31]	"LEU2"	"NFS1"	"BUD3"	"GBP2"	"ILV6"	"CWH36"
[37]	"PEL1"	"RER1"	"CDC10"	"MRPL32"	"YCP4"	"CIT2"
[43]	"YCP7"	"SAT4"	"RVS161"	"YCQ0"	"ADP1"	"PGK1"
[49]	"POL4"	"YCQ7"	"SRD1"	"MAK32"	"PET18"	"MAK31"
[55]	"HSP30"	"YCR3"	"SYN"	"YCR6"	"GNS1"	"FEN2"
[61]	"RIM1"	"CRY1"	"YCS2"	"YCS3"	"GNS1"	"RBK1"
[67]	"PH087"	"BUD5"	"MATALPHA2"	"MATALPHA1"	"TSM1"	"YCT5"
[73]	"PETCR46"	"YCT7"	"YCT9"	"ARE1"	"RSC6"	"THR4"
[79]	"CTR86"	"PWP2"	"YCU9"	"YCV1"	"G10"	"HCM1"
[85]	"RAD18"	"CYPR"	"YCW1"	"YCW2"	"SSK22"	"SOL2"
[91]	"ERS1"	"PAT1"	"SRB8"	"YCX3"	"TUP1"	"YC16"
[97]	"ABP1"	"KIN82"	"MSH3"	"CDC39"	"YCY4"	"A2"
[103]	"GIT1"	"YCZ0"	"YCZ1"	"YCZ2"	"YCZ3"	"PAU3"
[109]	"YCZ5"	"YCZ6"	"YCZ7"			

The file `input.out` contains the values obtained with `codonW` for the GC content and GC3s content:

```
inputoutfile <- system.file("sequences/input.out", package = "seqinr")
cat(readLines(inputoutfile, n = 10), sep = "\n")
```

```
title          GC3s      GC
YCG9_Probable_13 0.335    0.394
YCG8_573_residues_ 0.439    0.446
ALPHA2_633_residue 0.328    0.351
ALPHA1_528_residue 0.345    0.379
CHA1_1083_residue 0.328    0.394
KRR1_951_residue  0.364    0.384
PRD1_2139_residue 0.430    0.397
KAR4_1008_residue 0.354    0.383
PBN1_1251_residue 0.330    0.386
```

```
input.res <- read.table(inputoutfile, header = TRUE)
head(input.res)
```

```
      title GC3s  GC
1 YCG9_Probable_13 0.335 0.394
2 YCG8_573_residues_ 0.439 0.446
3 ALPHA2_633_residue 0.328 0.351
4 ALPHA1_528_residue 0.345 0.379
5 CHA1_1083_residue 0.328 0.394
6 KRR1_951_residue 0.364 0.384
```


Let's try to reproduce the results for the G+C content, we know that we have to remove the last stop codon:

```
input.gc <- sapply(input, function(s) GC(s[1:(length(s) -
3)]))
max(abs(input.gc - input.res$GC))
```

```
[1] 0.0004946237
```

```
plot(x = input.gc, y = input.res$GC, las = 1, xlab = "Results with GC()",
     ylab = "Results from codonW", main = "Comparison of G+C content results")
abline(c(0, 1))
```

## A.2. WHY DO I HAVE NOT EXACTLY THE SAME G+C CONTENT AS IN CODONW?87




The results are consistent if we consider that we have 3 significant digits in the file `input.out`. Now, let's try to reproduce the results for G+C in third codon positions:

```
input.gc3 <- sapply(input, function(s) GC3(s[1:(length(s) -  
3)]))  
max(abs(input.gc3 - input.res$GC3s))
```

```
[1] 0.054
```

```
plot(x = input.gc3, y = input.res$GC3s, las = 1, xlab = "Results with GC3()",  
     ylab = "Results from codonW", main = "Comparison of G+C content in third codon positions results")  
abline(c(0, 1))
```

**Comparison of G+C content in third codon positions results**


There is clearly a problem here. Looking into the documentation of `codonW`, GC3s is the G+C content in third codon position after removing non-synonymous and stop codons (those corresponding to Met, Trp, Stp). Let's remove these codons:

```
codons <- words()
names(codons) <- sapply(codons, function(c) aaa(translate(s2c(c),
  numcode = 1)))
okcodons <- codons[!names(codons) %in% c("Met", "Trp", "Stp")]
gc3s <- function(s) {
  tmp <- splitseq(s)
  tmp <- tmp[tmp %in% okcodons]
  tmp <- s2c(paste(tmp, collapse = ""))
  GC3(tmp)
}
input.gc3s <- sapply(input, gc3s)
max(abs(input.gc3s - input.res$GC3s))
```

```
[1] 0.0004980843
```

```
plot(x = input.gc3s, y = input.res$GC3s, las = 1, xlab = "Results with GC3()",
  ylab = "Results from codonW", main = "Comparison of G+C content in third codon positions results\n(M",
  abline(c(0, 1))
```

## A.2. WHY DO I HAVE NOT EXACTLY THE SAME G+C CONTENT AS IN CODONW?89



The results are now consistent. But thinking more about it there is still a problem with the codons for Ile:

```
codons[names(codons) == "Ile"]
```

```
Ile Ile Ile
"ata" "atc" "att"
```

There are three codons for Ile. If the distribution of the four bases was uniform and selectively neutral in third codon position of synonymous codons, then we would expect to get a G+C of 50% in quartet and duet codons at third codons positions because they all have the same number of W (A or T) and S (C or G) bases in third position. But for Ile we have two codons ending in W versus only one in S so that we would get a G+C of  $\frac{1}{3}$  instead of  $\frac{1}{2}$ . This point was clearly stated [54] by Sueoka in 1988:


**G + C Content of the Three Codons Positions.** In the present analysis, observed G + C contents of the first, second, and third codon positions ( $P_1$ ,  $P_2$ , and  $P_3$ , respectively) are corrected average G + C contents of the three codon positions that are calculated from 56 triplets out of 64. Because of the inequality of  $\alpha$  and  $\gamma$  at the third codon position, the three stop codons (TAA, TAG, and TGA) and the three codons for isoleucine (ATT, ATC, and ATA) were excluded in calculation of  $P_3$ , and two single codons for methionine (ATG) and tryptophan (TGG) were excluded in all three ( $P_1$ ,  $P_2$ , and  $P_3$ )

Let's compute  $P_3$  and compare it with GC3s:

```
P3codons <- codons[!names(codons) %in% c("Met", "Trp", "Ile",
  "Stp")]
P3 <- function(s) {
  tmp <- splitseq(s)
  tmp <- tmp[tmp %in% P3codons]
  tmp <- s2c(paste(tmp, collapse = ""))
  GC3(tmp)
}
input.P3 <- sapply(input, P3)
max(abs(input.P3 - input.res$GC3s))
```

```
[1] 0.02821505
```

```
plot(x = input.P3, y = input.res$GC3s, las = 1, xlab = "Results with P3",
  ylab = "Results from codonW GC3s", main = "Comparison of P3 and GC3s")
abline(c(0, 1))
```



This is not exactly the same, the maximum observed difference here is about 3%. In practice,  $P_3$ , GC3, and GC3s are only slightly different [55].

### A.3 How do I get a sequence from its name?

This question is adapted from an e-mail (22 Jun 2006) by Gang Xu. I know that the UniProt (SwissProt) entry of my protein is P08758, if I know its name<sup>1</sup>, how can I get the sequence?

```
choosebank("swissprot")
query("myprot", "AC=P08758")
getSequence(myprot$req[[1]])
```


<sup>1</sup> More exactly, this is the accession number. Sequence names are not stable over time, it's always better to use the accession numbers.

```

[1] "A" "Q" "V" "L" "R" "G" "T" "V" "T" "D" "F" "P" "G" "F" "D" "E" "R" "A"
[19] "D" "A" "E" "T" "L" "R" "K" "A" "M" "K" "G" "L" "G" "T" "D" "E" "E" "S"
[37] "I" "L" "T" "L" "L" "T" "S" "R" "S" "N" "A" "Q" "R" "Q" "E" "I" "S" "A"
[55] "A" "F" "K" "T" "L" "F" "G" "R" "D" "L" "L" "D" "D" "L" "K" "S" "E" "L"
[73] "T" "G" "K" "F" "E" "K" "L" "I" "V" "A" "L" "M" "K" "P" "S" "R" "L" "Y"
[91] "D" "A" "Y" "E" "L" "K" "H" "A" "L" "K" "G" "A" "G" "T" "N" "E" "K" "V"
[109] "L" "T" "E" "I" "I" "A" "S" "R" "T" "P" "E" "E" "L" "R" "A" "I" "K" "Q"
[127] "V" "Y" "E" "E" "E" "Y" "G" "S" "S" "L" "E" "D" "D" "V" "V" "G" "D" "T"
[145] "S" "G" "Y" "Y" "Q" "R" "M" "L" "V" "V" "L" "L" "Q" "A" "N" "R" "D" "P"
[163] "D" "A" "G" "I" "D" "E" "A" "Q" "V" "E" "Q" "D" "A" "Q" "A" "L" "F" "Q"
[181] "A" "G" "E" "L" "K" "W" "G" "T" "D" "E" "E" "K" "F" "I" "T" "I" "F" "G"
[199] "T" "R" "S" "V" "S" "H" "L" "R" "K" "V" "F" "D" "K" "Y" "M" "T" "I" "S"
[217] "G" "F" "Q" "I" "E" "E" "T" "I" "D" "R" "E" "T" "S" "G" "N" "L" "E" "Q"
[235] "L" "L" "L" "A" "V" "V" "K" "S" "I" "R" "S" "I" "P" "A" "Y" "L" "A" "E"
[253] "T" "L" "Y" "Y" "A" "M" "K" "G" "A" "G" "T" "D" "D" "H" "T" "L" "I" "R"
[271] "V" "M" "V" "S" "R" "S" "E" "I" "D" "L" "F" "N" "I" "R" "K" "E" "F" "R"
[289] "K" "N" "F" "A" "T" "S" "L" "Y" "S" "M" "I" "K" "G" "D" "T" "S" "G" "D"
[307] "Y" "K" "K" "A" "L" "L" "L" "L" "C" "G" "E" "D" "D"

```

## A.4 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), powerpc-apple-darwin8.6.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: MASS 7.2-27.1, ade4 1.4-1, ape 1.8-2, gee 4.13-10, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0





---

---

# APPENDIX B

---

## GNU Free Documentation License

Version 1.2, November 2002

Copyright ©2000,2001,2002 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### Preamble

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### B.1 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the

terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The **"Document"**, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as **"you"**. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A **"Modified Version"** of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A **"Secondary Section"** is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The **"Invariant Sections"** are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The **"Cover Texts"** are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A **"Transparent"** copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called **"Opaque"**.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The **"Title Page"** means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title

page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "**Entitled XYZ**" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "**Acknowledgements**", "**Dedications**", "**Endorsements**", or "**History**".) To "**Preserve the Title**" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

## B.2 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

## B.3 COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy

of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## B.4 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and

publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## B.5 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

## B.6 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## B.7 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

## B.8 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

## B.9 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## B.10 FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.





---

# APPENDIX C

---

## Genetic codes

Lobry, J.R.

### C.1 Standard genetic code

The standard genetic code given in table C.1 was produced with the following `\R` code and inserted with `\input{../tables/stdcode.tex}` within this L<sup>A</sup>T<sub>E</sub>X document and referenced as `\ref{stdcode}` in the text.

```
tablecode(latexfile = "../tables/stdcode.tex", label = "stdcode",
          size = "small")
```

### C.2 Available genetic code numbers

The genetic code numbers are those from the NCBI<sup>1</sup> (<http://130.14.29.110/Taxonomy/Utils/wprintgc.cgi?mode=c>). This compilation from Andrzej (Anjay) Elzanowski, Jim Ostell, Detlef Leipe, and Vladimir Soussov is based primarily on two previous reviews [41, 23].

```
codes <- SEQINR.UTIL$CODES.NCBI
availablecodes <- which(codes$CODES != "deleted")
codes[availablecodes, "ORGANISMES", drop = FALSE]
```

```

                                ORGANISMES
1                                standard
2          vertebrate.mitochondrial
3                yeast.mitochondrial
4  protozoan.mitochondrial+mycoplasma
5          invertebrate.mitochondrial
6                ciliate+dasycladacean
9  echinoderm+flatworm.mitochondrial
10                        euplotid
11          bacterial+plantplastid
12                alternativeyeast
13                ascidian.mitochondrial
14  alternativeflatworm.mitochondrial
15                        blepharism
```

---

<sup>1</sup> National Center for Biotechnology Information, Bethesda, Maryland, U.S.A.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly


---

Table C.1: Genetic code number 1: standard.

```

16      chlorophycean.mitochondrial
21      trematode.mitochondrial
22      scenedesmus.mitochondrial
23      hraustochytrium.mitochondria

```


The tables of variant genetic codes outlining the differences were produced with the following  code:

```

cdorder <- paste(paste(rep(s2c("tcag"), each = 16), s2c("tcag"),
  sep = ""), rep(s2c("tcag"), each = 4), sep = "")
stdcode <- sapply(lapply(cdorder, s2c), translate, numcode = 1)
for (cd in availablecodes[-1]) {
  Tfile <- paste("../tables/codnum", cd, ".tex", sep = "")
  preemph <- "\\textcolor{red}{\\textbf{"
  postemph <- "}}"
  stcodon <- (stdcode == sapply(lapply(cdorder, s2c), translate,
    numcode = cd))
  pre <- ifelse(stcodon, "", preemph)
  post <- ifelse(stcodon, "", postemph)
  tablecode(numcode = cd, latexfile = Tfile, size = "small",
    preaa = pre, postaa = post)
  cat(paste("\\input{" , Tfile, "}", sep = ""), sep = "\\n")
}

```

### C.3 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), powerpc-apple-darwin8.6.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: MASS 7.2-27.1, ade4 1.4-1, ape 1.8-2, gee 4.13-10, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
<b>ATA</b>	<b>Met</b>	ACA	Thr	AAA	Lys	<b>AGA</b>	<b>Stp</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Stp</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.2: Genetic code number 2: vertebrate.mitochondrial.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
<b>CTT</b>	<b>Thr</b>	CCT	Pro	CAT	His	CGT	Arg
<b>CTC</b>	<b>Thr</b>	CCC	Pro	CAC	His	CGC	Arg
<b>CTA</b>	<b>Thr</b>	CCA	Pro	CAA	Gln	CGA	Arg
<b>CTG</b>	<b>Thr</b>	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
<b>ATA</b>	<b>Met</b>	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.3: Genetic code number 3: yeast.mitochondrial.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.4: Genetic code number 4: protozoan.mitochondrial+mycoplasma.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
<b>ATA</b>	<b>Met</b>	ACA	Thr	AAA	Lys	<b>AGA</b>	<b>Ser</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Ser</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.5: Genetic code number 5: invertebrate.mitochondrial.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	<b>TAA</b>	<b>Gln</b>	TGA	Stp
TTG	Leu	TCG	Ser	<b>TAG</b>	<b>Gln</b>	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.6: Genetic code number 6: ciliate+dasycladacean.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	<b>AAA</b>	<b>Asn</b>	<b>AGA</b>	<b>Ser</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Ser</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.7: Genetic code number 9: echinoderm+flatworm.mitochondrial.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Cys</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.8: Genetic code number 10: euplotid.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.9: Genetic code number 11: bacterial+plantplastid.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
<b>CTG</b>	<b>Ser</b>	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.10: Genetic code number 12: alternativeyeast.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
<b>ATA</b>	<b>Met</b>	ACA	Thr	AAA	Lys	<b>AGA</b>	<b>Gly</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Gly</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.11: Genetic code number 13: ascidian.mitochondrial.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	<b>TAA</b>	<b>Tyr</b>	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	<b>AAA</b>	<b>Asn</b>	<b>AGA</b>	<b>Ser</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Ser</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.12: Genetic code number 14: alternativeflatworm.mitochondrial.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	<b>TAG</b>	<b>Gln</b>	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.13: Genetic code number 15: blepharism.



TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	<b>TAG</b>	<b>Leu</b>	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.14: Genetic code number 16: chlorophycean.mitochondrial.

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	TCA	Ser	TAA	Stp	<b>TGA</b>	<b>Trp</b>
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
<b>ATA</b>	<b>Met</b>	ACA	Thr	<b>AAA</b>	<b>Asn</b>	<b>AGA</b>	<b>Ser</b>
ATG	Met	ACG	Thr	AAG	Lys	<b>AGG</b>	<b>Ser</b>
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

Table C.15: Genetic code number 21: trematode.mitochondrial.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
TTA	Leu	<b>TCA</b>	<b>Stp</b>	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	<b>TAG</b>	<b>Leu</b>	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.16: Genetic code number 22: scenedesmus.mitochondrial.

---

TTT	Phe	TCT	Ser	TAT	Tyr	TGT	Cys
TTC	Phe	TCC	Ser	TAC	Tyr	TGC	Cys
<b>TTA</b>	<b>Stp</b>	TCA	Ser	TAA	Stp	TGA	Stp
TTG	Leu	TCG	Ser	TAG	Stp	TGG	Trp
CTT	Leu	CCT	Pro	CAT	His	CGT	Arg
CTC	Leu	CCC	Pro	CAC	His	CGC	Arg
CTA	Leu	CCA	Pro	CAA	Gln	CGA	Arg
CTG	Leu	CCG	Pro	CAG	Gln	CGG	Arg
ATT	Ile	ACT	Thr	AAT	Asn	AGT	Ser
ATC	Ile	ACC	Thr	AAC	Asn	AGC	Ser
ATA	Ile	ACA	Thr	AAA	Lys	AGA	Arg
ATG	Met	ACG	Thr	AAG	Lys	AGG	Arg
GTT	Val	GCT	Ala	GAT	Asp	GGT	Gly
GTC	Val	GCC	Ala	GAC	Asp	GGC	Gly
GTA	Val	GCA	Ala	GAA	Glu	GGA	Gly
GTG	Val	GCG	Ala	GAG	Glu	GGG	Gly

---

Table C.17: Genetic code number 23: hraustochytrium.mitochondria.

---

---

# APPENDIX D

---

## Release notes

Lobry, J.R., Palmeira, L.

### D.1 release 1.0-6

Release 1.0-6 is a minor release to fix a problem found and solved by Kurt Hornik (namely a change from `SET_ELEMENT` to `SET_STRING_ELT` in C code for `s2c()` in file `util.c`). The few changes are as follows.

- More typographical option for the output  $\text{\LaTeX}$  table of `tablecode()` are now available to outline deviations from the standard genetic code (see example in the appendix "genetic codes" of the manual).
- A new dataset `aaindex` extracted from the `aaindex` database [26, 56, 40] is now available. It contains a list of 544 physicochemical and biological properties for the 20 amino-acids
- The default value for argument `dia` is now `FALSE` in function `tablecode()`.
- The example code for `data(chargaff)` has been changed.

### D.2 release 1.0-5

- A new function `dotPlot()` is now available.
- A new function `crelistfromclientdata()` is now available to create a list on the server from a local file of sequence names, sequence accession numbers, species names, or keywords names.
- A new function `pmw()` to compute the molecular weight of a protein is now available.

- A new function `reverse.align()` contributed by Anamaria Necşulea is now available to align CDS at the protein level and then reverse translate this at the nucleic acid level from a `clustalw` output. This can be done on the fly if `clustalw` is available on your platform.
- An undocumented behavior was reported by Guy Perrière for `uco()` when computing RSCU on sequences where an amino-acid is missing. There is now a new argument `NA.rscu` that allows the user to force the missing values to his favorite magic value.
- There was a bug in `read.fasta()`: some sequence names were truncated, this is now fixed (thanks to Marcus G. Daniels for pointing this). In order to be more consistent with standard functions such as `read.table()` or `scan()`, the file argument starts now with a lower case letter (`file`) in function `read.fasta()`, but the old-style `File` is still functional for forward-compatibility. There is a new logical argument in `read.fasta()` named `as.string` to allow sequences to be returned as strings instead of vector of single characters. The automatic conversion of DNA sequences into lower case letters can now be disabled with the new logical argument `forcedNAtolower`. It is also possible to disable the automatic attributes settings with the new logical argument `set.attributes`.
- A new function `write.fasta()` is now available.
- The function `kaks()` now forces character in sequences to upper case. This default behavior can be neutralized in order to save time by setting the argument `forceUpperCase` to `FALSE`.

### D.3 release 1.0-4

- The scaling factor  $n_{..}$  was missing in equation 5.3.
- The files `louse.fasta`, `louse.names`, `gopher.fasta`, `gopher.names` and `ortho.fasta` that were used for examples in the previous version of this document are no more downloaded from the internet since they are now distributed in the `sequences/` folder of the package.
- An example of synonymous and non synonymous codon usage analysis was added to the vignette along with two toy data sets (`toyaa` and `toycodon`).
- A FAQ section was added to the vignette.
- A bug in `getAnnot()` when the number of lines was zero is now fixed.
- There is now a new argument, `latexfile`, in `tablecode()` to export genetic codes tables in a  $\text{\LaTeX}$  document, for instance table 1.2 and table 1.3 here.
- There is now a new argument, `freq`, in `count()` to compute word frequencies instead of counts.
- Function `splitseq()` has been entirely rewritten to improve speed.

- Functions computing the G+C content: `GC()`, `GC1()`, `GC2()`, `GC3()` were rewritten to improve speed, and their document files were merged to facilitate usage.
- The following new functions have been added:
  - `syncodons()` returns all synonymous codons for a given codon. Argument `numcode` specifies the desired genetic code.
  - `ucoweight()` returns codon usage bias on a sequence as the number of synonymous codons present in the sequence for each amino acid.
  - `synsequence()` generates a random coding sequence which is synonymous to a given sequence and has a chosen codon usage bias.
  - `permutation()` generates a new sequence from a given sequence, while maintaining some constraints from the given sequence such as nucleotide frequency, codon usage bias, ...
  - `rho()` computes the rho statistic on dinucleotides as defined in [25].
  - `zscore()` computes the zscore statistic on dinucleotides as defined in [42].
- Two datasets (`dinuc1` and `proch10`) were added to illustrate these new functions.

## D.4 release 1.0-3

- The new package maintainer is Dr. Simon Penel, PhD, who has now a fixed position in the laboratory that issued `seqinR` (`penel@biomserv.univ-lyon1.fr`). Delphine Charif was successful too to get a fixed position in the same lab, with now a different research task (but who knows?). Thanks to the close vicinity of our pioneering maintainers the transition was sweet. The DESCRIPTION file of the `seqinR` package has been updated to take this into account.
- The reference paper for the package is now *in press*. We do not have the full reference for now, you may use `citation("seqinr")` to check if it is complete now:

```
citation("seqinr")
```

To cite `seqinR` in publications use:

```
in the body of the text (J.R. Lobry, personal communication), or
wait for the exact complete reference.
```

A BibTeX entry for LaTeX users is

```
@incollection{
  author = {D. Charif and J.R. Lobry},
  title = {SeqinR 1.0-2: a contributed package to the R project for statistical computing devoted to biological sequence analysis},
  booktitle = {Structural approaches to sequence evolution: Molecules, networks, populations},
  year = {2006},
  editor = {U. Bastolla, M. Porto, H.E. Roman and M. Vendruscolo},
  volume = {NA},
  series = {Biological and Medical Physics, Biomedical Engineering},
  pages = {NA},
  address = {New York},
  month = {NA},
  organization = {NA},
```

```


    publisher = {Springer Verlag},
    note = {in press},
  }

```

Note that the original article and updates are available in the  
`../../../../seqinR.Rcheck/seqinR/doc/` folder in PDF format

- There was a bug when sending a **gfrag** request to the server for long (Mb range) sequences. The length argument was converted to scientific notations that are not understood by the server. This is now corrected and should work up to the Gb scale.
- The **query()** function has been improved by de-looping list element info request, there are now downloaded at once which is much more efficient. For example, a query from a researcher-home ADSL connection with a list with about 1000 elements was 60 seconds and is now only 4 seconds (*i.e.* 15 times faster now).
- A new parameter **virtual** has been added to **query()** so that long lists can stay on the server without trying to download them automatically. A query like **query(s\$socket,"allcds","t=cds", virtual = TRUE)** is now possible.
- Relevant genetic codes and frames are now automatically propagated.
- **SeqinR** sends now its name and version number to the server.
- Strict control on ambiguous DNA base alphabet has been relaxed.
- Default value for parameter **invisible** of function **query()** is now **TRUE**.

## D.5 Session Informations

This part was compiled under the following  environment:

- Version 2.3.1 (2006-06-01), **powerpc-apple-darwin8.6.0**
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: MASS 7.2-27.1, ade4 1.4-1, ape 1.8-2, gee 4.13-10, lattice 0.13-8, nlme 3.1-73, seqinr 1.0-6, xtable 1.3-0

---

# BIBLIOGRAPHY

- [1] A.L. Bak, J.F. Atkins, C.E. Singer, and B.N. Ames. Evolution of dna base compositions in microorganisms. *Science*, 175:1391–1393, 1972.
- [2] J. Buckheit and D. L. Donoho. *Wavelets and Statistics*, chapter Wavelab and reproducible research. Springer-Verlag, Berlin, New York, 1995. A. Antoniadis editor.
- [3] D Charif, J Thioulouse, J R Lobry, and G Perrière. Online synonymous codon usage analyses with the ade4 and seqinR packages. *Bioinformatics*, 21(4):545–7, 2005.
- [4] D.B Dahl and *et al.* *xtable: Export tables to LaTeX or HTML*, 2005. R package version 1.3-0.
- [5] Duncan Temple Lang (duncan@wald.ucdavis.edu). *XML: Tools for parsing and generating XML within R and S-Plus*, 2006. R package version 0.99-8.
- [6] J. Felsenstein. PHYLIP-phylogeny inference package (version 3.2). *Cladistics*, 5:164–166, 1989.
- [7] A.C. Frank and J.R. Lobry. Oriloc: prediction of replication boundaries in unannotated bacterial chromosomes. *Bioinformatics*, 16(6):560–561, 2000.
- [8] N. Galtier, M. Gouy, and C. Gautier. SeaView and Phylo\_win, two graphic tools for sequence alignment and molecular phylogeny. *Comput. Applic. Biosci.*, 12:543–548, 1996.
- [9] A. Garay-Arroyo, J.M. Colmenero-Flores, A. Garciarrubio, and A.A. Covarrubias. Highly hydrophilic proteins in prokaryotes and eukaryotes are common during conditions of water deficit. *J. Biol. Chem.*, 275:5668–5674, 2000.
- [10] C. Gautier. *Analyses statistiques et évolution des séquences d’acides nucléiques*. PhD thesis, Université Claude Bernard - Lyon I, 1987.

- [11] C. Gautier, M. Gouy, M. Jacobzone, and R. Grantham. *Nucleic acid sequences handbook. Vol. 1.* Praeger Publishers, London, UK, 1982. ISBN 0-275-90798-8.
- [12] C. Gautier, M. Gouy, M. Jacobzone, and R. Grantham. *Nucleic acid sequences handbook. Vol. 2.* Praeger Publishers, London, UK, 1982. ISBN 0-275-90799-6.
- [13] S.J. Gould. *Wonderful life.* Norton, New York, USA, 1989.
- [14] S.J. Gould. Ladders and cones: Constraining evolution by canonical icons. In R.B. Silvers, editor, *Hidden Histories of Science*, pages 37–67, New York, USA, 1995. New York Review of Books.
- [15] M. Gouy, F. Milleret, C. Mugnier, M. Jacobzone, and C. Gautier. ACNUC: a nucleic acid sequence data base and analysis system. *Nucleic Acids Res.*, 12:121–127, 1984.
- [16] R. Grantham. Amino acid difference formula to help explain protein evolution. *Science*, 185:862–864, 1974.
- [17] M.A. Hannah, A.G. Heyer, and D.K. Hinch. A global survey of gene regulation during cold acclimation in *Arabidopsis thaliana*. *PLoS Genet.*, 1:e26, 2005.
- [18] D. G. Higgins and P. M. Sharp. CLUSTAL: a package for performing multiple sequence alignment on a microcomputer. *Gene*, 73:237–244, 1988.
- [19] K. Hornik. *The R FAQ: Frequently Asked Questions on R (version 2.3.2006-07-13)*, 2006. ISBN 3-900051-08-9 <http://CRAN.R-project.org/doc/FAQ/>.
- [20] L.D. Hurst. The Ka/Ks ratio: diagnosing the form of sequence evolution. *Trends Genet.*, 18:486–487, 2002.
- [21] R. Ihaka and R. Gentleman. R: A language for data analysis and graphics. *J. Comp. Graph. Stat.*, 3:299–314, 1996.
- [22] M. Jacobzone and C. Gautier. *ANALSEQ Manuel d’utilisation.* UMR CNRS 5558, Biométrie, Génétique et Biologie des Populations, 1989.
- [23] T. H. Jukes and S. Osawa. Evolutionary changes in the genetic code. *Comp. Biochem. Physiol. B.*, 106:489–494, 1993.
- [24] T.H. Jukes and C.R. Cantor. Evolution of protein molecules. In H.N. Munro, editor, *Mammalian Protein Metabolism*, pages 21–132, New York, 1969. Academic Press.
- [25] S. Karlin and V. Brendel. Chance and statistical significance in protein and dna sequence analysis. *Science*, 257:39–49, 1992.
- [26] S. Kawashima and M. Kanehisa. AAindex: amino acid index database. *Nucleic Acids Res.*, 28:374–374, 2000.
- [27] J. Keogh. Circular transportation facilitation device, 2001.



- [28] M. Kimura. A simple method for estimating evolutionary rates of base substitutions through comparative studies of nucleotide sequences. *J. Mol. Evol.*, 16:111–120, 1980.
- [29] J. Kyte and R.F. Doolittle. A simple method for displaying the hydropathic character of a protein. *J. Mol. Biol.*, 157:105–132, 1982.
- [30] P. Legendre, Y. Desdevises, and E. Bazin. A statistical test for host-parasite coevolution. *Syst. Biol.*, 51:217–234, 2002.
- [31] F. Leisch. Sweave: Dynamic generation of statistical reports using literate data analysis. *Proceedings in Computational Statistics*, Compstat 2002:575–580, 2002.
- [32] W.-H. Li. Unbiased estimation of the rates of synonymous and nonsynonymous substitution. *J. Mol. Evol.*, 36:96–99, 1993.
- [33] J.R. Lobry. Life history traits and genome structure: aerobiosis and G+C content in bacteria. *Lecture Notes in Computer Sciences*, 3039:679–686, 2004.
- [34] J.R. Lobry and D. Chessel. Internal correspondence analysis of codon and amino-acid usage in thermophilic bacteria. *Journal of Applied Genetics*, 44:235–261, 2003.
- [35] J.R. Lobry and C. Gautier. Hydrophobicity, expressivity and aromaticity are the major trends of amino-acid usage in 999 *Escherichia coli* chromosome-encoded genes. *Nucleic Acids Res.*, 22:3174–80, 1994.
- [36] J.R. Lobry and N. Sueoka. Asymmetric directional mutation pressures in bacteria. *Genome Biology*, 3(10):research0058.1–research0058.14, 2002.
- [37] A.O. Lovejoy. *The Great Chain of Being: A Study of the History of an Idea*. Harvard University Press, Cambridge, Massachusetts, USA, 1936.
- [38] P. Mackiewicz, J. Zakrzewska-Czerwińska, A. Zawilak, M.R. Dudek, and S. Cebrat. Where does bacterial replication start? rules for predicting the *oriC* region. *Nucleic Acids Research*, 32:3781–3791, 2004.
- [39] Paul Murrell and Richard Walton. *grImport: Importing Vector Graphics*, 2006. R package version 0.2.
- [40] K. Nakai, A. Kidera, and M. Kanehisa. Cluster analysis of amino acid indices for prediction of protein structure and function. *Protein Eng.*, 2:93–100, 1988.
- [41] S. Osawa, T. H. Jukes, K. Watanabe, and A. Muto. Recent evidence for evolution of the genetic code. *Microbiol. Rev.*, 56:229–264, 1992.
- [42] L. Palmeira, L. Guéguen, and J.R. Lobry. UV-targeted dinucleotides are not depleted in light-exposed prokaryotic genomes. *Mol. Biol. Evol.*, 000:000–000, 2006. in press.
- [43] W.R. Pearson and D.J. Lipman. Improved tools for biological sequence comparison. *Proc. Natl. Acad. Sci. USA*, 85:2444–2448, 1988.

- [44] J.F. Peden. *Analysis of codon usage*. PhD thesis, University of Nottingham, 1999.
- [45] G. Perrière and J. Thioulouse. Use and misuse of correspondence analysis in codon usage studies. *Nucleic Acids Res.*, 30:4548–4555, 2002.
- [46] R Development Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2006. ISBN 3-900051-07-0.
- [47] R Development Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2006. ISBN 3-900051-07-0.
- [48] R. Rudner, J.D. Karkas, and E. Chargaff. Separation of microbial deoxyribonucleic acids into complementary strands. *Proceedings of the National Academy of Sciences of the United States of America*, 63:152–159, 1969.
- [49] N. Saitou and M. Nei. The neighbor-joining method: a new method for reconstructing phylogenetic trees. *Mol. Biol. Evol.*, 4:406–425, 1984.
- [50] R. B. Setlow. Cyclobutane-type pyrimidine dimers in polynucleotides. *Science*, 153:379–386, 1966.
- [51] P.M. Sharp and W.-H. Li. The codon adaptation index - a measure of directional synonymous codon usage bias, and its potential applications. *Nucleic Acids Research*, 15:1281–1295, 1987.
- [52] C.E. Singer and B.N. Ames. Sunlight ultraviolet and bacterial dna base ratios. *Science*, 170:822–826, 1970.
- [53] R. Staden. Graphic methods to determine the function of nucleic acid sequences. *Nucleic Acids Res.*, 12:521–538, 1984.
- [54] N. Sueoka. Directional mutation pressure and neutral molecular evolution. *Proceedings of the National Academy of Sciences of the United States of America*, 85:2653–2657, 1988.
- [55] N. Sueoka. Two aspects of dna base composition: G+C content and translation- coupled deviation from intra-strand rule of  $A = T$  and  $G = C$ . *J. Mol. Evol.*, 49:49–62, 1999.
- [56] K. Tomii and M. Kanehisa. Analysis of amino acid indices and mutation matrices for sequence comparison and structure prediction of proteins. *Protein Eng.*, 9:27–36, 1996.
- [57] I.M. Wallace, G. Blackshields, and D.G. Higgins. Multiple sequence alignments. *Curr. Opin. Struct. Biol.*, 15:261–266, 2005.