

Package ‘roxygen’

November 11, 2009

Version 0.1-1

License GPL (>= 2)

Description A Doxygen-like in-source documentation system for Rd, collation, namespace and callgraphs.

Title Literate Programming in R

Author Peter Danenberg <pcd@roxygen.org>, Manuel Eugster
<Manuel.Eugster@stat.uni-muenchen.de>

Maintainer Peter Danenberg <pcd@roxygen.org>

URL <http://roxygen.org>

Suggests Rgraphviz (>= 1.19.2), tools (>= 2.9.1)

Collate 'functional.R' 'list.R' 'roxygen.R' 'string.R' 'parse.R' 'parseS4.R' 'roclet.R' 'callgraph.R'
'description.R' 'collate.R' 'namespace.R' 'Rd.R' 'Rdmerge.R' 'Rdap.R' 'Rdtank.R' 'Rd2.R'
'roxygenize.R'

R topics documented:

roxygen-package	3
assign.parent	4
caar	5
cadar	5
caddr	6
cadr	6
car	7
cat.description	7
ccccdr	8
ccdr	8
cdr	9
Compose	9
copy.dir	10
Curry	10
debug	11
description.dependencies	11
DESCRIPTION.FILE	12
DOC.DIR	12

expression.from.partitum	12
first.non.null	13
guess.name	13
Identity	14
include	14
INST.DIR	14
is.assignment	15
is.even	15
is.function.definition	16
is.nil	16
is.null.string	17
is.odd	17
LINE.DELIMITER	17
make.callgraph.roclet	18
make.collate.roclet	18
make.description.parser	19
make.namespace.roclet	20
make.Rd.roclet	21
make.Rd2.roclet	23
make.roclet	24
MAN.DIR	25
MATTER	25
NAMESPACE.FILE	25
Negate	25
nil	25
NIL.STRING	26
noop.description	26
nwords	26
pairwise	27
parse.assignee	27
parse.call	28
parse.default	28
parse.description	29
parse.description.file	29
parse.description.text	30
parse.element	30
parse.error	31
parse.file	31
parse.files	32
parse.formals	32
parse.message	33
parse.name	33
parse.name.description	34
parse.preref	34
parse.ref	35
parse.ref.list	35
parse.ref.preref	36
parse.ref.srcref	36
parse.refs	37
parse.srcref	37
parse.text	38
parse.toggle	38

parse.value	39
parse.warning	39
parser.default	40
parser.preref	40
parser.srcref	40
preorder.flatten.expression	41
preorder.walk.expression	41
preref.parsers	41
prerefs	42
R.DIR	42
Reduce.paste	42
register.parser	43
register.parsers	43
register.preref.parser	44
register.preref.parsers	44
register.srcref.parser	45
register.srcref.parsers	45
roxygen	45
ROXYGEN.DIR	46
roxygenize	46
SPACE	46
src.lines	47
srcref.parsers	47
strcar	47
stredr	48
strcons	48
strmap	49
substr.regexr	49
TAG.DELIMITER	50
trim	50
trim.left	50
trim.right	51
word.ref	51
zip	52
zip.c	52
zip.list	53

Index

54

Description

Roxygen is a Doxygen-like documentation system for R; allowing in-source specification of Rd files, collation and namespace directives.

Details

Package:	Roxygen
Type:	Package
Version:	0.1-1
Date:	2008-08-25
License:	GPL (>= 2)
LazyLoad:	yes

Roxygen is run on a package (hereafter <package>) by R CMD roxygen <package> or Rcmd roxygen.sh <package> on Windows. By default, it creates a directory '<package>.roxygen' with the complete package cum populated Rd files, 'NAMESPACE', etc.; but can also operate de-structively on the package itself with the '-d' option.

See the vignette ('roxygen.pdf') or manual ('roxygen-manual.pdf') for details.

Author(s)

Peter Danenberg <pcd@roxygen.org>, Manuel Eugster <Manuel.Eugster@stat.uni-muenchen.de>
Maintainer: Peter Danenberg <pcd@roxygen.org>

See Also

See [make.Rd.roclet](#), [make.namespace.roclet](#), [make.collate.roclet](#), [make.callgraph.roclet](#) for an overview of roxygen tags.

See [roxygenize](#) for an alternative to 'R CMD roxygen'.

Examples

```
## To process a package in 'pkg', run `R CMD roxygen pkg'; or:
## Not run: roxygenize('pkg')
```

`assign.parent` *Assign a variable in the parent environment when <<- doesn't seem to work.*

Description

Assign a variable in the parent environment when <<- doesn't seem to work.

Usage

```
assign.parent(var, value, env)
```

Arguments

var	string of the variable to assign
value	value to be assigned
env	environment of the assignment (<code>environment()</code>)

Value

NULL

caar

Composite car/cdr...

Description

Composite car/cdr

Usage

caar(list)

Arguments

list the list from which to extract

Value

The extracted elements

cadar

Composite car/cdr...

Description

Composite car/cdr

Usage

cadar(list)

Arguments

list the list from which to extract

Value

The extracted elements

caddr	<i>Composite car/cdr...</i>
-------	-----------------------------

Description

Composite car/cdr

Usage

`caddr(list)`

Arguments

`list` the list from which to extract

Value

The extracted elements

cadr	<i>Composite car/cdr...</i>
------	-----------------------------

Description

Composite car/cdr

Usage

`cadr(list)`

Arguments

`list` the list from which to extract

Value

The extracted elements

car

First element of a list...

Description

First element of a list

Usage

car(list)

Arguments

list the list to first

Value

The first element

cat.description

Print the field-value pair to a given file or standard out.

Description

Print the field-value pair to a given file or standard out.

Usage

cat.description(field, value, file="")

Arguments

field the field to be printed

value the value to be printed

file the file whither to print (a blank string being standard out)

Value

NULL

cddd	<i>Composite car/cdr...</i>
------	-----------------------------

Description

Composite car/cdr

Usage

`cddd(list)`

Arguments

`list` the list from which to extract

Value

The extracted elements

cddr	<i>Composite car/cdr...</i>
------	-----------------------------

Description

Composite car/cdr

Usage

`cddr(list)`

Arguments

`list` the list from which to extract

Value

The extracted elements

cdr	<i>Return elements after the first of a list.</i>
-----	---

Description

Return elements after the first of a list.

Usage

```
cdr(list)
```

Arguments

list	the list from which to extract
------	--------------------------------

Value

The elements after the first, or `nil` if only one

Compose	<i>Compose an arbitrary number of functions.</i>
---------	--

Description

Compose an arbitrary number of functions. My Happy Hacking keyboard gave out during the writing of this procedure; moment of silence, please.

Usage

```
Compose(....)
```

Arguments

...	the functions to be composed
-----	------------------------------

Value

A composed function

`copy.dir`*Recursively copy a directory thither; optionally unlinking...***Description**

Recursively copy a directory thither; optionally unlinking the target first; optionally overwriting; optionally verbalizing.

Usage

```
copy.dir(source, target, unlink.target=FALSE, overwrite=FALSE,
        verbose=FALSE)
```

Arguments

<code>source</code>	the source directory
<code>target</code>	the target directory
<code>unlink.target</code>	delete target directory first?
<code>overwrite</code>	overwrite target files?
<code>verbose</code>	verbalize transaction?

Value

NULL

Note

Not tested on non-linux platforms

`Curry`*Pre-specify a procedures named parameters, returning a new procedure.***Description**

Pre-specify a procedures named parameters, returning a new procedure.

Usage

```
Curry(FUN, ...)
```

Arguments

<code>FUN</code>	the function to be curried
<code>...</code>	the determining parameters

Details

Thanks, Byron Ellis. <https://stat.ethz.ch/pipermail/r-devel/2007-November/047318.html>

Value

A new function partially determined

`debug`

Convenience function to print variable-value pairs.

Description

Convenience function to print variable-value pairs.

Usage

```
debug(...)
```

Arguments

... named variable of the form a=b, ...

Value

NULL

`description.dependencies`

Gather a DESCRIPTION's dependencies from the...

Description

Gather a ‘DESCRIPTION’’s dependencies from the Package, Depends, Imports, Suggests, and Enhances fields.

Usage

```
description.dependencies(description.file)
```

Arguments

`description.file`
the ‘DESCRIPTION’ to parse

Value

A list of dependencies

TODO

Test this!

DESCRIPTION.FILE *Whither to copy collate...*

Description

Whither to copy collate

DOC.DIR *Whither to install docs...*

Description

Whither to install docs

expression.from.partitum
 Extract the expression from the parse tree.

Description

Extract the expression from the parse tree.

Usage

`expression.from.partitum(partitum)`

Arguments

partitum partitum the parsed elements

Value

the extracted expression

first.non.null	<i>Find the first non-null argument.</i>
----------------	--

Description

Find the first non-null argument.

Usage

```
first.non.null(...)
```

Arguments

...	the arguments
-----	---------------

Value

The first non-null argument

guess.name	<i>Pluck name from a hierarchy of candidates; viz.</i>
------------	--

Description

Pluck name from a hierarchy of candidates; viz. name, assignee, S4class, S4method, S4generic.

Usage

```
guess.name(partitum)
```

Arguments

partitum	the parsed elements
----------	---------------------

Value

The guessed name (possibly NULL)

Identity

Identity function.

Description

Identity function.

Usage

`Identity(...)`

Arguments

... tautological arguments

Details

Is concatenation benign?

Value

The tautologized arguments, concatenated

include

Collate value parser..

Description

Collate value parser

See Also

`make.collate.roclet`

INST.DIR

Whither to copy installables...

Description

Whither to copy installables

is.assignment	<i>Whether the expression implies assignment by <- or =.</i>
---------------	---

Description

Whether the expression implies assignment by <- or =.

Usage

```
is.assignment(expression)
```

Arguments

expression the expression to check for assignment

Value

Whether or not the expression assigns by <- =

is.even	<i>Is a number even?</i>
---------	--------------------------

Description

Is a number even?

Usage

```
is.even(a)
```

Arguments

a the number to test

Value

Whether the number is even

`is.function.definition`

Whether the expression assigns function...

Description

Whether the expression assigns function

Usage

`is.function.definition(expression)`

Arguments

`expression` the expression to check for assignment

Value

Whether the expression assigns a function

`is.nil`

Whether a list is empty.

Description

Whether a list is empty.

Usage

`is.nil(list)`

Arguments

`list` the list to test

Value

Whether the list is empty

is.null.string	<i>Does the string contain no matter, but very well [:space:]?</i>
----------------	--

Description

Does the string contain no matter, but very well [:space:]?

Usage

```
is.null.string(string)
```

Arguments

string	the string to check
--------	---------------------

Value

TRUE if the string contains words, otherwise FALSE

is.odd	<i>Is a number odd?</i>
--------	-------------------------

Description

Is a number odd?

Usage

```
is.odd(a)
```

Arguments

a	the number to test
---	--------------------

Value

Whether the number is odd

LINE.DELIMITER	<i>Sequence that distinguishes roxygen comment from normal comment.</i>
----------------	---

Description

Sequence that distinguishes roxygen comment from normal comment.

`make.callgraph.roclet`

Make a callgraph roclet which produces a static call graph...

Description

Make a callgraph roclet which produces a static call graph from a given function at a given depth with or without primitives.

Usage

```
make.callgraph.roclet(dependencies, dir=".", verbose=TRUE)
```

Arguments

<code>dependencies</code>	packages required to evaluate interesting functions
<code>dir</code>	the directory to place the callgraphs in
<code>verbose</code>	announce what we're doing

Details

The callgraph roclet supports the following tags:

1. `@callGraphCreate` a call graph of the default depth, excluding primitive functions.
2. `@callGraphPrimitivesCreate` a call graph of the default depth, including primitive functions.
3. `@callGraphDepthChange` the depth of the callgraph from the default of 2.

The callgraph roclet is awkward in the sense that it requires a function's package to be loadable; which means, like calling LaTeX multiple times, one has to run roxygen on a package, install it, run roxygen again to get the callgraphs, and possibly install the package again.

TODO

- `index.html`‘`index.html`’ in ‘`inst/doc`’ for callgraphs, possibly with thumbnails in png
- Text-only option `option` for text-only callgraphs (which are clearer, in my opinion)

`make.collate.roclet`

Make collate roclet which parses the given files; topologically...

Description

Make collate roclet which parses the given files; topologically sorting `@includes`, and either merging the `Collate:` directive with a pre-existing ‘DESCRIPTION’ or writing to standard out.

Usage

```
make.collate.roclet(merge.file, target.file="", verbose=TRUE)
```

Arguments

merge.file	‘DESCRIPTION’ file with which to merge directive; or NULL for none
target.file	whither to cat directive (whether merged or not); blank line is standard out
verbose	whether to describe what we’re doing with the target.file

Details

Each @include tag should specify the filename of one intrapackage dependency; multiple @include tags may be given.

Contains the member function parse which parses an arbitrary number of files, and parse.dir which recursively parses a directory tree.

Value

Rd roclet

See Also

[make.roclet](#)

Examples

```
#' `example-a.R`, `example-b.R` and `example-c.R` reside
#' in the `example` directory, with dependencies
#' a -> {b, c}. This is `example-a.R`.
#' @include example-b.R
#' @include example-c.R
roxygen()

roclet <- make.collate.roclet()
## Not run: roclet$parse.dir('example')
```

make.description.parser

Make a parser to parse DESCRIPTION files.

Description

Make a parser to parse ‘DESCRIPTION’ files.

Usage

```
make.description.parser(parse.default=cat.description,
                      pre.parse=noop.description, post.parse=noop.description)
```

Arguments

parse.default	the default parser receiving a field and value
pre.parse	a function receiving the parsed fields before individual parsing
post.parse	a function receiving the parsed fields after individual parsing

Details

Contains the member functions `register.parser`, taking a field and parser; and `parse`, taking the parsed fields from `parse.description.file` or similar.

Value

`NULL`

`make.namespace.roclet`

Make a namespace roclet which parses the given files and writes a list of...

Description

Make a namespace roclet which parses the given files and writes a list of namespace directives to a given file or standard out; see *Writing R Extensions* (<http://cran.r-project.org/doc/manuals/R-exts.pdf>) for details.

Usage

```
make.namespace.roclet(outfile = "", verbose = TRUE)
```

Arguments

<code>outfile</code>	whither to send output; blank string means standard out
<code>verbose</code>	whether to announce what we're doing with the <code>outfile</code>

Details

The namespace roclet supports the following tags:

Roxygen tag	'NAMESPACE' equivalent
<code>@export</code>	<code>export</code>
<code>@exportClass</code>	<code>exportClasses</code>
<code>@exportMethod</code>	<code>exportMethod</code>
<code>@exportPattern</code>	<code>exportPattern</code>
<code>@S3method</code>	<code>S3method</code>
<code>@import</code>	<code>import</code>
<code>@importFrom</code>	<code>importFrom</code>
<code>@importClassesFrom</code>	<code>importClassesFrom</code>
<code>@importMethodsFrom</code>	<code>importMethodsFrom</code>

1. `@export` May be specified with or without value; if unadorned, roxygen will try to guess the exported value by assignee, `setMethod`, `setClass`, etc. Otherwise, `@export f g ...` translates to `export(f, g, ...)`.
2. `@exportClass` Overrides `setClass`.
3. `@exportMethod` Overrides `setMethod` or `setGeneric`.
4. `@exportPattern` See “1.6.2 Registering S3 methods” from *Writing R Extensions*.

5. `@S3method`Overrides the export of an S3 method.
6. `@import`See “1.6.1 Specifying imports and exports” from *Writing R Extensions*.
7. `@importFrom`See “1.6.1 Specifying imports and exports” from *Writing R Extensions*.
8. `@importClassesFrom`See “1.6.6 Name spaces with formal classes and methods” from *Writing R Extensions*.
9. `@importMethodsFrom`See “1.6.6 Name spaces with formal classes and methods” from *Writing R Extensions*.

Value

Namespace roclet

Examples

```
#' An example file, example.R, which imports
#' packages foo and bar
#' @import foo bar
roxygen()

#' An exportable function
#' @export
fun <- function() {}

roclet <- make.namespace.roclet()
## Not run: roclet$parse('example.R')
```

make.Rd.roclet	<i>Make an Rd roclet which parses the given files and, if specified, populates...</i>
----------------	---

Description

Make an Rd roclet which parses the given files and, if specified, populates the given subdirectory with Rd files; or writes to standard out. See *Writing R Extensions* (<http://cran.r-project.org/doc/manuals/R-exts.pdf>) for details.

Usage

```
make.Rd.roclet(subdir, verbose=TRUE)
```

Arguments

subdir	directory into which to place the Rd files; if NULL, standard out.
verbose	whether to declare what we're doing in the <i>subdir</i>

Details

The first paragraph of a roxygen block constitutes its description, the subsequent paragraphs its details; moreover, the Rd roclet supports these tags:

Roxygen tag	Rd analogue
@author	\author
@aliases	\alias, ...
@concept	\concept
@example	n/a
@examples	\examples
@format	\format
@keywords	\keyword, ...
@method	\method
@name	\name
@note	\note
@param	\arguments{\item, ...}
@references	\references
@return	\value
@seealso	\seealso
@source	\source
@title	\title
@TODO	n/a
@usage	\usage

1. @author See “2.1.1 Documenting functions” from *Writing R Extensions*.
2. @aliases A default alias is plucked from the @name or assignee; otherwise, @alias a b ... translates to \alias{a}, \alias{b}, &c. If you specify one alias, however, specify them all.
3. @concept See “2.8 Indices” from *Writing R Extensions*.
4. @example Each @example tag specifies an example file relative to the package head; if the file resides in ‘tests’, for instance, it will be checked with R CMD check. The contents of the file will be concatenated under \examples{...}.
5. @examples Verbatim examples; see “2.1.1 Documenting functions” from *Writing R Extensions*.
6. @format See “2.1.2 Documenting data sets” from *Writing R Extensions*.
7. @keywords @keywords a b ... translates to \keyword{a}, \keyword{b}, &c.
8. @method Use @method <generic> <class> to document S3 functions.
9. @name In the absense of an explicit @name tag, the name of an assignment is plucked from the assignee.
10. @note See “2.1.1 Documenting functions” from *Writing R Extensions*.
11. @param Each function variable should have a @param <variable> <description> specified.
12. @references See “2.1.1 Documenting functions” from *Writing R Extensions*.
13. @return The return value of the function, or NULL.
14. @seealso See “2.1.1 Documenting functions” from *Writing R Extensions*.
15. @source See “2.1.2 Documenting data sets” from *Writing R Extensions*.

16. @title A default title is plucked from the first sentence of the description; that is, the first phrase ending with a period, question mark or newline. In the absence of a description, the title becomes the @name or assignee; lastly, it can be overridden with @title.
17. @TODO Note to developers to get off their asses.
18. @usage A default usage is construed from a function's formals, but can be overridden with @usage (e.g. in the case of multiple functions in one Rd unit).

Value

Rd roclet

TODO

param method setClass setGeneric setMethod make.Rd.roclet

Examples

```
#' This sentence describes the function.
#'
#' Here are the details (notice the preceding blank
#' line); the name, title, usage and alias will be
#' automatically generated.
#'
#' @param a a parameter
#' @return NULL
f <- function(a=1) NULL

#' S3 functions require a @method tag for
#' the time being.
#'
#' @method specialize foo
#' @param f a generic foo
#' @param ... ignored
#' @return The specialized foo
specialize.foo <- function(f, ...)
actually.specialize(f)

roclet <- make.Rd.roclet('man')
## Not run: roclet$parse('example.R')
```

`make.Rd2.roclet` *New implementation of the Rd roclet; same functionality as the original...*

Description

New implementation of the Rd roclet; same functionality as the original implementation plus basic S4 handling.

Usage

```
make.Rd2.roclet(subdir, verbose=TRUE, exportonly=FALSE,
documentedonly=TRUE)
```

Arguments

<code>subdir</code>	directory into which to place the Rd files; if NULL, standard out.
<code>verbose</code>	whether to declare what we're doing in the <i>subdir</i>
<code>exportonly</code>	create Rd files only for exported "things"
<code>documentedonly</code>	create Rd files only for "things" which are documented with Roxygen

Details

See [make.Rd.roclet](#) for description and available tags; new tags are:

1. `@nordSuppress` Rd creation.
2. `@rdname` Definition of the Rd name; blocks with the same `@rdname` are merged into one Rd file.
3. `@slot` Each S4 class slot should have a `@slot <name> <description>` specified.

Value

Rd roclet

`make.roclet`

Abstract roclet that serves as a rudimentary API.

Description

Abstract roclet that serves as a rudimentary API.

Usage

```
make.roclet(parse.default, pre.parse, post.parse, pre.files,
            post.files)
```

Arguments

<code>parse.default</code>	the default parser taking key and value
<code>pre.parse</code>	a callback function taking a list of parsed elements; called before processing a file
<code>post.parse</code>	a callback function taking a list of parsed elements; called after processing a file
<code>pre.files</code>	a callback function with no arguments; called before any file has been parsed
<code>post.files</code>	a callback function with no arguments; called after every file has been parsed

Details

Contains the following member functions:

- `register.parser`takes key and parser
- `register.parser`takes parser and keys
- `register.default.parser`takes a key
- `register.default.parser`takes parsers
- `parse`parses material contained in files

MAN.DIR	<i>Whither to copy Rds...</i>
---------	-------------------------------

Description

Whither to copy Rds

MATTER	<i>Anti-anti-words...</i>
--------	---------------------------

Description

Anti-anti-words

NAMESPACE.FILE	<i>Whither to copy namespace...</i>
----------------	-------------------------------------

Description

Whither to copy namespace

Negate	<i>Negate a function; borrowed from src/library/base/R/funprog...</i>
--------	---

Description

Negate a function; borrowed from src/library/base/R/funprog.R for pre-2.7 Rs.

Usage

`Negate(f)`

Arguments

`f` the function to be negated

Value

The negated function

nil	<i>The empty list...</i>
-----	--------------------------

Description

The empty list

`NIL.STRING` *Analogue to the empty list...*

Description

Analogue to the empty list

`noop.description` *Description parser that does nothing...*

Description

Description parser that does nothing

Usage

`noop.description(field, value)`

Arguments

<code>field</code>	the field to be parsed
<code>value</code>	the value to be parsed

Value

`NULL`

`nwords` *Number of words a string contains.*

Description

Number of words a string contains.

Usage

`nwords(string)`

Arguments

<code>string</code>	the string whose words to count
---------------------	---------------------------------

Value

Number of words in the string

pairwise

Combine a list into pairwise elements; lists should...

Description

Combine a list into pairwise elements; lists should be of the same length. In case of odd numbers of members, the last will be removed.

Usage

```
pairwise(list)
```

Arguments

list the list to be pairwise decomposed

Value

A list of pairwise elements

parse.assignee

Find the assignee of the expression...

Description

Find the assignee of the expression

Usage

```
parse.assignee(expression)
```

Arguments

expression the expression in which to find the assignee

Value

The expression's assignee

`parse.call`*Parse a function call, paying special attention to...***Description**

Parse a function call, paying special attention to assignments by <- or =.

Usage

```
parse.call(expressions)
```

Arguments

`expressions` the expression to search through

Value

List of formals and assignee in case of assignment, the processed expression in case of non-assigning function calls (see `parse.srcref`).

`parse.default`*Default parser which simply emits the key and expression;...***Description**

Default parser which simply emits the key and expression; used for elements with optional values (like `@export`) where roclts can do more sophisticated things with NULL.

Usage

```
parse.default(key, rest)
```

Arguments

<code>key</code>	the parsing key
<code>rest</code>	the expression to be parsed

Value

A list containing the key and expression (possibly null)

```
parse.description  Parse description: the premier part of a roxygen block...
```

Description

Parse description: the premier part of a roxygen block containing description and option details separated by a blank roxygen line.

Usage

```
parse.description(expression)
```

Arguments

expression the description to be parsed

Value

A list containing the parsed description

```
parse.description.file
Convenience function to call...
```

Description

Convenience function to call `parse.description.text` with the given ‘DESCRIPTION’ file.

Usage

```
parse.description.file(description.file)
```

Arguments

description.file
the ‘DESCRIPTION’ file to be parsed

Value

NULL

parse.description.text

Parse lines of text corresponding to a package DESCRIPTION file.

Description

Parse lines of text corresponding to a package DESCRIPTION file.

Usage

```
parse.description.text(description)
```

Arguments

description the lines of tex

Value

A list of values indexed by field

parse.element

Parse a raw string containing key and expressions.

Description

Parse a raw string containing key and expressions.

Usage

```
parse.element(element)
```

Arguments

element the string containing key and expressions

Value

A list containing the parsed constituents

parse.error	<i>Centrally formatted error; stopping execution...</i>
-------------	---

Description

Centrally formatted error; stopping execution

Usage

```
parse.error(key, message)
```

Arguments

key	the offending key
message	the apposite message

Value

NULL

parse.file	<i>Parse a source file containing roxygen directives.</i>
------------	---

Description

Parse a source file containing roxygen directives.

Usage

```
parse.file(file)
```

Arguments

file	string naming file to be parsed
------	---------------------------------

Value

List containing parsed directives

<code>parse.files</code>	<i>Parse many files at one.</i>
--------------------------	---------------------------------

Description

Parse many files at one.

Usage

```
parse.files(...)
```

Arguments

... files to be parsed

Value

List containing parsed directives

See Also

[parse.file](#)

<code>parse.formals</code>	<i>Find the formal arguments associated with a given...</i>
----------------------------	---

Description

Find the formal arguments associated with a given expression (may be NULL).

Usage

```
parse.formals(expressions)
```

Arguments

expressions the expressions from which to extract formal arguments

Value

The formal arguments of said expression or NULL

parse.message	<i>Centrally formatted message...</i>
---------------	---------------------------------------

Description

Centrally formatted message

Usage

```
parse.message(key, message)
```

Arguments

key	the offending key
message	the apposite message

Value

The formatted message

parse.name	<i>Parse an element containing a single name and only a name;...</i>
------------	--

Description

Parse an element containing a single name and only a name; extra material will be ignored and a warning issued.

Usage

```
parse.name(key, name)
```

Arguments

key	parsing key
name	the name to be parsed

Value

A list containing key and name

```
parse.name.description
```

Parse an element containing a mandatory name...

Description

Parse an element containing a mandatory name and description (such as @param).

Usage

```
parse.name.description(key, rest)
```

Arguments

key	the parsing key
rest	the expression to be parsed

Value

A list containing the key, name and description

```
parse.preref
```

Resorts to the default parser but with a warning about the...

Description

Resorts to the default parser but with a warning about the unknown key.

Usage

```
parse.preref(key, rest)
```

Arguments

key	the parsing key
rest	the expression to be parsed

Value

A list containing the key and expression (possibly null)

See Also

[parse.default](#)

`parse.ref`

Parse either srcrefs, prrefs or pairs of the same.

Description

Parse either srcrefs, prrefs or pairs of the same.

Usage

```
parse.ref(ref, ...)
```

Arguments

ref	the srcref, prref or pair of the same
...	ignored

Value

List containing the parsed srcref/prref

`parse.ref.list`

Parse a prref/srcrefs pair...

Description

Parse a prref/srcrefs pair

Usage

```
## S3 method for class 'list':  
parse.ref (ref, ...)
```

Arguments

ref	the prref/srcref pair
...	ignored

Value

List combining the parsed prref/srcref

parse.ref.preref *Parse a preref...*

Description

Parse a preref

Usage

```
## S3 method for class 'preref':  
parse.ref (ref, ...)
```

Arguments

ref	the preref to be parsed
...	ignored

Value

List containing the parsed preref

parse.ref.sreref *Parse a sreref...*

Description

Parse a sreref

Usage

```
## S3 method for class 'sreref':  
parse.ref (ref, ...)
```

Arguments

ref	the sreref to be parsed
...	ignored

Value

List containing the parsed sreref

parse.refs	<i>Parse each of a list of preref/srcref pairs.</i>
------------	---

Description

Parse each of a list of preref/srcref pairs.

Usage

```
parse.refs(preref.srcrefs)
```

Arguments

preref.srcrefs	list of preref/srcref pairs
----------------	-----------------------------

Value

List combining parsed preref/srcrefs

parse.srcref	<i>By default, srcrefs are ignored; this parser returns nil.</i>
--------------	--

Description

By default, srcrefs are ignored; this parser returns nil.

Usage

```
parse.srcref(pivot, expression)
```

Arguments

pivot	the parsing pivot
expression	the expression to be parsed

Value

nil

`parse.text`*Text-parsing hack using tempfiles for more facility.***Description**

Text-parsing hack using tempfiles for more facility.

Usage

```
parse.text(...)
```

Arguments

...	lines of text to be parsed
-----	----------------------------

Value

The parse tree

`parse.toggle`*Turn a binary element on; parameters are ignored.***Description**

Turn a binary element on; parameters are ignored.

Usage

```
parse.toggle(key, rest)
```

Arguments

key	parsing key
rest	the expression to be parsed

Value

A list with the key and TRUE

parse.value	<i>Parse an element with a mandatory value.</i>
-------------	---

Description

Parse an element with a mandatory value.

Usage

```
parse.value(key, rest)
```

Arguments

key	the parsing key
rest	the expression to be parsed

Value

A list containing the key and value

parse.warning	<i>Centrally formatted warning...</i>
---------------	---------------------------------------

Description

Centrally formatted warning

Usage

```
parse.warning(key, message)
```

Arguments

key	the offending key
message	the apposite message

Value

NULL

`parser.default` *Default parser-lookup; if key not found, return...*

Description

Default parser-lookup; if key not found, return the default parser specified.

Usage

```
parser.default(table, key, default)
```

Arguments

<code>table</code>	the parser table from which to look
<code>key</code>	the key upon which to look
<code>default</code>	the parser to return upon unsuccessful lookup

Value

The parser

`parser.preref` *Preref parser-lookup; defaults to parse.preref...*

Description

Preref parser-lookup; defaults to `parse.preref`.

Arguments

<code>key</code>	the key upon which to look
------------------	----------------------------

Value

The parser

`parser.srcref` *Srcref parser-lookup; defaults to parse.srcref...*

Description

Srcref parser-lookup; defaults to `parse.srcref`.

Arguments

<code>key</code>	the key upon which to look
------------------	----------------------------

Value

The parser

```
preorder.flatten.expression
```

Flatten a nested expression into a list, preorderly.

Description

Flatten a nested expression into a list, preorderly.

Usage

```
preorder.flatten.expression(expression)
```

Arguments

expression the root of the expression to be flattened

Value

A list containing the flattened expression

```
preorder.walk.expression
```

Recursively walk an expression (as returned by parse) in...

Description

Recursively walk an expression (as returned by parse) in preorder.

Usage

```
preorder.walk.expression(proc, expression)
```

Arguments

proc the procedure to apply to each subexpression
expression the root of the expression

Value

NULL

```
preref.parsers
```

Preref parser table...

Description

Preref parser table

TODO

number parser?

`preref`*Comment blocks (possibly null) that precede a file's expressions.***Description**

Comment blocks (possibly null) that precede a file's expressions.

Usage

```
preref(srcfile, srcrefs)
```

Arguments

<code>srcfile</code>	result of running <code>srcfile</code> on an interesting file
<code>srcrefs</code>	the resultant srcrefs

Value

A list of preref that resemble srcrefs in form, i.e. with srcfile and lloc

`R.DIR`*Whence to copy source code...***Description**

Whence to copy source code

`Reduce.paste`*Ad-hoc abstraction to paste processed list-elements together.***Description**

Ad-hoc abstraction to paste processed list-elements together.

Usage

```
Reduce.paste(proc, elts, sep)
```

Arguments

<code>proc</code>	the procedure to apply to the elements
<code>elts</code>	the elements to be processed
<code>sep</code>	the glue to joined the processed elements

Value

The processed elements as a glued string

```
register.parser      Register a parser with a table...
```

Description

Register a parser with a table

Usage

```
register.parser(table, key, parser)
```

Arguments

table	the table under which to register
key	the key upon which to register
parser	the parser callback to register; a function taking key and expression

Value

NULL

```
register.parsers      Register many parsers at once.
```

Description

Register many parsers at once.

Usage

```
register.parsers(table, parser, ...)
```

Arguments

table	the table under which to register
parser	the parser to register
...	the keys upon which to register

Value

NULL

```
register.preref.parser  
    Specifically register a preref parser...
```

Description

Specifically register a preref parser

Arguments

key	the key upon which to register
parser	the parser callback to register; a function taking key and expression

Value

NULL

See Also

[register.parser](#)

```
register.preref.parsers  
    Register many preref parsers at once.
```

Description

Register many preref parsers at once.

Arguments

parser	the parser to register
...	the keys upon which to register

Value

NULL

```
register.srcref.parser  
  Specifically register a srcref parser...
```

Description

Specifically register a srcref parser

Arguments

key	the key upon which to register
parser	the parser callback to register; a function taking <code>key</code> and <code>expression</code>

Value

NULL

See Also

[register.parser](#)

```
register.srcref.parsers  
  Register many srcref parsers at once.
```

Description

Register many srcref parsers at once.

Arguments

parser	the parser to register
...	the keys upon which to register

Value

NULL

```
roxygen          No-op for sourceless files...
```

Description

No-op for sourceless files

Value

NULL

`ROXYGEN.DIR` *Whither to copy package...*

Description

Whither to copy package

`roxygenize` *Process a package with the Rd, namespace and collate roclets.*

Description

Process a package with the Rd, namespace and collate roclets.

Usage

```
roxygenize(package.dir, roxygen.dir, copy.package=TRUE, overwrite=TRUE,
           unlink.target=FALSE, use.Rd2=FALSE)
```

Arguments

<code>package.dir</code>	the package's top directory
<code>roxygen.dir</code>	whither to copy roxygen files; defaults to ‘ <code>package.roxygen</code> ’.
<code>copy.package</code>	copies the package over before adding/manipulating files.
<code>overwrite</code>	overwrite target files
<code>unlink.target</code>	unlink target directory before processing files
<code>use.Rd2</code>	use the Rd2 roclt

Value

`NULL`

TODO

Options to enable/disable specific roclt (`--no-callgraphs`, etc.)

`SPACE` *Absence of words...*

Description

Absence of words

`src.lines`

Extract the source code from parsed elements...

Description

Extract the source code from parsed elements

Usage

```
src.lines(partitum)
```

Arguments

partitum the parsed elements

Value

The lines of source code

`srcref.parsers`

Srcref parser table...

Description

Srcref parser table

`strcar`

First word in a string.

Description

First word in a string.

Usage

```
strcar(string)
```

Arguments

string the string whose word to finde

Value

The first word

strcdr	<i>Words after first in a string.</i>
--------	---------------------------------------

Description

Words after first in a string.

Usage

strcdr(string)

Arguments

string	the string whose words to find
--------	--------------------------------

Value

The words after first in the string

strcons	<i>Join two string.</i>
---------	-------------------------

Description

Join two string.

Usage

strcons(consor, consee, sep)

Arguments

consor	the joining string
consee	the joined string
sep	the intervening space

Value

The joined strings

`strmap`

Map through the words in a string, joining the mapped...

Description

Map through the words in a string, joining the mapped words with a separator.

Usage

```
strmap(proc, sep, string)
```

Arguments

proc	procedure to apply to each word
sep	the separator joining the mapped words
string	the string to be mapped

Details

General enough to be designated ‘map’: isn’t it closer to a specialized reduce?

Value

Mapped words separated by `sep`

`substr.regexr`

Actually do the substring representation that...

Description

Actually do the substring representation that `regexr` should do; does not acknowledge groups, since `regexr` doesn’t.

Usage

```
substr.regexr(pattern, text)
```

Arguments

pattern	the pattern to match
text	the text to match against

Value

The matched substring

TAG . DELIMITER	<i>Symbol that delimits tags.</i>
-----------------	-----------------------------------

Description

Symbol that delimits tags.

trim	<i>Trim [:space:] on both sides of a string.</i>
------	--

Description

Trim [:space:] on both sides of a string.

Usage

```
trim(string)
```

Arguments

string	the string to be trimmed
--------	--------------------------

Value

A trimmed string

trim.left	<i>Trim [:space:] to the left of a string.</i>
-----------	--

Description

Trim [:space:] to the left of a string.

Usage

```
trim.left(string)
```

Arguments

string	the string to be trimmed
--------	--------------------------

Value

A left-trimmed string

trim.right	<i>Trim [:space:] to the right of a string.</i>
------------	---

Description

Trim [:space:] to the right of a string.

Usage

```
trim.right(string)
```

Arguments

string	the string to be trimmed
--------	--------------------------

Value

A right-trimmed string

word.ref	<i>Find the nth word in a string.</i>
----------	---------------------------------------

Description

Find the nth word in a string.

Usage

```
word.ref(string, n)
```

Arguments

string	the string to search in
n	the nth word to find

Value

A list containing:

start	the first letter of the word.
end	the last letter of the word.

Undefined if no such word; though end may be less than start in such a case.

`zip`

Zip n lists together into tuples of...

Description

Zip n lists together into tuples of length n .

Usage

`zip(zipper, ...)`

Arguments

<code>zipper</code>	the zipping function
<code>...</code>	the lists to be zipped

Value

A list of tuples

`zip.c`

Zip using c.

Description

Zip using `c`.

Usage

`zip.c(...)`

Arguments

<code>...</code>	the lists to be zipped
------------------	------------------------

Value

A list of tuples

See Also

[zip](#)

`zip.list`

Zip using list.

Description

Zip using list.

Usage

`zip.list(...)`

Arguments

`...` the lists to be zipped

Value

A list of tuples

See Also

[zip](#)

Index

*Topic **package**
 roxygen-package, 1

aliases (make.Rd.roclet), 19
assign.parent, 2
author (make.Rd.roclet), 19

caar, 3
cadar, 3
caddr, 4
cadr, 4
callGraph
 (make.callgraph.roclet), 16
callGraphDepth
 (make.callgraph.roclet), 16
callGraphPrimitives
 (make.callgraph.roclet), 16
car, 5
cat.description, 5
cdddr, 6
cddr, 6
cdr, 7
Compose, 7
concept (make.Rd.roclet), 19
copy.dir, 8
Curry, 8

debug, 9
description.dependencies, 9
DESCRIPTION.FILE, 10
DOC.DIR, 10

example (make.Rd.roclet), 19
examples (make.Rd.roclet), 19
export (make.namespace.roclet), 18
exportClass
 (make.namespace.roclet), 18
exportMethod
 (make.namespace.roclet), 18
exportPattern
 (make.namespace.roclet), 18
expression.from.partitum, 10

first.non.null, 11

guess.name, 11
Identity, 12
import (make.namespace.roclet), 18
importClassesFrom
 (make.namespace.roclet), 18
importFrom
 (make.namespace.roclet), 18
importMethodsFrom
 (make.namespace.roclet), 18
include, 12
INST.DIR, 12
is.assignment, 13
is.even, 13
is.function.definition, 14
is.nil, 14
is.null.string, 15
is.odd, 15

keywords (make.Rd.roclet), 19
LINE.DELIMITER, 15

make.callgraph.roclet, 2, 16
make.collate.roclet, 2, 16
make.description.parser, 17
make.namespace.roclet, 2, 18
make.Rd.roclet, 2, 19, 22
make.Rd2.roclet, 21
make.roclet, 17, 22
MAN.DIR, 23
MATTER, 23

name (make.Rd.roclet), 19
NAMESPACE.FILE, 23
Negate, 23
nil, 23
NIL.STRING, 24
noop.description, 24
nord (make.Rd2.roclet), 21
note (make.Rd.roclet), 19
nwords, 24

pairwise, 25
parse.assignee, 25

parse.call, 26
parse.default, 26, 32
parse.description, 27
parse.description.file, 18, 27
parse.description.text, 27, 28
parse.element, 28
parse.error, 29
parse.file, 29, 30
parse.files, 30
parse.formals, 30
parse.message, 31
parse.name, 31
parse.name.description, 32
parse.preref, 32
parse.ref, 33
parse.ref.list, 33
parse.ref.preref, 34
parse.ref.srcref, 34
parse.refs, 35
parse.srcref, 35
parse.text, 36
parse.toggle, 36
parse.value, 37
parse.warning, 37
parser.default, 38
parser.preref, 38
parser.srcref, 38
preorder.flatten.expression, 39
preorder.walk.expression, 39
preref.parsers, 39
prrefs, 40

R.DIR, 40
rdname (*make.Rd2.roclet*), 21
Reduce.paste, 40
references (*make.Rd.roclet*), 19
register.parser, 41, 42, 43
register.parsers, 41
register.preref.parser, 42
register.preref.parsers, 42
register.srcref.parser, 43
register.srcref.parsers, 43
return (*make.Rd.roclet*), 19
roxygen, 43
roxygen-package, 1
ROXYGEN.DIR, 44
roxygenize, 2, 44

S3method (*make.namespace.roclet*),
 18
seealso (*make.Rd.roclet*), 19
slot (*make.Rd2.roclet*), 21
SPACE, 44